


Ch. 12 Hash Tables


- Array or linked list
 - Overall $O(n)$ time
- Binary search trees
 - Expected $\theta(\log n)$ -time search, insertion, and deletion
 - But, $\theta(n)$ in the worst case
- Balanced binary search trees
 - Guarantees $O(\log n)$ -time search, insertion, and deletion
 - Red-black tree, AVL tree
- Balanced k -ary trees
 - Guarantees $O(\log n)$ -time search, insertion, and deletion w/ smaller constant factor
 - 2-3 tree, 2-3-4 tree, B-trees
- Hash table
 - Expected $\theta(1)$ -time search, insertion, and deletion

- Stack, queue, priority queue
 - do not support *search* operation
 - i.e., do not support *dictionary*
- But, hash table does not support finding the minimum (or maximum) element
- Applications that need radically fast operations
 - 119 emergent calls and locating caller's address
 - Air flight information system
 - 주민등록 시스템

Address calculator



Collision



Insert

tableInsert(x)

{ // $A[]$: hash table, x : new key to insert

if ($A[h(x)]$ is not occupied) {

$A[h(x)] = x$;

else {

 Find an appropriate index i by a collision-resolution method;

$A[i] = x$;

 }

}

Hash Functions

- Toy functions
 - Selection digits
 - $h(001\textcolor{red}{3}6482\textcolor{red}{5}) = 35$
 - Folding
 - $h(\textcolor{blue}{00}1\textcolor{red}{3}6\textcolor{red}{4}8\textcolor{green}{2}5) = 1190$
- Modulo arithmetic
 - $h(x) = x \bmod \textit{tableSize}$
 - *tableSize* is recommended to be prime
- Multiplication method
 - $h(x) = (xA \bmod 1) * \textit{tableSize}$
 - *A*: constant in (0, 1)
 - *tableSize* is not critical, usually 2^p for an integer p


Collision Resolution

- Collision
 - The situation that two keys are mapped into the same location in the hash table
- Collision resolution
 - resolves collision by a seq. of hash values
 - $h_0(x)(=h(x)), h_1(x), h_2(x), h_3(x), \dots$

Collision-Resolution Methods

- Open addressing (resolves in the array)
 - Linear probing
 - $h_i(x) = (h_0(x) + i) \bmod \text{tableSize}$
 - Quadratic probing
 - $h_i(x) = (h_0(x) + i^2) \bmod \text{tableSize}$
 - Double hashing
 - $h_i(x) = (\alpha(x) + i \cdot \beta(x)) \bmod \text{tableSize}$
 - $\alpha(x), \beta(x)$: hash functions
- Separate chaining
 - Each $\text{table}[i]$ is maintained by a linked list


Linear probing with
 $h(x) = x \bmod 101$




- Linear probing
 - $h_i(x) = (h_0(x) + i) \bmod tableSize$
 - bad w/ primary clustering

Quadratic probing with
 $h(x) = x \bmod 101$

- Quadratic probing
 - $h_i(x) = (h_0(x) + i^2) \bmod \text{tableSize}$
 - bad w/ secondary clustering



Double hashing during the insertion of 58, 14, and 91



- Double hashing
 - $h_i(x) = (h_0(x) + i \cdot \beta(x)) \bmod \text{tableSize}$
 - $\beta(x)$: another hash function

Double Hashing의 예

$$h_i(x) = (h(x) + i f(x)) \bmod m$$

예: 입력 순서 15, 19, 28, 41, 67

0	
1	
2	15
3	
4	67
5	
6	19
7	
8	
9	28
10	
11	41
12	

$h_0(15) = h_0(28) = h_0(41) = h_0(67) = 2$

$h_1(67) = 3$

$h_1(28) = 8$

$h_1(41) = 10$

$$h(x) = x \bmod 13$$
$$f(x) = (x \bmod 11) + 1$$
$$h_i(x) = (h(x) + i f(x)) \bmod 13$$

삭제시 조심할 것

0	13
1	1
2	15
3	16
4	28
5	31
6	38
7	7
8	20
9	
10	
11	
12	25

(a) 원소 1 삭제

0	13
1	
2	15
3	16
4	28
5	31
6	38
7	7
8	20
9	
10	
11	
12	25


(b) 38 검색, 문제발생

0	13
1	DELETED
2	15
3	16
4	28
5	31
6	38
7	7
8	20
9	
10	
11	
12	25

(c) 표식을 해두면 문제없다

- Increasing the size of hash table
 - Load factor α
 - The rate of occupied slots in the table
 - A high load factor harms performance
 - We need to increase the size of hash table
 - Increasing the hash table
 - Roughly double the table size
 - Rehash all the items on the new table

Separate chaining





Each location of the hash table contains a reference to a linked list

The Efficiency of Hashing

- Approximate average # of comparisons for a search
 - Linear probing
 - $\frac{1}{2}(1 + \frac{1}{(1-\alpha)})$ for a successful search
 - $\frac{1}{2}(1 + \frac{1}{(1-\alpha)^2})$ for an unsuccessful search
 - Quadratic probing and double hashing
 - $-\ln(1-\alpha) / \alpha$ for a successful search
 - $\frac{1}{1-\alpha}$ for an unsuccessful search
 - Separate chaining (except the access for the indexing array)
 - $1 + \alpha/2$ for a successful search
 - α for an unsuccessful search

The Relative Efficiency of Collision-Resolution Methods



Good Hash Functions

- should be easy and fast to compute
- should scatter the data evenly on the hash table

Observation

- Load factor가 낮을 때는 probing 방법들은 대체로 큰 차이가 없다.
- Successful search는 insertion할 당시의 궤적을 그대로 밟는다.