

Lecture 20 – Typing Recursive Functions

COSE212: Programming Languages

Jihyeok Park



2023 Fall

- **TFAE** – FAE with **type system**.
 - **Type Checker** and **Typing Rules**
 - Interpreter and Natural Semantics
- Let's learn how to apply **type system** to recursive functions.
- RFAE is an extension of FAE with
 - ① **recursive functions**
 - ② **conditional expressions**
- **TRFAE** – RFAE with **type system**.
 - **Type Checker** and **Typing Rules**
 - Interpreter and Natural Semantics

1. Types for Recursive Functions

Recall: `mkRec` and Recursive Functions

`mkRec` in TFAE

2. TRFAE – RFAE with Type System

Concrete Syntax

Abstract Syntax

3. Type Checker and Typing Rules

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

1. Types for Recursive Functions

Recall: `mkRec` and Recursive Functions

`mkRec` in TFAE

2. TRFAE – RFAE with Type System

Concrete Syntax

Abstract Syntax

3. Type Checker and Typing Rules

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

A **recursive function** is a function that calls itself, and it is useful for **iterative processes** on **inductive data structures**.

Let's define a **recursive function** `sum` that computes the sum of integers from 1 to n in Scala:

```
def sum(n: Int): Int =  
  if (n < 1) 0           // base case  
  else n + sum(n - 1)    // recursive case  
  
sum(10) // 10 + 9 + 8 + 7 + 6 + 5 + 4 + 3 + 2 + 1 + 0 = 55
```

We learned two ways to support recursion functions:

① by introducing a **helper function** called `mkRec` in FAE as follows:

```
/* FAE */
val mkRec = body => {
  val fX = fY => {
    val f = x => fY(fY)(x);
    body(f)
  };
  fX(fX)
};
val sum = mkRec(sum => n => if (n < 1) 0 else n + sum(n + -1)); sum(10)
```

or ② by adding **new syntax** for recursive functions in RFAE:

```
/* RFAE */
def sum(n) = if (n < 1) 0 else n + sum(n + -1); sum(10)
```

Can we define `mkRec` in TFAE? **No!** Let's see why.

```
/* TFAE */  
val mkRec = (body: ???) => {  
  val fX = (fY: ???) => {  
    val f = (x: ???) => fY(fY)(x);  
    body(f)  
  };  
  fX(fX)  
};  
val sum = mkRec((sum: ???) => (n: ???) =>  
  if (n < 1) 0  
  else n + sum(n + -1));  
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

```
/* TFAE */  
val mkRec = (body: ???) => {  
  val fX = (fY: ???) => {  
    val f = (x: ???) => fY(fY)(x);  
    body(f)  
  };  
  fX(fX)  
};  
val sum = mkRec((sum: ???) => (n: Number) =>  
  if (n < 1) 0  
  else n + sum(n + -1));  
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.


```
/* TFAE */  
val mkRec = (body: ???) => {  
  val fX = (fY: ???) => {  
    val f = (x: ???) => fY(fY)(x);  
    body(f)  
  };  
  fX(fX)  
};  
val sum = mkRec((sum: Number => Number) => (n: Number) =>  
  if (n < 1) 0  
  else n + sum(n + -1));  
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

```
/* TFAE */  
val mkRec = (body: (Number => Number) => Number => Number) => {  
  val fX = (fY: ???) => {  
    val f = (x: ???) => fY(fY)(x);  
    body(f)  
  };  
  fX(fX)  
};  
val sum = mkRec((sum: Number => Number) => (n: Number) =>  
  if (n < 1) 0  
  else n + sum(n + -1));  
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

```
/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: ???) => {
    val f = (x: ???) => fY(fY)(x);
    body(f)                                     // f: Number => Number
  };
  fX(fX)
};
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

```
/* TFAE */  
val mkRec = (body: (Number => Number) => Number => Number) => {  
  val fX = (fY: ???) => {  
    val f = (x: Number) => fY(fY)(x);  
    body(f)                                // f: Number => Number  
  };  
  fX(fX)  
};  
val sum = mkRec((sum: Number => Number) => (n: Number) =>  
  if (n < 1) 0  
  else n + sum(n + -1));  
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

```
/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: ???) => {
    val f = (x: Number) => fY(fY)(x);    // fY(fY): Number => Number
    body(f)                             // f: Number => Number
  };
  fX(fX)
};
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

```
/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: T) => {
    val f = (x: Number) => fY(fY)(x);    // fY(fY): Number => Number
    body(f)                             // f: Number => Number
  };
  fX(fX)
};
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

Let T be the type of fY .

Then, T should be equal to $T \Rightarrow \text{Number} \Rightarrow \text{Number}$.

```
/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: T => Number => Number) => {
    val f = (x: Number) => fY(fY)(x);    // fY(fY): Number => Number
    body(f)                             // f: Number => Number
  };
  fX(fX)
};
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

Let T be the type of fY .

Then, T should be equal to $T \Rightarrow \text{Number} \Rightarrow \text{Number}$.

```
/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: (T => Number => Number) => Number => Number) => {
    val f = (x: Number) => fY(fY)(x);    // fY(fY): Number => Number
    body(f)                             // f: Number => Number
  };
  fX(fX)
};
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)
```

Let's fill out the parts of ??? for type annotations one by one.

Let T be the type of fY .

Then, T should be equal to $T \Rightarrow \text{Number} \Rightarrow \text{Number}$.


```

/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: ((T => Number => Number) => Number => Number) => Number
    => Number) => {
    val f = (x: Number) => fY(fY)(x);    // fY(fY): Number => Number
    body(f)                             // f: Number => Number
  };
  fX(fX)
};
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)

```

Let's fill out the parts of ??? for type annotations one by one.

Let T be the type of fY .

Then, T should be equal to $T \Rightarrow \text{Number} \Rightarrow \text{Number}$.

```

/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: (((T => Number => Number) => Number => Number) => Number
    => Number) => Number => Number) => {
    val f = (x: Number) => fY(fY)(x);    // fY(fY): Number => Number
    body(f)                             // f: Number => Number
  };
  fX(fX)
};
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)

```

Let's fill out the parts of ??? for type annotations one by one.

Let T be the type of fY .

Then, T should be equal to $T \Rightarrow \text{Number} \Rightarrow \text{Number}$.

```

/* TFAE */
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: (((T => Number => Number) => Number => Number) =>
    Number => Number) => Number => Number) => Number => Number) => {
    val f = (x: Number) => fY(fY)(x);    // fY(fY): Number => Number
    body(f)                             // f: Number => Number
  };
  fX(fX)
};

val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)

```

Let's fill out the parts of ??? for type annotations one by one.

Let T be the type of fY .

Then, T should be equal to $T \Rightarrow \text{Number} \Rightarrow \text{Number}$.

We cannot define such **recursive type** in TFAE.

Since Scala supports **recursive types**, we can define mkRec as follows:¹

```
type Number = BigInt
case class T(self: T => Number => Number) // T = T => Number => Number
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: T) => {
    val f = (x: Number) => fY.self(fY)(x);
    body(f)
  };
  fX(T(fX))
}
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)
```

¹This code is given by 최민석 and 최용욱 and slightly modified. Thanks!

Since Scala supports **recursive types**, we can define mkRec as follows:¹

```
import scala.language.implicitConversions
given Conversion[T, T => Number => Number] = _.self
given Conversion[T => Number => Number, T] = T(_)
type Number = BigInt
case class T(self: T => Number => Number) // T = T => Number => Number
val mkRec = (body: (Number => Number) => Number => Number) => {
  val fX = (fY: T) => {
    val f = (x: Number) => fY(fY)(x);
    body(f)
  };
  fX(fX)
}
val sum = mkRec((sum: Number => Number) => (n: Number) =>
  if (n < 1) 0
  else n + sum(n + -1));
sum(10)
```

However, we cannot do it in TFAE. So, let's add **type system** to RFAE!

¹This code is given by 최민석 and 최용욱 and slightly modified. Thanks!

1. Types for Recursive Functions

Recall: `mkRec` and Recursive Functions

`mkRec` in TFAE

2. TRFAE – RFAE with Type System

Concrete Syntax

Abstract Syntax

3. Type Checker and Typing Rules

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

Before defining TRFAE, guess the type of the following RFAE expressions:

```
/* RFAE */ def f(n) = n; f
```

Without type annotation for parameter `n`, we cannot guess its type.

```
/* RFAE */ def f(n: Number) = n; f
```

With type annotation for parameter `n`, we can guess its type.

How about this?

```
/* RFAE */ def f(n: Number) = f(n); f
```

Unfortunately, its return type is not clear and actually can be any type.

So, we need **type annotation** for both parameters and return types.

```
/* RFAE */ def f(n: Number): Number = f(n); f
```

Now, let's extend RFAE into TRFAE with **type system**.

```
/* TRFAE */  
def sum(n: Number): Number = {  
  if (n < 1) 0  
  else n + sum(n + -1)  
};  
sum(10) // 55
```

```
/* TRFAE */  
def fib(n: Number): Number = {  
  if (n < 2) n  
  else fib(n + -1) + fib(n + -2)  
};  
fib(7) // 13
```

For TRFAE, we need to consider the **type system** of the following cases:

- ① arithmetic comparison operators
- ② conditionals
- ③ recursive function definitions

We need to add following concrete syntax from RFAE for TRFAE:

- 1 **type annotations** for **recursive function definitions**
- 2 **types** (number, boolean, and arrow types)

```
// expressions
<expr> ::= ...
    | <expr> "<" <expr>
    | "if" "(" <expr> ")" <expr> "else" <expr>
    | "def" <id> "(" <id> ":" <type> ")" ":" <type>
      "=" <expr> ";" <expr>

// types
<type> ::= "(" <type> ")" // only for precedence
    | "Number"           // number type
    | "Boolean"          // boolean type
    | <type> "=>" <type> // arrow type
```

Similarly, we can define the **abstract syntax** of TRFAE as follows:

Expressions	Types
$\mathbb{E} \ni e ::= \dots$	$\mathbb{T} \ni \tau ::= \text{num} \quad (\text{NumT})$
$e < e \quad (\text{Lt})$	$\text{bool} \quad (\text{BoolT})$
$\text{if } (e) \ e \ \text{else } e \quad (\text{If})$	$\tau \rightarrow \tau \quad (\text{ArrowT})$
$\text{def } x(x:\tau):\tau = e; e \quad (\text{Rec})$	

We can define the abstract syntax of TRFAE in Scala as follows:

```
enum Expr:
  ...
  case Lt(left: Expr, right: Expr)
  case If(cond: Expr, thenExpr: Expr, elseExpr: Expr)
  case Rec(x: String, p: String, pty: Type, rty: Type, b: Expr, s: Expr)
enum Type:
  case NumT
  case BoolT
  case ArrowT(paramTy: Type, retTy: Type)
```

1. Types for Recursive Functions

Recall: `mkRec` and Recursive Functions

`mkRec` in TFAE

2. TRFAE – RFAE with Type System

Concrete Syntax

Abstract Syntax

3. Type Checker and Typing Rules

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

Let's ❶ design **typing rules** of TRFAE to define when an expression is well-typed in the form of:

$$\boxed{\Gamma \vdash e : \tau}$$

and ❷ implement a **type checker** in Scala according to typing rules:

```
def typeCheck(expr: Expr, tenv: TypeEnv): Type = ???
```

The type checker returns the **type** of e if it is well-typed, or rejects it and throws a **type error** otherwise.

Similar to TFAE, we will keep track of the **variable types** using a **type environment** Γ as a mapping from variable names to their types.

$$\text{Type Environments} \quad \Gamma \in \mathbb{X} \xrightarrow{\text{fin}} \mathbb{T} \quad (\text{TypeEnv})$$

```
type TypeEnv = Map[String, Type]
```

```
def typeCheck(expr: Expr, tenv: TypeEnv): Type = expr match
...
case Lt(left, right) =>
  mustSame(typeCheck(left, tenv), NumT)
  mustSame(typeCheck(right, tenv), NumT)
  BoolT
```

$$\boxed{\Gamma \vdash e : \tau}$$

$$\tau\text{-Lt} \frac{\Gamma \vdash e_1 : \text{num} \quad \Gamma \vdash e_2 : \text{num}}{\Gamma \vdash e_1 < e_2 : \text{bool}}$$

Type checker should do

- 1 check the types of e_1 and e_2 are num in Γ
- 2 return bool as the type of $e_1 < e_2$

```
def typeCheck(expr: Expr, tenv: TypeEnv): Type = expr match
...
case If(cond, thenExpr, elseExpr) => ???
```

$$\Gamma \vdash e : \tau$$

$$\tau\text{-If} \frac{\text{???}}{\Gamma \vdash \text{if } (e_0) \ e_1 \ \text{else} \ e_2 : \text{???}}$$

Let's think about the types of the following TRFAE expressions:

<code>if (true) 1 else 2</code>	should be	<code>Number</code>
<code>if (true) 1 else true</code>	might be	<code>Number?</code>
<code>(x: Boolean) => if (x) 1 else x</code>	cannot have a type	

Type checker cannot know the actual value of condition expression.

```
def typeCheck(expr: Expr, tenv: TypeEnv): Type = expr match
  ...
  case If(cond, thenExpr, elseExpr) => ???
```

$$\Gamma \vdash e : \tau$$

$$\tau\text{-If} \frac{\text{???}}{\Gamma \vdash \text{if } (e_0) \ e_1 \ \text{else} \ e_2 : \text{???}}$$

Let's think about the types of the following TRFAE:

<code>if (true) 1 else 2</code>	should be	<code>Number</code>
<code>if (true) 1 else true</code>		<code>REJECT</code>
<code>(x: Boolean) => if (x) 1 else x</code>		<code>REJECT</code>

Type checker cannot know the **actual value** of **condition expression**.

Let's accept only if **both types** of then- and else-expressions are **same**.

```
def typeCheck(expr: Expr, tenv: TypeEnv): Type = expr match
  ...
  case If(cond, thenExpr, elseExpr) =>
    mustSame(typeCheck(cond, tenv), BoolT)
    val thenTy = typeCheck(thenExpr, tenv)
    val elseTy = typeCheck(elseExpr, tenv)
    mustSame(thenTy, elseTy)
    thenTy
```

$$\boxed{\Gamma \vdash e : \tau}$$

$$\tau\text{-If} \frac{\Gamma \vdash e_0 : \text{bool} \quad \Gamma \vdash e_1 : \tau \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash \text{if } (e_0) e_1 \text{ else } e_2 : \tau}$$

Type checker should do

- ① check the type of e_0 is `bool` in Γ
- ② check the types of e_1 and e_2 are equal in Γ
- ③ return the type of e_1 (or e_2)


```
def interp(expr: Expr, env: Env): Value = expr match
...
case Rec(f, p, pty, rty, body, scope) =>
  ???
```

$$\boxed{\Gamma \vdash e : \tau}$$
$$\tau\text{-Rec} \frac{\text{???}}{\Gamma \vdash \text{def } x_0(x_1:\tau_1):\tau_2=e_2; e_3 : \text{???}}$$

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Rec(f, p, pty, rty, body, scope) =>

  mustSame(typeCheck(body, ???), rty)
  ???
```

$$\boxed{\Gamma \vdash e : \tau}$$

$$\tau\text{-Rec} \frac{\text{???} \vdash e_2 : \tau_2 \quad \text{???}}{\Gamma \vdash \text{def } x_0(x_1 : \tau_1) : \tau_2 = e_2; e_3 : \text{???}}$$

Type checker should do

- ① check the type of e_2 is τ_2 in ???
- ② ???

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Rec(f, p, pty, rty, body, scope) =>

  mustSame(typeCheck(body, tenv + (p -> pty)), rty)
  ???
```

$$\boxed{\Gamma \vdash e : \tau}$$

$$\tau\text{-Rec} \frac{\Gamma[x_1 : \tau_1] \vdash e_2 : \tau_2 \quad ???}{\Gamma \vdash \text{def } x_0(x_1 : \tau_1) : \tau_2 = e_2; e_3 : ???}$$

Type checker should do

- ① check the type of e_2 is τ_2 in the type environment extended with type information for parameter $(x_1 : \tau_1)$
- ② ???

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Rec(f, p, pty, rty, body, scope) =>
  val fty = ArrowT(pty, rty)
  mustSame(typeCheck(body, tenv + (f -> fty) + (p -> pty)), rty)
  ???
```

$$\boxed{\Gamma \vdash e : \tau}$$

$$\tau\text{-Rec} \frac{\Gamma[x_0 : \tau_1 \rightarrow \tau_2, x_1 : \tau_1] \vdash e_2 : \tau_2 \quad ???}{\Gamma \vdash \text{def } x_0(x_1 : \tau_1) : \tau_2 = e_2; e_3 : ???}$$

Type checker should do

- ① check the type of e_2 is τ_2 in the type environment extended with type information for function $(x_0 : \tau_1 \rightarrow \tau_2)$ and parameter $(x_1 : \tau_1)$
- ② ???

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Rec(f, p, pty, rty, body, scope) =>
  val fty = ArrowT(pty, rty)
  mustSame(typeCheck(body, tenv + (f -> fty) + (p -> pty)), rty)
  typeCheck(scope, ???)
```

$$\boxed{\Gamma \vdash e : \tau}$$

$$\tau\text{-Rec} \frac{\Gamma[x_0 : \tau_1 \rightarrow \tau_2, x_1 : \tau_1] \vdash e_2 : \tau_2 \quad ??? \vdash e_3 : \tau_3}{\Gamma \vdash \text{def } x_0(x_1 : \tau_1) : \tau_2 = e_2; e_3 : \tau_3}$$

Type checker should do

- ① check the type of e_2 is τ_2 in the type environment extended with type information for function $(x_0 : \tau_1 \rightarrow \tau_2)$ and parameter $(x_1 : \tau_1)$
- ② return the type of e_3 in ???

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Rec(f, p, pty, rty, body, scope) =>
  val fty = ArrowT(pty, rty)
  mustSame(typeCheck(body, tenv + (f -> fty) + (p -> pty)), rty)
  typeCheck(scope, tenv + (f -> fty))
```

$$\boxed{\Gamma \vdash e : \tau}$$

$$\tau\text{-Rec} \quad \frac{\Gamma[x_0 : \tau_1 \rightarrow \tau_2, x_1 : \tau_1] \vdash e_2 : \tau_2 \quad \Gamma[x_0 : \tau_1 \rightarrow \tau_2] \vdash e_3 : \tau_3}{\Gamma \vdash \text{def } x_0(x_1 : \tau_1) : \tau_2 = e_2; e_3 : \tau_3}$$

Type checker should do

- ① check the type of e_2 is τ_2 in the type environment extended with type information for function $(x_0 : \tau_1 \rightarrow \tau_2)$ and parameter $(x_1 : \tau_1)$
- ② return the type of e_3 in the type environment extended with type information for function $(x_0 : \tau_1 \rightarrow \tau_2)$

1. Types for Recursive Functions

Recall: `mkRec` and Recursive Functions

`mkRec` in TFAE

2. TRFAE – RFAE with Type System

Concrete Syntax

Abstract Syntax

3. Type Checker and Typing Rules

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

- Please see this document¹ on GitHub.
 - Implement `typeCheck` function.
 - Implement `interp` function.
- It is just an exercise, and you **don't need to submit** anything.
- However, some exam questions might be related to this exercise.

¹<https://github.com/ku-plrg-classroom/docs/tree/main/cose212/trfae>.

- Algebraic Data Types (1)

Jihyeok Park

`jihyeok_park@korea.ac.kr`

`https://plrg.korea.ac.kr`