

Lecture 5 – Identifiers (2)

COSE212: Programming Languages

Jihyeok Park



2023 Fall

- **Identifiers**
 - Bound identifiers
 - Free identifiers
 - Shadowing
- **VAE – AE with variables**
 - Concrete syntax
 - Abstract syntax

- **Identifiers**
 - Bound identifiers
 - Free identifiers
 - Shadowing
- **VAE – AE with variables**
 - Concrete syntax
 - Abstract syntax
- In this lecture, let's learn **natural semantics** for VAE, and implement an **interpreter** for VAE.

1. Evaluation with Environments

2. Interpreter and Natural Semantics for VAE

- Numbers

- Addition and Multiplication

- Variable Definition

- Variable Lookup

3. Examples

1. Evaluation with Environments

2. Interpreter and Natural Semantics for VAE

Numbers

Addition and Multiplication

Variable Definition

Variable Lookup

3. Examples

Let's evaluate the following VAE expressions:

```
/* VAE */  
val x = 1; {           // [ x -> 1 ]  
  val y = 2; {         // [ x -> 1, y -> 2 ]  
    x + y              // x + y = 1 + 2 = 3  
  }  
}
```

Let's evaluate the following VAE expressions:

```
/* VAE */  
val x = 1; {           // [ x -> 1 ]  
  val y = 2; {         // [ x -> 1, y -> 2 ]  
    x + y              // x + y = 1 + 2 = 3  
  }  
}
```

How to evaluate the expression $x + y$ into the value 3?

$$\vdash x + y \Rightarrow 3$$

Let's evaluate the following VAE expressions:

```
/* VAE */  
val x = 1; {           // [ x -> 1 ]  
  val y = 2; {         // [ x -> 1, y -> 2 ]  
    x + y              // x + y = 1 + 2 = 3  
  }  
}
```

How to evaluate the expression $x + y$ into the value 3?

$$\vdash x + y \Rightarrow 3$$

We need to keep track of the **environment** that maps identifiers to values:

$$[x \mapsto 1, y \mapsto 2] \vdash x + y \Rightarrow 3$$


```
type Value = BigInt           // values
def interp(expr: Expr): Value = ... // interpreter
```

$$\vdash e \Rightarrow n$$

Originally, the interpreter takes an expression and returns a value.

```
type Value = BigInt                                // values
type Env = Map[String, Int]                        // environments
def interp(expr: Expr, env: Env): Value = ... // interpreter
```

$$\sigma \vdash e \Rightarrow n$$

Now, we extend the interpreter to take an **environment** as well.

```
type Value = BigInt                                // values
type Env = Map[String, Int]                        // environments
def interp(expr: Expr, env: Env): Value = ...    // interpreter
```

$$\sigma \vdash e \Rightarrow n$$

Now, we extend the interpreter to take an **environment** as well.

For example, we want to evaluate the expression $x + y$ into the value 3 with the environment $[x \mapsto 1, y \mapsto 2]$:

```
val env : Env    = Map("x" -> 1, "y" -> 2)    // [ x -> 1, y -> 2 ]
val expr: Expr   = Expr("x + y")              // Add(Id("x"), Id("y"))
val v  : Value   = interp(expr, env)           // 3
```

$$[x \mapsto 1, y \mapsto 2] \vdash x + y \Rightarrow 3$$

For VAE, we need to 1) implement the **interpreter** with **environments**

```
def interp(expr: Expr, env: Env): Value = ???
```

For VAE, we need to 1) implement the **interpreter** with **environments**

```
def interp(expr: Expr, env: Env): Value = ???
```

and 2) define the **natural semantics** with **environments**.

$$\sigma \vdash e \Rightarrow n$$

We read it as “*the **expression** e evaluates to the **number** n with the **environment** σ .*”

For VAE, we need to 1) implement the **interpreter** with **environments**

```
def interp(expr: Expr, env: Env): Value = ???
```

and 2) define the **natural semantics** with **environments**.

$$\sigma \vdash e \Rightarrow n$$

We read it as “*the **expression** e evaluates to the **number** n with the **environment** σ .*”

We use the following notations:

Expressions	e	(Expr)
Environments	$\sigma \in \mathbb{X} \xrightarrow{\text{fin}} \mathbb{Z}$	(Env)
Integers	$n \in \mathbb{Z}$	(BigInt)
Identifiers	$x \in \mathbb{X}$	(String)

1. Evaluation with Environments

2. Interpreter and Natural Semantics for VAE

- Numbers

- Addition and Multiplication

- Variable Definition

- Variable Lookup

3. Examples

The **interpreter** for VAE:

```
def interp(expr: Expr, env: Env): Value = expr match
  case Num(n)           => ???
  case Add(l, r)        => ???
  case Mul(l, r)        => ???
  case Val(x, e, b)     => ???
  case Id(x)            => ???
```

The inference rule of each case for the **natural semantics** of VAE:

$$\sigma \vdash e \Rightarrow n$$

Expressions	$e ::= n$	(Num)
	$e + e$	(Add)
	$e \times e$	(Mul)
	$\text{val } x = e; e$	(Val)
	x	(Id)


```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Num(n)          => ???
  ...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{NUM} \frac{\text{???}}{\sigma \vdash n \Rightarrow \text{???}}$$

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Num(n)      => n
  ...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{Num} \frac{}{\sigma \vdash n \Rightarrow n}$$

The **expression** n evaluates to the **number** n with the **environment** σ .

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Add(l, r)    => ???
  ...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{ADD} \frac{\text{???}}{\sigma \vdash e_1 + e_2 \Rightarrow \text{???}}$$

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Add(l, r)    => interp(l, env) + interp(r, env)
  ...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{ADD} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma \vdash e_2 \Rightarrow n_2}{\sigma \vdash e_1 + e_2 \Rightarrow n_1 + n_2}$$

The **expression** $e_1 + e_2$ evaluates to the **number** $n_1 + n_2$ with the **environment** σ when

- 1 The **expression** e_1 evaluates to the **number** n_1 with the **environment** σ .
- 2 The **expression** e_2 evaluates to the **number** n_2 with the **environment** σ .

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Mul(l, r)    => interp(l, env) * interp(r, env)
...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{MUL} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma \vdash e_2 \Rightarrow n_2}{\sigma \vdash e_1 \times e_2 \Rightarrow n_1 \times n_2}$$

The **expression** $e_1 \times e_2$ evaluates to the **number** $n_1 \times n_2$ with the **environment** σ when

- 1 The **expression** e_1 evaluates to the **number** n_1 with the **environment** σ .
- 2 The **expression** e_2 evaluates to the **number** n_2 with the **environment** σ .

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Val(x, e, b) => ???
...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{VAL} \frac{\text{???}}{\sigma \vdash \text{val } x = e_1; e_2 \Rightarrow \text{???}}$$

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Val(x, e, b) => ... interp(e, env) ...
  ...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{VAL} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \dots}{\sigma \vdash \text{val } x = e_1; e_2 \Rightarrow ???}$$

The **expression** `val x = e1; e2` evaluates to the **number** ??? with the **environment** σ when

- ① The **expression** e_1 evaluates to the **number** n_1 with the **environment** σ .
- ② ...

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Val(x, e, b) => ... env + (x -> interp(e, env)) ...
...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{VAL} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma[x \mapsto n_1] \quad \dots}{\sigma \vdash \text{val } x = e_1; e_2 \Rightarrow ???}$$

The **expression** $\text{val } x = e_1; e_2$ evaluates to the **number** $???$ with the **environment** σ when

- ① The **expression** e_1 evaluates to the **number** n_1 with the **environment** σ .
- ② ... the **environment** $\sigma[x \mapsto n_1]$.


```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Val(x, e, b) => interp(b, env + (x -> interp(e, env)))
  ...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{VAL} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma[x \mapsto n_1] \vdash e_2 \Rightarrow n_2}{\sigma \vdash \text{val } x = e_1; e_2 \Rightarrow n_2}$$

The **expression** $\text{val } x = e_1; e_2$ evaluates to the **number** n_2 with the **environment** σ when

- ① The **expression** e_1 evaluates to the **number** n_1 with the **environment** σ .
- ② The **expression** e_2 evaluates to the **number** n_2 with the **environment** $\sigma[x \mapsto n_1]$.

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Id(x)          => ???
  ...
```

$$\sigma \vdash e \Rightarrow n$$

$$\text{ID} \frac{\text{???}}{\sigma \vdash x \Rightarrow \text{???}}$$

```
def interp(expr: Expr, env: Env): Value = expr match
...
case Id(x)          => env.getOrElse(x, error(s"unknown identifier: $x"))
...
)
```

$$\boxed{\sigma \vdash e \Rightarrow n}$$

$$\text{ID} \frac{x \in \text{Domain}(\sigma)}{\sigma \vdash x \Rightarrow \sigma(x)}$$

The **expression** x evaluates to the **number** $\sigma(x)$ with the **environment** σ when

- 1 The **variable** x is in the domain of the **environment** σ .

1. Evaluation with Environments

2. Interpreter and Natural Semantics for VAE

Numbers

Addition and Multiplication

Variable Definition

Variable Lookup

3. Examples

Example 1

$$\begin{array}{c} \text{ID} \frac{x \in \text{Domain}([x \mapsto 1])}{[x \mapsto 1] \vdash x \Rightarrow 1} \quad \text{NUM} \frac{}{[x \mapsto 1] \vdash 2 \Rightarrow 2} \\ \text{NUM} \frac{}{\emptyset \vdash 1 \Rightarrow 1} \quad \text{ADD} \frac{}{[x \mapsto 1] \vdash x + 2 \Rightarrow 3} \\ \text{VAL} \frac{}{\emptyset \vdash \text{val } x = 1; x + 2 \Rightarrow 3} \end{array}$$

$$\begin{array}{c}
 \text{NUM} \frac{}{\emptyset \vdash 1 \Rightarrow 1} \quad \text{ID} \frac{x \in \text{Domain}([x \mapsto 1])}{[x \mapsto 1] \vdash x \Rightarrow 1} \quad \text{NUM} \frac{}{[x \mapsto 1] \vdash 2 \Rightarrow 2} \\
 \text{VAL} \frac{\text{ADD} \frac{}{[x \mapsto 1] \vdash x + 2 \Rightarrow 3}}{\emptyset \vdash \text{val } x = 1; x + 2 \Rightarrow 3}
 \end{array}$$

We can name environments σ_i to make the derivation tree concise.

$$\begin{array}{c}
 \text{NUM} \frac{}{\emptyset \vdash 1 \Rightarrow 1} \quad \text{ID} \frac{x \in \text{Domain}(\sigma_0)}{\sigma_0 \vdash x \Rightarrow 1} \quad \text{NUM} \frac{}{\sigma_0 \vdash 2 \Rightarrow 2} \\
 \text{VAL} \frac{\text{ADD} \frac{}{\sigma_0 \vdash x + 2 \Rightarrow 3}}{\emptyset \vdash \text{val } x = 1; x + 2 \Rightarrow 3}
 \end{array}$$

where

$$\sigma_0 = [x \mapsto 1]$$

$$\begin{array}{c}
 \text{NUM} \frac{}{\emptyset \vdash 1 \Rightarrow 1} \quad \text{VAL} \frac{\text{NUM} \frac{}{\sigma_0 \vdash 2 \Rightarrow 2} \quad \text{ADD} \frac{\text{ID} \frac{x \in \text{Domain}(\sigma_1)}{\sigma_1 \vdash x \Rightarrow 1} \quad \text{ID} \frac{y \in \text{Domain}(\sigma_1)}{\sigma_1 \vdash y \Rightarrow 2}}{\sigma_1 \vdash x + y \Rightarrow 3}}{\sigma_0 \vdash \text{val } y = 2; x + y \Rightarrow 3}} \\
 \text{VAL} \frac{}{\emptyset \vdash \text{val } x = 1; \{\text{val } y = 2; x + y\} \Rightarrow 3}
 \end{array}$$

where

$$\begin{aligned}
 \sigma_0 &= [x \mapsto 1] \\
 \sigma_1 &= [x \mapsto 1, y \mapsto 2]
 \end{aligned}$$

Example 3

$$\begin{array}{c}
 \text{NUM} \frac{}{\emptyset \vdash 1 \Rightarrow 1} \quad \text{VAL} \frac{\text{NUM} \frac{}{\sigma_0 \vdash 2 \Rightarrow 2} \quad \text{ID} \frac{x \in \text{Domain}(\sigma_1)}{\sigma_1 \vdash x \Rightarrow 2}}{\sigma_0 \vdash \text{val } x = 2; x \Rightarrow 2} \quad \text{ID} \frac{x \in \text{Domain}(\sigma_0)}{\sigma_0 \vdash x \Rightarrow 1} \\
 \text{VAL} \frac{\text{ADD} \frac{\sigma_0 \vdash \text{val } x = 2; x \Rightarrow 2 \quad \sigma_0 \vdash x \Rightarrow 1}{\sigma_0 \vdash \{\text{val } x = 2; x\} + x \Rightarrow 3}}{\emptyset \vdash \text{val } x = 1; \{\text{val } x = 2; x\} + x \Rightarrow 3}
 \end{array}$$

where

$$\begin{aligned}
 \sigma_0 &= [x \mapsto 1] \\
 \sigma_1 &= [x \mapsto 2]
 \end{aligned}$$

Example 4

$$\begin{array}{c} \text{NUM} \frac{}{\emptyset \vdash 1 \Rightarrow 1} \quad \text{ID} \frac{x \in \text{Domain}(\sigma_0)}{\sigma_0 \vdash x \Rightarrow 1} \\ \text{VAL} \frac{}{\emptyset \vdash \text{val } x = 1; x \Rightarrow 1} \quad \text{ID} \frac{x \notin \text{Domain}(\emptyset)}{\emptyset \vdash x \Rightarrow \text{FAIL}} \\ \text{VAL} \frac{}{\emptyset \vdash \{\text{val } x = 1; x\} + x \Rightarrow \text{FAIL}} \end{array}$$

where

$$\sigma_0 = [x \mapsto 1]$$

```
def interp(expr: Expr, env: Env): Value = expr match
  case Num(n)          => n
  case Add(l, r)        => interp(l, env) + interp(r, env)
  case Mul(l, r)        => interp(l, env) * interp(r, env)
  case Val(x, e, b)     => interp(b, env + (x -> interp(e, env)))
  case Id(x)            => env.getOrElse(x, error(s"unknown variable: $x"))
```

$$\boxed{\sigma \vdash e \Rightarrow n}$$

$$\text{NUM} \frac{}{\sigma \vdash n \Rightarrow n}$$

$$\text{ADD} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma \vdash e_2 \Rightarrow n_2}{\sigma \vdash e_1 \times e_2 \Rightarrow n_1 \times n_2}$$

$$\text{MUL} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma \vdash e_2 \Rightarrow n_2}{\sigma \vdash e_1 \times e_2 \Rightarrow n_1 \times n_2}$$

$$\text{VAL} \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma[x \mapsto n_1] \vdash e_2 \Rightarrow n_2}{\sigma \vdash \text{val } x = e_1; e_2 \Rightarrow n_2}$$

$$\text{ID} \frac{x \in \text{Domain}(\sigma)}{\sigma \vdash x \Rightarrow \sigma(x)}$$

- Please see this document¹ on GitHub.
 - Implement `interp` function.
 - Implement `freeIds` function.
 - Implement `bindingIds` function.
 - Implement `boundIds` function.
 - Implement `shadowedIds` function.
- It is just an exercise, and you **don't need to submit** anything.
- However, some exam questions might be related to this exercise.

¹<https://github.com/ku-plrg-classroom/docs/tree/main/cose212/vae>.

- First-Order Functions

Jihyeok Park

jihyeok_park@korea.ac.kr

<https://plrg.korea.ac.kr>