

# Tree Path Assignments to Sets-A Generalization of the Consecutive Ones Property

N.S. Narayanaswamy<sup>1</sup> and Anju Srinivasan Zabil<sup>2</sup>

Indian Institute of Technology Madras, Chennai, [swamy@cse.iitm.ernet.in](mailto:swamy@cse.iitm.ernet.in),  
Indian Institute of Technology Madras, Chennai, [anjuzabil@gmail.com](mailto:anjuzabil@gmail.com)

**Abstract.** We consider the following constraint satisfaction problem: Given a set  $\mathcal{F}$  of subsets of a finite set  $U$  of cardinality  $n$ , a tree  $T$  on  $n$  vertices, and an assignment of paths from  $T$  to each of the subsets, does there exist a bijection  $f : U \rightarrow \{v_1, \dots, v_n\}$  such that for each element of  $\mathcal{F}$ , its image under  $f$  is same as the path assigned to it? A path assignment to a given set of subsets is called *feasible* if there exists such a bijection. In this paper, we characterize feasible path assignments to a given set of subsets and a tree. This result is a natural generalization of results on matrices with the Consecutive Ones Property (COP) which can be viewed as a special instance of the problem in which the given tree is a path on  $n$  vertices. We also present a characterization of set systems and trees which have a feasible path assignment. We also show that testing for a feasible path assignment is isomorphism-complete. On the other hand, it is known that if the given tree is a path a feasible assignment can be found in polynomial time, and we observe that it can actually be done in logspace.

## 1 Introduction

Consecutive ones property (COP) of binary matrices is a widely studied combinatorial problem. The problem is to rearrange rows(columns) of a binary matrix in such a way that every column(rows) has its 1s occur consecutively. If this is possible the matrix is said to have COP. It has several practical applications in diverse fields including scheduling[HL06], information retrieval[Kou77] and computational biology[ABH98]. Further, it is a tool in graph theory[Gol04] for interval graph recognition, characterization of hamiltonian graphs, and in integer linear programming[HT02, HL06]. Recognition of COP is polynomial time solvable by several algorithms. PQ trees[BL76], variations of PQ trees[MM96, Hsu01, Hsu02, McC04], ICPIA[NS09] are the main ones. The problem of COP can be easily seen as a simple constraint satisfaction problem involving a system of sets from a universe. Every column of the binary matrix can be converted into a set of integers which are the indices of the rows with 1s in that column. When observed in this context, if the matrix has COP, a reordering of its rows will result in sets that have only consecutive integers. In other words, the sets are intervals. Indeed the problem now becomes finding interval assignments to the given set system [NS09] with a single permutation of the universe (set of row indices) permutes each set to its interval. The result in [NS09] characterize interval assignments to the sets which can be obtained from a single permutation of the rows. They show that for each set, the interval cardinality assigned to it must be same as the cardinality of the set, and the intersection cardinality of any two sets must be same as the intersection cardinality of the corresponding intervals. While this is naturally a necessary condition, it is shown that it is indeed sufficient. Such an interval assignment is called an Intersection Cardinality Preserving Interval Assignment (ICPIA). The idea of decomposing a given 0-1 matrix into prime matrices is then taken from [Hsu02] to test if an ICPIA exists for a given set system.

**Our Work:** A natural generalization of the interval assignment problem is feasible tree path assignments to a set system which is the topic of this paper. The problem is defined as follows - given a set system  $\mathcal{F}$  from a universe  $U$  and a tree  $T$ , does there exist a bijection from the  $U$  to the vertices of  $T$  such that each set in the system maps to a path in  $T$ . We refer to this as the Tree Path Assignment problem for an input  $(\mathcal{F}, T)$  pair. As a special case if  $T$  is a path the problem becomes the interval assignment problem. We focus on the question of generalizing the notion of an ICPIA [NS09] to characterize feasible path assignments. We show that for a given set system, a tree  $T$ , and an assignment of paths from  $T$  to the sets, there is a

bijection between  $U$  and  $V(T)$  if and only if all intersection cardinalities among any 3 sets (not necessarily distinct) is same as the intersection cardinality of the paths assigned to them. This characterization is proved constructively and it gives a natural data structure that stores all the relevant bijections between  $U$  and  $V(T)$ . Further, it also gives an efficient algorithm to test if a path assignment to the sets is feasible. This also naturally generalizes the result in [NS09].

It is an interesting fact that for a matrix with the COP, the intersection graph of the corresponding set system is an interval graph. A similar connection to a subclass of chordal graphs, and this subclass contains interval graphs, exists for the generalization of COP. In this case, the intersection graph of the corresponding set system must be a *path chordal* graph. Chordal graphs are of great significance, extensively studied, and have several applications. One of the well known and interesting properties of a chordal graphs is its connection with intersection graphs[Gol04]. For every chordal graph, there exists a tree and a family of subtrees of this tree such that the intersection graph of this family is isomorphic to the chordal graph[Ren70, Gav78, BP93]. Certain format of these trees are called clique trees[APY92] of the graph which is a compact representation of the chordal graph. There has also been work done on the generalization of clique trees to clique hypergraphs[KM02]. If the chordal graph can be represented as the intersection graph of paths in a tree, then the graph is called path graph[Gol04] or path chordal graph. Therefore, it is clear that if there is a bijection from  $U$  to  $V(T)$  such that the sets map to paths, then the intersection graph of the set system is indeed a path chordal graph. This is, however, only a necessary condition and can be checked efficiently, as path graph recognition is polynomial solvable[Gav78, Sch93]. Indeed, it is possible to construct a set system and tree, such that the intersection graph is a path chordal graph, but there is no bijection between  $U$  and  $V(T)$  such that the sets map to paths. This connection indeed suggests that our problem is indeed as hard as path graph isomorphism. Further path graph isomorphism is known to be isomorphism-complete, see for example [KKLV10]. In the second part of this paper, we decompose our search for a bijection between  $U$  and  $V(T)$  into subproblems. Each subproblem is on a set system in which for each set, there is another set in the set system with which the intersection is *strict*- there is a non-empty intersection, but neither is contained in the other. This is in the spirit of results in [Hsu02, NS09] where to test for COP in a given matrix, the COP problem is solved on an equivalent set of prime matrices. Our decomposition localizes the challenge of path graph isomorphism to two problems.

Finally, we show that Tree Path Assignment is isomorphism-complete. We also point out Consecutive Ones Testing is in Logspace from two different results in the literature [KKLV10, McC04]. To the best of our knowledge this observation has not been made earlier.

**Roadmap:** In Section 2 we present the necessary preliminaries, in Section 3 we present our characterization of feasible tree path assignments, and in Section 4 we present the characterizing subproblems for finding a bijection between  $U$  and  $V(T)$  such that sets map to tree paths. Finally, in Section 5 we conclude by showing that Tree Path Assignment is GI-Complete, and also observe that Consecutive Ones Testing is in Logspace.

## 2 Preliminaries

In this paper, the collection  $\mathcal{F} = \{S_i \mid S_i \subseteq U, S_i \neq \emptyset, i \in I\}$  is a *set system* of universe,  $U = \{1, \dots, n\}$ . Moreover, a set system is assumed to “cover” the universe, i.e.  $\bigcup_{i \in I} S_i = U$ .

The graph  $T = (V, E)$  represents a given tree with  $|V| = n$ . Further, for simplicity,  $V$  is defined as  $\{1, \dots, n\}$ . All paths referred to in this paper are paths of  $T$  unless explicitly specified.

A *path assignment*  $\mathcal{A}$  to  $\mathcal{F}$  is defined as a set assignment where second universe is the vertex set  $V$  of a given tree  $T$  and every second subset in the ordered pairs is a path in this tree. Formally, the definition is as follows.

$$\mathcal{A} = \{(S_i, P_i) \mid S_i \in \mathcal{F}, P_i \subseteq V \text{ s.t. } T[P_i] \text{ is a path, } i \in I\}$$

In other words,  $P_i$  is the path on the tree  $T$  assigned to  $S_i$  in  $\mathcal{A}$ . As mentioned before for set systems, the paths cover the whole tree, i.e.  $\bigcup_{i \in I} P_i = V$

Generalizing the definition of *feasibility* in [NS09] to a set assignment, a path assignment  $\mathcal{A}$  is defined to be *feasible* if there exists a bijection defined as follows.

$$\sigma : U \rightarrow V(T), \text{ such that } \sigma(S_i) = P_i \text{ for all } i \in I, \sigma \text{ is a bijection} \quad (1)$$

Let  $X$  be a partially ordered set with  $\preceq$  being the partial order on  $X$ .  $\text{mub}(X)$  represents an element in  $X$  which is a maximal upper bound on  $X$ .  $X_m \in X$  is a maximal upper bound of  $X$  if  $\nexists X_q \in X$  such that  $X_m \preceq X_q$ .

The set  $I$  represents the index set  $[m]$ . If index  $i$  is used without further qualification, it is meant to be  $i \in I$ . Any function, if not defined on a domain of sets, when applied on a set is understood as the function applied to each of its elements. i.e. for any function  $f$  defined with domain  $U$ , the abuse of notation is as follows;  $f(S)$  is used instead of  $\hat{f}(S)$  where  $\hat{f}(S) = \{y \mid y = f(x), x \in S\}$ .

When referring to a tree as  $T$  it could be a reference to the tree itself, or the vertices of the tree. This will be clear from the context.

Finally, an in-tree is a directed rooted tree in which all edges are directed toward to the root.

### 3 Characterization of Feasible Tree Path Assignment

Consider a path assignment  $\mathcal{A} = \{(S_i, P_i) \mid S_i \in \mathcal{F}, P_i \text{ is a path from } T, i \in [m]\}$  to a set system  $\mathcal{F} = \{S_i \mid S_i \subseteq U, i \in [m]\}$ , where  $T$  is a given tree,  $U$  is the set system's universe and  $m$  is the number of sets in  $\mathcal{F}$ . We call  $\mathcal{A}$  an *Intersection Cardinality Preserving Path Assignment (ICPPA)* if it has the following properties.

- i.  $|S_i| = |P_i|$  for all  $i \in [m]$
- ii.  $|S_i \cap S_j| = |P_i \cap P_j|$  for all  $i, j \in [m]$
- iii.  $|S_i \cap S_j \cap S_k| = |P_i \cap P_j \cap P_k|$  for all  $i, j, k \in [m]$

**Lemma 1.** *If  $\mathcal{A}$  is an ICPPA, and  $(S_1, P_1), (S_2, P_2), (S_3, P_3) \in \mathcal{A}$ , then  $|S_1 \cap (S_2 \setminus S_3)| = |P_1 \cap (P_2 \setminus P_3)|$ .*

*Proof.*  $|S_1 \cap (S_2 \setminus S_3)| = |(S_1 \cap S_2) \setminus S_3| = |S_1 \cap S_2| - |S_1 \cap S_2 \cap S_3|$ . Due to conditions (ii) and (iii) of ICPPA,  $|S_1 \cap S_2| - |S_1 \cap S_2 \cap S_3| = |P_1 \cap P_2| - |P_1 \cap P_2 \cap P_3| = |(P_1 \cap P_2) \setminus P_3| = |P_1 \cap (P_2 \setminus P_3)|$ . Thus lemma is proven.  $\square$

**Lemma 2.** *Consider four paths in a tree  $Q_1, Q_2, Q_3, Q_4$  such that they have nonempty pairwise intersection and  $Q_1, Q_2$  share a leaf. Then there exists distinct  $i, j, k \in \{1, 2, 3, 4\}$  such that,  $Q_1 \cap Q_2 \cap Q_3 \cap Q_4 = Q_i \cap Q_j \cap Q_k$ .*

*Proof.* *Case 1:* Consider  $Q_3 \cap Q_4$  and let us call it  $Q$ . This is clearly a path (intersection of two paths is a path). Suppose  $Q$  does not intersect with  $Q_1 \setminus Q_2$ , i.e.  $Q \cap (Q_1 \setminus Q_2) = \emptyset$ . Then  $Q \cap Q_1 \cap Q_2 = Q \cap Q_2$ . Similarly, if  $Q \cap (Q_2 \setminus Q_1) = \emptyset$ ,  $Q \cap Q_1 \cap Q_2 = Q \cap Q_1$ . Thus it is clear that if the intersection of any two paths does not intersect with any of the set differences of the remaining two paths, the claim in the lemma is true. *Case 2:* Let us consider the complement of the previous case. i.e. the intersection of any two paths intersects with both the set differences of the other two. First let us consider  $Q \cap (Q_1 \setminus Q_2) \neq \emptyset$  and  $Q \cap (Q_2 \setminus Q_1) \neq \emptyset$ , where  $Q = Q_3 \cap Q_4$ . Since  $Q_1$  and  $Q_2$  share a leaf, there is exactly one vertex at which they branch off from the path  $Q_1 \cap Q_2$  into two paths  $Q_1 \setminus Q_2$  and  $Q_2 \setminus Q_1$ . Let this vertex be  $v$ . It is clear that if path  $Q_3 \cap Q_4$ , must intersect with paths  $Q_1 \setminus Q_2$  and  $Q_2 \setminus Q_1$ , it must contain  $v$  since these are paths from a tree. Moreover,  $Q_3 \cap Q_4$  intersects with  $Q_1 \cap Q_2$  at exactly  $v$  and only at  $v$  which means that  $Q_1 \cap Q_2$  does not intersect with  $Q_3 \setminus Q_4$  or  $Q_4 \setminus Q_3$  which contradicts initial condition of this case. Thus this case cannot occur and case 1 is the only possible scenario.

Thus lemma is proven  $\square$

In the remaining part of this section we show that a path assignment is feasible if and only if it is an ICPPA. One direction of this claim is clear: that if a path assignment is feasible, then all intersection cardinalities are preserved, that is the path assignment is an ICPPA. The reason is that a feasible path assignment has an associated bijection between  $U$  and  $V(T)$  such that the sets map to paths. The rest of the section is devoted to constructively proving that it is sufficient, for a path assignment to be an ICPPA. At a top-level, the constructive approaches refine the path assignment iteratively, such that at the end of each iteration we have a path assignment, and finally we have a family of bijections. First we present and then prove the correctness of Algorithm 1. This algorithm refines the path assignment by considering pairs of paths that share a leaf.

---

**Algorithm 1** Permutations from an ICPPA  $\{(S_i, P_i) | i \in I\}$

---

```

Let  $\Pi_0 = \{(S_i, P_i) | i \in I\}$ 
 $j = 1$ ;
while There is  $(P_1, Q_1), (P_2, Q_2) \in \Pi_{j-1}$  with  $Q_1$  and  $Q_2$  having a common leaf do
     $\Pi_j = \Pi_{j-1} \setminus \{(P_1, Q_1), (P_2, Q_2)\}$ ;
     $\Pi_j = \Pi_j \cup \{(P_1 \cap P_2, Q_1 \cap Q_2), (P_1 \setminus P_2, Q_1 \setminus Q_2), (P_2 \setminus P_1, Q_2 \setminus Q_1)\}$ ;
     $j = j + 1$ ;
end while
 $\Pi = \Pi_j$ ;
Return  $\Pi$ ;

```

---

**Lemma 3.** *In Algorithm 1, at the end of  $j$ th iteration,  $j \geq 0$ , of the while loop of Algorithm 1, the following invariants are maintained.*

- Invariant I:  $Q$  is a path in  $T$  for each  $(P, Q) \in \Pi_j$
- Invariant II:  $|P| = |Q|$  for each  $(P, Q) \in \Pi_j$
- Invariant III: For any two  $(P, Q), (P', Q') \in \Pi_j$ ,  $|P' \cap P''| = |Q' \cap Q''|$ .
- Invariant IV: For any three,  $(P', Q'), (P'', Q''), (P, Q) \in \Pi_j$ ,  $|P' \cap P'' \cap P| = |Q' \cap Q'' \cap Q|$ .

*Proof.* Proof is by induction on the number of iterations,  $j$ . In the rest of the proof, the term “new sets” will refer to the new sets added in  $j$ th iteration as defined in line 4 of Algorithm 1, i.e. the following three assignment pairs for some  $(P_1, Q_1), (P_2, Q_2) \in \Pi_{j-1}$  where  $Q_1$  and  $Q_2$  intersect and share a leaf:  $(P_1 \cap P_2, Q_1 \cap Q_2)$ , or  $(P_1 \setminus P_2, Q_1 \setminus Q_2)$ , or  $(P_2 \setminus P_1, Q_2 \setminus Q_1)$ .

The base case,  $\Pi_0 = \{(S_i, P_i) | i \in [m]\}$ , is trivially true since it is the input which is an ICPPA. Assume the lemma is true till the  $j - 1$  iteration. Consider  $j$ th iteration:

If  $(P, Q), (P', Q')$  and  $(P'', Q'')$  are in  $\Pi_j$  and  $\Pi_{j-1}$ , all the invariants are clearly true because they are from  $j - 1$  iteration.

If  $(P, Q)$  is in  $\Pi_j$  and not in  $\Pi_{j-1}$ , then it must be one of the new sets added in  $\Pi_j$ . Since  $(P_1, Q_1)$  and  $(P_2, Q_2)$  are from  $\Pi_{j-1}$  and  $Q_1, Q_2$  intersect and have a common leaf, it can be verified that the new sets are also paths.

By hypothesis for invariant III, invariant II also holds for  $(P, Q)$  no matter which new set in  $\Pi_j$  it is.

To prove invariant III, if  $(P, Q)$  and  $(P', Q')$  are not in  $\Pi_{j-1}$ , then they are both new sets and invariant III holds trivially (new sets are disjoint). Next consider  $(P, Q), (P', Q') \in \Pi_j$  with only one of them, say  $(P', Q')$ , in  $\Pi_{j-1}$ . Then  $(P, Q)$  is one of the new sets added in line 4. It is easy to see that if  $(P, Q)$  is  $(P_1 \cap P_2, Q_1 \cap Q_2)$ , then due to invariant IV in hypothesis, invariant III becomes true in this iteration. Similarly, using lemma 1 invariant III is proven if  $(P, Q)$  is  $(P_1 \setminus P_2, Q_1 \setminus Q_2)$ , or  $(P_2 \setminus P_1, Q_2 \setminus Q_1)$ .

To prove invariant IV, consider three assignments  $(P, Q), (P', Q'), (P'', Q'')$ . If at least two of these pairs are in not  $\Pi_{j-1}$ , then they are any two of the new sets. Note that these new sets are disjoint and hence if  $(P', Q'), (P'', Q'')$  are any of these sets,  $|P \cap P' \cap P''| = |Q \cap Q' \cap Q''| = 0$  and invariant IV is true. Now we consider the case if at most one of  $(P, Q), (P', Q'), (P'', Q'')$  is not in  $\Pi_{j-1}$ . If none of them are not in  $\Pi_{j-1}$

(i.e. all of them are in  $\Pi_{j-1}$ ), invariant IV is clearly true. Consider the case where exactly one of them is not in  $\Pi_{j-1}$ . w.l.o.g let that be  $(P, Q)$  and it could be any one of the new sets. If  $(P, Q)$  is  $(P_1 \cap P_2, Q_1 \cap Q_2)$ , from lemma 2 and invariant III hypothesis, invariant IV is proven. Similarly if  $(P, Q)$  is any of the other new sets, invariant IV is proven by also using lemma 1.  $\square$

It can be observed that the output of algorithm 1 is such that every leaf is incident on at most a single path in the new set of assignments. This is due to the loop condition at line 2. Let  $v_1$  be the leaf incident on path  $P_i$ . Assign to it any one element from  $S_i \setminus \bigcup_{i \neq j} S_j$ . Remove  $(S_i, P_i)$  from assignments and add  $(\{x_1\}, \{v_1\}), (S_i \setminus \{x_1\}, P_i \setminus \{v_1\})$ . Now all assignments except single leaf assignments are paths from the subtree  $T_0 = T \setminus \{v \mid v \text{ is a leaf in } T\}$ . This is the function of Algorithm 2.

---

**Algorithm 2** Leaf assignments from an ICPPA  $\{(S_i, P_i) \mid i \in I\}$

---

Let  $\Pi_0 = \{(S_i, P_i) \mid i \in [m]\}$ . Paths are such that no two paths  $P_i, P_j, i \neq j$  share a leaf.

$j = 1$

**while** there is a leaf  $v$  and a unique  $(S_{i_1}, P_{i_1})$  such that  $v \in P_{i_1}$  **do**

$\Pi_j = \Pi_{j-1} \setminus \{(S_{i_1}, P_{i_1})\}$

$X = S_{i_1} \setminus \bigcup_{i \neq i_1, i \in I} S_i$

**if**  $X$  is empty **then**

        exit

**end if**;

    Let  $x$  = arbitrary element from  $X$

$\Pi_j = \Pi_j \cup \{(S_{i_1} \setminus \{x\}), (P_{i_1} \setminus \{v\}), (\{x\}, \{v\})\}$

$j = j + 1$

**end while**

$\Pi = \Pi_j$

Return  $\Pi$

---

**Lemma 4.** In Algorithm 2, for all  $j \geq 0$ , at the end of the  $j$ th iteration the four invariants given in lemma 3 are valid.

*Proof.* First we see that  $X = S_{i_1} \setminus \bigcup_{i \neq i_1, i \in I} S_i$  is non empty in every iteration for an ICPPA. Suppose  $X$  is empty. We know that  $v \in P_{i_1} \setminus \bigcup_{i \neq i_1, i \in I} P_i$  since  $v$  is in the unique path  $P_{i_1}$ . Since this is an ICPPA  $|S_{i_1}| = |P_{i_1}|$ . For any  $x \in S_{i_1}$  it is contained in at least two sets due to our assumption. Let  $S_{i_2}$  be a second set that contains  $x$ . We know  $v \notin P_{i_2}$ . Therefore there cannot exist a permutation that maps elements of  $S_{i_2}$  to  $P_{i_2}$ . This contradicts our assumption that this is an ICPPA. Thus  $X$  cannot be empty.

We use mathematical induction on the number of iterations for this proof. The term “new sets” will refer to the sets added in  $\Pi_j$  in the  $j$ th iteration, i.e.  $(P' \setminus \{x\}, Q' \setminus \{v\})$  and  $(\{x\}, \{v\})$  for some  $(P', Q')$  in  $\Pi_{j-1}$  such that  $v$  is a leaf and  $Q'$  is the unique path incident on it.

For  $\Pi_0$  all invariants hold because it is output from algorithm 1 which is an ICPPA. Hence base case is proved. Assume the lemma holds for  $\Pi_{j-1}$ . Consider  $\Pi_j$  and any  $(P, Q) \in \Pi_j$ . If  $(P, Q)$  is in  $\Pi_j$  and  $\Pi_{j-1}$  invariants I and II are true because of induction assumption. If it is only in  $\Pi_j$ , then it is  $\{(P' \setminus \{x\}), (Q' \setminus \{v\})\}$  or  $(\{x\}, \{v\})$  for some  $(P', Q')$  in  $\Pi_{j-1}$ . By definition,  $x$  is an element in  $P'$  (as defined in the algorithm) and  $v$  is a leaf in  $Q'$ . If  $(P, Q)$  is  $\{(P' \setminus \{x\}), (Q' \setminus \{v\})\}$ ,  $Q$  is a path since only a leaf is removed from path  $Q'$ . We know  $|P'| = |Q'|$ , therefore  $|P' \setminus \{x\}| = |Q' \setminus \{v\}|$ . Hence in this case invariants I and II are obvious. It is easy to see these invariants hold if  $(P, Q)$  is  $(\{x\}, \{v\})$ .

For invariant III consider  $(P_1, Q_1), (P_2, Q_2)$  in  $\Pi_j$ . If both of them are also in  $\Pi_{j-1}$ , claim is proved. If one of them is not in  $\Pi_{j-1}$  then it has to be  $\{(P' \setminus \{x\}), (Q' \setminus \{v\})\}$  or  $(\{x\}, \{v\})$  for some  $(P', Q')$  in  $\Pi_{j-1}$ . Since by definition,  $Q'$  is the only path with  $v$  and  $P'$  the only set with  $x$  in the previous iteration,  $|P_1 \cap (P' \setminus \{x\})| = |P_1 \cap P'|$  and  $|Q_1 \cap (Q' \setminus \{v\})| = |Q_1 \cap Q'|$  and  $|P_1 \cap \{x\}| = 0, Q_1 \cap \{v\} = 0$ . Thus invariant III is also proven.

To prove invariant IV, consider  $(P_1, Q_1), (P_2, Q_2), (P_3, Q_3)$  in  $\Pi_j$ . If exactly one of them, say  $P_3 \notin \Pi_{j-1}$ , it is one of the new sets. By the same argument used to prove invariant III,  $|P_1 \cap P_2 \cap (P' \setminus \{x\})| = |P_1 \cap P_2 \cap P'|$  and  $|Q_1 \cap Q_2 \cap (Q' \setminus \{x\})| = |Q_1 \cap Q_2 \cap Q'|$ . Since  $P_1, P_2, P'$  are all in  $\Pi_{j-1}$ , by induction hypothesis  $|P_1 \cap P_2 \cap P'| = |Q_1 \cap Q_2 \cap Q'|$ . Also  $|P_1 \cap P_2 \cap \{x\}| = 0, Q_1 \cap Q_2 \cap \{v\} = 0$ . If two or more of them are not in  $\Pi_{j-1}$ , then it can be verified that  $|P_1 \cap P_2 \cap P_3| = |Q_1 \cap Q_2 \cap Q_3|$  since the new sets in  $\Pi_j$  are either disjoint or as follows: assuming  $P_1, P_2 \notin \Pi_{j-1}$  and new sets are derived from  $(P', Q'), (P'', Q'') \in \Pi_{j-1}$  with  $x_1, x_2$  exclusively in  $P_1, P_2, (\{x_1\}, \{v_1\}), (\{x_2\}, \{v_2\}) \in \Pi_j$  thus  $v_1, v_2$  are exclusively in  $Q_1, Q_2$  resp. it follows that  $|P_1 \cap P_2 \cap P_3| = |(P' \setminus \{x_1\}) \cap (P'' \setminus \{x_2\}) \cap P_3| = |P' \cap P'' \cap P_3| = |Q' \cap Q'' \cap Q_3| = |(Q' \setminus \{v_1\}) \cap (Q'' \setminus \{v_2\}) \cap Q_3| = |Q_1 \cap Q_2 \cap Q_3|$ . Thus invariant IV is also proven.  $\square$

Using algorithms 1 and 2 we prove the following theorem.

**Theorem 1.** *If  $\mathcal{A}$  is an ICPPA, then there exists a bijection  $\sigma : U \rightarrow V(T)$  such that  $\sigma(S_i) = P_i$  for all  $i \in I$*

*Proof.* This is a constructive proof. First, the given ICPPA  $\mathcal{A}$  and tree  $T$  are given as input to Algorithm 1. This yields a “filtered” ICPPA as the output which is input to Algorithm 2. It can be observed that the output of Algorithm 2 is a set of path assignments to sets and one-to-one assignment of elements of  $U$  to each leaf of  $T$ . To be precise, it would be of the form  $\mathcal{B}_0 = \mathcal{A}_0 \cup \mathcal{L}_0$ . The leaf assignments are defined in  $\mathcal{L}_0 = \{(x_i, v_i) \mid x_i \in U, v_i \in T, x_i \neq x_j, v_i \neq v_j, i \neq j, i, j \in [k]\}$  where  $k$  is the number of leaves in  $T$ . The path assignments are defined in  $\mathcal{A}_0 \subseteq \{(S'_i, P'_i) \mid S'_i \subseteq U_0, P'_i \text{ is a path from } T_0\}$  where  $T_0$  is the tree obtained by removing all the leaves in  $T$  and  $U_0 = U \setminus \{x \mid x \text{ is assigned to a leaf in } \mathcal{L}_0\}$ . Now we have a subproblem of finding the permutation for the path assignment  $\mathcal{A}_0$  which has paths from tree  $T_0$  and sets from universe  $U_0$ . Now we repeat the procedure and the path assignment  $\mathcal{A}_0$  and tree  $T_0$  is given as input to Algorithm 1. The output of this algorithm is given to Algorithm 2 to get a new union of path and leaf assignments  $\mathcal{B}_1 = \mathcal{A}_1 \cup \mathcal{L}_1$  defined similar to  $\mathcal{B}_0, \mathcal{L}_0, \mathcal{A}_0$ . In general, the two algorithms are run on path assignment  $\mathcal{A}_{i-1}$  with paths from tree  $T_{i-1}$  to get a new subproblem with path assignment  $\mathcal{A}_i$  and tree  $T_i$ .  $T_i$  is the subtree of  $T_{i-1}$  obtained by removing all its leaves. More importantly, it gives leaf assignments  $\mathcal{L}_i$  to the leaves in tree  $T_{i-1}$ . This is continued until we get a subproblem with path assignment  $\mathcal{A}_{d-1}$  and tree  $T_{d-1}$  for some  $d \leq n$  which is just a path. From the last lemma we know that  $\mathcal{A}_{d-1}$  is an ICPPA. Another observation is that an ICPPA with all its tree paths being intervals (subpaths from a path) is nothing but an ICPIA[NS09]. Let  $\mathcal{A}_{d-1}$  be equal to  $\{(S''_i, P''_i) \mid S''_i \subseteq U_{d-1}, P''_i \text{ is a path from } T_{d-1}\}$ . It is true that the paths  $P''_i$ s may not be precisely an interval in the sense of consecutive integers because they are some nodes from a tree. However, it is easy to see that the nodes of  $T_{d-1}$  can be ordered from left to right and ranked to get intervals  $I_i$  for every path  $P''_i$  as follows.  $I_i = \{[l, r] \mid l = \text{the lowest rank of the nodes in } P''_i, r = l + |P''_i| - 1\}$ . Let assignment  $\mathcal{A}_d$  be with the renamed paths.  $\mathcal{A}_d = \{(S''_i, I_i) \mid (S''_i, P''_i) \in \mathcal{A}_{d-1}\}$ . What has been effectively done is renaming the nodes in  $T_{d-1}$  to get a tree  $T_d$ . The ICPIA  $\mathcal{A}_d$  is now in the format that the ICPIA algorithm requires which gives us the permutation  $\sigma' : U_{d-1} \rightarrow T_{d-1}$

$\sigma'$  along with all the leaf assignments  $\mathcal{L}_i$  gives us the permutation for the original path assignment  $\mathcal{A}$ . More precisely, the permutation for tree path assignment  $\mathcal{A}$  is defined as follows.  $\sigma : U \rightarrow T$  such that the following is maintained.

$$\begin{aligned} \sigma(x) &= \sigma'(x), \text{ if } x \in U_{d-1} \\ &= \mathcal{L}_i(x), \text{ where } x \text{ is assigned to a leaf in a subproblem } \mathcal{A}_{i-1}, T_{i-1} \end{aligned}$$

To summarize, run algorithm 1 and 2 on  $T$ . After the leaves have been assigned to specific elements from  $U$ , remove all leaves from  $T$  to get new tree  $T_0$ . The leaf assignments are in  $\mathcal{L}_0$ . Since only leaves were removed  $T_0$  is indeed a tree. Repeat the algorithms on  $T_0$  to get leaf assignments  $\mathcal{L}_1$ . Remove the leaves in  $T_0$  to get  $T_1$  and so on until the pruned tree  $T_d$  is a single path. Now run ICPIA algorithm on  $T_d$  to get permutation  $\sigma'$ . The relation  $\mathcal{L}_0 \cup \mathcal{L}_1 \cup \dots \cup \mathcal{L}_d \cup \sigma'$  gives the bijection required in the original problem.  $\square$

## 4 Finding an assignment of tree paths to a set system

In the previous section we have shown that the problem of finding a Tree Path Assignment to an input  $(\mathcal{F}, T)$  is equivalent to finding an ICPPA to  $\mathcal{F}$  in tree  $T$ . In this section we characterize those set systems that have an ICPPA in a given tree. As a consequence of this characterization we identify two sub-problems that must be solved to obtain an ICPPA. We do not solve the problem and in the next section show that finding an ICPPA in a given tree is GI-Complete.

A set system can be concisely represented by a binary matrix where the row indices denote the universe of the set system and the column indices denote each of the sets. Let the binary matrix be  $M$  with order  $n \times m$ , the set system be  $\mathcal{F} = \{S_i \mid i \in [m]\}$ , universe of set system  $U = \{x_1, \dots, x_n\}$ . If  $M$  represents  $\mathcal{F}$ ,  $|U| = n, |\mathcal{F}| = m$ . Thus  $(i, j)$ th element of  $M$ ,  $M_{ij} = 1$  iff  $x_i \in S_j$ . If  $\mathcal{F}$  has a feasible tree path assignment (ICPPA)  $\mathcal{A} = \{(S_i, P_i) \mid i \in [m]\}$ , then we say its corresponding matrix  $M$  has an ICPPA. Conversely we say that a matrix  $M$  has an ICPPA if there exists an ICPPA  $\mathcal{A}$  as defined above.

We now define the strict intersection graph or overlap graph of  $\mathcal{F}$ . This graph occurs at many places in the literature, see for example [KKLV10, Hsu02, NS09]. The vertices of the graph correspond to the sets in  $\mathcal{F}$ . An edge is present between vertices of two sets iff the corresponding sets have a nonempty intersection and none is contained in the other. Formally, intersection graph is  $G_f = (V_f, E_f)$  such that  $V_f = \{v_i \mid S_i \in \mathcal{F}\}$  and  $E_f = \{(v_i, v_j) \mid S_i \cap S_j \neq \emptyset \text{ and } S_i \not\subseteq S_j, S_j \not\subseteq S_i\}$ . We use this graph to decompose  $M$  as described in [Hsu02, NS09]. A prime sub-matrix of  $M$  is defined as the matrix formed by a set of columns of  $M$  which correspond to a connected component of the graph  $G_f$ . Let us denote the prime sub-matrices by  $M_1, \dots, M_p$  each corresponding to one of the  $p$  components of  $G_f$ . Clearly, two distinct matrices have a distinct set of columns. Let  $col(M_i)$  be the set of columns in the sub-matrix  $M_i$ . The support of a prime sub-matrix  $M_i$  is defined as  $supp(M_i) = \bigcup_{j \in col(M_i)} S_j$ . Note that for each  $i$ ,  $supp(M_i) \subseteq U$ . For a set of prime sub-matrices  $X$

we define  $supp(X) = \bigcup_{M \in X} supp(M)$ .

Consider the relation  $\preceq$  on the prime sub-matrices  $M_1, \dots, M_p$  defined as follows:

$$\{(M_i, M_j) \mid \text{A set } S \in M_i \text{ is contained in a set } S' \in M_j\} \cup \{(M_i, M_i) \mid 1 \leq i \leq p\}$$

This relation is the same as that defined in [NS09]. The prime submatrices and the above relation can be defined for any set system. We will use this structure of prime submatrices to present our results on an ICPPA for a set system  $\mathcal{F}$ . Recall the following lemmas, and theorem that  $\preceq$  is a partial order, from [NS09].

**Lemma 5.** *Let  $(M_i, M_j) \in \preceq$ . Then there is a set  $S' \in M_j$  such that for each  $S \in M_i$ ,  $S \subseteq S'$ .*

**Lemma 6.** *For each pair of prime sub-matrices, either  $(M_i, M_j) \notin \preceq$  or  $(M_j, M_i) \notin \preceq$ .*

**Lemma 7.** *If  $(M_i, M_j) \in \preceq$  and  $(M_j, M_k) \in \preceq$ , then  $(M_i, M_k) \in \preceq$ .*

**Lemma 8.** *If  $(M_i, M_j) \in \preceq$  and  $(M_i, M_k) \in \preceq$ , then either  $(M_j, M_k) \in \preceq$  or  $(M_k, M_j) \in \preceq$ .*

**Theorem 2.**  *$\preceq$  is a partial order on the set of prime sub-matrices of  $M$ . Further, it uniquely partitions the prime sub-matrices of  $M$  such that on each set in the partition  $\preceq$  induces a total order.*

For the purposes of this paper, we refine the total order mentioned in Theorem 2. We do this by identifying an in-tree rooted at each maximal upper bound under  $\preceq$ . Each of these in-trees will be on disjoint vertex sets, which in this case would be disjoint sets of prime-submatrices. The in-trees are specified by selecting the appropriate edges from the Hasse diagram associated with  $\preceq$ . Let  $\mathcal{I}$  be the following set:

$$\mathcal{I} = \{(M_i, M_j) \in \preceq \mid \nexists M_k \text{ s.t. } M_i \preceq M_k, M_k \preceq M_j\} \cup \{(M_i, M_i) \mid i \in [p]\}$$

**Theorem 3.** *Consider the directed graph  $X$  whose vertices correspond to the prime sub-matrices, and the edges are given by  $\mathcal{I}$ . Then,  $X$  is a vertex disjoint collection of in-trees and the root of each in-tree is a maximal upper bound in  $\preceq$ .*

*Proof.* To observe that  $X$  is a collection of in-trees, we observe that for vertices corresponding to maximal upper bounds, no out-going edge is present in  $X$ . Secondly, for each other element, exactly one out-going edge is chosen (due to lemma 8 and the condition in set  $\mathcal{I}$  definition), and for the minimal lower bound, there is no in-coming edge. Consequently,  $X$  is acyclic, and since each vertex has at most one edge leaving it, it follows that  $X$  is a collection of in-trees, and for each in-tree, the root is a maximal upper bound in  $\preceq$ . Hence the theorem.  $\square$

Let the partition of  $X$  given by Theorem 3 be  $\{X_1, \dots, X_r\}$ . Further, each in-tree itself can be layered based on the distance from the root. The root is considered to be at level zero. For  $j \geq 0$ , Let  $X_{i,j}$  denote the set of prime matrices in level  $j$  of in-tree  $X_i$ .

**Lemma 9.** *Let  $M$  be a matrix and let  $X$  be the directed graph whose vertices are in correspondence with the prime submatrices of  $M$ . Further let  $\{X_1, \dots, X_r\}$  be the partition of  $X$  into in-trees as defined above. Then, matrix  $M$  has an ICPA in tree  $T$  iff  $T$  can be partitioned into vertex disjoint subtrees  $\{T_1, T_2, \dots, T_r\}$  such that, for each  $1 \leq i \leq r$ , the set of prime sub-matrices corresponding to vertices in  $X_i$  has an ICPA in  $T_i$ .*

*Proof.* Let us consider the reverse direction first. Let us assume that  $T$  can be partitioned into  $T_1, \dots, T_r$  such that for each  $1 \leq i \leq r$ , the set of prime sub-matrices corresponding to vertices in  $X_i$  has an ICPA in  $T_i$ . It is clear from the properties of the partial order  $\preceq$  that these ICPAs naturally yield an ICPA of  $M$  in  $T$ . The main property used in this inference is that for each  $1 \leq i \neq j \leq r$ ,  $\text{supp}(X_i) \cap \text{supp}(X_j) = \phi$ .

To prove the forward direction, we show that if  $M$  has an ICPA, say  $\mathcal{A}$ , in  $T$ , then there exists a partition of  $T$  into vertex disjoint subtree  $T_1, \dots, T_r$  such that for each  $1 \leq i \leq r$ , the set of prime sub-matrices corresponding to vertices in  $X_i$  has an ICPA in  $T_i$ . For each  $1 \leq i \leq r$ , we define based on  $\mathcal{A}$  a subtree  $T_i$  corresponding to  $X_i$ . We then argue that the trees thus defined are vertex disjoint, and complete the proof. Consider  $X_i$  and consider the prime sub-matrix in  $X_{i,0}$ . Consider the paths assigned under  $\mathcal{A}$  to the sets in the prime sub-matrix in  $X_{i,0}$ . Since the component in  $G_f$  corresponding to this matrix is a connected component, it follows that union of paths assigned to this prime-submatrix is a subtree of  $T$ . We call this subtree  $T_i$ . All other prime-submatrices in  $X_i$  are assigned paths in  $T_i$  since  $\mathcal{A}$  is an ICPA, and the support of other prime sub-matrices in  $X_i$  are contained in the support of the matrix in  $X_{i,0}$ . Secondly, for each  $1 \leq i \neq j \leq r$ ,  $\text{supp}(X_i) \cap \text{supp}(X_j) = \phi$ , and since  $\mathcal{A}$  is an ICPA, it follows that  $T_i$  and  $T_j$  are vertex disjoint. Finally, since  $|U| = |V(T)|$ , it follows that  $T_1, \dots, T_r$  is a partition of  $T$  into vertex disjoint sub-trees such that for each  $1 \leq i \leq r$ , the set of matrices corresponding to nodes in  $X_i$  has an ICPA in  $T_i$ . Hence the lemma.  $\square$

The essence of the following lemma is that an ICPA only needs to be assigned to the prime sub-matrix corresponding to the root of each in-tree, and all the other prime sub-matrices only need to have an Intersection Cardinality Preserving Interval Assignments (ICPIA). Recall, an ICPIA is an assignment of intervals to sets such that the cardinality of an assigned interval is same as the cardinality of the interval, and the cardinality of intersection of any two sets is same as the cardinality of the intersection of the corresponding intervals. It is shown in [NS09] that the existence of an ICPIA is a necessary and sufficient condition for a matrix to have COP. We present the pseudo-code to test if  $M$  has an ICPA in  $T$ .

**Lemma 10.** *Let  $M$  be a matrix and let  $X$  be the directed graph whose vertices are in correspondence with the prime submatrices of  $M$ . Further let  $\{X_1, \dots, X_r\}$  be the partition of  $X$  into in-trees as defined earlier in this section. Let  $T$  be the given tree and let  $\{T_1, \dots, T_r\}$  be a given partition of  $T$  into vertex disjoint sub-trees. Then, for each  $1 \leq i \leq r$ , the set of matrices corresponding to vertices of  $X_i$  has an ICPA in  $T_i$  if and only if the matrix in  $X_{i,0}$  has an ICPA in  $T_i$  and all other matrices in  $X_i$  have an **ICPIA**.*

*Proof.* The proof is based on the following fact-  $\preceq$  is a partial order and  $X$  is a digraph which is the disjoint union of in-trees. Each edge in the in-tree is a containment relationship among the supports of the corresponding sub-matrices. Therefore, any ICPA to a prime sub-matrix that is not the root is contained in a path assigned to the sets in the parent matrix. Consequently, any ICPA to the prime sub-matrix that is not at the root is an ICPIA, and any ICPIA can be used to construct an ICPA to the matrices corresponding to nodes in  $X_i$  provided the matrix in the root has an ICPA in  $T_i$ . Hence the lemma.  $\square$



Lemma 9 and Lemma 10 point out two algorithmic challenges in finding an ICPPA for a given set system  $\mathcal{F}$  in a tree  $T$ . Given  $\mathcal{F}$ , finding  $X$  and its partition  $\{X_1, \dots, X_r\}$  into in-trees can be done in polynomial time. On the other hand, as per lemma 9 we need to partition  $T$  into vertex disjoint sub-trees  $\{T_1, \dots, T_r\}$  such that for each  $i$ , the set of matrices corresponding to nodes in  $X_i$  have an ICPPA in  $T_i$ . This seems to be a challenging step, and it must be remarked that this step is easy when  $T$  itself is a path, as each individual  $T_i$  would be sub-paths. The second algorithmic challenge is identified by lemma 10 which is to assign an ICPPA from a given tree to the matrix associated with the root node of  $X_i$ .

---

**Algorithm 3** Algorithm to find an ICPPA for a matrix  $M$  on tree  $T$ : *main\_ICPPA*( $M, T$ )

---

Identify the prime sub-matrices. This is done by constructing the strict overlap graph and identify connected components. Each connected component yields a prime sub-matrix.  
Construct the partial order  $\preceq$  on the set of prime sub-matrices.  
Construct the partition  $X_1, \dots, X_r$  of the prime sub-matrices induced by  $\preceq$   
For each  $1 \leq i \leq r$ , Check if all matrices except those in  $X_{i,0}$  has an ICPIA. If a matrix does not have ICPIA exit with a negative answer. To check for the existence of ICPIA, use the result in [NS09].  
Find a partition of  $T_1, \dots, T_r$  such that matrices in  $X_{i,0}$  has an ICPPA in  $T_i$ . If not such partition exists, exit with negative answer.

---

## 5 Complexity of Tree Path Assignment-A Discussion

Recall that the input to the Tree Path Assignment question is an order pair  $(\mathcal{F}, T)$  where  $\mathcal{F}$  is a family of subsets of an universe  $U$ , and  $T$  is a tree such that  $|V(T)| = |U|$ . The question is to come up with a bijection from  $U$  to  $V(T)$  such that the image of each set in  $\mathcal{F}$  is a path in  $T$ . We show that this problem is at least as hard as the problem of testing if two given path chordal graphs are isomorphic.

**Theorem 4.** *Tree Path Assignment is isomorphism-complete.*

*Proof.* It is well known (see for example [KKLV10]) that testing isomorphism of path chordal graphs is isomorphism complete. We show a reduction of path chordal graph isomorphism to tree path assignment. Given  $G_1$  and  $G_2$  two path chordal graphs, let  $T_2$  be the clique tree of  $G_2$  obtained from say [Gav78]. The nodes of  $T_2$  correspond to the maximal cliques of  $G_2$  and each vertex of  $G_2$  corresponds to a path in  $G_2$ . This is a well-known characterization of path chordal graphs and  $T_2$  can be computed in polynomial time. In  $G_1$ , let  $S_v$  denote the maximal cliques of  $G_1$  that contain  $v$ . This can be computed in polynomial time as  $G_1$  is path chordal, and all chordal graph only have a linear number of maximal cliques. The universe  $U$  corresponds bijectively to the set of maximal cliques in  $G_1$ , and  $\mathcal{F} = \{S_v | v \in V(G_1)\}$ . Now, we claim that  $(\mathcal{F}, T_2)$  has a tree path assignment if and only if  $G_1$  and  $G_2$  are isomorphic. This is clear since for each vertex  $v \in G_1$ , there is an associated  $S_v$  which is the set of maximal cliques containing  $v$ . In  $G_2$ , each vertex corresponds to a path in  $T_2$ , and the nodes on this path corresponds to the maximal cliques in  $G_2$ . Consequently, a tree path assignment will naturally yield an isomorphism between  $G_1$  and  $G_2$ , and vice versa. Therefore, Tree Path Assignment is isomorphism-complete.  $\square$

### 5.1 Consecutive Ones Testing is in Logspace

While Tree Path Assignment is isomorphism-complete, it is polynomial time solvable when the given tree is a path. Indeed, in this case we encounter a restatement of matrices with the COP. The known approaches to testing for COP fall into two categories: those that provide a witness when the input matrix does not have COP, and those that do not provide a witness. The first linear time algorithm for testing COP for a binary matrix was using a data structure called PQ trees, which represent all COP orderings of  $M$ , invented by [BL76]. There is a PQ tree for a matrix iff the matrix has COP. Indeed, this is an algorithmic characterization

of the consecutive ones property and the absence of the PQ-tree does not yield any witness to the reason for failure. A closely related data structure is the generalized PQ tree in [McC04]. In generalized PQ tree the P and Q nodes are called prime and linear nodes. Aside from that, it has a third type of node called degenerate nodes which is present only if the set system does not have COP [McC04]. Using the idea of generalized PQ tree, [McC04] proves that checking for bipartiteness in the certain incomparability graph is sufficient to check for COP. [McC04] invented a certificate to confirm when a binary matrix does not have COP. [McC04] describes a graph called incompatibility graph of a set system  $\mathcal{F}$  which has vertices  $(a, b), a \neq b$  for every  $a, b \in U$ ,  $U$  being the universe of the set system. There are edges  $((a, b), (b, c))$  and  $((b, a), (c, b))$  if there is a set  $S \in \mathcal{F}$  such that  $a, c \in S$  and  $b \notin S$ . In other words the vertices of an edge in this graph represents two orderings that cannot occur in a consecutive ones ordering of  $\mathcal{F}$ .

**Theorem 5 (Theorem 6.1, [McC04]).** *Let  $\mathcal{F}$  be an arbitrary set family on domain  $V$ . Then  $\mathcal{F}$  has the consecutive ones property if and only if its incompatibility graph is bipartite, and if it does not have the consecutive ones property, the incompatibility graph has an odd cycle of length at most  $n + 3$ .*

This theorem gives a certificate as to why a given matrix does not have COP. Similarly, the approach of testing for an ICPIA in [NS09] also gives a different certificate- a prime sub-matrix that does not have an ICPIA. Further, the above theorem can be used to check if a given matrix has COP in logspace by checking if its incompatibility graph is bipartite. [Rei84] showed that checking for bipartiteness can be done in logspace. Thus we conclude that consecutive ones testing can be done in logspace.

More recently, [KKLV10] showed that interval graph isomorphism can be done in logspace. Their paper proves that a canon for interval graphs can be calculated in logspace using an interval hypergraph representation of the interval graph with each hyperedge being a set to which an interval shall be assigned by the canonization algorithm. An overlap graph (subgraph of intersection graph, edges define only strict intersections and no containment) of the hyperedges of the hypergraph is created and canons are computed for each overlap component. The overlap components define a tree like relation due to the fact that two overlap components are such that either all the hyperedges of one is disjoint from all in the other, or all of them are contained in one hyperedge in the other. This is similar to the containment tree defined in [NS09] and in this paper. Finally the canon for the whole graph is created using logspace tree canonization algorithm from [Lin92]. The interval labelling done in this process of canonization is exactly the same as the problem of assigning feasible intervals to a set system, and thus the problem of finding a COP ordering in a binary matrix [NS09].

**Theorem 6 (Theorem 4.7, [KKLV10]).** *Given an interval hypergraph  $\mathcal{H}$ , a canonical interval labeling  $l_{\mathcal{H}}$  for  $\mathcal{H}$  can be computed in FL.*

We present the following reduction to see that COP testing is indeed in logspace. Given a binary matrix  $M$  of order  $n \times m$ , let  $S_i = \{j \mid M[j, i] = 1\}$ . Let  $\mathcal{F} = \{S_i \mid i \in [m]\}$  be this set system. Construct a hypergraph  $\mathcal{H}$  with its vertex set being  $\{1, 2, \dots, n\}$ . The edge set of  $\mathcal{H}$  is isomorphic to  $\mathcal{F}$ . Thus every edge in  $\mathcal{H}$  represents a set in the given set system  $\mathcal{F}$ . Let this mapping be  $\pi : E(\mathcal{H}) \rightarrow \mathcal{F}$ . It is easy to see that if  $M$  has COP, then  $\mathcal{H}$  is an interval hypergraph. From theorem 6, it is clear that the interval labeling  $l_{\mathcal{H}} : V(\mathcal{H}) \rightarrow [n]$  can be calculated in logspace. Construct sets  $I_i = \{l_{\mathcal{H}}(x) \mid x \in E, E \in E(\mathcal{H}), \pi(E) = S_i\}$ , for all  $i \in [m]$ . Since  $\mathcal{H}$  is an interval hypergraph,  $I_i$  is an interval for all  $i \in [m]$ , and is the interval assigned to  $S_i$  if  $M$  has COP.

Now we have the following corollary.

**Corollary 1.** *If a binary matrix  $M$  has COP then the interval assignments to each of its columns can be calculated in FL.*

Finally, we conclude by asking about the complexity of Tree Path Assignment restricted to other subclasses of trees. In particular, is Tree Path Assignment in caterpillars easier than Tree Path assignment in general trees.

## Bibliography

- [ABH98] Atkins, Boman, and Hendrickson. A spectral algorithm for seriation and the consecutive ones problem. *SICOMP: SIAM Journal on Computing*, 28, 1998.
- [APY92] Barry Peyton Alex, Alex Pothén, and Xiaoqing Yuan. A clique tree algorithm for partitioning a chordal graph into transitive subgraphs, 1992.
- [BL76] Kellogg S. Booth and George S. Lueker. Testing for the consecutive ones property, interval graphs, and graph planarity using PQ-tree algorithms. *Journal of Computer and System Sciences*, 13(3):335–379, December 1976.
- [BP93] J. R. S. Blair and B. Peyton. An introduction to chordal graphs and clique trees. In A. George, J. R. Gilbert, and J. H. U. Liu, editors, *Graph Theory and Sparse Matrix Computations*, pages 1–29, New York, 1993. Springer.
- [Gav78] Fanica Gavril. A recognition algorithm for the intersection graphs of paths in trees. *Discrete Mathematics*, 23(3):211 – 227, 1978.
- [Gol04] Martin Charles Golumbic. *Algorithmic graph theory and perfect graphs*, volume 57 of *Annals of Discrete Mathematics*. Elsevier Science B.V., 2004. Second Edition.
- [HL06] Dorit S. Hochbaum and Asaf Levin. Cyclical scheduling and multi-shift scheduling: Complexity and approximation algorithms. *Discrete Optimization*, 3(4):327–340, 2006.
- [Hsu01] Wen-Lian Hsu. PC-trees vs. PQ-trees. *Lecture Notes in Computer Science*, 2108:207–217, 2001.
- [Hsu02] Wen-Lian Hsu. A simple test for the consecutive ones property. *J. Algorithms*, 43(1):1–16, 2002.
- [HT02] Hochbaum and Tucker. Minimax problems with bitonic matrices. *NETWORKS: Networks: An International Journal*, 40, 2002.
- [KKLV10] Johannes Köbler, Sebastian Kuhnert, Bastian Laubner, and Oleg Verbitsky. Interval graphs: Canonical representation in logspace. *Electronic Colloquium on Computational Complexity (ECCC)*, 17:43, 2010.
- [KM02] P. S. Kumar and CEV Madhavan. Clique tree generalization and new subclasses of chordal graphs. pages 109–131, 2002.
- [Kou77] Lawrence T. Kou. Polynomial complete consecutive information retrieval problems. *SIAM Journal on Computing*, 6(1):67–75, March 1977.
- [Lin92] Steven Lindell. A logspace algorithm for tree canonization (extended abstract). In *STOC*, pages 400–404. ACM, 1992.
- [McC04] Ross M. McConnell. A certifying algorithm for the consecutive-ones property. In *SODA: ACM-SIAM Symposium on Discrete Algorithms (A Conference on Theoretical and Experimental Analysis of Discrete Algorithms)*, 2004.
- [MM96] J. Meidanis and Erasmo G. Munuera. A theory for the consecutive ones property. In *Proceedings of WSP’96 - Third South American Workshop on String Processing*, pages 194–202, 1996.
- [NS09] N. S. Narayanaswamy and R. Subashini. A new characterization of matrices with the consecutive ones property. *Discrete Applied Mathematics*, 157(18):3721–3727, 2009.
- [Rei84] John H. Reif. Symmetric complementation. *JACM: Journal of the ACM*, 31(2):401–421, 1984.
- [Ren70] Peter L. Renz. Intersection representations of graphs by arcs. *Pacific J. Math.*, 34(2):501–510, 1970.
- [Sch93] Alejandro A. Schaffer. A faster algorithm to recognize undirected path graphs. *Discrete Applied Mathematics*, 43:261–295, 1993.