

Tree Path Labeling of Set Systems

A Generalization of Consecutive Ones Property

Anju Srinivasan

as part of **M. S.** by Research
advised by **Dr. N. S. Narayanaswamy**
CSE, IITM, Chennai - 36

XX Dec 2011

1 Introduction

An Illustration

Motivation

Definitions

2 Characterization of a feasible TPL

ICPPL

Filtering algorithm

3 Computing a feasible TPL on k -subdivided trees

Algorithm

4 Conclusion

Application

An Illustration

Caveat

- A very simplistic example.
- Aims only to introduce the combinatorial problem of TPL.

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but **will** be in at least one, say

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but **will** be in at least one, say
 - $R = \{g, h, i, j, k\}$

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but **will** be in at least one, say
 - $R = \{g, h, i, j, k\}$
 - $B = \{a, b, e, g\}$

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but **will** be in at least one, say
 - $R = \{g, h, i, j, k\}$
 - $B = \{a, b, e, g\}$
 - $O = \{c, b, d\}$

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but **will** be in at least one, say
 - $R = \{g, h, i, j, k\}$
 - $B = \{a, b, e, g\}$
 - $O = \{c, b, d\}$
 - $G = \{e, f, g, i\}$

A Study Group Housing problem

- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but **will** be in at least one, say
 - $R = \{g, h, i, j, k\}$
 - $B = \{a, b, e, g\}$
 - $O = \{c, b, d\}$
 - $G = \{e, f, g, i\}$
- There are n single occupancy apartments in the university campus for their accommodation.

A Study Group Housing problem


- A set of n students arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m study groups, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but **will** be in at least one, say
 - $R = \{g, h, i, j, k\}$
 - $B = \{a, b, e, g\}$
 - $O = \{c, b, d\}$
 - $G = \{e, f, g, i\}$
- There are n single occupancy apartments in the university campus for their accommodation.
- All these apartments are placed such that streets connecting them do not form loops

A Study Group Housing problem


The problem

How should the students be allocated apartments such that each study group has the least distance to travel for a discussion?


A Study Group Housing problem



A Study Group Housing problem



A Study Group Housing problem



Tree Path Labeling of Set Systems

The combinatorial problem terminology

Terminology

- The set of study groups i.e. sets of students \rightarrow SET SYSTEM / HYPERGRAPH
- The streets with apartments \rightarrow TARGET TREE
- The route mapping to study groups \rightarrow TREE PATH LABELING (TPL)
- The apartment allocation \rightarrow PATH HYPERGRAPH ISOMORPHISM

Tree Path Labeling of Set Systems

The combinatorial problem terminology

Terminology

- The set of study groups i.e. sets of students \rightarrow SET SYSTEM / HYPERGRAPH
- The streets with apartments \rightarrow TARGET TREE
- The route mapping to study groups \rightarrow TREE PATH LABELING (TPL)
- The apartment allocation \rightarrow PATH HYPERGRAPH ISOMORPHISM

Tree Path Labeling of Set Systems

The combinatorial problem terminology

Terminology

- The set of study groups i.e. sets of students \rightarrow SET SYSTEM / HYPERGRAPH
- The streets with apartments \rightarrow TARGET TREE
- The route mapping to study groups \rightarrow TREE PATH LABELING (TPL)
- The apartment allocation \rightarrow PATH HYPERGRAPH ISOMORPHISM

Tree Path Labeling of Set Systems

The combinatorial problem terminology

Terminology

- The set of study groups i.e. sets of students \rightarrow SET SYSTEM / HYPERGRAPH
- The streets with apartments \rightarrow TARGET TREE
- The route mapping to study groups \rightarrow TREE PATH LABELING (TPL)
- The apartment allocation \rightarrow PATH HYPERGRAPH ISOMORPHISM

Tree Path Labeling of Set Systems

The combinatorial problem terminology

Terminology

- The set of study groups i.e. sets of students \rightarrow SET SYSTEM / HYPERGRAPH
- The streets with apartments \rightarrow TARGET TREE
- The route mapping to study groups \rightarrow TREE PATH LABELING (TPL)
- The apartment allocation \rightarrow PATH HYPERGRAPH ISOMORPHISM

Tree Path Labeling of Set Systems

The combinatorial problem

Terminology [contd.]

There *exists* an apartment allocation that “fits” the route mapping

Tree Path Labeling of Set Systems

The combinatorial problem

Terminology [contd.]

There *exists* a hypergraph isomorphism that “fits” the TPL

Tree Path Labeling of Set Systems

The combinatorial problem

Terminology [contd.]

There *exists* a hypergraph isomorphism that “fits” the TPL
→ the TPL is FEASIBLE

Tree Path Labeling of Set Systems

The combinatorial problem

Terminology [contd.]

There *exists* a hypergraph isomorphism that “fits” the TPL
→ the TPL is FEASIBLE

There *exists* an apartment allocation that gives the optimal route mapping

Tree Path Labeling of Set Systems

The combinatorial problem

Terminology [contd.]

There *exists* a hypergraph isomorphism that “fits” the TPL
→ the TPL is FEASIBLE

There *exists* a hypergraph isomorphism that gives
paths/adjacent vertices in tree

Tree Path Labeling of Set Systems

The combinatorial problem


Terminology [contd.]

There *exists* a hypergraph isomorphism that “fits” the TPL
→ the TPL is FEASIBLE

There *exists* a hypergraph isomorphism that gives
paths/adjacent vertices in tree
→ the hypergraph is a PATH HYPERGRAPH

Consecutive Ones \rightarrow Path Labeling

The motivation



Tree path labeling of path hypergraphs

The two problems

1

Characterization of a *feasible TPL* and finding the certificate for feasibility i.e. *hypergraph isomorphism*

2

Computation of a *feasible TPL* if any

Tree path labeling of path hypergraphs

The two problems

1

Characterization of a *feasible TPL* and finding the certificate for feasibility i.e. *hypergraph isomorphism*

2

Computation of a *feasible TPL* if any

1

Characterization of feasible TPL

Given

- i. a set system or hypergraph \mathcal{F} ,
- ii. a feasible TPL $\ell : \mathcal{F} \rightarrow \mathcal{P}$ where \mathcal{P} is a path system from tree T and $\text{supp}(\mathcal{P}) = V(T)$,

what is the hypergraph isomorphism

$$\underline{\phi : \text{supp}(\mathcal{F}) \rightarrow \text{supp}(\mathcal{P})}$$

such that the induced labeling $\ell_\phi = \ell$?

2

Computing a feasible TPL

Given hypergraph \mathcal{F} with certain properties and a k -subdivided star T , can we find a feasible TPL ℓ to T ?

1

Characterization of feasible TPL

The characterization

ICPPL + a filtering algorithm

^a: [TBD Write the theorem]

The characterization

ICPPL + a filtering algorithm

^a: [TBD Write the theorem]

2

Computing a feasible TPL

Given hypergraph \mathcal{F} with certain properties and a k -subdivided star T , can we find a feasible TPL ℓ to T ?

Special case


Interval assignment problem / COP

- ① T is a path \implies paths in T are intervals ^{a:} [quick illustration]
- ② Only pairwise intersection cardinality needs to be preserved \implies ICPIA [NS09]
- ③ Higher level intersection cardinalities preserved by **Helly Property** – [Gol04]
- ④ $filter_1, filter_2$ do not need the the **exit** conditions. ^{a:} [is this cryptic?]

This problem is equivalent to Consecutive Ones Property of binary matrices [NS09]


Path Labeling → Graph Isomorphism

Application




Path Labeling \rightarrow Graph Isomorphism

Application



Path Labeling → Graph Isomorphism

Application



beamericonarticle

Second Edition.

beamericonarticle

Electronic Colloquium on Computational Complexity (ECCC), 17:43, 2010.

beamericonarticle

Discrete Applied Mathematics, 157(18):3721–3727, 2009.