

Generalization of the Consecutive-ones Property

A THESIS

submitted by

ANJU SRINIVASAN

for the award of the degree of

MASTER OF SCIENCE *by Research*

from the department of

COMPUTER SCIENCE AND ENGINEERING

at

INDIAN INSTITUTE OF TECHNOLOGY MADRAS

Guindy, Chennai - 600036



JANUARY 2012

TABLE OF CONTENTS

ACKNOWLEDGEMENTS	i
ABSTRACT	iii
LIST OF TABLES	vi
LIST OF FIGURES	vii
ABBREVIATIONS	viii
NOTATION	ix
1 Introduction	1
1.1 Organization of the document	1
1.2 Illustration of the problem	1
1.3 Basic preliminaries - general definitions and nomenclature . . .	5
1.4 Consecutive-ones Property Testing - a Brief Survey	6
1.4.1 Matrices with COP	6
1.4.2 Optimization problems in COP	8
1.5 Application of COP in Areas of Graph Theory and Algorithms .	9
1.6 Generalization of COP - the Motivation	9
1.7 Summary of New Results in this Thesis	11
2 Consecutive-ones Property – A Survey of Important Results	14
2.1 COP in Graph Theory	14
2.2 Matrices with COP	17
2.2.1 Tucker’s forbidden submatrices for COP	18
2.2.2 PQ tree – a linear COT algorithm	20
2.3 Optimization problems in COP	22

2.4	Certifying Algorithms	23
2.5	COP in Relational Database Model	23
2.6	COP in Graph Isomorphism	23
3	Tree Path Labeling of Path Hypergraphs - the New Results	25
3.1	Introduction	25
3.2	Preliminaries to new results	27
3.3	Characterization of Feasible Tree Path Labeling	30
3.4	Computing feasible TPL with special target trees ^{c1}	41
3.4.1	Target tree is a Path	42
3.4.2	Target tree is a k -subdivided Star	42
3.5	TPL with no restrictions	46
3.5.1	Finding an assignment of tree paths to a set system . . .	47
3.6	Complexity of Tree Path Assignment-A Discussion	51
3.6.1	Consecutive Ones Testing is in Logspace	52
4	Conclusion	54
	REFERENCES ^{c2}	56

^{c1} give
problem
definition etc

^{c2}*minor*: (i)make
names in bib
file uniform
style w.r.t.
firstname/initials
(ii) have back
refs - i.e.
pages that cite
the item.

LIST OF TABLES

1.1	Students and study groups in <i>Wallace Studies Institute</i>	2
1.2	A solution to study group accomodation problem	2
2.1	Graph matrices PLACEHOLDER	17
2.2	A brief history of COP research	18

LIST OF FIGURES

1.1	<i>Infinite Loop</i> street map.	4
1.2	<i>Infinite Loop</i> street map with study group routes allocated.	4
1.3	Solution to the student accommodation problem.	4
1.4	Matrices with and without COP.	5
1.5	Examples of k -subdivided stars. (a) $k = 0$ (b) $k = 2$	12
2.1	Matrices defined in Def. 2.1.1	16
2.2	Tucker's forbidden subgraphs	19
2.3	Tucker's forbidden submatrices	20
2.4	An example for PQ -tree	21
3.1	(a) 8-subdivided star with 7 rays (b) 3-subdivided star with 3 rays	43

CHAPTER 2

Consecutive-ones Property – A Survey of Important Results

This chapter surveys several results that are significant to this thesis or to COP in general. These predominantly pertain to characterizations of COP, algorithmic tests to check for COP (COT), optimization problems on binary matrices that do not have COP and some applications of COP.

c1

c1 *important:* All
have a few
lines about
organization
of chapter

2.1 COP in Graph Theory

COP is closely connected to several types of graphs by way of describing certain combinatorial graph properties. There are also certain graphs, like convex bipartite graphs, that are defined solely by some of its associated matrix having COP. In this section we will see the relevance of consecutive-ones property to graphs. To see this we introduce certain binary matrices that are used to define graphs in different ways. While adjacency matrix is perhaps the most commonly used such matrix, Definition 2.1.1 defines this and a few more.

Definition 2.1.1:

Matrices that define graphs. [Dom08, Def. 2.4]. Let G and H be defined as follows. $G = (V, E_G)$ is a graph with vertex set $V = \{v_i \mid i \in [n]\}$ and edge set $E_G \subseteq \{(v_i, v_j) \mid i, j \in [n]\}$ such that $|E_G| = m$. $H = (A, B, E_H)$ is a bipartite graph with partitions $A = \{a_i \mid i \in [n_a]\}$ and $B = \{b_i \mid i \in [n_b]\}$.

2.1.1–i. *Adjacency matrix* of G is the symmetric $n \times n$ binary matrix M with $m_{i,j} = 1$ if and only if $(v_i, v_j) \in E_G$ for all $i, j \in [n]$.

2.1.1–ii. *Augmented adjacency matrix* of G is obtained from its adjacency matrix by setting all main diagonal elements to **1**, i. e. $m_{i,i} = 1$ for all $i \in [n]$.

2.1.1–iii. *Maximal clique matrix* or *vertex-clique incidence matrix* of G is the $n \times k$ binary matrix M with $m_{i,j} = 1$ if and only if $v_i \in C_j$ for all $i \in [n], j \in [k]$ where $\{C_j \mid j \in [k]\}$ is the set of maximal cliques of G .

2.1.1–iv. *Half adjacency matrix* of H is the $n_a \times n_b$ binary matrix M with $m_{i,j} = 1$ if and only if $(a_i, b_j) \in E_H$.



Now we will see in Definition 2.1.2 certain graph classes that is related to COP or CROP.

Definition 2.1.2:

Graphs that relate to COP.[Dom08, Def. 2.5] Let G be a graph and H be a bipartite graph.

- 2.1.2–i. G is *convex-round* if its adjacency matrix has the CROP.
- 2.1.2–ii. G is *concave-round* if its augmented adjacency matrix has CROP. ^{c1} ^{c2}
- 2.1.2–iii. G is an *interval graph* if its vertices can be mapped to intervals on the real line such that two vertices are adjacent if and only if their corresponding intervals overlap ^{c3}. G is an interval graph if and only if its maximal clique matrix has COP [FG65]¹
- a. G is a *unit interval graph* if it is an interval graph such that all intervals have the same length.²
- b. G is a *proper interval graph* if it is an interval graph such that no interval properly contains another.² ^{c4}
- 2.1.2–iv. G is a *circular-arc graph* if its vertices can be mapped to a set of arcs on a circle such that two vertices are adjacent if and only if their corresponding arcs overlap. ^{c5}
- 2.1.2–v. H is *convex bipartite on columns (rows)* if its half adjacency matrix has COP on rows (columns).
- 2.1.2–vi. H is *biconvex bipartite* or *doubly convex*[YC95] if its half adjacency matrix has COP on both rows and columns.
- 2.1.2–vii. H is *circular convex* if its half adjacency matrix has CROP.



Interval graphs and circular-arc graphs have a long history in research. The interest around them is due to their very desirable property that several problems that are NP-hard^{c6} on general graphs are not so in these graph classes, i. e. they

^{c1} cite BHY00

^{c2} *minor*: add CROP to glossary

^{c3} cite Ben59, Haj57

^{c4} cite rob69,gar07 in endnote. pg 33 dom

^{c5} *pressing*: how is CO/ROP related?

^{c6} *minor*: all NPC problems are NPH yes?




Figure 2.1: A_1 is the *adjacency matrix* and A_2 is the *augmented adjacency matrix* of G_1 . A'_2 is obtained from A_2 by permuting its rows and columns to achieve *CROP order*, i. e. A_2 has CROP – thus G_1 is a *concave-round graph* (Def. 2.1.2 ii) and a *circular-arc graph* (Tab. 2.1) B is the maximal clique matrix of G_2 and has COP – thus G_2 is an *interval graph* (Def. 2.1.2 ii). C is the half adjacency matrix of bipartite graph H and has COP on rows – thus H is a convex bipartite graph. – [PLACEHOLDER IMAGES](#) –

are polynomial time solvable on them. In a similar fashion, a lot of problems that are hard on general matrices have efficient solutions on matrices with COP or CROP [Dom08, more citations pg. 33].

Table 2.1 summarises the way these graphs are characterized by their matrices having COP or CROP. Our focus in this chapter (and thesis) is mainly COP and having seen how useful COP is in identifying or characterizing many types of graphs, we will now see results that study recognition of COP in matrices in the following section.

tab 2.1 - have an abridged version of table 2.1 in dom. see notes for the possibility of a “circle diagram”.

Table 2.1: Graph matrices [PLACEHOLDER](#)

2.2 Matrices with COP

The most important questions with respect to a particular property desired in a structure/object are perhaps the following.

- Does the desired property exist in the given input?
- If the test is affirmative, what is a certificate of the affirmative?
- If the test is negative, what are the optimization possibilities for the property in the input? In other words, how close to having the property can the input be?
- If the test is negative, what is a certificate of the negative?

In this section and the rest of the chapter we see results that shaped the corresponding areas respectively for consecutive-ones property in binary matrices.

- a. Does a given binary matrix have COP?
- b. What is the COP permutation for the given matrix with COP?
- c. What are the optimizations possible and practically useful on the given matrix without COP?
- d. If algorithm for (a) returns **false**, can a certificate for this be computed?

Without doubt, besides computing answers to these questions, we are interested in the efficiency of these computations in terms of computational complexity theory. Results towards questions (a) and (b) are surveyed in this section. Those for question (c) are discussed in Section 2.3 and question (d) is discussed in Section 2.4.

It may be noted that one way to design an algorithm to test for COP is by deriving one from any interval graph recognition algorithm using the result HMPV00^{c1} ^{c2} [Dom08] which demonstrates how such a derivation can be done. However, this does not necessarily yield an efficient algorithm. We will see results that directly solve the problem on matrices since it is known that questions (a) and (b) stated above for COP are efficiently solvable. Table 2.2 gives a snapshot of these results.

^{c1} cite
hmpv00

^{c2} in endnote
put the
theorem 2.7 -
dom pg 43

History

1899	• First mention of COP (archaeology)	Petrie [Kendall 69, <i>Pacific Journal of Mathematics</i>]
1951	• Heuristics for COP testing (COT)	Robinson [51, <i>American Antiquity</i>]
1965	• First poly time algorithm for COT	Fulkerson, Gross [65, <i>Pacific Journal of Mathematics</i>]
1972	• Characterization of COP matrices • Forbidden matrix configurations	Tucker [72, <i>Journal of Combinatorial Theory</i>]
1976	• First linear time algorithm for COT • PQ trees	Booth, Lueker [76, <i>Journal of Computer System Science</i>]
Circa 2000 ²	• Linear algorithm for COT <i>without</i> PQ trees	Hsu [02, <i>Journal of Algorithms</i>]
2001	• PC trees • A generalization of PQ	Hsu [01, <i>7th Annual International Conference on Computing and Combinatorics</i>]
1996	• PQR trees • A generalization of PQ to non COP matrices • IDs subcollection of columns preventing COP	Meidanis, Munuera [96, <i>Proc of III South American Workshop on String processing</i>]
Circa 1998 ³	• Almost linear time algorithm to construct PQR trees	Meidanis, Telles [98, <i>Discrete Applied Mathematics</i>]
2009	• A New Characterization of Matrices with the Consecutive ones property	Narayanaswamy, Subashini [09, <i>Discrete Applied Mathematics</i>]

² Published 2002

³ Published 2003

Table 2.2: A brief history of COP research OLD IMG - PLACEHOLDER - A LATEX TABLE WILL REPLACE THIS + WILL BE UPDATED

2.2.1 Tucker's forbidden submatrices for COP

A polynomial time algorithm for COP testing was seen for the first time in [FG65] which uses overlapping properties of columns with **1s**. A few years later, a deeply significant result based on very different ideas in understanding COP came from Tucker which gave a combinatorial (negative) characterization of matrices with COP [Tuc72]. This result influenced most of the COP results that followed in the

literature ^{c3}including linear time algorithms for COP recognition.

^{c3}pressing: did it? which ones?

[Tuc72] discovered certain forbidden structures for convex bipartite graphs³ and by definition of this graph class, this translates to a set of forbidden submatrices for matrices with consecutive-ones property. The following are the theorems from [Tuc72] that achieved this characterization.

Theorem 2.2.1 proves that convex bipartite graphs cannot have *asteroidal triples*⁴ contained in the corresponding vertex partition⁵. Theorem 2.2.2 shows what are the structures in a bipartite graph that force one of its vertex partitions to have asteroidal triples – in other words, it identifies the subgraphs that prevent the graph from being convex bipartite.

Theorem 2.2.1. ([Tuc72, Th. 6], [Dom08, Th. 2.3])

A bipartite graph $G = (V_1, V_2, E)$ is convex bipartite on columns⁶ if and only if V_1 contains no asteroidal triple of G .

Theorem 2.2.2. ([Tuc72, Th. 7], [Dom08, Th. 2.4])

In a bipartite graph $G = (V_1, V_2, E)$ the vertex set V_1 contains no asteroidal triple if and only if G contains none of the graphs G_{I_k} , G_{II_k} , G_{III_k} (with $k \geq 1$), G_{IV} , G_V as shown in Figure 2.2 as subgraphs.




Figure 2.2: Tucker's forbidden subgraphs for convex bipartite graphs. [PLACEHOLDER IMG](#)

Theorem 2.2.1 and Theorem 2.2.2 result in the following Theorem 2.2.3 which characterizes matrices with COP.

Theorem 2.2.3. ([Tuc72, Th. 9], [Dom08, Th. 2.5])

A matrix M has COP if and only if it contains none of the matrices M_{I_k} , M_{II_k} , M_{III_k} (with $k \geq 1$), M_{IV} , M_V as shown in Figure 2.3 as submatrices.

$$\begin{array}{ccc}
\begin{array}{c} \overbrace{\begin{array}{cccccc} 1 & 1 & 0 & \cdots & 0 \\ 0 & 1 & 1 & 0 & \cdots & 0 \\ & & \cdots & & & \\ 0 & \cdots & 0 & 1 & 1 \\ 1 & 0 & \cdots & 0 & 1 \end{array}}^{k+2} \\ M_{I_k}, k \geq 1 \end{array} &
\begin{array}{c} \overbrace{\begin{array}{cccccc} 1 & 1 & 0 & \cdots & 0 \\ 0 & 1 & 1 & 0 & \cdots & 0 \\ & & \cdots & & & \\ 0 & \cdots & 0 & 1 & 1 & 0 \\ 0 & 1 & \cdots & \cdots & 1 & 1 \\ 1 & \cdots & \cdots & 1 & 0 & 1 \end{array}}^{k+3} \\ M_{II_k}, k \geq 1 \end{array} &
\begin{array}{c} \overbrace{\begin{array}{cccccc} 1 & 1 & 0 & \cdots & 0 \\ 0 & 1 & 1 & 0 & \cdots & 0 \\ & & \cdots & & & \\ 0 & \cdots & 0 & 1 & 1 & 0 \\ 0 & 1 & \cdots & 1 & 0 & 1 \end{array}}^{k+3} \\ M_{III_k}, k \geq 1 \end{array} \\
\\
\begin{array}{c} \begin{array}{cccccc} 1 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 1 \\ 1 & 0 & 1 & 0 & 1 & 0 \end{array} \\ M_{IV} \end{array} &
\begin{array}{c} \begin{array}{cccccc} 1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 \\ 1 & 1 & 1 & 1 & 0 \\ 1 & 0 & 1 & 0 & 1 \end{array} \\ M_V \end{array}
\end{array}$$

Figure 2.3: Tucker's forbidden submatrices for convex bipartite graphs. [PLACEHOLDER](#) [IMG](#)

It can be verified that the matrices in Figure 2.3 are the half adjacency matrices of the graphs in Figure 2.2 respectively which is not surprising due to Definition 2.1.2 v.

2.2.2 PQ tree – a linear COT algorithm

Booth and Lueker in their paper [BL76] gave the first linear algorithm for consecutive-ones property testing by way of an interval graph recognition algorithm. Their result has close relations to the characterization of interval graphs by [GH64]. A graph G is an interval graph if and only if all its maximal cliques can be linearly ordered such that for any vertex v in G , all the cliques that v is incident on are consecutive in this order. Clearly, this means that the maximal clique incidence matrix^{c0} must have COP on rows. This algorithm constructs a data structure called *PQ-tree*. A *PQ-tree* represents all the COP orderings of the matrix it is associated with. [BL76]'s algorithm uses the fact that if a matrix has COP, a *PQ-tree* for it can be constructed. It is interesting to note that aside from interval graph recognition and COP testing, *PQ-tree* is also useful in other applications like finding planar embeddings of planar graphs [?, McC04] and recognizing CROP in a matrix.

Definition 2.2.1:

[*PQ-tree* [BL76, McC04]]

A *PQ-tree* of matrix M with COP, is a tree with the following properties.

- i. Each leaf uniquely represents a row (column) of M . The leaf order of the tree gives a COP order for column (row)⁷ for M .
- ii. Every non-leaf node in the tree are labeled P or Q .

^{c0} Definition 2.1.1 iii

- iii. The children of P nodes are unordered. They can be permuted in any fashion to obtain a new COP order for M .
- iv. The children of Q nodes are linearly ordered. Their order can be reversed to get obtain a new COP order for M .



Thus, effectively, there exists a bijection between set of matrices with COP and the set of PQ -trees (accurately speaking, each matrix with COP bijectively maps to an equivalence class of PQ -trees due to properties (iii) and (iv)). See Figure 2.4 for an example of PQ -tree.




Figure 2.4: An example for PQ -tree. Permuting the order of the left child of the root, we see that (d,a,b,c,e,f,g,h,i,j,k) is a COP order. Reversing the order of the right child of the root, we see that (a,b,c,d,e,f,k,j,h,i,g) is yet another COP order. PLACEHOLDER IMG. [McC04, Fig. 1⁸]

The [BL76] algorithm with input $n \times m$ matrix M starts with a PQ -tree for a vacuous $n \times 0$ matrix M' (submatrix induced by 0 columns). This is known as a *universal* PQ -tree which is one with its root as a P node and only leaves as its children – each leaf representative of a row of input (by definition of COP for columns). This induced submatrix M' vacuously has COP. Each column is then added iteratively to M' to check if the new M' has COP. By a complicated, but linear, procedure the algorithm does one of the following actions in each iteration: (a) declare that M has no COP, or (b) modify the current PQ -tree to represent the new M' (which clearly, must have COP, since if not, option (a) would have been executed).

-I- Variations - PQR, PC etc. [MM96, Hsu01, McC04]

PQR trees is a generalized data structure based on PQ trees [MM96, MPT98]. [TM05] describes an improved algorithm to build PQR trees. ^{c1}.

Generalized PQ trees McC04 - brief. Will be elaborated in Section 2.4

Hsu also invented PC trees [Hsu01]^{c2} which is claimed to be much easier to implement.

^{c1} improv in terms of what?

^{c2} This result first appeared inproc ISAAC92

- II- Set theoretic characterizations [Hsu02, NS09]
 [Hsu02] describes the simpler algorithm for COT.^{c3}
 [NS09] describes a characterization of consecutive-ones property solely based on the cardinality properties of the set representations of the columns (rows); every column (row) is equivalent to a set that has the row (column) indices of the rows (columns) that have one entries in this column (row). This is interesting and relevant, especially to this thesis because it simplifies COT to a great degree by reducing the solution search space owing to the a simple set theoretic characterization.
- III- Parallel algorithms [AS95, BS03, CY91]

c3 *pressing*: in terms of what?

c1

c1 *pressing*: The results in cite bl76 on COT are based on the result that interval graphs are AT-free chordal graphs. - Tucker's?

c2

c2 *pressing*: cite uses these results to give the first polynomial time algorithm for COT. WHICH RESULTS? check. how do they use it?

c3

2.3 Optimization problems in COP

c4

So far we have been concerned about matrices that have the consecutive ones property. However in real life applications, it is rare that data sets represented by binary matrices have COP, primarily due to the noisy nature of data available. At the same time, COP is not arbitrary and is a desirable property in practical data representation [COR98, JKC⁺04, Kou77]. In this context, there are several interesting problems when a matrix does not have COP but is “close” to having COP or is allowed to be altered to have COP. These are the optimization problems related to a matrix which does not have COP. Some of the significant problems are surveyed in this section.

c3 *pressing*: ADDE peo exists iff chordal. lexicographic BFS [tag:chordalGraph]

c4 Expand on ref:sec:optcop

^{c5c6} [Tuc72] showed that a matrix that does not have COP have certain substructures that prevent it from having COP. Tucker classified these forbidden substructures into five classes of submatrices. This result is presented in the context of convex bipartite graphs which [Tuc72] proved to be AT-free^{c7}. By definition, convex bipartite graph have half adjacency matrices that have COP on either rows or columns (graph is biconvex if it has COP on both)[Dom08]. A half adjacency matrix is a binary matrix representing a bipartite graph as follows. The set of rows and the set of columns form the two partitions of the graph. Each row node is adjacent to those nodes that represent the columns that have 1s in the corresponding row. [Tuc72] proves that this bipartite graph has no asteroidal triple if and only if the matrix has COP and goes on to identify the forbidden substructures for these bipartite graphs. The matrices corresponding to these substructures are the forbidden submatrices.

c5 - sect 4.1 in cite:d08phd has many results surveyed. hardness results, approx. results. results are usually for a class of matrices (a, b) where number 1s in columns and rows are restricted to a and b . problem of flipping at most k entries of M to make it attain COP. this is NP complete cite:b75-phd

Once a matrix has been detected to not have COP (using any of the COT algorithms mentioned earlier), it is naturally of interest to find out the smallest forbidden substructure (in terms of number of rows and/or columns and/or number of entries that are 1s). [Dom08] discusses a couple of algorithms which are efficient if the number of 1s in a row is small. This is of significance in the case of sparse matrices where this number is much lesser than the number of columns. $(*, \Delta)$ -matrices are matrices with no restriction on number of 1s in any column but has at most Δ 1s in any row. MIN COS-R (MIN COS-C), MAX COS-R (MAX COS-C) are similar problems which deals with inducing COP on a matrix. In MIN COS-R (MIN COS-C) the question is to find the minimum number of rows (columns) that must be deleted to result in a matrix with COP. In the dual problem MAX COS-R (MAX COS-C) the search is for the maximum number of rows (columns) that induces a submatrix with COP. Given a matrix M with no COP, [Boo75] shows that finding a submatrix M' with all columns^{c8} but a maximum cardinality subset of rows such that M' has COP is NP complete. [HG02] corrects an error of the abridged proof of this reduction as given in [GJ79]. [Dom08] discusses all these problems in detail giving an extensive survey of the previously existing results which are almost exhaustively all approximation results and hardness results. Taking this further, [Dom08] presents new results in the area of parameterized algorithms for this problem^{c9}.

c6 (1) cite:lb62 showed that interval graphs are AT-free, describe AT (2) show the close relationship b/w COP and graphs sec 2.2, pg 31

c7 check this up. give details. - doms?

c8 check if b75 deals with COP col or COP row. also is it any submatrix with k less than r rows or submatrix must have all columns?

Another problem is to find the minimum number of entries in the matrix that can be toggled to result in a matrix with COP. [Vel85] discusses approximation of COP AUGMENTATION which

c9 elaborate - what are the results?

is the problem of changing of the minimum number of zero entries to **1s** so that the resulting matrix has COP. As mentioned earlier, this problem is known to be NP complete due to [Boo75]. [Vel85] also proves, using a reduction to the longest path problem, ^{c10} that finding a Tucker's forbidden submatrix of at least k rows is NP complete. ^{c11 c12}

[JKC⁺04] discusses the use of matrices with almost-COP (instead of one block of consecutive **1s**, they have x blocks, or *runs*, of consecutive **1s** and x is not too large) in the storage of very large databases. The problem is that of reordering of a binary matrix such that the resulting matrix has at most k runs of **1s**. This is proved to be NP hard using a reduction from the Hamiltonian path problem. ^{c1 c2c3 c4 c5}

2.4 Certifying Algorithms

Certifying algorithm (Generalized PQ trees) [McC04] – Move this to section on certifying algo.

[McC04] describes a different approach to COT. While all previous COT algorithms gave the COP order if the matrix has the property but exited stating negative if otherwise, this algorithm gives an evidence by way of a certificate of matrix even when it has no COP. This enables a user to verify the algorithm's result even when the answer is negative. This is significant from an implementation perspective because automated program verification is hard and manual verification is more viable. Hence having a certificate reinforces an implementation's credibility. Note that when the matrix *has* COP, the COP order is the certificate. The internal machinery of this algorithm is related to the weighted betweenness problem addressed^{c6} in [COR98]. ^{c7}

2.5 COP in Relational Database Model

^{c8 c9}

2.6 COP in Graph Isomorphism

^{c10 c11}

The survey from kklv10 conclusion.

Chapter Notes

¹This follows [GH64] which states that the maximal cliques of interval graph G can be linearly ordered such that for all $v \in V(G)$, cliques containing v are consecutive in the ordering [Gol04, Th. 8.1].

²The set of unit interval graphs and the set of proper interval graphs are the same

³The terminology in [Tuc72] differs. It uses the term *graphs with V_1 -consecutive arrangement* instead of *convex bipartite graphs*.

⁴If $G = (V, E)$ is a graph, a set of three vertices from V form an *asteroidal triple* if between any two of them there exists a path in G that does not contain any vertex from the closed neighborhood of the third vertex.

⁵The partition corresponds to columns (rows) if its half adjacency matrix has COP columns (rows).

^{c10} or is it a survey of another result? check.

^{c11} how is this different from booth's 75 result??

^{c12} where should this go? cite—tz04 (approx submatrix with COP sparse matrices)

^{c1} Theorem 2.1 in jkckv

^{c2} (1) A connection of COP problem to the travelling salesman problem is also introduced. what does this mean? – COP can be used as a tool to reorder $0.5T \leq runs(M) \leq$ (2) The optimization version of the k -run problem, i.e. minimization of number of blocks of ones is proven to be NP complete by cite:k77

^{c3} are these two the same?

^{c4} what is the reduction?

^{c5} other problems similar to COP – cite:ckl96 (ILP, circ ones, one drop) – cite:th98 (generalization of COP - minimax, biotonic column) Tucker

^{c6} in what way??

^{c7} expand on the COP order graph creation and it having to be bipartite for M to have COP, and thus an odd cycle being an evidence of no COP.

^{c8} Expand on sec:apprdbm

^{c9} (set systems theme)

^{c10} Expand on sec:appgraphiso

^{c11} (canonization theme)

⁶Abridged to match terminology adopted in this document. See previous note.

⁷Note that COP order for column requires permutation of rows and vice versa.

⁸[McC04] illustrates COP on rows. Our convention in this document is COP on columns and thus example matrix has been transposed.

c1

c1 remove if
none.

REFERENCES

- [ABH98] J. E. Atkins, E. G. Boman, and B. Hendrickson. A spectral algorithm for seriation and the consecutive ones problem. *SICOMP: SIAM Journal on Computing*, 28, 1998.
- [AS95] Annexstein and Swaminathan. On testing consecutive-ones property in parallel. In *SPAA: Annual ACM Symposium on Parallel Algorithms and Architectures*, 1995.
- [BL76] Kellogg S. Booth and George S. Lueker. Testing for the consecutive ones property, interval graphs, and graph planarity using *PQ*-tree algorithms. *Journal of Computer and System Sciences*, 13(3):335–379, December 1976.
- [BLS99] Andreas Brandstädt, Van Bang Le, and Jeremy P. Spinrad. *Graph classes: a survey*. Society for Industrial and Applied Mathematics, Philadelphia, PA, USA, 1999.
- [Boo75] Kellogg S. Booth. *PQ-tree algorithms*. PhD thesis, Univ. California, Berkeley, 1975.
- [BP92] J. R. S. Blair and B. Peyton. An introduction to chordal graphs and clique trees. Technical report, Oak Ridge National Laboratory, Oak Ridge, Tennessee 37831, 1992.
- [BS03] David A. Bader and Sukanya Sreshta. A new parallel algorithm for planarity testing, April 11 2003.
- [COR98] Thomas Christof, Marcus Oswald, and Gerhard Reinelt. Consecutive ones and a betweenness problem in computational biology. *Lecture Notes in Computer Science*, 1412, 1998.
- [CY91] Lin Chen and Yaacov Yesha. Parallel recognition of the consecutive ones property with applications. *J. Algorithms*, 12(3):375–392, 1991.
- [Dom08] Michael Dom. *Recognition, Generation, and Application of Binary Matrices with the Consecutive-Ones Property*. PhD thesis, Institut für Informatik, Friedrich-Schiller-Universität Jena, Germany, 2008. Published by Cuvillier, 2009.
- [FG65] D. R. Fulkerson and O. A. Gross. Incidence matrices and interval graphs. *Pac. J. Math.*, 15:835–855, 1965.
- [Gav78] Fanica Gavril. A recognition algorithm for the intersection graphs of paths in trees. *Discrete Mathematics*, 23(3):211 – 227, 1978.
- [GH64] P. C. Gilmore and A. J. Hoffman. A characterization of comparability graphs and of interval graphs. *Can. J. Math.*, 16:539–548, 1964.
- [GJ79] M. R. Garey and D. S. Johnson. *Computers and Intractability*. Freeman, San Francisco, 1979.
- [Gol04] Martin Charles Golumbic. *Algorithmic graph theory and perfect graphs*, volume 57 of *Annals of Discrete Mathematics*. Elsevier Science B.V., 2004. Second Edition.
- [HG02] Hajiaghayi and Ganjali. A note on the consecutive ones submatrix problem. *IPL: Information Processing Letters*, 83, 2002.
- [HL06] Dorit S. Hochbaum and Asaf Levin. Cyclical scheduling and multi-shift scheduling: Complexity and approximation algorithms. *Discrete Optimization*, 3(4):327–340, 2006.
- [Hsu01] Wen-Lian Hsu. PC-trees vs. PQ-trees. *Lecture Notes in Computer Science*, 2108:207–217, 2001.
- [Hsu02] Wen-Lian Hsu. A simple test for the consecutive ones property. *J. Algorithms*, 43(1):1–16, 2002.

- [HT02] Hochbaum and Tucker. Minimax problems with bitonic matrices. *NETWORKS: Networks: An International Journal*, 40, 2002.
- [JKC⁺04] Johnson, Krishnan, Chhugani, Kumar, and Venkatasubramanian. Compressing large boolean matrices using reordering techniques. In *VLDB: International Conference on Very Large Data Bases*. Morgan Kaufmann Publishers, 2004.
- [KKLV10] Johannes Köbler, Sebastian Kuhnert, Bastian Laubner, and Oleg Verbitsky. Interval graphs: Canonical representation in logspace. *Electronic Colloquium on Computational Complexity (ECCC)*, 17:43, 2010.
- [KM02] P. S. Kumar and C. E. Veni Madhavan. Clique tree generalization and new subclasses of chordal graphs. *Discrete Applied Mathematics*, 117:109–131, 2002.
- [Kou77] Lawrence T. Kou. Polynomial complete consecutive information retrieval problems. *SIAM Journal on Computing*, 6(1):67–75, March 1977.
- [Lin92] Steven Lindell. A logspace algorithm for tree canonization (extended abstract). In *STOC*, pages 400–404. ACM, 1992.
- [McC04] Ross M. McConnell. A certifying algorithm for the consecutive-ones property. In *SODA: ACM-SIAM Symposium on Discrete Algorithms (A Conference on Theoretical and Experimental Analysis of Discrete Algorithms)*, 2004.
- [MM96] J. Meidanis and Erasmo G. Munuera. A theory for the consecutive ones property. In *Proceedings of WSP’96 - Third South American Workshop on String Processing*, pages 194–202, 1996.
- [MPT98] Meidanis, Porto, and Telles. On the consecutive ones property. *DAMATH: Discrete Applied Mathematics and Combinatorial Operations Research and Computer Science*, 88, 1998.
- [NS09] N. S. Narayanaswamy and R. Subashini. A new characterization of matrices with the consecutive ones property. *Discrete Applied Mathematics*, 157(18):3721–3727, 2009.
- [PPY94] Barry W. Peyton, Alex Pothén, and Xiaoqing Yuan. A clique tree algorithm for partitioning a chordal graph into transitive subgraphs. Technical report, Old Dominion University, Norfolk, VA, USA, 1994.
- [Rei84] John H. Reif. Symmetric complementation. *JACM: Journal of the ACM*, 31(2):401–421, 1984.
- [Ren70] Peter L. Renz. Intersection representations of graphs by arcs. *Pacific J. Math.*, 34(2):501–510, 1970.
- [Sch93] Alejandro A. Schaffer. A faster algorithm to recognize undirected path graphs. *Discrete Applied Mathematics*, 43:261–295, 1993.
- [TM05] Guilherme P. Telles and João Meidanis. Building PQR trees in almost-linear time. *Electronic Notes in Discrete Mathematics*, 19:33–39, 2005.
- [Tuc72] Alan Tucker. A structure theorem for the consecutive 1’s property. *J. Comb. Theory Series B*, 12:153–162, 1972.
- [Vel85] Marinus Veldhorst. Approximation of the consecutive ones matrix augmentation problem. *SIAM Journal on Computing*, 14(3):709–729, August 1985.
- [YC95] Yu and Chen. Efficient parallel algorithms for doubly convex-bipartite graphs. *TCS: Theoretical Computer Science*, 147:249–265, 1995.