

Tree Path Labeling of Path Hypergraphs

Generalization of the Consecutive-ones Property

Anju Srinivasan

as part of **M. S.** by Research
advised by **Dr. N. S. Narayanaswamy**
CSE, IITM, Chennai - 36

25 March 2013

① Introduction

An Illustration

Terminology

Motivation

② Problems

③ Characterization of a feasible TPL

ICPPL

④ Computing a feasible TPL on k -subdivided trees

⑤ Conclusion

Application

An Illustration

- To introduce the combinatorial problem of TPL.

Study Group Accommodation problem

- A set of n **students** arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.

Study Group Accommodation problem

- A set of n **students** arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m **study groups**, say $\{R, B, O, G\}$, $m = 4$

Study Group Accommodation problem

- A set of n **students** arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m **study groups**, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but *will* be in at least one, say

$$R = \{g, h, i, j, k\}, B = \{a, b, e, g\}, O = \{c, b, d\}, \\ G = \{e, f, g, i\}$$

Study Group Accommodation problem

- A set of n **students** arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m **study groups**, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but *will* be in at least one, say
 $R = \{g, h, i, j, k\}$, $B = \{a, b, e, g\}$, $O = \{c, b, d\}$,
 $G = \{e, f, g, i\}$
- There are n single occupancy **apartments** in the university campus for their accommodation.

Study Group Accommodation problem

- A set of n **students** arrive for a summer course, say $\{a, b, c, d, e, f, g, h, i, j, k\}$, $n = 11$.
- They form m **study groups**, say $\{R, B, O, G\}$, $m = 4$
- A student may be in more than one study group but *will* be in at least one, say
 $R = \{g, h, i, j, k\}$, $B = \{a, b, e, g\}$, $O = \{c, b, d\}$,
 $G = \{e, f, g, i\}$
- There are n single occupancy **apartments** in the university campus for their accommodation.
- All these apartments are placed such that streets connecting them do not form loops - **streets form a tree**

Study Group Accommodation problem

The problem

How should the students be allocated apartments such that:

- students of each study group are neighbours?


Study Group Accommodation problem

The problem

How should the students be allocated apartments such that:

- students of each study group are neighbours?
- i.e. a study group forms **a path in the tree**.

Study Group Accommodation problem




$$R = \{g, h, i, j, k\}$$

$$B = \{a, b, e, g\}$$

$$O = \{c, b, d\}$$

$$G = \{e, f, g, i\}$$

Study Group Accommodation problem



$$R = \{g, h, i, j, k\}$$

$$\rightarrow \{9, 1, 5, 3, 11\}$$

$$B = \{a, b, e, g\}$$

$$\rightarrow \{7, 2, 6, 5\}$$


$$O = \{c, b, d\}$$

$$\rightarrow \{4, 2, 8\}$$

$$G = \{e, f, g, i\}$$

$$\rightarrow \{10, 6, 5, 3\}$$

Study Group Accommodation problem



$$R = \{g, h, i, j, k\}$$

$$\rightarrow \{9, 1, 5, 3, 11\}$$

$$B = \{a, b, e, g\}$$

$$\rightarrow \{7, 2, 6, 5\}$$

$$O = \{c, b, d\}$$

$$\rightarrow \{4, 2, 8\}$$

$$G = \{e, f, g, i\}$$

$$\rightarrow \{10, 6, 5, 3\}$$

Tree Path Labeling of Path Hypergraphs

- The set of study groups \rightarrow **Set system / Hypergraph**

Tree Path Labeling of Path Hypergraphs

- The set of study groups → **Set system / Hypergraph**
- The streets with apartments → **Target tree**

Tree Path Labeling of Path Hypergraphs

- The set of study groups → **Set system / Hypergraph**
- The streets with apartments → **Target tree**
- The path mapping to study groups → **Tree Path Labeling (TPL)**

Tree Path Labeling of Path Hypergraphs

- The set of study groups → **Set system / Hypergraph**
- The streets with apartments → **Target tree**
- The path mapping to study groups → **Tree Path Labeling (TPL)**
- The apartment allocation → **Path Hypergraph Isomorphism**

Tree Path Labeling of Path Hypergraphs

There *exists* an apartment allocation that “fits” the path mapping

Tree Path Labeling of Path Hypergraphs

There *exists* a **hypergraph isomorphism** that “fits” the **TPL**

Tree Path Labeling of Path Hypergraphs

There *exists* a **hypergraph isomorphism** that “fits” the **TPL**
 \Rightarrow the TPL is **FEASIBLE**

Tree Path Labeling of Path Hypergraphs

There *exists* a **hypergraph isomorphism** that “fits” the **TPL**
 \Rightarrow the TPL is **FEASIBLE**

There *exists* an apartment allocation that gives some study group path mapping

Tree Path Labeling of Path Hypergraphs

There *exists* a **hypergraph isomorphism** that “fits” the **TPL**
 \Rightarrow the TPL is **FEASIBLE**

There *exists* a **hypergraph isomorphism** that gives **at least one feasible TPL**

Tree Path Labeling of Path Hypergraphs

There *exists* a **hypergraph isomorphism** that “fits” the **TPL**


⇒ the TPL is **FEASIBLE**

There *exists* a **hypergraph isomorphism** that gives **at least one feasible TPL**

⇒ the hypergraph is a **PATH HYPERGRAPH**

Consecutive Ones \rightarrow Path Labeling

The motivation



COMPUTE FEASIBLE TREE PATH LABELING

Input	A hypergraph \mathcal{F} with vertex set U and a tree T .
Question	Does there exist a set of paths \mathcal{P} from T and a bijection $\ell : \mathcal{F} \rightarrow \mathcal{P}$, such that FEASIBLE TREE PATH LABELING returns true on (\mathcal{F}, T, ℓ) .

COMPUTE FEASIBLE TREE PATH LABELING

- Is the given hypergraph \mathcal{F} a **path hypergraph** w.r.t. target tree T ?
- i.e. find at least one feasible tree path labeling $\ell : \mathcal{F} \rightarrow P$, P is a set of paths on T .
- Complexity is inconclusive for arbitrary trees, polynomial time for certain classes of trees.

FEASIBLE TREE PATH LABELING

Input	A hypergraph \mathcal{F} with vertex set U , a tree T , a set of paths \mathcal{P} from T and a bijection $\ell : \mathcal{F} \rightarrow \mathcal{P}$.
Question	<p>Does there exist a bijection $\phi : U \rightarrow V(T)$ such that ϕ when applied on any hyperedge in \mathcal{F} will give the path mapped to it by the given tree path labeling ℓ.</p> <p>i.e., $\ell(S) = \{\phi(x) \mid x \in S\}$, for every hyperedge $S \in \mathcal{F}$.</p>

FEASIBLE TREE PATH LABELING

- Is the given TPL ℓ of hypergraph \mathcal{F} on tree T feasible?
- What is the **hypergraph isomorphism** $\phi : U \rightarrow V(T)$?
- Solvable in polynomial time.

COMPUTE INTERVAL LABELING

COMPUTE FEASIBLE TREE PATH LABELING when target tree is an interval or path P_n

COMPUTE INTERVAL LABELING

- Is the given hypergraph \mathcal{F} an **interval hypergraph** [KKLV10]?
- Equivalent to consecutive ones property checking or ICPIA [NS09]
- Solvable in polynomial time.

COMPUTE k -SUBDIVIDED STAR PATH LABELING

COMPUTE FEASIBLE TREE PATH LABELING when target tree is a k -subdivided star and every hyperedge in \mathcal{F} is of size at most $k + 2$

COMPUTE k -SUBDIVIDED STAR PATH LABELING


- Solvable in polynomial time.

k -subdivided star

A star with all its edges subdivided exactly k times.

k -subdivided star


A star with all its edges subdivided exactly k times.



$k = 0$, star

k -subdivided star

A star with all its edges subdivided exactly k times.



2-subdivided star

FEASIBLE TREE PATH LABELING

Input	A hypergraph \mathcal{F} with vertex set U , a tree T , a set of paths \mathcal{P} from T and a bijection $\ell : \mathcal{F} \rightarrow \mathcal{P}$.
Question	Does there exist a bijection $\phi : U \rightarrow V(T)$ such that ϕ when applied on any hyperedge in \mathcal{F} will give the path mapped to it by the given tree path labeling ℓ . i.e., $\ell(S) = \{\phi(x) \mid x \in S\}$, for every hyperedge $S \in \mathcal{F}$.

A characterization of feasible TPL

Intersection Cardinality Preserving Path Labeling (ICPPL)

A path labeling (\mathcal{F}, ℓ) on the given tree T s.t.

$$|S_1 \cap S_2 \cap S_3| = |\ell(S_1) \cap \ell(S_2) \cap \ell(S_3)|$$

for all not necessarily distinct $S_1, S_2, S_3 \in \mathcal{F}$

A characterization of feasible TPL

Intersection Cardinality Preserving Path Labeling (ICPPL)

A path labeling (\mathcal{F}, ℓ) on the given tree T s.t.

$$|S_1 \cap S_2 \cap S_3| = |\ell(S_1) \cap \ell(S_2) \cap \ell(S_3)|$$

for all not necessarily distinct $S_1, S_2, S_3 \in \mathcal{F}$

Theorem

A path labeling (\mathcal{F}, ℓ) on tree T is feasible iff it is an ICPPL.

Finding path hypergraph isomorphism ϕ

Given an ICPPL (\mathcal{F}, ℓ) on tree T

- Uses two filters to refine (\mathcal{F}, ℓ)

Finding path hypergraph isomorphism ϕ

Given an ICPPL (\mathcal{F}, ℓ) on tree T

- Uses two filters to refine (\mathcal{F}, ℓ)
- **filter common leaf** - ensures that the resulting ICPPL has no two path labels sharing a leaf.

Finding path hypergraph isomorphism ϕ

Given an ICPPL (\mathcal{F}, ℓ) on tree T

- Uses two filters to refine (\mathcal{F}, ℓ)
- **filter common leaf** - ensures that the resulting ICPPL has no two path labels sharing a leaf.
- **filter fix leaf** - finds the pre-image of each leaf in T .

Finding path hypergraph isomorphism ϕ

Given an ICPPL (\mathcal{F}, ℓ) on tree T

- Uses two filters to refine (\mathcal{F}, ℓ)
- **filter common leaf** - ensures that the resulting ICPPL has no two path labels sharing a leaf.
- **filter fix leaf** - finds the pre-image of each leaf in T .
- Remove leaves from T and their preimages from \mathcal{F} . Repeat filters until T becomes a path.

Finding path hypergraph isomorphism ϕ

Given an ICPPL (\mathcal{F}, ℓ) on tree T

- Uses two filters to refine (\mathcal{F}, ℓ)
- **filter common leaf** - ensures that the resulting ICPPL has no two path labels sharing a leaf.
- **filter fix leaf** - finds the pre-image of each leaf in T .
- Remove leaves from T and their preimages from \mathcal{F} . Repeat filters until T becomes a path.
- When T is a path, problem becomes interval assignment. Use ICPIA [NS09]

Finding path hypergraph isomorphism ϕ

filter common leaf (\mathcal{F}, ℓ)

- Pick any two paths P_1, P_2 in (\mathcal{F}, ℓ) that share a leaf. Let $\ell(S_i) = P_i$ for all $S_i \in \mathcal{F}$.

Finding path hypergraph isomorphism ϕ

filter common leaf (\mathcal{F}, ℓ)

- Pick any two paths P_1, P_2 in (\mathcal{F}, ℓ) that share a leaf. Let $\ell(S_i) = P_i$ for all $S_i \in \mathcal{F}$.
- Remove S_1, S_2, P_1, P_2 from (\mathcal{F}, ℓ)

Finding path hypergraph isomorphism ϕ

filter common leaf (\mathcal{F}, ℓ)

- Pick any two paths P_1, P_2 in (\mathcal{F}, ℓ) that share a leaf. Let $\ell(S_i) = P_i$ for all $S_i \in \mathcal{F}$.
- Remove S_1, S_2, P_1, P_2 from (\mathcal{F}, ℓ)
- Add to (\mathcal{F}, ℓ) :
 - $\ell(S_1 \setminus S_2) = P_1 \setminus P_2$
 - $\ell(S_2 \setminus S_1) = P_2 \setminus P_1$
 - $\ell(S_1 \cap S_2) = P_1 \cap P_2$

Finding path hypergraph isomorphism ϕ

filter common leaf (\mathcal{F}, ℓ)

- Pick any two paths P_1, P_2 in (\mathcal{F}, ℓ) that share a leaf. Let $\ell(S_i) = P_i$ for all $S_i \in \mathcal{F}$.
- Remove S_1, S_2, P_1, P_2 from (\mathcal{F}, ℓ)
- Add to (\mathcal{F}, ℓ) :
 - $\ell(S_1 \setminus S_2) = P_1 \setminus P_2$
 - $\ell(S_2 \setminus S_1) = P_2 \setminus P_1$
 - $\ell(S_1 \cap S_2) = P_1 \cap P_2$
- Repeat till no two paths share a leaf.

Finding path hypergraph isomorphism ϕ

filter common leaf (\mathcal{F}, ℓ)

Lemma

Let (\mathcal{F}', ℓ') be the resulting labeling after applying filter common leaf to TPL (\mathcal{F}, ℓ) . If (\mathcal{F}, ℓ) is an ICPPL, (\mathcal{F}', ℓ') is also an ICPPL.

Finding path hypergraph isomorphism ϕ

filter common leaf (\mathcal{F}, ℓ)

Lemma

Let (\mathcal{F}', ℓ') be the resulting labeling after applying filter common leaf to TPL (\mathcal{F}, ℓ) . If (\mathcal{F}, ℓ) is an ICPPL, (\mathcal{F}', ℓ') is also an ICPPL.

Proof.

- Induction on iteration of the filter.
- Invariants: $\ell_j(S)$ is a path, ℓ_j maintains ICPPL's intersection cardinality equations.
- ICPPL also preserves 4-way intersection cardinalities.



Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path
- Pick a leaf v , let it be on path P . Let $\ell(S) = P$

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path
- Pick a leaf v , let it be on path P . Let $\ell(S) = P$
- Pick an element x from S which is not present in any other set. i.e. $x \in S \setminus \bigcup_{S_i \neq S} S_i$

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path
- Pick a leaf v , let it be on path P . Let $\ell(S) = P$
- Pick an element x from S which is not present in any other set. i.e. $x \in S \setminus \bigcup_{S_i \neq S} S_i$
- Remove S, P from (\mathcal{F}, ℓ)

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path
- Pick a leaf v , let it be on path P . Let $\ell(S) = P$
- Pick an element x from S which is not present in any other set. i.e. $x \in S \setminus \bigcup_{S_i \neq S} S_i$
- Remove S, P from (\mathcal{F}, ℓ)
- Add $\ell(S \setminus x) = P \setminus v$. Define $\phi(x) = v$

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path
- Pick a leaf v , let it be on path P . Let $\ell(S) = P$
- Pick an element x from S which is not present in any other set. i.e. $x \in S \setminus \bigcup_{S_i \neq S} S_i$
- Remove S, P from (\mathcal{F}, ℓ)
- Add $\ell(S \setminus x) = P \setminus v$. Define $\phi(x) = v$
- Remove leaf v from T

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path
- Pick a leaf v , let it be on path P . Let $\ell(S) = P$
- Pick an element x from S which is not present in any other set. i.e. $x \in S \setminus \bigcup_{S_i \neq S} S_i$
- Remove S, P from (\mathcal{F}, ℓ)
- Add $\ell(S \setminus x) = P \setminus v$. Define $\phi(x) = v$
- Remove leaf v from T
- Repeat till there are no more unique paths for leaves. Call filter common leaf.

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

- A leaf is unique to a path
- Pick a leaf v , let it be on path P . Let $\ell(S) = P$
- Pick an element x from S which is not present in any other set. i.e. $x \in S \setminus \bigcup_{S_i \neq S} S_i$
- Remove S, P from (\mathcal{F}, ℓ)
- Add $\ell(S \setminus x) = P \setminus v$. Define $\phi(x) = v$
- Remove leaf v from T
- Repeat till there are no more unique paths for leaves. Call filter common leaf.
- End if T is empty

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

Critical part is finding $x \in S \setminus \cup_{S_i \neq S} S_i$

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

Critical part is finding $x \in S \setminus \cup_{S_i \neq S} S_i$

Lemma

If $\ell(S)$ uniquely has a leaf, S_{priv} is *non-empty* where
 $S_{priv} = S \setminus \cup_{S_i \neq S} S_i$.

Finding path hypergraph isomorphism ϕ

filter fix leaf (\mathcal{F}, ℓ)

Critical part is finding $x \in S \setminus \cup_{S_i \neq S} S_i$

Lemma

If $\ell(S)$ uniquely has a leaf, S_{priv} is **non-empty** where
 $S_{priv} = S \setminus \cup_{S_i \neq S} S_i$.

Proof.

- Let $\mathcal{F}' = S \cap S_i$ and $\ell'(S \cap S_i) = P \cap P_i$ for all $S_i \in \mathcal{F}$, $\ell(S_i) = P_i$.
- $S_{two} = \text{supp}(\mathcal{F}')$, $P_{two} = \text{supp}(\ell')$
- (\mathcal{F}', ℓ') is an ICPIA. Therefore $|S_{two}| = |P_{two}|$. Hence $|S_{priv}| = |P_{priv}|$. We know P has at least a leaf.

COMPUTE k -SUBDIVIDED STAR PATH LABELING

COMPUTE FEASIBLE TREE PATH LABELING when target tree is a k -subdivided star and every hyperedge in \mathcal{F} is of size at most $k + 2$

Why k -subdivided star?

- When the root vertex is removed, we get disjoint paths.

Why k -subdivided star?

- When the root vertex is removed, we get disjoint paths.
- Super marginal sets are assigned paths that contain leaves.

Supermarginal set

Marginal set is a set whose intersections with all other sets in \mathcal{F} form a single inclusion chain. **Supermarginal set** is a marginal set that is not contained in any other set.

Why k -subdivided star?

- When the root vertex is removed, we get disjoint paths.
- Super marginal sets are assigned paths that contain leaves.
- Sets that overlap with the super marginal set are considered using ICPIA [NS09] until a path containing root vertex is assigned.

Supermarginal set

Marginal set is a set whose intersections with all other sets in \mathcal{F} form a single inclusion chain. **Supermarginal set** is a marginal set that is not contained in any other set.

Why k -subdivided star?


- When the root vertex is removed, we get disjoint paths.
- Super marginal sets are assigned paths that contain leaves.
- Sets that overlap with the super marginal set are considered using ICPIA [NS09] until a path containing root vertex is assigned.
- ICPPL is used when path label must be from two rays.

Supermarginal set

Marginal set is a set whose intersections with all other sets in \mathcal{F} form a single inclusion chain. **Supermarginal set** is a marginal set that is not contained in any other set.


Path Labeling \rightarrow Graph Isomorphism

Application




Path Labeling \rightarrow Graph Isomorphism

Application



Path Labeling \rightarrow Graph Isomorphism

Application



References I



Martin Charles Golumbic.

Algorithmic graph theory and perfect graphs, volume 57 of *Annals of Discrete Mathematics*.

Elsevier Science B.V., 2004.

Second Edition.



Johannes Köbler, Sebastian Kuhnert, Bastian Laubner, and Oleg Verbitsky.

Interval graphs: Canonical representation in logspace.

Electronic Colloquium on Computational Complexity (ECCC), 17:43, 2010.



N. S. Narayanaswamy and R. Subashini.

A new characterization of matrices with the consecutive ones property.

Discrete Applied Mathematics, 157(18):3721–3727, 2009.

Thank you

Questions?