

Version 7.0

Template Designers Guide

2017-08-01

Index

1	General.....	1
2	Template management.....	1
3	Page-, component- and metadata templates	3
3.1	Creating a template.....	3
3.1.1	hyperCMS Tags	6
3.1.2	Language setting.....	10
3.1.3	Template variables	11
3.1.4	Examples of the use of tags hyperCMS	13
3.1.5	hyperCMS TagWizard	18
3.3	Deleting templates.....	22
3.4	Editing templates.....	22
3.5	License notification.....	23
3.6	Meta data mapping	24
4	Metadata/Content hierarchy.....	25
5	Template media management	26
5.1	Managing media categories	26
5.2	Uploading files.....	26
5.3	Removing files.....	27
5.4	Searching for files	28
6	Legal reference / flag	29
6.1	Questions and suggestions	29
6.2	Imprint.....	29
6.3	Legal information.....	29


1 General

When designing templates you should care about the effective maintenance of the corporate design. It is recommended to use only a few page templates and stay flexible by using component templates and scripts instead.

2 Template management

Templates define the design and the appearance of your website as well as the editable elements of a page or component (e.g. text, images, links, etc.). Using either the TagWizard of the template management system or code generated with an HTML-editor (e.g. Dreamweaver) you can create new templates. HTML-files can be imported into hyperCMS directly. Using the TagWizard you can create new templates online in an easy way and without programming skills.

All templates are managed by a version management system. When editing and saving a template a new version is created automatically by the system. Therefore you can undo any change in a document or just view the single versions of a template.




All versions of a template are being archived. Every time you save, a new version of the template is created. Therefore it is possible to view, select and use previous versions of the template.

The hyper Content Management Server distinguishes between „pages“ and „components“ and needs design templates for both. The functionalities of the templates, however, vary only slightly. Basically, „pages“ and „components“ are treated nearly the same. There are some differences in personalisation; e.g. customer trackings can only be used on pages whereas profiles are always used on components. The definition of metadata and the page title only is possible by using page templates.

Besides the above mentioned templates for pages and components there are templates for metadata, which take an exceptional position. They are used for defining the keywords for multimedia files and folders. Metadata templates therefore do not define the design but the input options of metadata and are very limited compared to templates for pages or components. HTML- and script code is ignored and without function. It is important that there is a predefined template called „default“ in the system. The „default“ template cannot be removed or deleted. Every time a file is uploaded or a new folder is created the default metadata template is assigned to the new object.

Please select the corresponding option from the navigation bar to gain access to the templates for pages or components. If you do so, a toolbar will be shown in your working environment. If you move the mouse pointer over one of the icons, the name and description of the action will be displayed.




You can start the following actions:

- Creating a new template
- Deleting an existing template
- Editing an existing template
- Setting up the license notification (only for metadata templates)
- Configuration of the metadata mappings (only for metadata templates)
- Configuration of the metadata/content hierarchy browsing (only for metadata templates)

3 Page-, component- and metadata templates

3.1 Creating a template

Please click on the first icon on the left of the toolbar. A description field will appear requesting a name for the new template.




Enter the name (the name must be unique for each publication). Page templates always refer to a page whereas component templates are used to create components. Template Includes on the other hand are used to amend one or various page or component templates. The usage of template includes is similar to the one of file includes. By using include, it is possible to integrate recurrent code into any other page or component templates.

Metadata templates are used for gathering meta-information of folders and multimedia files (assets).

After selecting the type of the template, click on „OK“ and the editor will be displayed on top of your working environment. By using the editor you can now define the file extension of your page or component.

The file extension tells the web server which application to use for executing the file unless the file can directly be opened. Usual file extensions are: .asp, .php, .jsp or .html. Therefore it is important that your web server knows the file extensions and the corresponding applications to open the files. Please refer to the configuration notes of your web server.

The selection field for the application defines the template of the underlying application. Please make sure that the selected file extension corresponds with the application.

Template	Version	Information
Page template		Detail
File extension (without dot)		php
Application		PHP Hypertext Preprocessor (PHP) 
Article identification name		Active Server Pages (ASP)
Content identification name		Extensible Markup Language (XML) or Text
Hide content		Hypertext Markup Language (HTML)
		Java Server Pages (JSP)
		PHP Hypertext Preprocessor (PHP)
		Meta information
		<input type="checkbox"/> on publish <input type="checkbox"/> on edit

Please note the following overview of applications:

Application / Format	File Extension (usually)	Explanation
Active Server Pages	.asp	Active Server Pages (ASP) from Microsoft consists of a server-based script language related to Visual Basic.
Extensible Markup Language or Text	.xml, .txt, .xsl, etc.	<p>The Extensible Markup Language (XML) is a data description language. The Extensible StyleSheet Language (XSL) can be used to render XML-documents. It can also manage any format based on ASCII-code like e.g. text documents.</p> <p>Link management, personalisation, time management as well as applications with templates can not be used because server-based program code cannot be executed. XML-documents and XSL-documents are often used by other web applications to dynamically render HTML-pages. XML-documents are also used for data exchange and are directly provided by the web server.</p>
Hypertext Markup Language	.html, .htm	<p>HTML is the standard language but does not allow any server-based interactivity. Link management, personalisation, time management as well as applications can not be used. HTML-documents only need a web server; e.g.: Apache or Microsoft IIS.</p>
Java Server Pages	.jsp	Java Server Pages is a server-based programming language and is related to the computer language Java from SUN Systems. Common application servers are Tomcat, WebSphere as well as Bea Weblogic.
PHP Hypertext Preprocessor	.php, .phtml	PHP is a server-based script language. It can be used as a module on all common web servers like e.g. Apache or Microsoft IIS.

The so-called „hyperCMS TagWizard" can be found among the definition fields. You can copy existing HTML-code from your HTML-editor and paste it into the TagWizard.

On the basis of a small example we are now going to look at the practice on working with existing HTML-code in page and component templates:

The designer creates the design of a new page, which ends in HTML-code. All design-elements have been integrated in this code. The following HTML-code will show this on the basis of a small example:

Page template for creating pages

```
<html>
<head>
<title>Document</title>
<meta http-equiv="Content-Type" content="text/html; charset=utf-8">
</head>
<body bgcolor="#FFFFFF" text="#000000">
<p>Page Title</p>
<table width="100%" border="0" cellspacing="0" cellpadding="0">
<tr>
<td>Menu1</td>
<td>Menu2</td>
<td>Menu3</td>
<td>Menu4</td>
</tr>
</table>
<table width="100%" border="0" cellspacing="0" cellpadding="0">
<tr>
<td>Title</td>
</tr>
<tr>
<td>Text</td>
</tr>
</table>
</body>
</html>
```

Component Template
for the main
navigation bar of the
page

Component Template
for the content of the
page

As you can see in the example above, tables in the HTML-code are removed to use them for component templates. Instead of both of the tables the hyperCMS tags for both of the components [hyperCMS:components id='menu'] and [hyperCMS:componenttm id='pagecontent'] are integrated.

You should have some basic HTML-knowledge to create templates. This is why this task is usually done by web designers who generate HTML-code for pages respectively components out of their favourite HTML-editor. The generated HTML-code can then be converted into templates with the help of the hyperCMS TagWizard.

To create templates from existing HTML-code you must insert specific hyperCMS-tags. To do so, select the text or position in the HTML-code where an editable object should appear (e.g. formatted text with id='Introduction'). By clicking on one of the icons the hyperCMS tags are integrated into the HTML-code.

Be aware that an ID (Identification) has to be assigned to most of the elements. The ID can easily be defined via the form fields of the TagWizard.

To integrate media files we make use of a path variable. When publishing a page or component, the path variable is replaced by the URL (address) of the target of the publication.

%tplmedia% stands for the path of the template media repository.

3.1.1 hyperCMS Tags

The following tables describes all hyperCMS tags:

Article Tag prefix

(can be used as prefix for all text, media, link and component tags, excl. personalized component tags.)

Article	[hyperCMS:art...tag...]
Text Tag set	
unformatted text	[hyperCMS:textu id='...']
formatted text	[hyperCMS:textf id='...']
Text option from text list	[hyperCMS:textl id='...' list='...' file='...']
Checkbox	[hyperCMS:textc id='...' value='...']
Date, Date format (optional)	[hyperCMS:textd id='...' format='%Y-%m-%d']
Keywords with optional mandatory or open list	[hyperCMS:textk id='...' list='...' file='...' onlylist='yes/no']
Display name (optional)	label='...'
Content cannot be edited (optional)	onEdit='hidden'
hide content (optional)	onPublish='hidden'
Read-only content	readonly='readonly'
Width of editorfield in pixel (optional)	width='...'
Height of editorfield in pixel (optional)	height='...'
Toolbar selection for richtext editor (optional)	toolbar='...'
constraints definitions for non-formatted text (optional)	constraint='...'
Meta-information type (optional)	infotype='meta'
Default value (optional)	default='...'
Prefix and suffix will be added to content if it is not empty	prefix='...' suffix='...'
valid language value (optional)	language='...'
edit/write permission for certain user groups (optional)	groups='...'
dpi value to autoscale images (optional)	dpi='...'
Autoconvert images to the given colorspace [CMY, CMYK, Gray, HCL, HCLp, HSB, HSI, HSL, HSV, HWB, Lab, LCHab, LCHuv, LMS, Log, Luv, OHTA, Rec601YCbCr, Rec709YCbCr, RGB, scRGB, sRGB, Transparent, XYZ, YCbCr, YCC, YDbDr, YIQ, YPbPr, YUV] (optional)	colorspace='...'
Autoconvert images to the given ICC-Profile [ICC Profiles: hypercms/library/ICC_Profiles] (optional)	iccprofile='...'

Media Tag set

File	[hyperCMS:mediafile id='...']
Alignment	[hyperCMS:mediaalign id='...']
Width	[hyperCMS:mediawidth id='...']
Height	[hyperCMS:mediaheight id='...']
alternative text	[hyperCMS:mediaalttext id='...']
Display name (optional)	label='...'
Content cannot be edited (optional)	onEdit='hidden'
hide content (optional)	onPublish='hidden'
Media type [audio, compressed, flash, image, text, video] (optional)	mediatype='...'
Meta-information type (optional)	infotype='meta'
Path type [file, url, uri, download, wrapper] (optional)	pathtype='...'
use thumbnail image	thumbnail='yes'
valid language value (optional)	language='...'
edit/write permission for certain user groups (optional)	groups='...'
dpi value to autoscale images (optional)	dpi='...'
Autoconvert images to the given colorspace [CMY, CMYK, Gray, HCL, HCLp, HSB, HSI, HSL, HSV, HWB, Lab, LCHab, LCHuv, LMS, Log, Luv, OHTA, Rec601YCbCr, Rec709YCbCr, RGB, scRGB, sRGB, Transparent, XYZ, YCbCr, YCC, YDbDr, YIQ, YPbPr, YUV] (optional)	colorspace='...'
Autoconvert images to the given ICC-Profile [ICC Profiles: hypercms/library/ICC_Profiles] (optional)	iccprofile='...'

Link Tag set

hyper reference	[hyperCMS:linkhref id='...']
Frame target	[hyperCMS:linktarget id='...']
Link text	[hyperCMS:linktext id='...']
Display name (optional)	label='...'
Content cannot be edited (optional)	onEdit='hidden'
hide content (optional)	onPublish='hidden'
Meta-information type (optional)	infotype='meta'
valid language value (optional)	language='...'
edit/write permission for certain user groups (optional)	groups='...'

Component Tag set

Single component	[hyperCMS:components id='...']
Multi component	[hyperCMS:componenttm id='...']
Display name (optional)	label='...'
Content cannot be edited (optional)	onEdit='hidden'
hide content (optional)	onPublish='hidden'
static include (optional)	include='static'
Hide icons on edit (optional)	icon='hidden'
Meta-information type (optional)	infotype='meta'
Default value (optional)	default='...'
valid language value (optional)	language='...'
edit/write permission for certain user groups (optional)	groups='...'

Title Tag set

Page title	[hyperCMS:pagetitle]
------------	----------------------

Display name (optional)
Default value (optional)
valid language value (optional)

label='...'
default='...'
language='...'

Meta information Tag set

Author
Keywords
Description
content-type

[hyperCMS:pageauthor]
[hyperCMS:pagekeywords]
[hyperCMS:pagedescription]
[hyperCMS:pagecontenttype]
[hyperCMS:compcontenttype
content='...']

Language
Display name (optional)
Default value (optional)
edit/write permission for certain user groups (optional)

[hyperCMS:pagelanguage]
label='...'
default='...'
groups='...'

Geo location

Geo location

Display name (optional)
Content cannot be edited (optional)
hide content (optional)
edit/write permission for certain user groups (optional)

[hyperCMS:geolocation
infotype='meta']
label='...'
onEdit='hidden'
onPublish='hidden'
groups='...'

Language session setting

Session name and values

Display name (optional)
Default value (optional)
valid language value (optional)

[hyperCMS:language name='...'
list='...']
label='...'
default='...'
language='...'

Personalization Tag set

(content can be personalized for customers based on the customer profile of a component)

Customer tracking
Default value (optional)
edit/write permission for certain user groups (optional)

[hyperCMS:pagetracking]
default='...'
groups='...'

Script Tag set

Template script

[hyperCMS:scriptbegin ... scriptend]

Database Connectivity Tag set (DB-Connect file has to be defined)

DB-connectivity

[hyperCMS:dbconnect file='... File
...']

Workflow Tag set (workflow must be defined)

assign workflow

[hyperCMS:workflow name='...']

Stylesheet references for components Tag set

Styelsheet (optional)

[hyperCMS:compstylesheet file='...']

Template and file inclusion Tag set

Template include
File include

[hyperCMS:tplinclude file='...File ...']
[hyperCMS:fileinclude file='...File ...']

View option of the object Tag set

Name of the view (cmsview, inlineview, preview, formedit, [hyperCMS:objectview name='...']
formmeta, formlock, template, publish)

Please note: Each ID of a text-, media- or component-tag set within a page, article or component must be unique. You can use the same ID for multiple elements of a tag set (e.g. unformatted text). Changes on one element also effect all other elements with the same ID; e.g. multiple usage of the tag [hyperCMS:textu id='Introduction'] within the same template.

It is not allowed to use different types of the same tag with the same ID, like e.g. [hyperCMS:textu id='Introduction'], [hyperCMS:textf id='Introduction'] and [hyperCMS:textl id='Introduction']. In this case hyperCMS will display an error message on the preview screen.

Please also note that the tag [hyperCMS:mediafile id='...'] always links to an asset. The tag [hyperCMS:linkhref id='...'] links to a page within the page structure or contains a freely defined link.

Default values

Using default values (default attribute) one can set standard values in hyperCMS tags. When using default values for components, the path has to be set in the following way:

%comp%/publication-name/location-path/component

Multiple components have to be divided by the separator ; .

Display name

Use the display name (label-attribute) inside a hyperCMS-tag to display a name instead of the tag ID.

3.1.2 Language setting

Use the language tag to define supported languages for editors.
The following example defines 2 languages, the display name and the default language:

```
[hyperCMS:language name='langcode' list='DE|EN' label='Deutsch|Englisch'  
default='EN']
```

Now a session variable "langcode" exists that holds the value "DE" or "EN". Please note that you will need to define a condition for the language content block depending on the selected application language of the:

```
<?php if ($_SESSION['langcode']=="DE") { ?>  
<h1>[hyperCMS:textu id='title_DE' label='Titel' language='DE'  
height='25']</h1>  
<p>[hyperCMS:textf id='content_DE' label='Inhalt' language='DE']</h1>  
<?php } ?>  
  
<?php if ($_SESSION['langcode']=="EN") { ?>  
<h1>[hyperCMS:textu id='title_EN' label='Title' language='EN'  
height='25']</h1>  
<p>[hyperCMS:textf id='content_EN' label='Content' language='EN']</h1>  
<?php } ?>
```

If you use the language-attribute inside a hyperCMS-tag, the value (language='DE') must be inside the given scope of the language-tag (list='DE|EN').

3.1.3 Template variables

You also have the possibility to work with template variables. These variables are placeholders for certain values and can be used in templates. Please note that variables are always written in small letters.

%container%	for the name of the content container of an object
%container_id%	for the ID of the content container of an object
%objecthash%	for the hash of an object
%object_id%	for the ID of an object
%template%	for the template file name of an object used
%publication%	for the publication where the object is located
%url_location%	for the absolute path (URL) of the location where the object is located
%abs_location%	for the absolute path in the filesystem of the location where the object is located
%object%	for the name of the object
%date%	describes the current date (format: JJJJ-MM-TT)
%view%	describes the display mode: publish ... published cmsview ... Editing view in EasyEdit mode preview ... Preview formedit ... Editing mode in form view formlock ... form view with editing locked formmeta ... Metadata in form view template ... Template preview

To integrate media files (assets) we can make use of a path variable. When publishing a page or component, the path variable is for instance replaced by the URL (address) of the target of the publication:

%tplmedia%	for the absolute path (URL) of the template media repository
%url_media%	for the absolute path (URL) of the content media repository (Alternative %media% can be used)
%abs_media%	for the absolute path in the filesystem of the content media repository
%url_page%	for the absolute path (URL) of the page root folder
%abs_page%	for the absolute path in the filesystem of the page root folder
%url_comp%	for the absolute path (URL) of the component root folder
%abs_comp%	for the absolute path in the filesystem of the component root folder
%url_rep%	for the absolute path (URL) of the external repository root folder
%abs_rep%	for the absolute path in the filesystem of the external repository root folder
%url_hypercms%	for the absolute path (URL) of the hyperCMS root folder
%abs_hypercms%	for the absolute path in the filesystem of the hyperCMS root folder

Please keep in mind to add a slash "/" to the end of the path variable, if you would like to complement the variable with a continuative path.

Definition of the date format when the format-attribute is used in the textd-Tag:

%a	'am' or 'pm'
%A	'AM' or 'PM'
%d	day of the month, 2 digits with leading zeroes (01 to 31)
%D	day of the week, textual, short, eg "Fri"
%F	month, textual, long; eg "January"
%h	hour, 12-hour format (01 to 12)
%H	hour, 24-hour format (00 to 23)
%g	hour, 12-hour format without leading zeros (1 to 12)
%G	hour, 24-hour format without leading zeros (0 to 23)
%i	minutes (00 to 59)
%j	day of the month without leading zeros (1 to 31)
%l	day of the week, textual, long, eg "Friday"
%L	1 if leap year, otherwise - 0
%m	month (01 to 12)
%n	month without leading zeros (1 to 12)
%M	month, textual, short, eg "Jan"
%s	seconds (00 to 59)
%t	number of days in the month (28 to 31)
%w	day of the week, numeric (0, Sunday to 6, Saturday)
%Y	year, 4 digits, eg 2007
%y	year, 2 digits, eg "07"
%z	day of the year (1 to 366)

3.1.4 Examples of the use of tags hyperCMS

3.1.4.1 Metadata in pages

Editable meta-information in a page template as well as the integration of a cascading style sheet (CSS) which is located in template media:

```
<title>[hyperCMS:pagetitle infotype='meta']</title>
<meta http-equiv="Content-Type" content="[hyperCMS:pagecontenttype
infotype='meta']">
<meta http-equiv="content-language" content="[hyperCMS:pagelanguage
infotype='meta']">
<meta name="Author" content="[hyperCMS:pageauthor infotype='meta'
default='Max Mustermann']">
<meta name="description" content="[hyperCMS:pagedescription
infotype='meta']">
<meta name="keywords" content="[hyperCMS:pagekeywords
infotype='meta']">
<link rel="stylesheet" hypercms_href="%tplmedia%/main.css" type="text/css">
```

The last line in the example above shows that the external CSS file (located in template media) have to use the path %tplmedia%. Thus, it is guaranteed that the external CSS-file "main.css" is integrated into the page. The file "main.css" has to be saved in the media database for templates.

To prevent EasyEdit from link tracking, the link has to be protected. This has to be done when using external style sheets (CSS files).

The link must not be changed by EasyEdit to correctly integrate the external file. The outcome would be a missing formatting because of the missing style sheet. Links (hyper references) are protected by changing "href" to "hypercms_href" as seen in the example above.

3.1.4.2 Image

Integration of various image parameters:

```

```

The attribute „mediatype“ of the media file tag ensures that only image files can be included.

The attribute "pathtype" can be used to define the type of reference to the media file:

- file ... absolute path in file system
- url ... URL
- uri ... URI (URL without the protocol and domain/host name)
- download ... download link forces media file download (provides access statistics)
- wrapper ... wrapper link provides media file in browser (provides access statistics)

3.1.4.3 Link

Defining the editable parameters of hyperlinks of an article:

```
<a href="[hyperCMS:artlinkhref id='partner']" target="[hyperCMS:artlinktarget1 id='partner']">[hyperCMS:artlinktext id='partner']</a>
```

3.1.4.4 Text

Editable unformatted text:

```
<font face="Verdana, Arial, Helvetica, sans-serif" size="1" color="#000000">[hyperCMS:textf id='langtext']</font>
```

Unformatted texts can also be subject to conditions, e.g.:

- Value must be entered
- Value must be an email address
- Only numeric values are allowed
- Numeric values between limits

The TagWizard provides support to that effect:

unformatted text constraints

value: ☐ required

accept: ☒ anything
☐ e-Mail address
☐ number
☐ number between and

3.1.4.5 Keywords

Mandatory keywords field using the taxonomy as source for the keywords:

```
[hyperCMS:textk id='Keywords' infotype='meta' height='75'  
file='%taxonomy%/default/en/0/4' onlylist=1 constraint='R']
```

This tag defines a metadata field that only allows keywords from the taxonomy as source. The following syntax for the attribute „file“ can be used that will also work for list-fields.

Usage of the taxonomy in the file-attribute:

Domain/Publication/Language-code/Taxonomy-ID/Taxonomy-sublevels

Domain ... %taxonomy%

Publication Name of the publication in order to select a specific taxonomy or „default“ for the standard taxonomy

Language-code 2-digit language code or „all“ for all languages

Taxonomy-ID Line number of the taxonomy keyword or 0 for all keywords

Taxonomy-sublevels Number of keyword sublevels of the selected taxonomy keyword

Usage of a folder path in the file-attribute:

Returns all subfolder names as selectable values.

%comp%/Publication/Folder/

%comp% Page %page% or Component/Asset %comp%

Publication ... Name of the Publication

Folder ... Name of the folder or location path that defines the root

Use a path to a file or service in the file-attribute:

All values stored in the file or provided by a service (REST) can be used.

Note that the values must be separated by , or ;.

Bsp: /home/values/names.txt

Bsp: https://www.domain.com/services/names.php?q=company

3.1.4.6 List fields

List field using a hardcoded list of values with 1 as default value:

```
[hyperCMS:textl id='Numbers' infotype='meta' list='1|2|3' default='1']
```

Also list fields can use the same file-attribute as keywords, so values from the taxonomy, a folder structure or from an external source can be integrated.

3.1.4.7 Template script

It is possible to directly integrate applications with PHP, which are executed within the publication (published page). The whole range of functions of PHP as well as the functions of the hyperCMS API can be used.

With the help of template scripts it is possible to integrate applications that are executed during the publishing process. Thus, the output of the executed program code is rendered within the published object/file.

In the manner described you can integrate dynamics into you templates, e.g. creating a directory of all pages, creating a document in the background, and a lot more.

The advantage of template scripts compared to the dynamic execution of code in PHP, ASP, or JSP files, where the application is executed each time the page or component is accessed, is the performance. A template script is only executed during the publishing process and does not require any computing time when accessing the page. For details on script programming please refer to the hyperCMS Programmers Guide.

```
<font face="Verdana, Arial, Helvetica, sans-serif" size="2">
[hyperCMS:scriptbegin

// Loading content from text file
$external_data = loadfile („E:/Information/", „Imprint.txt");

// Verifying whether file has been loaded successfully
// and output of content
if ($external_data) echo „Imprint: ".$external_data;
else echo "The imprint is under construction!";

scriptend]
</font>
```

At this point we also would like to mention that there are more characteristics of tags respectively the corresponding content. Content can also be hidden.

The hyperCMS TagWizard offers 3 options:

- Do not hide content
- Hide content for publishing (onPublish='hidden')
- Hide content for editing (onEdit='hidden')

If the content is not hidden, no further attribute in the tag will be necessary. If the content should only be displayed in a certain area of the page and should be hidden in another area, an additional attribute will be necessary. The following example shows a PHP-application that is integrated in a template and requires input from a user/visitor to start a query:

```
[hyperCMS:textl id='Productcategory' list='Hardware|Software|Service'
onPublish='hidden']
```

```
<div id="products">
<?php

// Determining the value of the variable which the editor
// defined by using a text option
$Productcat = "[hyperCMS:textl id='Productcategory'
list='Hardware|Software|Service' onEdit='hidden']";

// Querying and displaying the articles from a MySQL database
$user = "username";
$password = "password";
$database = "database";
    mysql_connect ("localhost", $user, $password);
    @mysql_select_db ($database) or die ("Unable to select database");

$result = mysql_query ("SELECT Name, Description, Price FROM Products
WHERE Category=$Productcat);

$num_of_rows = mysql_num_rows ($result);

if ($num_of_rows >= 1)
{
    echo "<table>";
        for ($count=1; $row=mysql_fetch_row ($result); ++$count)
        {
            echo "<tr><td>$count</td>";
            echo "<td>$row[0]</td>";
            echo "<td>$row[1]</td>";
            echo "<td>$row[2]</td></tr>";
        }

        echo "</table>";
    }
else echo "Cannot find any products!";

mysql_close ();
?>
</div>
```

Because of the numerous possibilities using hyperCMS tags in connection with HTML and JavaScript, we offer special trainings for template designers.

With templates you can also integrate any server-based applications into templates, such as database queries, dynamic generation of sitemaps, and so on. Please see the Programmers Guide for more details about how to use the hyperCMS API.

3.1.5 hyperCMS TagWizard

The hyperCMS TagWizard makes it possible to integrate hyperCMS tags into your templates without programming skills. With the help of this tool you can convert any HTML code into a template.

In the TagWizard you will find a ?-icon (Help). Left click on the icon and you will get a short explanation of the hyperCMS tags that can be used. If you move the mouse over an icon you get a short description of the meaning of the selected symbol.

Page template

Edit

Page template: Detail

Template	Version	Information
Page template	Detail	
File extension (without dot)	php	
Application	PHP Hypertext Preprocessor (PHP)	

Article identification name: [text input] **No article**

Content identification name: [text input] **Reset** ☐ Meta information

Hide content: ☐ on publish ☐ on edit

Toolbar: [Icons for file operations, navigation, and help]

```
[hyperCMS:fileinclude file='%abs_comp%/%publication%/configuration.php']
[hyperCMS:text id='NavigationHide' label='Hide in Navigation' value='yes' infotype='meta' onPublish='hidden']
[hyperCMS:text id='NavigationSortOrder' label='Navigation Sort Order' constraint='inRange0:1000' infotype='meta' onPublish='hidden' height='25']
<!DOCTYPE html>
<html>
<head>
<title>[hyperCMS:text id='Title' infotype='meta' height='25' label='Page Title' constraint='R']</title>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1, maximum-scale=1">
<meta name="description" content="[hyperCMS:text id='Description' infotype='meta' height='50']" />
<meta name="keywords" content="[hyperCMS:text id='Keywords' infotype='meta' height='50']" />
<link rel="shortcut icon" href="%tplmedia%/favicon.ico">
<!-- 57 x 57 Android and iPhone 3 icon -->
<link rel="apple-touch-icon" media="screen and (resolution: 163dpi)" href="%tplmedia%/mobile_icon57.png" />
<!-- 114 x 114 iPhone 4 icon -->
<link rel="apple-touch-icon" media="screen and (resolution: 326dpi)" href="%tplmedia%/mobile_icon114.png" />
<!-- 57 x 57 Nokia icon -->
<link rel="shortcut icon" href="%tplmedia%/mobile_icon57.png" />
<link rel="stylesheet" id="attitude_style-css" hypercms_href="%tplmedia%/style.css" type="text/css" media="all">
<script type="text/javascript" src="%tplmedia%/jquery-1.11.1.min.js"></script>
<script type="text/javascript" src="%tplmedia%/jquery-migrate-1.2.1.min.js"></script>
<script type="text/javascript" src="%tplmedia%/backtotop.js"></script>
<script type="text/javascript" src="%tplmedia%/tinynav.js"></script>
```

When editing a page template, the hyperCMS TagWizard shows two text fields respectively a checkbox for meta information at the top. The first field is used to define an article. Use this field to name your article (part of the ID). Each article is always associated with one or multiple page elements. For example name your article "news" and enter a text-tag with the content-ID "introduction". Thus, it is part of the article "news" carrying the prefix "art". Concurrently, you can see that the ID of the tag is composed of the article-ID and element-ID, e.g. `id='news:introduction'`. You can see this affiliation also by looking at the XML-content.

The ID (identification) must always be assigned to content-elements, whereas the definition of an article is not mandatory. The element features a key for identification, e.g. `[hyperCMS:textf id='longtext']`.

The checkbox for meta information declares a tag to be a meta information. So an editor can edit the meta information apart from the standard content displayed in a page.



























The toolbar with its icons situated below offers the possibility to insert the hyperCMS tags into the template at the current cursor-position or paste it over the selected area of the code (e.g. text). Therewith it is possible to create templates in a simple and easy way without programming. These templates can then be used for your pages and components.

When creating component or more simple constructed metadata templates, the hyperCMS TagWizard offers less actions.

Page components can be integrated into page- or even other component templates via the hyperCMS tag `[hyperCMS:tplinclude file='Path']`. Therewith it is possible to manage recurrent design elements independently from the template.

You can also use the tag `[hyperCMS:filepininclude file='Path']` for the integration of components. The indicated component will always be integrated in this location and cannot be influenced by the editor. E.g. this can be useful when integrating a navigation.














Explanation of icons of the hyperCMS TagWizard:

Symbol	Explanation
	Save the template
	Save the template with preview
	Insert the hyperCMS tag for the page title
	Insert the hyperCMS tag for meta information. Please note, that afore you have to select meta information from the menu.
	Insert the hyperCMS tag for the geo location of the object
	Insert the hyperCMS tag for the language setting of content. You have to define a session variable name and possible session values.
TXT	Insert the hyperCMS tag for unformatted text.
TXT	Insert the hyperCMS tag for formatted text (WYSIWYG-editor).
	Insert the hyperCMS tag for text options. With the selection of this symbol you will be asked to enter the text options. Please use the semicolon ';' to separate the inputs from each other.
	Insert the hyperCMS tag for a selection via checkbox
	Insert the hyperCMS tag for the date picker
	Insert the hyperCMS tag for keywords
	Insert the hyperCMS tag for unformatted comments
	Insert the hyperCMS tag for formatted comments
	Insert the hyperCMS tag for media files (e.g. image file).
	Insert the hyperCMS tag for image alignment.
	Insert the hyperCMS tag for image width.
	Insert the hyperCMS tag for image height.
	Insert the hyperCMS tag for text shown on mouse-over of an image.
	Insert the hyperCMS tag for a hyperlink.
	Insert the hyperCMS tag for the link target (important when using frames).
	Insert the hyperCMS tag for the link text.
	Insert the hyperCMS tag for a single component.
	Insert the hyperCMS tag for multiple components.
	Insert PHP-code for session handling. After the selection of this symbol you will be asked to enter the variables and the corresponding values, respectively the variables that should be registered during the session.
	Insert the hyperCMS tag for the database connection.
	Insert the hyperCMS tag for the integration of a workflow for all pages or components based on the template.
	Insert the hyperCMS tag for template scripts.
	Insert the hyperCMS tag for the current date at the time of publication (JJJJ-MM-TT).
	Insert the hyperCMS tag for the path of a template media file.
	Insert the hyperCMS tag for the integration of a template include. You are asked to enter the path of the template include.
	Insert the hyperCMS tag for dynamic integration of an external file or component. You are asked to enter the path of the external file. In PHP as an application internet addresses (URLs) as well as absolute or relative paths are allowed in the file system. In JSP the file must be located in the web application root. By using slash "/" at the beginning the root is defined. In ASP only relative paths are allowed. Unfortunately, there is no way to reference on the document root of the website.

In the picture of the hyperCMS TagWizard below you can see 3 tabs. The first tab from the left shows the template, the second tab enables access to all available versions of the template and the third provides you with general information on the template.

Template	Version	Information
Template	Detail	
Category	page template	
Last updated	2017-01-19 16:23	
File size	3977 bytes	

Let's have a look on the versions of a template. We get a chronological list of all versions sorted by date and time beginning with the oldest version:

Template	Version	Information			
Version date	Page template		Compare	Current	Delete
2015-09-16 16:34:59	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-08-03 12:47:45	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-08-03 12:47:57	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-08-03 12:49:30	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-08-03 12:49:49	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-08-03 12:50:21	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-08-04 12:51:24	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-08-04 14:42:26	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2016-11-09 20:31:16	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
2017-01-19 16:11:32	 Detail (Source Code)		<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>
Current version	 Detail (Source Code)		<input type="checkbox"/>	<input checked="" type="radio"/>	<input type="checkbox"/>
Submit changes to versions					
Compare selected versions					

To have a look on the design of a version, just click on the template name. By doing so a new browser window will open and provide you with a preview that shows the editable elements by using placeholders.

Two versions can be compared. The difference between the old and the new version will be shown as red crossed-out (deleted) and green text (new).

It is also possible to delete template versions by activating the corresponding checkbox and clicking "OK". Thus, the selected templates are irretrievable removed from the system.

Furthermore it is possible to update an old version so that it is the current version. Simply click on the radio button for the version you want to use as your current version and click "OK". All pages and components which use this template will now access this (now current) version of the template. Please note that the new design of online pages and components will only be affected after you publish them again.

3.3 Deleting templates

To delete a template please click on the third icon from the left in the toolbar. After that you can select a template. Please be aware that you really do not need the template anymore because it will be irretrievably removed from the system. After clicking on the icon a selection field is opened. Here you can select the template you would like to delete. This window also provides a preview of the template. If you are sure to delete the template simply click on the "OK"-button. Please note, that also all other versions of the template will be removed.

3.4 Editing templates

To edit existing templates please click on the fourth symbol on the left in the toolbar and select the requested template. The code of the template is then displayed in the TagWizard editor and can now be edited. All changes affect the pages or components that use this template. Thus, it is possible to e.g. add additional text fields or images to the template. Existing pages are now supplemented by adding additional input options.

The same functions are also available for component templates. They are treated the same way as described above.

An important point when it comes to creating templates is the integration of media (background image, decoration images, flash movies etc.) and also external JavaScript or CSS (Cascading Style Sheets) files. Please note that these files also have to be uploaded to the system. This is done via the media database for templates which saves all external files of the templates.

3.5 License notification

In order to inform users about the expiration of a copyright license or other events, the license notification can be used. Several automatic notifications based on the id of a date tag, the used date format and the desired frequency of the notification via e-mail can be defined.

Metadata template

License notification

Select folder

- /Boarderline/
- Back
- Dropbox
- Multimedia
- News
- Produkte

Apply license notification on selected folder

Text-ID (expiration date) to monitor
LicenseEnd

Date format (e.g. %Y-%m-%d or %d.%m.%Y)
%Y-%m-%d

User (comma seperated)
admin

Select period
Monthly

Applied settings on selected folders
LicenseEnd@/Boarderline/(daily): admin

Save settings

3.6 Meta data mapping

Meta data mapping is only available for metadata templates.

Meta data mapping enables the mapping of metadata of files (mostly images used IPTC- and XMP-format) with the defined meta data schema in the system.


When uploading an image holding metadata, the meta data will be extracted and saved according to the mapping definition. Then the metadata is available and can be editing in the system.

A standard mapping exists already for the most used EXIF, ID3, IPTC and XMP tags of media files and can be easily edited. The XMP format is based on XML and can map multiple metadata schemas such as Dublin Core (DC) and Adobe Photoshop.

A special feature can be used for the Adobe Lightroom XMP tag `lr:hierarchicalSubject`. This tag includes both field names and their values. If you want to import the content pairs into the system, the value "automatic" must be used or retained. Please note that the metadata template has to contain the fields with the appropriate ID in order to see and also edit the information.

`lr:hierarchicalSubject => automatic`

After changes in the mapping definition the media files can be re-indexed in order to save the new content from the files in the system.



4 Metadata/Content hierarchy

In order to enable users to browse objects by their metadata/contents a hierarchy can be defined. The hierarchy can hold up to 10 different Text-IDs on different hierarchy levels. Up to 5 different levels can be used. However it is recommended to use maximum 3 levels for better overview while browsing the objects.

You can define one or more hierarchy definitions. All of them will be presenting to users with page or asset access for browsing. Save the hierarchy definition so it can be used by all users.

If you want to support the label in multiple languages, please use the language code before the label, e.g.: en:Title; de:Titel; fr:Titre

Metadata template

Metadata/Content hierarchy

Select hierarchy
Demo

Name
Demo

Level	Text-ID	Label (en:Title; de:Titel; fr:Titre)
1	Creator	Creator
2	Title	Title
2	Description	Description
2	Keywords	Keywords
2		
2		
2		
2		
2		

Save settings

Hierarchy Tree View:

- DemoDAM
 - Administration
 - Workflow
 - Templates
 - Creator (Yellow folder)
 - None
 - Coffy (Blue folder)
 - Description
 - Keywords
 - Title
 - Beach dog
 - Freeimages.co.uk (Blue folder)
 - Description
 - Keywords
 - Title
 - aromatherapy candles
 - aromatherapy scented
 - audio jack
 - audio mixer
 - audio spectrum
 - audio waveforms
 - bamboo backdrop
 - calm ocean
 - carillon mechanism


The hierarchy will be presented to users with two different folder types/colours:
 Yellow folder ... Content category based on the Text-ID of the content
 Blue folder ... Content/Keyword

5 Template media management

Template Media are a collection of different files that are used by templates. This disjunction of multimedia files that can be managed by editors prevents editors from manipulating constituents of the website's design. Only designers, who have the permission to embed media into templates, are allowed to manage template media.

Media files can be all kinds of files like images, CSS-files, video, audio, etc. The media management stores all media files centrally und allows categorization by individual needs. It also features an advanced search function using information like category, file type and search term.

After choosing the template media in the navigator the following icons appear in the toolbar:



To see further details about the single functions just move the mouse cursor over the icons.

The following functions are available:

- Create media category
- Delete media category
- Rename media category
- Upload media file
- Delete media file
- Browse and search media files

5.1 Managing media categories

Using the first three icons you can create, delete and rename categories. By clicking on one of the icons additional fields are displayed on the desktop, which call for input.

After creating a category you can store media files inside it.

5.2 Uploading files

To upload files click on the fourth icon from the left. Now two fields appear, one for selecting a category and one for browsing your local file system.

Select a target category for the file, click on the „browse“-Button to access your file system, then select the file and upload it by clicking „OK“.

5.3 Removing files

To permanently remove files from the system, click the „delete media file“-icon in the toolbar. In the following menu you can search the entire media repository by choosing a media category, file format and/or entering a filename in the search field.

If you want to display all available media files choose „all categories“ in the media category menu, „all formats“ in the file formats menu, leave the search field empty and click the submit button (green arrow).

As a result the list of files matching the search criteria is displayed. By clicking a file in the result list you can preview it. Images, Shockwave- and Flash-Files are displayed directly on the workspace as well as additional file information, such as file size (in bytes) and media size (height and width in pixels). Files with other formats (e.g. doc, xls, pdf,...) can be opened with the appropriate application (e.g. Word, Excel, Acrobat,...) by clicking the link below the file information.

Please note: Deleting a media file still used in a page or component can lead to display errors.

The screenshot shows the 'Template media' interface. At the top, there is a toolbar with icons for adding, deleting, and searching media files. Below the toolbar, the 'Delete media file' section is active. It contains a 'Select media files' panel on the left and a 'Delete media file' panel on the right. The 'Select media files' panel has dropdown menus for 'Select media category' (set to 'All categories') and 'Select file format' (set to 'Image'), a search input field, and a green arrow button. Below these, a list of 'Found media files' is shown: 'favicon.ico', 'Null_media.gif', 'Slider1.jpg', 'Slider2.jpg', and 'Slider3.jpg'. The 'Delete media file' panel has a 'Selected media file' input field containing 'DemoCMS/favicon.ico' and a green arrow button. Below this, a preview of the selected file 'favicon.ico' is shown, including its file size (<1 MB), width x height (16x16 px), and other metadata.

Template media

Delete media file

Select media files

Select media category
All categories

Select file format
Image

Search
[input field] [green arrow]

Found media files

- favicon.ico
- Null_media.gif
- Slider1.jpg
- Slider2.jpg
- Slider3.jpg

Delete media file

Selected media file DemoCMS/favicon.ico [green arrow]


favicon.ico

Original

File size <1 MB
width x height 16x16 px
Duration (hh:mm:ss)
Video codec BMP
Audio codec
Video bitrate
Audio bitrate
Audio frequency
Audio channels

5.4 Searching for files

By clicking the icon on the very right in the toolbar you open the search menu. It offers the same browsing and search functionality as described in „Delete Files“ above. You can search for files by entering search criteria like media category, format or filename and browse the entire repository.



6 Legal reference / flag

6.1 Questions and suggestions

For advanced questions and suggestions, please contact the support. We are available for every question regarding our reseller- and partner-program. You can apply for an access to our enhanced Online-Demo of the hyper Content Management Servers via our support.

hyperCMS Support:
support@hypercms.com
www.hypercms.com

6.2 Imprint

Responsible for the content:

hyperCMS
Content Management Solutions GmbH
Rembrandtstr. 35/6
A-1020 Vienna – Austria

office@hypercms.com
<http://www.hypercms.com>

6.3 Legal information

The present product information is based on the version of the program, which was available at the time the document was composed.

The maker reserves the rights of modifications and corrections of the program. Errors and misapprehension excluded.

© 2017 by hyperCMS Content Management Solutions