

Version 9.0 Programers Guide

# Inhalt

ı		ung	
2		CMS XML-Content-Repository	
	2.1 h	yperCMS spezifische Informationen	3
	2.2 M	leta-Informationen	4
	2.3 Te	ext	4
	2.4 M	ledien	5
		inks	
		omponenten	
		rtikel	
3		onsbibliotheken	
J		inbindung einer Bibliothek	
		aden der Konfiguration	/
	3.2.1		
	3.2.2		
		lobale Variablen	
		orlagenvariablen	
		ibliothek Object Operation	
	3.5.1	createfolder	12
	3.5.2	deletefolder	13
	3.5.3	renamefolder	.14
	3.5.4	createobject	15
	3.5.5	deleteobject	
	3.5.6	renameobject	
	3.5.7	cutobject	
	3.5.8	copyobject	
	3.5.9	copyconnectedobject	
	3.5.10	• •	
	3.5.11		
	3.5.12	•	
	3.5.13	1 J	
	3.5.14	1	
	3.5.15	•	
	3.5.16	<b>5</b>	
	3.5.17	getobjectcontainer	28
	3.6 B	earbeiten von Inhalten	28
	3.7 B	ibliothek File Operation	29
	3.7.1	loadfile	29
	3.7.2	savefile	
	3.7.3	loadlockfile	30
	3.7.4	savelockfile	
	3.7.5	lockfile	
	3.7.6	unlockfile	
	3.7.7	deletefile	
	3.7.8	appendfile	
		ML Bibliothek	
	3.8.1	setxmlparameter	
	3.8.2	getcontent	
	3.8.3	getxmlcontent	
	3.8.4	selectcontent	
	3.8.5	selectxmlcontent	
	3.8.6	deletecontent	
	3.8.8	setcontent	
	3.8.10	· ·	
	3.8.11		
	3.8.12	addcontent	40

	3.9 Bik	oliothek Meta Data Generator	41
	3.9.1	getmetakeywords	
	3.9.2	getmetakeywords	
		oliothek Notifications	
	3.10.1	licensenotification	
4		nenten und Applikationen	
5	•	se Connectivity	
J		stellen einer Database Connectivity	
6		SystemSystem	
7		er hyperCMS API Funktionen	
′		ain API Functions	
	7.1.1	correctnumber	
	7.1.1	cleancontent	
	7.1.2 7.1.3		
		remove_utf8_bom	
	7.1.4	convert_utf8	
	7.1.5	convertchars	
	7.1.6	specialchr	
	7.1.7	specialchr_encode	
	7.1.8	specialchr_decode	
	7.1.9	convertdate	
	7.1.10	offsettime	
	7.1.11	object_exists	
	7.1.12	is_utf8	
	7.1.13	is_latin1	
	7.1.14	makestring	
	7.1.15	splitstring	
	7.1.16	is_folder	52
	7.1.17	is_emptyfolder	52
	7.1.18	is_supported	53
	7.1.19	is_cloudstorage	53
	7.1.20	is_cloudobject	54
	7.1.21	is_date	54
	7.1.22	is_tempfile	54
	7.1.23	is_keyword	55
	7.1.24	is_thumbnail	
	7.1.25	is_config	55
	7.1.26	is_encryptedfile	
	7.1.27	is_document	
	7.1.28	is_image	
	7.1.29	is_rawimage	
	7.1.30	is_aiimage	
	7.1.31	is_video	
	7.1.32	is rawvideo	
	7.1.33	is_audio	
	7.1.34	is_mobilebrowser	
	7.1.35	is_iOS	
	7.1.36	is_activelanguage	
	7.1.37	copyrecursive	
	7.1.37	array_iunique	
		· ·	
	7.1.39	in_array_substrcreatefilename	
	7.1.40		
	7.1.41	correctfile	
	7.1.42	correctpath	
	7.1.43	convertpath	
	7.1.44	convertlink	
	7.1.45	deconvertpath	
	7.1.46	deconvertlink	
	7.1.47	mediapublicaccess	64

7.1.48	createviewlink	
7.1.49	createportallink	
7.1.50	createaccesslink	
7.1.51	createobjectaccesslink	
7.1.52	createwrapperlink	
7.1.53	createdownloadlink	67
7.1.54	createmultiaccesslink	.68
7.1.55	createmultidownloadlink	.68
7.1.56	cleandomain	69
7.1.57	fileversion	.70
7.1.58	createversion	70
7.1.59	rollbackversion	
7.1.60	deleteversion	
7.1.61	deleteversions	
7.1.62	loadfile_header	
7.1.63	loadfile_fast	
7.1.64	loadfile	
7.1.65	loadlockfile	
7.1.66	savefile	
7.1.67	savelockfile	
7.1.68	appendfile	
7.1.69	lockfile	
7.1.69		
	unlockfile	
7.1.71	deletefile	
7.1.72	restoremediafile	
7.1.73	preparemediafile	
7.1.74	deletemediafiles	
7.1.75	avoidfilecollision	
7.1.76	substr_in_array	
7.1.77	downloadobject	
7.1.78	downloadfile	
7.1.79	loadcontainer	
7.1.80	savecontainer	.81
7.1.81	checkworkflow	
7.1.82	inherit_db_load	82
7.1.83	inherit_db_read	82
7.1.84	inherit_db_close	.83
7.1.85	inherit_db_save	83
7.1.86	inherit_db_getparent	
7.1.87	inherit_db_getchild	
7.1.88	inherit_db_setparent	
7.1.89	inherit_db_insertparent	
7.1.90	inherit_db_deleteparent	
7.1.91	createinstance	
7.1.92	editinstance	
7.1.93	deleteinstance	
7.1.94	createpublication	
7.1.94	editpublication	
7.1.95	editpublicationsetting	
	·	
7.1.97	deletepublication	
7.1.98	createpersonalization	
7.1.99	deletepersonalization	
7.1.100	loadtemplate	
7.1.101	createtemplate	
7.1.102	edittemplate	
7.1.103	deletetemplate	
7.1.104	createportal	
7.1.105	editportal	.93

7.1.106	deleteportal	93
7.1.107	createuser	94
7.1.108	edituser	94
7.1.109	deleteuser	95
7.1.110	creategroup	96
7.1.111	editgroup	96
7.1.112	deletegroupdeletegroup	98
7.1.113	renamegroupfolder	99
7.1.114	deletegroupfolder	99
7.1.115	renameworkflowfolder	100
7.1.116	deleteworkflowfolder	100
7.1.117	createmediacat	101
7.1.118	renamemediacat	
7.1.119	deletemediacat	
7.1.120	uploadtomediacat	
7.1.121	deletefrommediacat	
7.1.122	createfolder	103
7.1.123	createfolders	
7.1.124	collectfolders	
7.1.125	copyfolders	
7.1.126	deletefolder	
7.1.127	renamefolder	
7.1.128	correctcontainername	
7.1.129	createobject	
7.1.130	uploadfile	
7.1.131	createmediaobject	
7.1.132	createmediaobjects	
7.1.133	editmediaobject	
7.1.134	manipulateobject	
7.1.135	deletemarkobject	
7.1.136	deleteunmarkobjectdeleteunmarkobject	
7.1.137	deleteobject	
7.1.137	renameobject	
7.1.139	renamefile	
7.1.140	cutobject	
7.1.140	copyobject	
7.1.141	copyconnectedobject	
7.1.142	pasteobject	
7.1.143	lockobject	
7.1.144	unlockobject	
7.1.145		
7.1.140	publishobject	
7.1.147	publishlinkedobject	
7.1.146	unpublishobject	
	processobjects	
7.1.150	collectobjects	
7.1.151	manipulateallobjects	
7.1.152	createqueueentry	
7.1.153	savemessage	
7.1.154	remoteclient	
7.1.155	HTTP_Post	
7.1.156	HTTP_Get	
7.1.157	HTTP_Proxy	
7.1.158	loadbalancer	
7.1.159	savelog	
7.1.160	loadlog	
7.1.161	deletelog	
7.1.162	debuglog	
7.1.163	notifyusers	127

	7.1.164	sendlicensenotification	1	27
	7.1.165	licensenotification	1	28
	7.1.166	sendresetpassword	1	28
	7.1.167	html_diff		
	7.1.168	createfavorite		
	7.1.169	deletefavorite		
	7.1.109	rewrite_targetURI		
	7.1.170	rewrite_targetoktrewrite_targetokt		
	7.1.171	·		
		load_csv		
	7.1.173	create_csv		
	7.1.174	sendmessage		
	7.1.175	linking_valid		
	7.1.176	linking_objects		
	7.1.177	linking_inscope		
	7.1.178	savecontent		
7.		API Functions		
		getserverload		
		getconfigvalue		
	7.2.3	getsession	1	35
	7.2.4	getrequest	1	36
	7.2.5	getrequest_esc	1	36
	7.2.6	getuserip	1	36
	7.2.7	getobjectlistcells		
	7.2.8	getlanguageoptions		
	7.2.9	getlanguagefile		
	7.2.10	getcodepage		
	7.2.11	getcalendarlang		
	7.2.12	getscaytlang		
	7.2.13	getescapedtext		
	7.2.14	getsearchhistory		
	7.2.15	gettaxonomy_sublevel		
	7.2.16	gettaxonomy_childs		
	7.2.17	gethierarchy_defintion		
	7.2.18	gethierarchy_sublevel		
	7.2.19	getkeywords		
	7.2.20	getmetakeywords		
	7.2.21	getmetakeywords		
	7.2.22	getgooglesitemap		
	7.2.23	getgoogleanalytics		
	7.2.24	getlistelements		
	7.2.25	getmetadatagetmetadata		
	7.2.26			
	7.2.26	getmetadata_multiobjectsgetmetadata_container		
	7.2.28	getobjectlist		
	7.2.29	getobjectcontainer		
	7.2.30	getcontainer		
	7.2.31	getwallpaper		
	7.2.32	getcontainername		
	7.2.33	getlocationname		
	7.2.34	getthemes		
	7.2.35	getthemelocation		
	7.2.36	getcategory		
	7.2.37	getpublication		
	7.2.38	getlocation		
	7.2.39	getobject		
	7.2.40	getmediacontainername		
	7.2.41	getmediafileversion		
	7.2.42	getobjectid	1	51

7 2.44 getobjectlink 7 2.45 getcontainerversions 7 2.46 getlocaltemplates 7 2.47 gettemplates 7 2.48 gettemplateversions 7 2.49 getfileinfo 7 2.50 getobjectlinfo 7 2.51 getfilesize 7 2.52 getmietype 7 2.53 getbase64fileextension 7 2.54 getfiletype 7 2.55 getpreviewwidth 7 2.56 getimagecolorkey 7 2.57 getimagecolors 7 2.58 getmediasize 7 2.59 getimageinfo 7 2.60 getpdfinfo 7 2.61 getvideoinfo 7 2.62 getbrowserinfo 7 2.63 getcontentlocation 7 2.64 getmedialocation 7 2.65 getlockedfileinfo 7 2.66 getfavorites 7 2.67 getclipboard 7 2.68 gethomeboxes 7 2.70 getusersonline 7 2.71 getchatstate 7 2.72 getimageiname 7 2.74 gethypertagname	152 153 154 154 155 156 156 156 158 158 158 159 159 160 161 161 162 162 163
7.2.46 getlocaltemplates 7.2.47 gettemplates 7.2.48 gettemplateversions 7.2.49 getfileinfo 7.2.50 getobjectinfo 7.2.51 getfilesize 7.2.52 getmimetype 7.2.53 getbase64fileextension 7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getydfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag. 7.2.75 gethypertagname	152 153 154 155 155 156 156 156 158 158 159 159 160 161 161 162 162 163
7.2.47 gettemplates 7.2.48 gettemplateversions 7.2.49 getfileinfo 7.2.50 getobjectinfo 7.2.51 getfilesize 7.2.52 getmimetype 7.2.53 getbase64fileextension 7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo. 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getusersonline 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag. 7.2.75 gethypertagname	153 154 155 155 156 156 156 158 158 158 159 160 160 161 162 162 163
7.2.48 getfemplateversions 7.2.49 getfileinfo 7.2.50 getobjectinfo 7.2.51 getfilesize 7.2.52 getmimetype 7.2.53 getbase64fileextension 7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getusersonline 7.2.69 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	153 154 155 155 156 156 157 158 158 159 159 160 161 161 162 162 163
7.2.49 getfileinfo 7.2.50 getobjectinfo 7.2.51 getfilesize 7.2.52 getmimetype 7.2.53 getbase64fileextension 7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertagname	154 155 156 156 156 157 158 158 159 159 160 161 161 162 162 163
7.2.50 getobjectinfo 7.2.51 getfilesize 7.2.52 getmimetype 7.2.53 getbase64fileextension 7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertagname	154 155 156 156 156 157 158 158 159 160 161 161 162 162 163
7.2.51 getfilesize 7.2.52 getmimetype 7.2.53 getbase64fileextension 7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertagname	155 156 156 156 157 158 158 159 160 161 161 162 162 163
7.2.52       getmimetype         7.2.53       getbase64fileextension         7.2.54       getfiletype         7.2.55       getpreviewwidth         7.2.56       getimagecolorkey         7.2.57       getimagecolors         7.2.58       getmediasize         7.2.59       getimageinfo         7.2.60       getpdfinfo         7.2.61       getvideoinfo         7.2.62       getrowserinfo.         7.2.63       getcontentlocation         7.2.64       getmedialocation         7.2.65       getlockedfileinfo         7.2.66       getfavorites         7.2.67       getclipboard         7.2.68       gethomeboxes         7.2.70       getuserboxes         7.2.71       getchatstate         7.2.72       getimagelib         7.2.73       getfilename         7.2.74       gethypertag         7.2.75       gethypertagname	155 156 156 157 158 158 159 160 161 161 162 162 163
7.2.53 getbase64fileextension 7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	156 156 157 158 158 159 159 160 161 161 162 162 163
7.2.54 getfiletype 7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	156 157 158 158 159 159 160 161 161 162 162 163
7.2.55 getpreviewwidth 7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertagname	156 157 158 158 159 160 161 161 162 162 163
7.2.56 getimagecolorkey 7.2.57 getimagecolors 7.2.58 getmediasize 7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo. 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag. 7.2.75 gethypertagname	157 158 158 159 160 160 161 161 162 162 163
7.2.57       getimagecolors         7.2.58       getmediasize         7.2.59       getimageinfo         7.2.60       getpdfinfo         7.2.61       getvideoinfo         7.2.62       getbrowserinfo         7.2.63       getcontentlocation         7.2.64       getmedialocation         7.2.65       getlockedfileinfo         7.2.66       getfavorites         7.2.67       getclipboard         7.2.68       gethomeboxes         7.2.69       getuserboxes         7.2.70       getusersonline         7.2.71       getchatstate         7.2.72       getimagelib         7.2.73       getfilename         7.2.74       gethypertag         7.2.75       gethypertagname	158 158 159 160 160 161 161 162 162 163
7.2.58       getmediasize         7.2.59       getimageinfo         7.2.60       getpdfinfo         7.2.61       getvideoinfo         7.2.62       getbrowserinfo         7.2.63       getcontentlocation         7.2.64       getmedialocation         7.2.65       getlockedfileinfo         7.2.66       getsavorites         7.2.67       getclipboard         7.2.68       gethomeboxes         7.2.69       getuserboxes         7.2.70       getusersonline         7.2.71       getchatstate         7.2.72       getimagelib         7.2.73       getfilename         7.2.74       gethypertagname         7.2.75       gethypertagname	158 159 159 160 161 161 162 162 163
7.2.59 getimageinfo 7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag. 7.2.75 gethypertagname	158 159 160 160 161 161 162 162 163
7.2.60 getpdfinfo 7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	159160161161162162163
7.2.61 getvideoinfo 7.2.62 getbrowserinfo 7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag. 7.2.75 gethypertagname	159 160 161 161 162 162 162 163
7.2.62 getbrowserinfo. 7.2.63 getcontentlocation. 7.2.64 getmedialocation. 7.2.65 getlockedfileinfo. 7.2.66 getfavorites. 7.2.67 getclipboard. 7.2.68 gethomeboxes. 7.2.69 getuserboxes. 7.2.70 getusersonline. 7.2.71 getchatstate. 7.2.72 getimagelib. 7.2.73 getfilename. 7.2.74 gethypertag. 7.2.75 gethypertagname.	160 160 161 161 162 162 163
7.2.63 getcontentlocation 7.2.64 getmedialocation 7.2.65 getlockedfileinfo 7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	160 161 162 162 162
7.2.64 getmedialocation. 7.2.65 getlockedfileinfo. 7.2.66 getfavorites. 7.2.67 getclipboard. 7.2.68 gethomeboxes. 7.2.69 getuserboxes. 7.2.70 getusersonline. 7.2.71 getchatstate. 7.2.72 getimagelib. 7.2.73 getfilename. 7.2.74 gethypertag. 7.2.75 gethypertagname.	161 161 162 162 163
7.2.65 getlockedfileinfo. 7.2.66 getfavorites. 7.2.67 getclipboard. 7.2.68 gethomeboxes. 7.2.69 getuserboxes. 7.2.70 getusersonline. 7.2.71 getchatstate. 7.2.72 getimagelib. 7.2.73 getfilename. 7.2.74 gethypertag. 7.2.75 gethypertagname.	161 162 162 162 163
7.2.66 getfavorites 7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	162 162 162 163
7.2.67 getclipboard 7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	162 162 163
7.2.68 gethomeboxes 7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	162 163
7.2.69 getuserboxes 7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	163
7.2.70 getusersonline 7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	
7.2.71 getchatstate 7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	
7.2.72 getimagelib 7.2.73 getfilename 7.2.74 gethypertag 7.2.75 gethypertagname	
7.2.73 getfilename	
7.2.74 gethypertag	
7.2.75 gethypertagname	
5 51 5	
/ 13 //	
7.2.76 gethtmltag	
7.2.77 gethtmltags	
7.2.78 getattribute	
3	
7.2.80 getcharset	
7.2.81 getal id	
7.2.83 getfirstkey	
7.2.84 getdirectoryfiles	
7.2.85 getuserinformation	
7.2.86 getworkflowitem	
7.3 Set API Functions	
7.3.1 setsession	
7.3.2 settemplate	
7.3.3 settaxonomy	
7.3.4 setarticle	
7.3.5 settext	
7.3.6 settext 7.3.6 setmedia	
7.3.7 setneda	
7.3.8 setcomplink	
7.3.9 sethead	/ 3
7.3.10 setrelation	173
7.3.11 setfilename	
7.3.12 setuserboxes	174
	174 174

7.4 Co	nnect API Functions	176
7.4.1	ftp_userlogon	176
7.4.2	ftp_userlogout	176
7.4.3	ftp_getfile	
7.4.4	ftp_putfile	
7.4.5	ftp_deletefile	
7.4.6	ftp_filelist	
7.4.7	createsharelink_facebook	
7.4.8	createsharelink_twitter	
7.4.9	createsharelink_googleplus	
7.4.10	createsharelink_linkedin	
7.4.11	createsharelink_pinterest	
	curity API Functions	
7.5.1	rootpermission	
7.5.2	globalpermission	
7.5.3	localpermission	
7.5.4	accessgeneral	
7.5.5	accesspermission	
7.5.6	setlocalpermission	
7.5.7	checkpublicationpermission	
7.5.8	checkadminpermission	
7.5.9	checkrootpermission	
7.5.10	checkglobalpermission	
7.5.11	checklocalpermission	
7.5.12	checklanguage	
7.5.13	checkgroupaccess	
7.5.14	userlogin	
7.5.15	setportalpermissions	
7.5.16	registerinstance	
7.5.17	registeruser	
7.5.18	registerassetbrowser	
7.5.19	createchecksum	
7.5.20	writesession	
7.5.21	writesessiondata	189
7.5.22	createsession	
7.5.23	killsession	189
7.5.24	checkdiskkey	
7.5.25	checkpassword	
7.5.26	loguserip	191
7.5.27	checkuserip	191
7.5.28	checkuserrequests	191
7.5.29	recreateusersession	192
7.5.30	checkusersession	192
7.5.31	allowuserip	192
7.5.32	valid_objectname	193
7.5.33	valid_locationname	193
7.5.34	valid_publicationname	194
7.5.35	html_encode	194
7.5.36	html_decode	194
7.5.37	scriptcode_encode	195
7.5.38	scriptcode_extract	195
7.5.39	scriptcode_clean_functions	
7.5.40	sql_clean_functions	
7.5.41	url_encode	
7.5.42	url_decode	197
7.5.43	shellcmd_encode	
7.5.44	hcms_crypt	
7.5.45	hcms_encrypt	198

7.5.46	hcms_decrypt	198
7.5.47	createtimetoken	199
7.5.48	checktimetoken	199
7.5.49	createtoken	
7.5.50	checktoken	
7.5.51	createuniquetoken	
7.5.52	createpassword	
7.5.52	rand_secure	
	dia API Functions	
7.6.1	ocr_extractcontent	
7.6.2	indexcontent	
7.6.3	unindexcontent	
7.6.4	reindexcontent	
7.6.5	createthumbnail_indesign	204
7.6.6	createthumbnail_video	204
7.6.7	createimages_video	205
7.6.8	createmedia	205
7.6.9	splitmedia	206
7.6.10	convertmedia	
7.6.11	convertimage	
7.6.12	rotateimage	
7.6.12	hex2rgb	
7.6.13	rgb2hex	
7.6.15	readmediaplayer_config	
7.6.16	savemediaplayer_config	
7.6.17	createdocument	
7.6.18	unzipfile	
7.6.19	clonefolder	212
7.6.20	zipfiles_helper	212
7.6.21	zipfiles	213
7.6.22	px2mm	213
7.6.23	px2inch	214
7.6.24	inch2px	
7.6.25	sec2time	
7.6.26	mediasize2frame	
7.6.27	vtt2array	
7.6.28	html2pdf	
7.6.29	•	
	mergepdftadata ARI Functions	
	tadata API Functions	
7.7.1	importmetadata	
7.7.2	loadtaxonomy	
7.7.3	savetaxonomy	
7.7.4	createtaxonomy	
7.7.5	splitkeywords	219
7.7.6	copymetadata	219
7.7.7	extractmetadata	219
7.7.8	xmlobject2array	220
7.7.9	id3_getdata	
7.7.10	id3_writefile	
7.7.13	id3_create	
7.7.11	xmp_getdata	
7.7.12	· ·	
	xmp_writefile	
7.7.14	xmp_create	
7.7.15	geo2decimal	
7.7.16	exif_getdata	
7.7.17	iptc_getdata	
7.7.18	iptc_getcharset	
7.7.19	iptc_maketag	224

7 7 20	into vunitofilo	225
7.7.20	iptc_writefile	
7.7.21	iptc_create	
7.7.22	createmapping	226
7.7.23	getmapping	226
7.7.24	metadata_exists	226
7.7.25	setmetadata	227
	k API Functions	
7.8.1	link_db_restore	
7.8.2		
	link_db_load	
7.8.3	link_db_read	
7.8.4	link_db_close	
7.8.5	link_db_save	229
7.8.6	link_db_update	230
7.8.7	link_db_insert	230
7.8.8	link_db_delete	
7.8.9	link_db_getobject	
7.8.10	link_update	
7.8.10		
	getlinkedobject	
7.8.12	getconnectedobject	
7.8.13	extractlinks	
7.9 Plu	gin API Functions	233
7.9.1	plugin_getdefaultconf	233
7.9.2	plugin_readmenu	234
7.9.3	plugin_parse	
7.9.4	plugin_generatedefinition	
7.9.5	plugin_saveconfig	
7.9.6	plugin_generatelink	
	er Interface API Functions	
7.10.1	windowwidth	
7.10.2	windowheight	236
7.10.3	toggleview	237
7.10.4	togglesidebar	
7.10.5	setfilter	
7.10.6	objectfilter	
7.10.7	showdate	
7.10.8	showshorttext	
7.10.9	showtopbar	
7.10.10	showtopmenubar	
7.10.11	showhomeboxes	240
7.10.12	showmessage	241
7.10.13	showinfopage	241
7.10.14	showinfobox	
7.10.15	showsharelinks	
7.10.16	showmetadata	
7.10.17	showobject	
7.10.18	showmedia	
7.10.19	showcompexplorer	
7.10.20		
7.10.21	showinlineeditor_head	
7.10.22	showinlinedatepicker_head	246
7.10.23	showinlineeditorshowinlineeditor	
7.10.24	showvideoplayer	
7.10.25	showvideoplayer_head	
7.10.25		
	showaudioplayer	
7.10.27	showaudioplayer_head	
7.10.28	debug_getbacktracestring	
7.10.29		
7.10.30	readnavigation	250

7.10.32         shownavigation         25           7.10.33         showselect         25           7.10.35         showmapping         25           7.10.36         showmapping         25           7.10.37         showthumbnail         25           7.10.39         showworkflowstatus         25           7.11         Template Engine API Functions         25           7.11.1         transformilink         25           7.11.2         followlink         25           7.11.3         rorohandler         25           7.11.4         viewinclusions         25           7.11.5         buildview         25           7.11.6         unescapeview         25           7.11.7         buildsearchform         25           7.11.8         buildbarchart         26           7.12.1         valid_tagname         26           7.12.1         valid_tagname         26           7.12.2         setxmlparameter         26           7.12.1         getxmlcontent         26           7.12.2         getxmlcontent         26           7.12.1         getxmlcontent         26           7.12.2         getxmlcont	7.10.32         shownavigation         252           7.10.33         showstelect         253           7.10.35         showmapping         254           7.10.36         showgallery         254           7.10.37         showthumbnail         255           7.10.38         showworkflowstatus         255           7.10.39         showworkflowstatus         256           7.11         Template Engine API Functions         256           7.11.1         fundiquestions         256           7.11.1         fundiquestions         257           7.11.2         followlink         257           7.11.3         errorhandler         257           7.11.4         viewinclusions         258           7.11.5         buildview         258           7.11.6         unescapeview         259           7.11.7         buildsearchform         259           7.11.8         buildsearchform         259           7.11.9         buildsearchform         259           7.11.1         buildsearchform         259           7.11.1         buildsearchform         259           7.11.1         publicate and			
7.10.33         showselect         25           7.10.34         showtranspling         25           7.10.35         showmapping         25           7.10.36         showgallery         25           7.10.37         showtaxonomytree         25           7.10.38         showtaxonomytree         25           7.10.39         showorkflowstatus         25           7.11.1         transformlink         25           7.11.1         transformlink         25           7.11.1         transformlink         25           7.11.2         followlink         25           7.11.3         errorhandler         25           7.11.4         viewlink         25           7.11.5         buildview         25           7.11.6         unescapeview         25           7.11.5         buildview         25           7.11.6         unescapeview         25           7.11.1         buildbarchart         26           7.11.1         buildbarchart         26           7.12.1         buildbarchart         26           7.12.1         valid Lagname         26           7.12.1         valid Lagname         26	7.10.33         showtranslator         253           7.10.35         showmapping         254           7.10.36         showgallery         254           7.10.37         showtaponomytree         255           7.10.38         showtaxonomytree         255           7.10.39         showvorkflowstatus         256           7.11.1         transformlink         256           7.11.1         transformlink         256           7.11.1         transformlink         257           7.11.3         errorhandler         257           7.11.4         viewlndusions         258           7.11.5         buildview         258           7.11.6         unescapeview         259           7.11.7         buildbarchart         260           7.12         XML API Functions         261           7.12.1         valid_tagname         261           7.12.2         setxmlparameter         261           7.12.3         getcontent         262           7.12.4         getcontent         262           7.12.5         getxmlcontent         264           7.12.7         selectcontent         264           7.12.1 <t< td=""><td>7.10.31</td><td>createnavigation</td><td>. 251</td></t<>	7.10.31	createnavigation	. 251
7.10.34         showtranslator         25           7.10.35         showapping         25           7.10.37         showthumbnall         25           7.10.38         showaconmytree         25           7.10.39         showaconmytree         25           7.11         Template Engine API Functions         25           7.11.1         transformlink         25           7.11.2         followlink         25           7.11.3         errorhandler         25           7.11.4         viewinclusions         25           7.11.5         buildview         25           7.11.6         unescapeview         25           7.11.7         buildsearchform         25           7.11.8         buildsearchform         25           7.11.7         buildsearchform         25           7.11.8         buildsearchform         25           7.11.9         buildsearchform         25           7.11.1         buildsearchform         25           7.11.1         buildsearchform         25           7.11.1         buildsearchform         25           7.11.1         buildsearchform         26           7.12.1	7.10.34         showtranslator         253           7.10.35         showgallery.         254           7.10.37         showthumbnail         255           7.10.39         showaconmytree         255           7.10.39         showaconmytree         255           7.11.03         showaconmytree         256           7.11         Template Engine API Functions         256           7.11.1         transformilink         256           7.11.2         followlink         257           7.11.3         errorhandler         257           7.11.4         viewinclusions         258           7.11.5         buildview         259           7.11.6         unescapeview         259           7.11.7         buildsearchform         259           7.11.7         buildsearchform         259           7.11.7         buildsearchfort         250           7.12.1         buildsearchfort         260	7.10.32	shownavigationshownavigation	.252
7.10.35         showgallery         25-           7.10.36         showtalmorbail         255-           7.10.38         showtaxonomytree         255-           7.10.39         showorkflowstatus         255-           7.11.1         Template Engine API Functions         256-           7.11.1         transformlink         255-           7.11.2         followlink         255-           7.11.3         errorhandler         256-           7.11.4         viewinculsions         256-           7.11.5         buildview         256-           7.11.6         unescapeview         256-           7.11.7         buildbarchart         266-           7.11.8         buildbarchart         266-           7.12.1         valid_tagname         266-           7.12.2         setxmlparameter         266-           7.12.1         valid_tagname         266-           7.12.2         setxmlcontent         266-           7.12.3         getxmlcontent         266-           7.12.4         getcontent         266-           7.12.5         getxmlcontent         266-           7.12.7         selectcontent         266-	7.10.35       showgallery       254         7.10.36       showdallery       255         7.10.38       showtaxonomytree       255         7.10.38       showtaxonomytree       255         7.10.39       showorkflowstatus       256         7.11.1       Template Engine API Functions       256         7.11.1       transformlink       257         7.11.2       cerorhandler       257         7.11.3       errorhandler       257         7.11.4       viewinculsoins       258         7.11.5       buildview       258         7.11.6       unescapeview       259         7.11.7       buildbarchart       250         7.12       Mulk API Functions       261         7.12       Mulk API Functions       261         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getometer       261         7.12.4       getiontent       262         7.12.5       getxmlcontent       262         7.12.6       getxmlcontent       263         7.12.7       selectiontent       264         7.12.9       selectxmlcont	7.10.33	showselect	.253
7.10.36       showgallery       25         7.10.37       showtaxonomytree       25         7.10.38       showtaxonomytree       25         7.11       Template Engine API Functions       25         7.11.1       transformlink       25         7.11.2       followlink       25         7.11.3       errorhandler       25         7.11.4       viewinclusions       25         7.11.5       bulldview       25         7.11.6       unescapeview       25         7.11.7       bulldbearchform       25         7.11.8       buildbearchform       25         7.11.9       bulldbearchform       25         7.11.1       valid_Lagname       26         7.12.1       valid_Lagname       26         7.12.2       setxmlparameter       26         7.12.3       getcontent       26         7.12.4       geticontent       26         7.12.5       getxmlcontent       26         7.12.1       selectiontent       26         7.12.1       selectontent       26         7.12.1       deleteiontent       26         7.12.10       selectxmlicontent       26	7.10.36       showgallery       254         7.10.37       showthumbnail       255         7.10.38       showavorkflowstatus       256         7.11       Template Engine API Functions       256         7.11.1       transformlink       256         7.11.1       transformlink       257         7.11.1       trollowlink       257         7.11.1       vicwinclusions       258         7.11.4       viewinclusions       258         7.11.5       buildview       258         7.11.6       unescapeview       259         7.11.7       buildsearchform       259         7.11.8       buildsearchfort       250         7.11.7       buildsearchfort       259         7.11.7       buildsearchfort       259         7.11.7       buildsearchfort       259         7.11.8       buildbarchart       260         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       261         7.12.4       geticontent       262         7.12.5       getxmlcont	7.10.34	showtranslator	.253
7.10.36       showgallery       25         7.10.37       showtaxonomytree       25         7.10.38       showtaxonomytree       25         7.11       Template Engine API Functions       25         7.11.1       transformlink       25         7.11.2       followlink       25         7.11.3       errorhandler       25         7.11.4       viewinclusions       25         7.11.5       bulldview       25         7.11.6       unescapeview       25         7.11.7       bulldbearchform       25         7.11.8       buildbearchform       25         7.11.9       bulldbearchform       25         7.11.1       valid_Lagname       26         7.12.1       valid_Lagname       26         7.12.2       setxmlparameter       26         7.12.3       getcontent       26         7.12.4       geticontent       26         7.12.5       getxmlcontent       26         7.12.1       selectiontent       26         7.12.1       selectontent       26         7.12.1       deleteiontent       26         7.12.10       selectxmlicontent       26	7.10.36       showgallery       254         7.10.37       showthumbnail       255         7.10.38       showavorkflowstatus       256         7.11       Template Engine API Functions       256         7.11.1       transformlink       256         7.11.1       transformlink       257         7.11.1       trollowlink       257         7.11.1       vicwinclusions       258         7.11.4       viewinclusions       258         7.11.5       buildview       258         7.11.6       unescapeview       259         7.11.7       buildsearchform       259         7.11.8       buildsearchfort       250         7.11.7       buildsearchfort       259         7.11.7       buildsearchfort       259         7.11.7       buildsearchfort       259         7.11.8       buildbarchart       260         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       261         7.12.4       geticontent       262         7.12.5       getxmlcont	7.10.35	showmapping	.254
7.10.37 showthumbnall       255         7.10.38 showtaxonomytree       255         7.10.39 showtorkflowstatus       256         7.11 Template Engine API Functions       256         7.11.1 transformlink       255         7.11.2 followlink       25         7.11.3 errorhandler       25         7.11.4 viewinclusions       255         7.11.5 bulldview       255         7.11.6 unescapeview       255         7.11.7 bulldsearchform       257         7.11.8 bulldbarchart       266         7.12 XML API Functions       266         7.12.1 valid_tagname       26         7.12.2 setxmlparameter       26         7.12.3 getcontent       26         7.12.4 geticontent       26         7.12.5 getxmlcontent       26         7.12.6 getxmlcontent       26         7.12.7 selectcontent       26         7.12.9 selectxmlicontent       26         7.12.10 deletecontent       26         7.12.11 deletecontent       26         7.12.12 deletecontent       26         7.12.13 setcontent_fast       26         7.12.14 setiontent       26         7.12.15 insertcontent       26         7.12.1	7.10.37         showthumbnail         255           7.10.38         showtaxonomytree         256           7.10.39         showworkflowstatus         256           7.11         Template Engine API Functions         256           7.11.1         transformilink         256           7.11.2         followlink         257           7.11.3         errorhandler         257           7.11.4         viewinclusions         258           7.11.5         buildview         258           7.11.6         unescapeview         259           7.11.7         buildbarchart         260           7.12         XML API Functions         259           7.12.1         valid_tagname         261           7.12.2         setxmlparameter         261           7.12.3         getcontent         262           7.12.4         geticontent         262           7.12.5         getxmlicontent         262           7.12.7         selectiontent         263           7.12.7         selectiontent         263           7.12.1         deleteicontent         264           7.12.10         selectxmlicontent         264           7.12	7.10.36	11 0	
7.10.38         showworkflowstatus         25           7.11         Template Engine API Functions         256           7.11.1         transformlink         25           7.11.2         followlink         25           7.11.3         errorhandler         25           7.11.4         viewinclusions         25           7.11.5         buildwe         25           7.11.6         unescapeview         25           7.11.7         buildsearchform         25           7.11.8         buildbarchart         26           7.11.7         buildsearchform         25           7.11.7         buildsearchform         25           7.11.7         buildsearchform         26           7.12.1         valid_tagname         26           7.12.1         valid_tagname         26           7.12.2         setxmlparameter         26           7.12.3         getcontent         26           7.12.4         geticontent         26           7.12.5         getxmlcontent         26           7.12.6         getxmlcontent         26           7.12.8         selectxmlcontent         26           7.12.8         select	7.10.38         showworkflowstatus         .255           7.11         Template Engine API Functions         .256           7.11.1         transformlink         .256           7.11.2         followlink         .257           7.11.3         errorhandler         .257           7.11.4         viewinclusions         .258           7.11.5         buildview         .258           7.11.6         unescapeview         .259           7.11.7         buildbearchform         .259           7.11.8         buildbearchart         .260           7.12         XML API Functions         .261           7.12.1         valid_tagname         .261           7.12.2         setxmlparameter         .261           7.12.3         getcontent         .261           7.12.4         geticontent         .262           7.12.5         getxmlcontent         .262           7.12.5         getxmlcontent         .262           7.12.8         selectiontent         .264           7.12.9         selectiontent         .264           7.12.1         deleticontent         .265           7.12.13         setcontent         .266	7.10.37		
7.10.39       showworkflowstatus       25         7.11       Template Engine API Functions       25         7.11.2       followlink       25         7.11.3       errorhandler       25         7.11.4       viewinclusions       25         7.11.5       buildview       25         7.11.6       unescapeview       25         7.11.7       buildsearchform       25         7.11.8       buildbarchart       26         7.11.1       valid_tagname       26         7.12.1       valid_tagname       26         7.12.2       setxmlparameter       26         7.12.3       getcontent       26         7.12.4       getticontent       26         7.12.5       getxmlicontent       26         7.12.6       getxmlicontent       26         7.12.7       selecticontent       26         7.12.9       selectxmlicontent       26         7.12.1       deletecontent       26         7.12.1       deletecontent       26         7.12.12       deletecontent       26         7.12.13       setcontent       26         7.12.14       seticontent       26	7.10.39       showworkflowstatus       256         7.11       Template Engine API Functions       256         7.11.1       transformlink       256         7.11.2       followlink       257         7.11.3       errorhandler       257         7.11.4       viewinclusions       258         7.11.5       buildview       258         7.11.7       buildview       258         7.11.7       buildview       259         7.11.7       buildbarchart       260         7.12       ML API Functions       261         7.12       vilk API Functions       261         7.12.1       vilk Question Functions       262         7.12.2       set extmiparameter       263         7.12.3 <td></td> <td></td> <td></td>			
7.11 Template Engine API Functions       25         7.11.1 transformlink       25         7.11.2 followlink       25         7.11.3 errorhandler       25         7.11.4 viewinclusions       25         7.11.5 buildview       25         7.11.6 unescapeview       25         7.11.7 buildsearchform       25         7.11.8 buildbarchart       26         7.12 XML API Functions       26         7.12.1 valid_tagname       26         7.12.2 sexmlparameter       26         7.12.3 getcontent       26         7.12.4 geticontent       26         7.12.5 getxmlcontent       26         7.12.6 getxmlicontent       26         7.12.7 selectiontent       26         7.12.8 selectiontent       26         7.12.9 selectxmlicontent       26         7.12.10 selectxmlicontent       26         7.12.11 deletecontent       26         7.12.12 setcontent       26         7.12.13 setcontent       26         7.12.14 seticontent       26         7.12.15 setcontent_fast       26         7.12.16 updatecontent       26         7.12.17 insertcontent       26         7.12.19 addcontent	7.11 Template Engine API Functions       256         7.11.1 transformlink       256         7.11.2 followlink       257         7.11.3 errorhandler       257         7.11.4 viewinclusions       258         7.11.6 unescapeview       258         7.11.7 buildsearchform       259         7.11.8 buildbearchart       260         7.12 XML API Functions       261         7.12.1 valid_tagname       261         7.12.2 setxmlparameter       261         7.12.3 getcontent       261         7.12.4 geticontent       262         7.12.5 getxmlcontent       262         7.12.6 getxmlicontent       263         7.12.7 selectcontent       263         7.12.8 selectiontent       264         7.12.9 selectxmlicontent       264         7.12.1 deleteiontent       265         7.12.11 deletecontent       265         7.12.12 deletecontent       265         7.12.13 setcontent_       266         7.12.14 seticontent       266         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       269			
7.11.1 transformlink       256         7.11.2 followlink       257         7.11.3 errorhandler       255         7.11.4 viewinclusions       256         7.11.5 buildview       256         7.11.7 buildsearchform       255         7.11.7 buildsearchform       255         7.11.8 buildbarchart       260         7.12.1 valid_tagname       26         7.12.2 setxmlparameter       26         7.12.3 getcontent       26         7.12.4 geticontent       26         7.12.5 getxmlcontent       26         7.12.6 getxmlicontent       26         7.12.7 selectcontent       26         7.12.9 selectxmlcontent       26         7.12.1 degetecontent       26         7.12.1 selectxmlicontent       26         7.12.1 selectxmlicontent       26         7.12.10 selectxmlicontent       26         7.12.11 deletecontent       26         7.12.12 deleteiontent       26         7.12.13 setcontent       26         7.12.15 setcontent_fast       26         7.12.16 updatecontent       26         7.12.17 insertcontent       26         7.12.18 inserticontent       26         7.12.20 addiconten	7.11.1       transformlink       256         7.11.2       followlink       257         7.11.3       errorhandler       257         7.11.4       viewinclusions       258         7.11.5       buildview       259         7.11.7       buildsearchform       259         7.11.7       buildbarchart       260         7.12       XML API Functions       261         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       262         7.12.4       geticontent       262         7.12.5       getxmlicontent       262         7.12.6       getxmlicontent       263         7.12.7       selectcontent       263         7.12.9       selectxmlicontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       264         7.12.11       deleteicontent       265         7.12.12       deleteicontent       265         7.12.13       setcontent_fast       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent </td <td></td> <td></td> <td></td>			
7.11.2 followlink       25         7.11.3 errorhandler       25         7.11.5 viewinclusions       256         7.11.5 buildview       256         7.11.6 unescapeview       255         7.11.7 buildsearchform       255         7.11.8 buildbarchart       266         7.12 XML API Functions       267         7.12.1 valid_tagname       26         7.12.2 setxmlparameter       26         7.12.3 getcontent       26         7.12.4 geticontent       26         7.12.5 getxmlcontent       26         7.12.6 getxmlicontent       26         7.12.7 selectontent       26         7.12.8 selectiontent       26         7.12.9 selectxmlcontent       26         7.12.10 selectiontent       26         7.12.11 deletecontent       26         7.12.12 deleteicontent       26         7.12.13 setcontent       26         7.12.14 seticontent       26         7.12.15 setcontent_fast       26         7.12.16 updatecontent       26         7.12.17 insertcontent       26         7.12.18 inserticontent       26         7.12.19 addoontent       26         7.13.3 Report API Functions	7.11.2 followlink       257         7.11.3 errorhandler       258         7.11.4 viewinclusions       258         7.11.5 buildview       258         7.11.6 unescapeview       259         7.11.7 buildsearchform       259         7.11.8 buildbarchart       260         7.12 XML API Functions       261         7.12.1 valid_tagname       261         7.12.2 setxmlparameter       261         7.12.3 getcontent       262         7.12.5 getxmlcontent       262         7.12.5 getxmlcontent       262         7.12.6 getxmlicontent       262         7.12.8 selectiontent       263         7.12.9 selectxmlicontent       264         7.12.10 selectxmlicontent       264         7.12.11 deletecontent       265         7.12.12 deleteicontent       265         7.12.13 setcontent       266         7.12.14 seticontent       266         7.12.15 setoontent       267         7.12.16 updatecontent       267         7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addicontent       269         7.13.10 updatecontent       269         7.13.1 cre	•		
7.11.3       errorhandler       25         7.11.4       viewinclusions       258         7.11.5       buildvew       25         7.11.7       buildsearchform       25         7.11.8       buildbarchart       26         7.11.8       buildbarchart       26         7.12.1       Vall API Functions       26         7.12.1       valid_tagname       26         7.12.2       setxmlparameter       26         7.12.3       getcontent       26         7.12.4       geticontent       26         7.12.5       getxmlicontent       26         7.12.6       getxmlicontent       26         7.12.7       selecticontent       26         7.12.9       selecticontent       26         7.12.9       selectxmlicontent       26         7.12.10       selectxmlicontent       26         7.12.11       deleteicontent       26         7.12.12       deleteicontent       26         7.12.13       setiontent       26         7.12.14       seticontent       26         7.12.15       setcontent       26         7.12.16       updatecontent       26 <td>7.11.3       errorhandler       257         7.11.4       viewinclusions       258         7.11.5       buildview       258         7.11.6       unescapeview       259         7.11.7       buildsearchform       259         7.11.8       buildbarchart       260         7.12       XML API Functions       261         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       262         7.12.4       geticontent       262         7.12.5       getxmlicontent       262         7.12.6       getxmlicontent       263         7.12.7       selecticontent       263         7.12.7       selecticontent       264         7.12.9       selectxmicontent       264         7.12.10       selectxmicontent       265         7.12.11       deleteicontent       265         7.12.12       deleteicontent       265         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent       266         7.12.16       updatecontent       <td< td=""><td></td><td></td><td></td></td<></td>	7.11.3       errorhandler       257         7.11.4       viewinclusions       258         7.11.5       buildview       258         7.11.6       unescapeview       259         7.11.7       buildsearchform       259         7.11.8       buildbarchart       260         7.12       XML API Functions       261         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       262         7.12.4       geticontent       262         7.12.5       getxmlicontent       262         7.12.6       getxmlicontent       263         7.12.7       selecticontent       263         7.12.7       selecticontent       264         7.12.9       selectxmicontent       264         7.12.10       selectxmicontent       265         7.12.11       deleteicontent       265         7.12.12       deleteicontent       265         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent       266         7.12.16       updatecontent <td< td=""><td></td><td></td><td></td></td<>			
7.11.4       viewinclusions.       256         7.11.5       buildview       255         7.11.7       buildsearchform       256         7.11.7       buildsearchform       257         7.11.8       buildbarchart       266         7.12       XML API Functions       267         7.12.1       valid_tagname       267         7.12.2       setxmlparameter       266         7.12.3       getcontent       266         7.12.4       geticontent       266         7.12.5       getxmlicontent       266         7.12.6       getxmlicontent       266         7.12.7       selectcontent       266         7.12.8       selecticontent       266         7.12.9       selectxmlicontent       266         7.12.10       selectxmlicontent       266         7.12.11       deletecontent       266         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setontent_fast       266         7.12.14       seticontent       266         7.12.15       setontent_fast	7.11.4       vewinclusions       258         7.11.5       buildview       259         7.11.7       buildsearchform       259         7.11.7       buildsearchform       259         7.11.8       buildbarchart       260         7.12       XML API Functions       261         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       262         7.12.4       getiontent       262         7.12.5       getxmlcontent       262         7.12.7       selectiontent       263         7.12.7       selectiontent       263         7.12.8       selectiontent       264         7.12.9       selectxmlcontent       264         7.12.10       selectxmlicontent       265         7.12.11       deleteicontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent_fast       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       269         7.12.19       addicontent <td></td> <td></td> <td></td>			
7.11.6       unescapeview       25         7.11.6       unescapeview       25         7.11.7       buildsearchform       25         7.11.8       buildbarchart       26         7.12       XML API Functions       26         7.12.1       valid_tagname       26         7.12.2       setxmlparameter       26         7.12.3       getcontent       26         7.12.4       geticontent       26         7.12.5       getxmlicontent       26         7.12.6       getxmlicontent       26         7.12.7       selecticontent       26         7.12.8       selecticontent       26         7.12.9       selectxmlicontent       26         7.12.10       selectxmlicontent       26         7.12.11       deletecontent       26         7.12.12       deletecontent       26         7.12.13       setcontent       26         7.12.14       seticontent       26         7.12.15       setzontent_fast       26         7.12.16       updatecontent       26         7.12.17       insertiontent       26         7.12.18       insertiontent       26	7.11.5       buildview       258         7.11.6       unescapeview       259         7.11.7       buildsearchform       259         7.11.8       buildbarchart       260         7.12       XML API Functions       261         7.12.1       valid_tagname       261         7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       262         7.12.4       geticontent       262         7.12.5       getxmlcontent       262         7.12.6       getxmlicontent       263         7.12.7       selecticontent       263         7.12.8       selecticontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       264         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       setiontent       266         7.12.15       setcontent       267         7.12.16       updatecontent       268         7.12.17       insertcontent <td< td=""><td></td><td></td><td></td></td<>			
7.11.6       unescapeview       256         7.11.7       buildsearchform       266         7.12       XML API Functions       267         7.12.1       valid_tagname       267         7.12.2       setxmlparameter       267         7.12.3       getcontent       266         7.12.4       geticontent       266         7.12.5       getxmlicontent       266         7.12.6       getxmlicontent       266         7.12.7       selectcontent       266         7.12.8       selecticontent       266         7.12.9       selectxmlicontent       266         7.12.10       selectxmlicontent       266         7.12.11       deletecontent       266         7.12.12       deletecontent       266         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent       266         7.12.16       updatecontent       266         7.12.17       inserticontent       266         7.12.18       inserticontent       266         7.12.19       addicontent       266         7.13.1       createreport	7.11.6       unescapeview       259         7.11.7       buildsearchform       259         7.11.8       buildbarchart       260         7.12.1       Valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       262         7.12.4       geticontent       262         7.12.5       getxmlicontent       262         7.12.7       selectiontent       263         7.12.8       selecticontent       263         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       264         7.12.11       deletecontent       265         7.12.12       deleteicontent       265         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent       266         7.12.11       seticontent       266         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.17       seticontent       267         7.12.18       inserticontent			
7.11.7 buildsearchform       256         7.11.8 buildbarchart       266         7.12 XML API Functions       26         7.12.1 valid_tagname       26         7.12.2 setxmlparameter       26         7.12.3 getcontent       26         7.12.4 geticontent       26         7.12.5 getxmlcontent       26         7.12.6 getxmlicontent       26         7.12.7 selectcontent       26         7.12.8 selectiontent       26         7.12.9 selectxmlicontent       26         7.12.10 selectxmlicontent       26         7.12.11 deletecontent       26         7.12.12 deleteicontent       26         7.12.13 setcontent       26         7.12.14 seticontent       26         7.12.15 setcontent_fast       26         7.12.16 updatecontent       26         7.12.17 insertcontent       26         7.12.18 inserticontent       26         7.12.19 addcontent       26         7.12.10 updatecontent       26         7.12.11 inserticontent       26         7.12.12 a delireport       27         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 bandyzeSQLselect <td>7.11.7 buildsearchform       259         7.11.8 buildbarchart       260         7.12 XML API Functions       261         7.12.1 valid_tagname       261         7.12.2 setxmlparameter       261         7.12.3 getcontent       261         7.12.4 geticontent       262         7.12.5 getxmlcontent       262         7.12.6 getxmlicontent       263         7.12.7 selectcontent       263         7.12.8 selecticontent       264         7.12.9 selectxmlicontent       264         7.12.10 selectxmlicontent       265         7.12.11 deletecontent       265         7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       266         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.19 addcontent       269         7.12.20 addicontent       269         7.13.3 loadreport       271         7.13.4 deletereport       271         7.13.5 analyzeSOLselect       273         7.13</td> <td></td> <td></td> <td></td>	7.11.7 buildsearchform       259         7.11.8 buildbarchart       260         7.12 XML API Functions       261         7.12.1 valid_tagname       261         7.12.2 setxmlparameter       261         7.12.3 getcontent       261         7.12.4 geticontent       262         7.12.5 getxmlcontent       262         7.12.6 getxmlicontent       263         7.12.7 selectcontent       263         7.12.8 selecticontent       264         7.12.9 selectxmlicontent       264         7.12.10 selectxmlicontent       265         7.12.11 deletecontent       265         7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       266         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.19 addcontent       269         7.12.20 addicontent       269         7.13.3 loadreport       271         7.13.4 deletereport       271         7.13.5 analyzeSOLselect       273         7.13			
7.11.8 buildbarchart       266         7.12 XML API Functions       26         7.12.1 Valid_tagname       26         7.12.2 setxmlparameter       26         7.12.3 getcontent       26         7.12.4 geticontent       26         7.12.5 getxmlcontent       26         7.12.6 getxmlicontent       26         7.12.7 selectcontent       26         7.12.9 selectcontent       26         7.12.9 selectxmlcontent       26         7.12.10 selectxmlicontent       26         7.12.11 deletecontent       26         7.12.12 deleteicontent       26         7.12.13 setcontent       26         7.12.14 seticontent       26         7.12.15 setcontent_fast       26         7.12.16 updatecontent       26         7.12.17 insertcontent       26         7.12.18 inserticontent       26         7.12.19 addcontent       26         7.12.19 addcontent       26         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 loadreport       27         7.13.4 deletereport       27         7.13.5 analyzeSQLselect       27         7.13.8 showareachart       2	7.11.8 buildbarchart       260         7.12 XML API Functions       261         7.12.1 valid_tagname       261         7.12.2 setxmlparameter       261         7.12.3 getcontent       262         7.12.4 geticontent       262         7.12.5 getxmlcontent       263         7.12.7 selectcontent       263         7.12.8 selecticontent       263         7.12.9 selectxmlcontent       264         7.12.10 selectxmlicontent       265         7.12.11 deletecontent       265         7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       266         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       268         7.12.19 addcontent       269         7.12.10 deleteroport       270         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       271         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       274         7.13.9 sho			
7.12 XML API Functions       26'         7.12.1 valid_tagname       26'         7.12.2 setxmlparameter       26'         7.12.3 getcontent       26'         7.12.4 geticontent       26'         7.12.5 getxmlicontent       26'         7.12.6 getxmlicontent       26'         7.12.7 selectcontent       26'         7.12.8 selecticontent       26'         7.12.10 selectxmlicontent       26'         7.12.11 deletecontent       26'         7.12.12 deleteicontent       26'         7.12.13 setcontent       26'         7.12.14 seticontent       26'         7.12.15 isotontent       26'         7.12.16 updatecontent       26'         7.12.17 insertcontent       26'         7.12.18 inserticontent       26'         7.12.19 addcontent       26'         7.12.19 addcontent       26'         7.12.20 addicontent       26'         7.13.3 Report API Functions       27'         7.13.2 editreport       27'         7.13.3 showereachart       27'         7.13.5 showereachart       27'         7.13.7 showelenmethart       27'         7.13.8 showareachart       27'         7.14.1	7.12 XML API Functions       261         7.12.1 valid_tagname       261         7.12.2 setxmlparameter       261         7.12.3 getcontent       261         7.12.4 geticontent       262         7.12.5 getxmlcontent       262         7.12.7 selectcontent       263         7.12.8 selecticontent       263         7.12.9 selectxmlcontent       264         7.12.10 selectxmlicontent       265         7.12.11 deletecontent       265         7.12.12 deleteicontent       265         7.12.13 setcontent       266         7.12.14 seticontent       266         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       268         7.12.19 addocntent       269         7.12.19 addocntent       269         7.12.20 addicontent       270         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 bandgreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.1 oshowgeolocationchart       274         7.1			
7.12.1       valid_tagname       26'         7.12.2       setxmlparameter       26'         7.12.3       getcontent       26'         7.12.4       geticontent       26'         7.12.5       getxmlcontent       26'         7.12.6       getxmlicontent       26'         7.12.7       selectcontent       26'         7.12.8       selectiontent       26'         7.12.9       selectxmlcontent       26'         7.12.10       selectxmlicontent       26'         7.12.11       deletecontent       26'         7.12.12       deleteicontent       26'         7.12.13       setcontent       26'         7.12.14       seticontent       26'         7.12.15       setcontent_fast       26'         7.12.16       updatecontent       26'         7.12.17       inserticontent       26'         7.12.18       inserticontent       26'         7.12.19       addontent       26'         7.12.20       addicontent       27'         7.13.1       createreport       27'         7.13.2       editreport       27'         7.13.3       loadereport       27	7.12.1       valid_tagname       261         7.12.2       setxmlparameter       261         7.12.3       getcontent       262         7.12.4       geticontent       262         7.12.5       getxmlcontent       262         7.12.6       getxmlicontent       263         7.12.7       selectcontent       263         7.12.8       selectiontent       264         7.12.9       selectxmlcontent       264         7.12.10       selectxmlcontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       268         7.12.19       addontent       270         7.13.2       addicontent       271         7.13.3       loadreport       271         7.13.4       deletereport       272         7.13.5       analyzeSOLselect <td< td=""><td></td><td></td><td></td></td<>			
7.12.2       setxmlparameter       26'         7.12.3       getcontent       26'         7.12.4       getiontent       26'         7.12.5       getxmlcontent       26'         7.12.6       getxmlicontent       26'         7.12.7       selectcontent       26'         7.12.8       selectxmlcontent       26'         7.12.9       selectxmlicontent       26'         7.12.10       selectxmlicontent       26'         7.12.11       deletecontent       26'         7.12.12       deleteicontent       26'         7.12.13       setcontent       26'         7.12.14       setiontent       26'         7.12.15       setcontent_fast       26'         7.12.16       updatecontent       26'         7.12.17       inserticontent       26'         7.12.18       inserticontent       26'         7.12.19       addcontent       26'         7.12.19       addcontent       26'         7.13.1       createreport       27'         7.13.2       editreport       27'         7.13.3       loadreport       27'         7.13.4       deletereport       27	7.12.2       setxmlparameter       .261         7.12.3       getcontent       .262         7.12.4       geticontent       .262         7.12.5       getxmlicontent       .263         7.12.7       selectiontent       .263         7.12.7       selecticontent       .264         7.12.9       selectxmlicontent       .264         7.12.10       selectxmlicontent       .265         7.12.11       deletecontent       .265         7.12.12       deleteicontent       .266         7.12.13       setcontent       .266         7.12.14       seticontent       .267         7.12.15       setcontent_fast       .267         7.12.16       updatecontent       .268         7.12.17       inserticontent       .268         7.12.18       inserticontent       .269         7.12.19       addicontent       .269         7.12.19       addicontent       .269         7.12.19       addicontent       .269         7.13.1       createreport       .271         7.13.2       editreport       .271         7.13.3       loadreport       .272         7.13.4       deleter			
7.12.3       getcontent       26'         7.12.4       geticontent       26'         7.12.5       getxmlcontent       26'         7.12.7       selectcontent       26'         7.12.8       selectcontent       26'         7.12.9       selectxmlcontent       26'         7.12.10       selectxmlicontent       26'         7.12.11       deletecontent       26'         7.12.12       deleticontent       26'         7.12.13       setcontent       26'         7.12.14       seticontent       26'         7.12.15       setcontent       26'         7.12.16       updatecontent       26'         7.12.17       insertcontent       26'         7.12.18       insertcontent       26'         7.12.19       addcontent       26'         7.12.19       addcontent       26'         7.12.19       addcontent       26'         7.13.1       createreport       27'         7.13.2       editreport       27'         7.13.3       loadreport       27'         7.13.4       deletereport       27'         7.13.5       analyzeSQLselect       27'     <	7.12.3       getcontent       261         7.12.4       geticontent       262         7.12.5       getxmlicontent       263         7.12.7       selectcontent       263         7.12.8       selecticontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       268         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       273         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       2			
7.12.4 geticontent       262         7.12.5 getxmlicontent       263         7.12.6 getxmlicontent       263         7.12.7 selectcontent       264         7.12.8 selecticontent       264         7.12.9 selectxmlicontent       264         7.12.10 selectxmlicontent       264         7.12.11 deletecontent       265         7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       266         7.12.15 setcontent_fast       26         7.12.16 updatecontent       266         7.12.17 insertcontent       266         7.12.18 inserticontent       266         7.12.19 addcontent       266         7.12.20 addicontent       266         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 loadreport       27         7.13.4 deletereport       27         7.13.5 analyzeSQLselect       27         7.13.6 showpiechart       27         7.13.7 showcolumnchart       27         7.13.8 showareachart       27         7.13.9 showtimelinechart       27         7.14.1 createproject       27         7.14.2 editpro	7.12.4       getiontent       262         7.12.5       getxmlcontent       262         7.12.6       getxmlicontent       263         7.12.7       selectcontent       263         7.12.8       selectiontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       268         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.5       analyzeSQLselect       272         7.13.6       showpiechart       273         7.13.7       showgeolocationchart		·	
7.12.5       getxmlcontent       262         7.12.6       getxmllcontent       263         7.12.7       selectcontent       264         7.12.8       selecticontent       264         7.12.9       selectxmlicontent       266         7.12.10       selectxmlicontent       266         7.12.11       deletecontent       266         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       26         7.12.15       setcontent_fast       26         7.12.16       updatecontent       26         7.12.17       inserticontent       26         7.12.18       inserticontent       26         7.12.19       addocntent       26	7.12.5       getxmlcontent       262         7.12.6       getxmlcontent       263         7.12.7       selectcontent       264         7.12.8       selecticontent       264         7.12.9       selectxmlcontent       265         7.12.10       selectxmlicontent       265         7.12.11       deleteicontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       268         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       272         7.13.3       loadreport       272         7.13.4       deletereport       273         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart			
7.12.6       getxmlicontent       26         7.12.7       selectcontent       26         7.12.8       selectxmlcontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       26         7.12.12       deleteicontent       26         7.12.13       setcontent       26         7.12.14       seticontent       26         7.12.15       setcontent_fast       26         7.12.16       updatecontent       26         7.12.17       inserticontent       26         7.12.18       inserticontent       26         7.12.19       addcontent       26         7.12.20       addicontent       27         7.13.1       createreport       27         7.13.2       editreport       27         7.13.3       loadreport       27         7.13.4       deletereport       27         7.13.5       analyzeSQLselect       27         7.13.6       showpiechart       27         7.13.7       showdelentart       27         7.13.8       showgeolocationchart       27 <td>7.12.6       getxmlicontent       263         7.12.7       selectcontent       263         7.12.8       selecticontent       264         7.12.9       selectxmlcontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleticontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       271         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       274         7.13.7       showgeolocationchart       274         7.13.9       showtimelinechart<td> —</td><td></td><td></td></td>	7.12.6       getxmlicontent       263         7.12.7       selectcontent       263         7.12.8       selecticontent       264         7.12.9       selectxmlcontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleticontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       271         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       274         7.13.7       showgeolocationchart       274         7.13.9       showtimelinechart <td> —</td> <td></td> <td></td>	—		
7.12.7       selectcontent       266         7.12.8       selecticontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       266         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent_fast       26         7.12.16       updatecontent       266         7.12.17       inserticontent       266         7.12.18       inserticontent       266         7.12.19       addcontent       266         7.12.20       addicontent       276         7.13.1       createreport       277         7.13.2       editreport       277         7.13.3       loadreport       277         7.13.4       deletereport       277         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showcolumnchart       275         7.13.10       showgeolocationchart </td <td>7.12.7       selectcontent       263         7.12.8       selectzmlcontent       264         7.12.9       selectxmlcontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.19       addcontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       274         7.13.9       showtimelinechart       274         7.13.10       showgeolocationchar</td> <td></td> <td></td> <td></td>	7.12.7       selectcontent       263         7.12.8       selectzmlcontent       264         7.12.9       selectxmlcontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.19       addcontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       274         7.13.9       showtimelinechart       274         7.13.10       showgeolocationchar			
7.12.8       selectxmlcontent       264         7.12.9       selectxmlcontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       266         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       26         7.12.15       setcontent_fast       26         7.12.16       updatecontent       26         7.12.17       inserticontent       26         7.12.18       inserticontent       26         7.12.19       addicontent       26         7.12.20       addicontent       27         7.13       reatereport       27         7.13.1       createreport       27         7.13.2       editreport       27         7.13.3       loadreport       27         7.13.4       deletereport       27         7.13.5       analyzeSQLselect       27         7.13.7       showpiechart       27         7.13.8       showpreachart       27         7.13.9       showtimelinechart       27         7.14       Project API Functions       27 <td>7.12.8       selectiontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       275         7.14.1       createproject<!--</td--><td>7.12.6</td><td></td><td></td></td>	7.12.8       selectiontent       264         7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       275         7.14.1       createproject </td <td>7.12.6</td> <td></td> <td></td>	7.12.6		
7.12.9       selectxmlicontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleticontent       266         7.12.13       setcontent       266         7.12.14       seticontent       266         7.12.15       setcontent_fast       26         7.12.16       updatecontent       26         7.12.17       inserticontent       26         7.12.18       inserticontent       26         7.12.19       addcontent       26         7.12.19       addcontent       26         7.12.20       addicontent       27         7.13.1       createreport       27         7.13.2       editreport       27         7.13.3       loadreport       27         7.13.4       deletereport       27         7.13.5       analyzeSQLselect       27         7.13.6       showpiechart       27         7.13.7       showtimelinechart       27         7.13.8       showareachart       27         7.13.9       showtimelinechart       27         7.14.1       createproject       27	7.12.9       selectxmlcontent       264         7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.8       showpiechart       274         7.13.9       showtimelinechart       274         7.13.10       showgeolocationchart       274         7.14.1       createprojec	7.12.7	selectcontent	. 263
7.12.10       selectxmlicontent       265         7.12.11       deletecontent       266         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       265         7.12.15       setcontent_fast       26         7.12.16       updatecontent       266         7.12.17       inserticontent       266         7.12.18       inserticontent       266         7.12.19       addcontent       26         7.12.20       addicontent       27         7.13       Report API Functions       27         7.13.1       createreport       27         7.13.2       editreport       27         7.13.3       loadreport       27         7.13.4       deletereport       27         7.13.5       analyzeSQLselect       27         7.13.6       showpiechart       27         7.13.7       showcolumnchart       27         7.13.8       showdimelinechart       27         7.13.9       showtimelinechart       27         7.14       Project API Functions       27         7.14.1       createproject	7.12.10       selectxmlicontent       265         7.12.11       deletecontent       265         7.12.12       deleteicontent       266         7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       269         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showcolumnchart       274         7.13.9       showtimelinechart       274         7.13.10       showgeolocationchart       275         7.14.1       createproj	7.12.8	selecticontent	. 264
7.12.11 deletecontent       266         7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       267         7.12.15 setcontent_fast       26         7.12.16 updatecontent       266         7.12.17 insertcontent       266         7.12.18 inserticontent       266         7.12.19 addcontent       266         7.12.20 addicontent       27         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 loadreport       27         7.13.4 deletereport       27         7.13.5 analyzeSQLselect       27         7.13.6 showpiechart       27         7.13.7 showcolumnchart       27         7.13.8 showareachart       27         7.13.9 showtimelinechart       27         7.13.10 showgeolocationchart       27         7.14.1 createproject       27         7.14.2 editproject       27         7.14.3 deleteproject       27         7.14.4 getprojectstructure       27         7.14.5 showprojectrecord       27          7.14.5 showprojectrecord       27	7.12.11 deletecontent       265         7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       267         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleterpoject       277         7.14.4 getprojectstructure       278	7.12.9	selectxmlcontent	. 264
7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       26         7.12.15 setcontent_fast       26         7.12.16 updatecontent       266         7.12.17 insertcontent       266         7.12.18 inserticontent       26         7.12.19 addcontent       26         7.12.20 addicontent       27         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 loadreport       27         7.13.4 deletereport       27         7.13.5 analyzeSQLselect       27         7.13.6 showpiechart       27         7.13.8 showareachart       27         7.13.9 showtimelinechart       27         7.13.10 showgeolocationchart       27         7.14.1 createproject       27         7.14.2 editproject       27         7.14.3 deleteproject       27         7.14.4 getprojectstructure       27         7.14.5 showprojectrecord       278         7.14.5 showprojectrecord       278          7.14.5 showprojectrecord       276	7.12.12 deleteicontent       266         7.12.13 setcontent       266         7.12.14 seticontent       267         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.8 showareachart       274         7.13.9 showtimelinechart       274         7.13.10 showgeolocationchart       275         7.14.1 createproject       277         7.14.2 editproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278	7.12.10	selectxmlicontent	. 265
7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       266         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       266         7.12.19       addcontent       266         7.12.20       addicontent       276         7.13       Report API Functions       277         7.13.1       createreport       277         7.13.2       editreport       277         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       272         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       276         7.14       Project API Functions       276         7.14.1       createrpoject       277         7.14.2       editproject       277         7.14.3       deleteproject       276         7.14.4       getprojectstructure	7.12.13       setcontent       267         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       insertcontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.14.1       createproject API Functions       276         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       277         7.14.4       getprojectstructure       278	7.12.11	deletecontent	. 265
7.12.13       setcontent       266         7.12.14       seticontent       267         7.12.15       setcontent_fast       266         7.12.16       updatecontent       268         7.12.17       inserticontent       268         7.12.18       inserticontent       266         7.12.19       addcontent       266         7.12.20       addicontent       276         7.13       Report API Functions       277         7.13.1       createreport       277         7.13.2       editreport       277         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       272         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       276         7.14       Project API Functions       276         7.14.1       createrpoject       277         7.14.2       editproject       277         7.14.3       deleteproject       276         7.14.4       getprojectstructure	7.12.13       setcontent       267         7.12.14       seticontent       267         7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       insertcontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.14.1       createproject API Functions       276         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       277         7.14.4       getprojectstructure       278	7.12.12	deleteicontent	.266
7.12.14 seticontent       26         7.12.15 setcontent_fast       26         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       266         7.12.19 addcontent       26         7.12.20 addicontent       27         7.13 Report API Functions       27         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 loadreport       27         7.13.4 deletereport       27         7.13.5 analyzeSQLselect       27         7.13.6 showpiechart       27         7.13.7 showcolumnchart       27         7.13.8 showareachart       27         7.13.9 showtimelinechart       27         7.14.1 createproject       27         7.14.2 editproject       27         7.14.3 deleteproject       27         7.14.4 getprojectstructure       27         7.14.5 showprojectrecord       27         7.14.5 showprojectrecord       27	7.12.14 seticontent       267         7.12.15 setcontent_fast       267         7.12.16 updatecontent       268         7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       274         7.13.10 showgeolocationchart       275         7.14 Project API Functions       276         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278	7.12.13		
7.12.15       setcontent_fast       26         7.12.16       updatecontent       268         7.12.17       insertcontent       268         7.12.18       inserticontent       266         7.12.19       addcontent       26         7.12.20       addicontent       27         7.13       Report API Functions       27         7.13.1       createreport       27         7.13.2       editreport       27         7.13.3       loadreport       27         7.13.4       deletereport       27         7.13.5       analyzeSQLselect       27         7.13.6       showpiechart       27         7.13.7       showcolumnchart       27         7.13.8       showareachart       27         7.13.9       showtimelinechart       27         7.13.10       showgeolocationchart       27         7.14.1       createproject       27         7.14.2       editproject       27         7.14.3       deleteproject       27         7.14.4       getprojectstructure       27         7.14.5       showprojectrecord       27	7.12.15       setcontent_fast       267         7.12.16       updatecontent       268         7.12.17       insertcontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       275         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278          7.14.4       getprojectstructure       278	7.12.14		
7.12.16       updatecontent       268         7.12.17       insertcontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       270         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       272         7.13.2       editreport       272         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       275         7.14.2       editproject       275         7.14.3       deleteproject       275         7.14.4       getprojectstructure       276         7.14.5       showprojectrecord       276	7.12.16       updatecontent       268         7.12.17       insertcontent       268         7.12.18       inserticontent       269         7.12.19       addcontent       270         7.12.20       addicontent       270         7.13       Report API Functions       271         7.13.1       createreport       271         7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       275         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278          7.14.4       getprojectstructure       278	7.12.15		
7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       27         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 loadreport       27         7.13.4 deletereport       27         7.13.5 analyzeSQLselect       27         7.13.6 showpiechart       27         7.13.7 showcolumnchart       27         7.13.8 showareachart       27         7.13.9 showtimelinechart       27         7.14.1 createproject API Functions       27         7.14.1 createproject       27         7.14.2 editproject       27         7.14.3 deleteproject       27         7.14.4 getprojectstructure       27         7.14.5 showprojectrecord       27	7.12.17 insertcontent       268         7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278			
7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       272         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       274         7.13.10 showgeolocationchart       275         7.14 Project API Functions       275         7.14.1 createproject       275         7.14.2 editproject       275         7.14.3 deleteproject       275         7.14.4 getprojectstructure       276         7.14.5 showprojectrecord       276	7.12.18 inserticontent       269         7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278		•	
7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       272         7.13.2 editreport       272         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       274         7.13.10 showgeolocationchart       275         7.14 Project API Functions       275         7.14.1 createproject       275         7.14.2 editproject       275         7.14.3 deleteproject       275         7.14.4 getprojectstructure       276         7.14.5 showprojectrecord       276	7.12.19 addcontent       269         7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278			
7.12.20 addicontent       276         7.13 Report API Functions       277         7.13.1 createreport       277         7.13.2 editreport       277         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       275         7.14 Project API Functions       276         7.14.1 createproject       277         7.14.2 editproject       276         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278         7.14.5 showprojectrecord       278	7.12.20 addicontent       270         7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       275         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278			
7.13 Report API Functions       27         7.13.1 createreport       27         7.13.2 editreport       27         7.13.3 loadreport       27         7.13.4 deletereport       27         7.13.5 analyzeSQLselect       27         7.13.6 showpiechart       27         7.13.7 showcolumnchart       27         7.13.8 showareachart       27         7.13.9 showtimelinechart       27         7.13.10 showgeolocationchart       27         7.14 Project API Functions       27         7.14.1 createproject       27         7.14.2 editproject       27         7.14.3 deleteproject       27         7.14.4 getprojectstructure       27         7.14.5 showprojectrecord       27	7.13 Report API Functions       271         7.13.1 createreport       271         7.13.2 editreport       271         7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       275         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278			
7.13.1       createreport       27         7.13.2       editreport       27         7.13.3       loadreport       27         7.13.4       deletereport       27         7.13.5       analyzeSQLselect       27         7.13.6       showpiechart       27         7.13.7       showcolumnchart       27         7.13.8       showareachart       27         7.13.9       showtimelinechart       27         7.13.10       showgeolocationchart       27         7.14       Project API Functions       27         7.14.1       createproject       27         7.14.2       editproject       27         7.14.3       deleteproject       27         7.14.4       getprojectstructure       27         7.14.5       showprojectrecord       27	7.13.1       createreport       271         7.13.2       editreport       272         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278			
7.13.2       editreport       27         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.13.2       editreport       271         7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278	•		
7.13.3       loadreport       272         7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       275         7.14       Project API Functions       275         7.14.1       createproject       275         7.14.2       editproject       275         7.14.3       deleteproject       275         7.14.4       getprojectstructure       276         7.14.5       showprojectrecord       278	7.13.3 loadreport       272         7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278		·	
7.13.4       deletereport       272         7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       276         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.13.4 deletereport       272         7.13.5 analyzeSQLselect       273         7.13.6 showpiechart       273         7.13.7 showcolumnchart       274         7.13.8 showareachart       274         7.13.9 showtimelinechart       275         7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278		·	
7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       278         7.14.3       deleteprojectstructure       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.13.5       analyzeSQLselect       273         7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278		·	
7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       278         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.13.6       showpiechart       273         7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278		•	
7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       278         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.13.7       showcolumnchart       274         7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278		<u> </u>	
7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       278         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.13.8       showareachart       274         7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278			
7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       278         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.13.9       showtimelinechart       275         7.13.10       showgeolocationchart       276         7.14       Project API Functions       277         7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278			
7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       278         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278         7.14.5 showprojectrecord       279	7.13.10 showgeolocationchart       276         7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278	7.13.8	showareachart	. 274
7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278         7.14.5 showprojectrecord       278	7.14 Project API Functions       277         7.14.1 createproject       277         7.14.2 editproject       277         7.14.3 deleteproject       278         7.14.4 getprojectstructure       278	7.13.9		
7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       278	7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278			
7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       278	7.14.1       createproject       277         7.14.2       editproject       277         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278	7.14 Proje	ct API Functions	.277
7.14.2       editproject       27         7.14.3       deleteproject       278         7.14.4       getprojectstructure       278         7.14.5       showprojectrecord       279	7.14.2editproject2777.14.3deleteproject2787.14.4getprojectstructure278			
7.14.3deleteproject2787.14.4getprojectstructure2787.14.5showprojectrecord279	7.14.3deleteproject2787.14.4getprojectstructure278	7.14.2		
7.14.4getprojectstructure2787.14.5showprojectrecord279	7.14.4 getprojectstructure278			
7.14.5 showprojectrecord279	5 1 <b>5</b>			
1 3	- I - J			
7 , 1 T.O SHOWALITURIAL L.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	7.14.6 showganttchart			
5	7.15 Task API Functions			

	7.15.1	createtask	280
	7.15.2	edittask	281
	7.15.3	deletetask	281
	7.15.4	tasknotification	282
	7.16 W	orkflow API Functions	282
	7.16.1	deleteworkflow	282
	7.16.2	buildworkflow	283
	7.16.3	workflowaccept	283
	7.16.4	acceptobject	283
	7.16.5	workflowreject	284
	7.16.6	rejectobjectrejectobject	285
	7.17 Cl	oud Storage API Functions	285
	7.17.1	loadcloudobject	
	7.17.2	savecloudobject	286
	7.17.3	copycloudobject	286
	7.17.4	renamecloudobject	287
	7.17.5	deletecloudobject	287
	7.17.6	synccloudobjects	288
	7.17.7	GCanalyzevideo	
	7.17.8	GCanalyzeimage	289
	7.17.9	GCspeech2text	
	7.18 In	nport/Export API Functions	290
	7.18.1	exportobjects	290
	7.18.2	importobjects	
	7.18.3	importmediafiles	
	7.18.4	importxmlfiles	
	7.18.5	calculatedate	292
	7.18.6	exportxmlfiles	
8	Rechtli	che Hinweise / Impressum	
		agen und Anregungen	
		npressum	
		echtliche Hinweise	

# 1 Einleitung

Die folgenden Kapitel behandeln die Funktionsbibliotheken des hyper Content & Digital Asset Management Servers und stellen somit die Dokumentation des API (Application Programming Interface) dar.

Alle Bibliotheken befinden sich innerhalb der hyperCMS Installation im Ordner "function" und können in die jeweiligen Scripts bzw. Templates eingebunden und genutzt werden. Damit lassen sich z.B. auch dynamische Seiten (Applikationen) unter Einsatz des XML-Content-Repository programmieren.

Sollten Sie Ihre Applikation auf einen physisch getrennten Server betreiben, so ist es wichtig, dass die Funktionsbibliotheken auch auf dem Publikationsserver zur Verfügung stehen. In diesem Fall ist es wichtig, dass die entsprechenden Dateien auch am Publikationsserver zur Verfügung stehen.

# 2 hyperCMS XML-Content-Repository

Das XML-Content-Repository beinhaltet alle XML-Content-Container und stellt somit alle Inhalte native XML zur Verfügung. Die Struktur (Schema) innerhalb eines XML-Content-Containers wird auf Basis des verwendeten Templates dynamisch erzeugt und besitzt folgendes Aussehen:

```
<?xml version="1.0" encoding="UTF-8" ?>
<container>
 <hyperCMS>
  <contentcontainer>0000023.xml</contentcontainer>
  <contentxmlschema>object/page</contentxmlschema>
  <contentorigin>%page%/Publication/testpage.php</contentorigin>
  <contentobjects>%page%/Publication/testpage.php|%page%/ Publication/linkedcopy_of_testpage.php
|</contentobjects>
  <contentuser>demouser</contentuser>
  <contentcreated>2002-12-01 10:02:40</contentcreated>
  <contentdate>2004-11-26 14:32:33</contentdate>
  <contentpublished>2004-11-26 14:39:41</contentpublished>
 <contentstatus>active</contentstatus>
 </hyperCMS>
 <head>
  <pagetitle>test</pagetitle>
  <pageauthor>Mr. Content</pageauthor>
  <pagedescription>just a small demonstration</pagedescription>
  <pagekeywords>demo of XML</pagekeywords>
  <pagecontenttype>text/html; charset=UTF-8</pagecontenttype>
  <pagelanguage>de</pagelanguage>
  <pagerevisit></pagerevisit>
 </head>
 <textcollection>
  <text>
   <text_id>headline</text_id>
   <textuser>demouser</textuser>
   <textcontent>fqfdqfdq</textcontent>
  </text>
  <text>
   <text_id>summary</text_id>
   <textuser>demouser</textuser>
   <textcontent><![CDATA[This is a
   <STRONG><EM>summary</EM></STRONG>]]></textcontent>
  </text>
 </textcollection>
 <mediacollection>
  <media>
   <media_id>logo</media_id>
   <mediauser>otheruser</mediauser>
   <mediafile>Publication/demo_hcms0000033.jpg</mediafile>
   <mediaobject>%page%/Publication/Multimedia/demo.jpg</mediaobject>
   <mediaalttext>demoimage</mediaalttext>
```

```
<mediaalign></mediaalign>
    <mediawidth>200</mediawidth>
    <mediaheight>100</mediaheight>
  </media>
 </mediacollection>
 kcollection>
  k>
    link_id>verweis</link_id>
    <linkuser>demouser</linkuser>
    <linkhref>http://localhost/index.php</linkhref>
    <linktarget>_blank</linktarget>
    linktext>click me</linktext>
  </link>
 </linkcollection>
 <componentcollection>
  <component>
    <component_id>teasers</component_id>
    <componentuser>otheruser</componentuser>
    <componentcond>$customer == "private"</componentcond>
    <componentfiles>%comp%/Publication/teaser_1.php|%comp%/Publication/teaser_2.php|</componentfiles>
   </component>
  <component>
    <component_id>banner</component_id>
    <componentuser>demouser</componentuser>
    <componentcond></componentcond>
    <componentfiles>%comp%/banner.php</componentfiles>
  </component>
 </componentcollection>
 <articlecollection>
  <article>
    <article_id>news</article_id>
    <articletitle>Top News</articletitle>
    <articledatefrom>2002-10-01</articledatefrom>
    <articledateto>2002-11-01</articledateto>
    <articlestatus>active</articlestatus>
    <articleuser>demouser</articleuser>
    <articletextcollection>
     <text>
      <text id>news:headline</text id>
      <textuser>demouser</textuser>
      <textcontent>News from Scene</textcontent>
     </text>
    </articletextcollection>
    <articlemediacollection>
    </articlemediacollection>
    <articlelinkcollection>
    </articlelinkcollection>
    <articlecomponentcollection>
    </articlecomponentcollection>
  </article>
  <article>
    <article id>special</article id>
    <articletitle>Special Info</articletitle>
    <articledatefrom>2002-01-01</articledatefrom>
    <articledateto>2002-01-01</articledateto>
    <articlestatus>inactive</articlestatus>
    <articleuser>otheruser</articleuser>
    <articletextcollection>
     <text>
      <text_id>special:informations</text_id>
      <textuser>otheruser</textuser>
      <textcontent><![CDATA[<STRONG><FONT color=#cc0033>What is really going on behind the
Scene</FONT></STRONG>... find it out]]></textcontent>
     </text>
    </articletextcollection>
    <articlemediacollection>
    </articlemediacollection>
    <articlelinkcollection>
    </articlelinkcollection>
    <articlecomponentcollection>
    </articlecomponentcollection>
  </article>
 </articlecollection>
</container>
```

Nach Durchsicht des Content Containers ist eine Struktur zu erkennen, die sich aus den folgenden wesentlichen Grundelementen für die Content-Ablage zusammensetzt:

- hyperCMS spezifische Informationen
- Meta-Informationen
- Text
- Medien (Bilder oder andere Multimedia-Dateien)
- Links
- Komponenten
- Artikel

Der gesamte Inhalt setzt sich aus diesem Grundbausteinen zusammen, deren Informationen wiederum innerhalb von XML-Tags abgelegt werden.

Artikel nehmen so wiederum die Elemente Text, Medien und Links in sich auf. Der gesamte Inhalt einer Seite oder Komponente lässt sich über den zugehörigen Content-Container beziehen.

# 2.1 hyperCMS spezifische Informationen

Die in diesem XML-Knoten erfassten Daten stellen primär für das Management des Containers relevante Informationen dar.

<hvperCMS>

<contentcontainer>0000023.xml</contentcontainer>

- <contentxmlschema>object/page</contentxmlschema>
- <contentorigin>%page%/testpage.php</contentorigin>
- <contentobjects>%page%/testpage.php|%page%/linkedcopy\_of\_testpage.php |</contentobjects>
- <contentuser>demouser</contentuser>
- <contentdate>2002-11-26</contentdate>
- <contentpublished>2002-11-26</contentpublished>
- <contentstatus>active</contentstatus>
- </hyperCMS>

#### Erklärung:

contentcontainer contentxmlschema contentorigin Name des Content Containers (einmalig über alle Publikationen) Schema des Objektes: Seite = page oder Komponente = comp Objekt (Seite oder Komponente) die zur Generierung des Content

Containers führte

contentobjects Alle Objekte die diesen Content Container benutzen

contentuser Objekteigentümer

contentdate Datum der letzten Änderung des Containers

contentpublished Datum der letzten Publizierung eines Objektes basierend auf den

**Content Container** 

contentstatus Der Status ist "active" solange ein Objekt das auf den Container basiert

existiert. Wurden alle Objekte die auf den Container basieren entfernt wird der Status "deleted" gesetzt. Der Container beinhaltet damit den letzten Informationsstand, kann jedoch nicht mehr genutzt werden.

# 2.2 Meta-Informationen

Die Standard Meta-Informationen einer HTML-Seite werden in diesem XML-Knoten beschrieben.

```
<head>
  <pagetitle>test</pagetitle>
  <pageauthor>Mr. Content</pageauthor>
  <pagedescription>just a small demonstration</pagedescription>
  <pagekeywords>demo of XML</pagekeywords>
  <pagecontenttype>text/html; charset=UTF-8</pagecontenttype>
  <pagelanguage>de</pagelanguage>
  <pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevisit></pagerevis
```

# Erklärung:

pagetitle Seitentitel pageauthor Seitenautor

pagedescription Beschreibung der Inhalte der Seite pagekeywords Liste der Schlüsselwörter der Seite

pagecontenttype Content-Type (Zeichensatz) der Seite oder Komponente

pagelanguage Sprachkürzel der Seite

pagerevisit Wiederbesuch der Seite durch Suchmaschinen

# 2.3 Text

Diese XML-Knoten speichern den Text.

```
<text>
<text_id>headline</text_id>
<textuser>demouser</textuser>
<textcontent>fgfdgfdg</textcontent>
</text>
```

# Erklärung:

text\_id Textidentifikation

textuser Texteigentümer (letzte Änderung des Textes durch einen Benutzer)

textcontent Inhalt des Textes

# 2.4 Medien

Dieser XML-Knoten beschreibt eingebunden Medien.

```
<media>
<media_id>logo</media_id>
<media_id>logo</media_id>
<mediauser>otheruser</mediauser>
<mediaile>Publication/demo_hcms0000033.jpg</mediafile>
<mediaobject>%page%/Publication/Multimedia/demo.jpg</mediaobject>
<mediaalttext>demoimage</mediaalttext>
<mediaalign></mediaalign>
<mediawidth>200</mediawidth>
<mediaheight>100</mediaheight>
</media>
```

Erklärung:

media\_id Medienidentifikation

mediauser Medieneigentümer (letzte Änderung des Mediums durch einen Benutzer)

mediafile eingebunden Mediendatei mit Angabe der Publikation

mediaobject Pfadangabe zur Multimediakomponente

mediaalttext Alternativtext des Mediums mediaalign Ausrichtung des Mediums

medawidth Dargestellte Breite des Mediums mediaheight Dargestellte Höhe des Mediums

# 2.5 Links

Dieser XML-Knoten beschreibt die Verlinkung zu Seiten.

# Erklärung:

link id Linkidentifikation

linkuser Linkeigentümer (letzte Änderung des Links durch einen Benutzer)

linkhref Referenz (Link) zu einer Seite oder Datei linktarget Ziel des Referenzierung (Name des Frames)

linktext Text der den Link beschreibt/darstellt

# 2.6 Komponenten

Dieser XML-Knoten beschreibt die Verlinkung zu Komponenten.

```
<component>
  <component_id>teasers</component_id>
  <componentuser>otheruser</componentuser>
  <componentcond>$customer == "private"</componentcond>
  <componentfiles>%comp%/teaser_1.php|%comp%/teaser_2.php|</componentfiles>
</component>
```

#### Erklärung:

component\_id Komponentenidentifikation

componentuser Komponenteneigentümer (letzte Änderung der Komponentenreferzierung

durch einen Benutzer)

componentcond Zugeordnetes Kundenprofil zu der Komponente

componentfiles Referenz (Komponenten-Link) zu einer oder mehreren Komponenten

# 2.7 Artikel

Dieser XML-Knoten beschreibt die Artikelinformation.

```
<article>
<article_id>news</article_id>
<article_id>news</articletitle>
<articletitle>Top News</articletitle>
<articledatefrom>2002-10-01</articledatefrom>
<articledateto>2002-11-01</articledateto>
<articlestatus>active</articlestatus>
<articleuser>demouser</articleuser>
<articletextcollection>
</articletextcollection>
</article>
```

# Erklärung:

article\_id Artikelnidentifikation articletitle Titel des Artikels

articeldatefrom Beginn der Veröffentlichung des Artikels articeldateto Ende der Veröffentlichung des Artikels

articlestatus Bestimmung der Veröffentlichung des Artikels:

active = immer veröffentlicht inactive = nicht veröffenlicht

timeswitched = zeitgesteuerte Veröffentlichung

articleuser Artikeleigentümer (letzte Änderung des Artikels durch einen Benutzer)

articlecollection Umfasst alle dem Artikel zugeordneten Inhalte

# 3 Funktionshibliotheken

# 3.1 Einbindung einer Bibliothek

Das Einbinden einer Konfiguratzion oder Bibliothek setzt voraus, dass man den absoluten oder relativen Pfad zur Bibliothek kennt. Durch Verwendung der Funktion "require" oder "require\_once" und der Angabe des Pfades inklusive der einzubinden Datei werden die enthaltenen Funktionen der Bilbliothek eingebunden. Sobald die Bibliothek eingebunden ist, können deren Funktionen im Script genutzt werden.

Um die hyperCMS-Funktionen nutzen zu können, bedarf es der Einbindung der Datei "hypercms\_api.inc.php". Diese Datei beinhaltet alle für die Programmierung benötigten Funktionen.

```
// absolute Angabe unter MS Windows
require_once ("C:/inetpub/wwwroot/hypercms/function/hypercms_api.inc.php");
// relative Angabe unter MS Windows oder auch UNIX-Derivaten
require_once ("function/hypercms_api.inc.php");
```

# 3.2 Laden der Konfiguration

# 3.2.1 Content Management Server

Um die Konfiguration von hyperCMS nutzen zu können muss die entsprechende Datei geladen warden. Diese beinhaltet alle wesentlichen Einstellungen des zu behandelnden Mandanten (Site).

Mit Hilfe der Identifikation einer Publikation, z.B. mit der Variable \$site kann die Konfiguration einer Publikation geladen werden. Die hyperCMS Hauptkonfigurationsatei befindet sich im Verzeichnis "hypercms/config" und trägt den Namen "config.inc.php". Die publikationsspezifischen Konfigurationsateien befinden sich im Verzeichnis "data/config". Deren Dateiname setzt sich aus dem Namen der Publikation sowie der Endung ".inc.php" zusammen, Bsp: site.inc.php.

```
// Einbinden der Hauptkonfigurationsatei (auf Pfadangabe ist zu achten):
require_once ("C:/inetpub/wwwroot/hypercms/config.inc.php");

// Einbinden Konfiguration einer Publikation
// Achtung: Bitte verwenden Sie valid_publicationname, um den Namen zu verifizieren, bevor
// Sie die Datei einbinden
if (valid_publicationname ($site))
{
    require_once ($mgmt_config['abs_path_data']."config/".$site.".conf.php");
}
```

Die Config-Dateien können geöffnet und gelesen werden. Jeder Parameter wird darin beschrieben und steht für die Nutzung in Programmen zur Verfügung. Bitte werfen Sie daher einen Blick in die Konfiguration, um mehr über die Parameter und deren Namen zu erfahren.

Es ist auch notwendig eine Sprache zu wählen. Hierfür dient die Variabel \$lang. \$lang beinhaltet das Sprachkürzel, welche in der Konfiguration "hypercms/config/config.inc.php" eingesehen werden können.

```
// Setzen der Spracheinstellung für Nachrichten von Funktionen, Deutsch (de) $lang = "de";
```

Da Sie die Funktionen des hyper API benutzen möchten, müssen Sie auch noch dieses einbinden.

```
// Einbinden der Funktionsbibliothek: require_once ($mgmt_config['abs_path_cms']."/function/hypercms_api.inc.php");
```

Nun können Sie die Funktionen des APIO nutzen, um z.B. einen Content Container einer bestimmtes Objektes über unterschiedliche Methoden zu laden:

```
// Laden der Seite

$pagedata = loadfile ("%page%/MyPublication/home/", "index.php");

// Content Container Name auslesen

$contentcontainer = filepointer ($pagedata, "content");

// Laden des veröffentlichten Content Container aus dem Content Repository

$containerdata = loadcontainer ($contentcontainer, "published", $user);

// Oder noch einfacher direkt über den Objektpfad

$containerdata = getobjectcontainer ("MyPublication", "%page%/MyPublication/home/",

"index.php", $user);
```

Funktionen laden die Konfiguration einer Publikatzion, sollte diese nicht verfügbar sein. Da viele Funktionen die Einstellungen einer Publikation benötigen, ist es ratsam die Konfiguration immer einzubinden.

# 3.2.2 Publication Server

Beachten Sie, dass die Konfiguration des Publication Servers (Publikationsziel) davon getrennt in einer INI-Datei abgelegt ist. Benötigen Sie die Publikationziel-Einstellungen, so müssen Sie die INI-Datei laden und parsen. Danach stehen Ihnen die Variablen in einem Array zur Verfügung.

Die INI-Datei des Publikationszieles befindet sich im externen Repository im Verzeichnis "repository/config". Der Name der Datei entspricht dem Namen der Publikation mit der Dateierweiterung ".ini".

```
// laden und parsen der INI-Datei mit hilfe von PHP
$publ_config = parse_ini_file ("C:/inetpub/wwwroot/repository/config/Mandant_1.ini");
// Zugreifen auf die Variablen des Publikationszieles
echo "Das ist der Document Root der Seiten der Publikation: ".$publ_config[abs_publ_page];
```

# 3.3 Globale Variablen

Viele Funktionen nutzen globale Variablen die in der Konfiguration gespeichert sind und den Funktionen zur Verfügung stehen. Sie sollten daher bei der Wahl der Variablennamen in Ihren eigenen Scripts acht geben, dass Sie nicht die von hyperCMS genutzen globalen Variablen verwenden.

Die folgende Liste zeigt alle globalen Variablen von hyperCMS, die nicht in eigenen Scripts manipuliert/verändert werden dürfen:

```
$mgmt_config
$lang
$lang_name
$lang_shortcut
$lang_codepage
$lang_shortcut_default
```

Viele globale Variablen von hyperCMS sind für die Verwendung in hyperCMS-Scripts und PHP-Scripts nützlich, diese stehen nur dann zur Verfügung, wenn die entsprechende Konfiguration zuvor geladen wurde, oder eine hyperCMS-Script (wird nur während des Publikationsprozesses ausgeführt) in Verwendung ist. Da dies bei der Voransicht als auch beim Publizieren von Seiten und Komponenten passiert, können diese Variablen in hyperCMS-Scripts genutzt werden. Bei dynamischen Applikationen, die bei jedem Aufruf der Seite oder Komponente durch einen Besucher ausgeführt werden, muss die Konfiguration direkt im Template eingebunden werden, sofern Variablen von hyperCMS benötigt werden.

## **Content Management Server:**

**\$lang** Sprachkürzel It. config.inc.php

**\$mgmt\_config[**'url\_path\_cms'] URL des hyperCMS Root Verzeichnis It. config.inc.php **mgmt\_config[**'abs\_path\_cms'] absoluter Pfad zum hyperCMS Root Verzeichnis It.

config.inc.php

**\$mgmt\_config[**'url\_path\_page'**]** URL des Doc Roots der Publikation im Managementsystem

**\$mgmt\_config[**'abs\_path\_page'**]** absoluter Pfad zum Doc Roots der Publikation im

Managementsystem

**\$mgmt\_config[**'url\_path\_comp'**]** URL des Komponenten Root der Publikation im

Managementsystem

mgmt\_config['abs\_path\_comp'] absoluter Pfad zum Komponenten Roots der Publikation im

Managementsystem

#### **Publication Server:**

hyperCMS-Scripts können die Variablen ohne weiteres zutun nutzen. Die Werte werden im Array \$publ\_config gespeichert, sind aber auch optional auch ohne Array nutzbar. Wird das Script/Anwendung bei jedem publikationsseitigen Aufruf ausgeführt, so ist die Konfigurationsdatei gesondert zu laden.

**\$publ\_config[**'url\_publ\_page'**]** URL des Doc Roots der Publikation im Publikationssystem

**\$publ\_config[**'abs\_publ\_page'**]** absoluter Pfad zum Doc Roots der Publikation im

Publikationssystem

**\$publ\_config**['url\_publ\_comp'] URL des Komponenten Roots der Publikation im

Publikationssystem

**\$publ\_config[**'abs\_publ\_comp'**]** absoluter Pfad zum Komponenten Roots der Publikation im

Publikationssystem

Optional (veraltet):

**\$url\_publ\_page** URL des Doc Roots der Publikation im Publikationssystem

**\$abs\_publ\_page** absoluter Pfad zum Doc Roots der Publikation im

Publikationssystem

**\$url\_publ\_comp**URL des Komponenten Roots der Publikation im

Publikationssystem

\$abs\_publ\_comp absoluter Pfad zum Komponenten Roots der Publikation im

Publikationssystem

# 3.4 Vorlagenvariablen

Es gibt auch die Möglichkeit mit hyperCMS-eigenen Vorlagenvariablen zu arbeiten. Diese Variablen stellen eine Besonderheit dar, da sie nicht mit hyperCMS-Script in Verbindung stehen müssen. Sie sind vielmehr Platzhalter für den Wert einer Variable und können in Vorlagen beliebig eingesetzt werden.

Diese neutrale Form der Variablen sollte primär in Templates Verwendung finden, da damit ein technologieneutraler Einsatz stattfinden kann.

Achten Sie bitte auf die Kleinschreibung aller Variablen!

**%container%** steht für den Namen des Content Containers eines Objektes.

%container\_id% steht für die ID des Content Containers eines Objektes.

%objecthash% steht für den Hash eines Objektes %object\_id% steht für die ID eines Objektes

**%template**% steht für den Dateinamen der verwendeten Vorlage des Objektes.

**%publication%** steht für die Publikation in dem sich das Objekte befindet.

**%url\_location%** steht für die absolute Pfadangabe (URL) der Position an dem sich das

aktuelle Objekt befindet.

%abs\_location% steht für die absolute Pfadangabe im Dateisystem der Position an dem

sich das aktuelle Objekt befindet

**%object%** steht für den Namen des Objektes.

**%date%** beschreibt das aktuelle Datum im Format JJJJ-MM-TT.

**%view%** beschreibt den Anzeigemodus:

publish ... publiziert

cmsview ... Bearbeitungsansicht im EasyEdit Modus

preview ... Voransicht

formedit ... Bearbeitunsgsmodus in Formularansicht formlock ... Formularansicht mit gesperrter Bearbeitung

formmeta ... Metadaten in Formularansicht

template ... Template-Voransicht

Für die Einbindung von Mediendateien wird eine Pfadvariable benutzt. Diese Pfadvariable wird beim Publizieren der Seite oder Komponente z.B. durch die URL (Adresse) der Konfiguration des Publikationszieles ersetzt:

%tplmedia% steht für die absolute Pfadangabe (URL) des Vorlagen Medien

Repository.

%url\_media% steht für die absolute Pfadangabe (URL) des Content Medien Repository

(Alternativ kann auch %media% verwendet werden)

%abs\_media% steht für die absolute Pfadangabe im Dateisystem des Content Medien

Repository.

Auch die publikationsseitigen Wurzelverzeischnisse der Seiten und Komponenten lassen sich abrufen:

%url\_page% steht für die absolute Pfadangabe (URL) des Seiten-

Wurzelverzeichnisses.

%abs\_page% steht für die absolute Pfadangabe im Dateisystem des Seiten-

Wurzelverzeichnisses.

%url\_comp% steht für die absolute Pfadangabe (URL) des Komponenten-

Wurzelverzeichnisses.

%abs\_comp% steht für die absolute Pfadangabe im Dateisystem des Komponenten-

Wurzelverzeichnisses.

%url\_rep% steht für die absolute Pfadangabe (URL) des externen Repository-

Wurzelverzeichnisses.

%abs\_rep% steht für die absolute Pfadangabe im Dateisystem des externen

Repository-Wurzelverzeichnisses.

%url\_hypercms% steht für die absolute Pfadangabe (URL) des hyperCMS-

Wurzelverzeichnisses.

%abs\_ hypercms% steht für die absolute Pfadangabe im Dateisystem des hyperCMS-

Wurzelverzeichnisses.

Achten Sie darauf "/" am Ende der Pfadvariable zu ergänzen, wenn die Variable durch einen weiterführenden Pfad ergänzt werden soll.

# Definition des Datumsformats bei Verwendung des format-Attributes im textd-Tag:

```
%a
      'am' oder 'pm'
      'AM' oder 'PM'
%A
%d
      Tag des Monats, 2 Stellen mit führender Null (01 bis 31)
%D
      Wochentag als Text in Kurzform, z.B. "Fre"
%F
      Monat als Text in Langform, z.B. "Januar"
%h
      Stunde, 12-Stunden Format (01 bis 12)
%Н
      Stunde, 24-Stunden Format (00 bis 23)
%g
      Stunde, 12-Stunden Format ohne führender Null (1 bis 12)
%G
      Stunde, 24-Stunden Format ohne führender Null (0 bis 23)
%i
      Minuten (00 bis 59)
      Tag des Monats ohne führender Null (1 bis 31)
%i
      Wochentag als Text in Langform, z.B. "Freitag"
%I
%L
      1 falls Schaltjahr, sonst - 0
%m
      Monat (01 bis 12)
%n
      Monat ohne führender Null (1 bis 12)
%M
      Monat als Text in Kurzform, z.B. "Jan"
%s
      Sekonden (00 bis 59)
      Anzahl der Tage im Monat (28 bis 31)
%t
%w
      Wochentag numerisch (0, Sonntag bis 6, Samstag)
      Jahr, 4-stellig, z.B. "2007"
%Y
      Jahr, 2-stellig, z.B. "07"
%у
%z
      Tag des Jahres (1 bis 366)
```

In Zusammenhang mit der Nutzung des hyperCMS APIs ist es oft ratsam, bei Pfadangaben die Platzhalter %page% und %comp% zu nutzen. Diese Pfadvariablen lassen sich nur managementseitig nutzen, sie stehen für die Pfade zu den Wurzelverzeischnissen von Seiten und Komponenten.

Zu beachten ist, dass die Variable immer gepaart mit dem Publikationsnamen das Wurzelverzeichnis bildet, z.B:

%page%/%publication%/ .... Wurzelverzeichnis der Seiten der aktuellen Publikation

**%page%/Publikationsname/** steht für die absolute Pfadangabe des Seiten-Wurzelverzeichnisses.

**%comp%/Publikationsname/** steht für die absolute Pfadangabe des Komponenten - Wurzelverzeichnisses.

# 3.5 Bibliothek Object Operation

Diese Bibliothek beinhaltet alle Funktionen für die Manipulation von Objekten (Seiten, Komponenten oder Dateien). Bitte benutzen Sie ausschließlich diese Funktionen für den Zugriff auf Objekte, die das System verwaltet.

### 3.5.1 createfolder

## Syntax:

createfolder (\$site, \$location, \$foldernew, \$user)

#### Beschreibung:

Erzeugt einen neuen Ordner.

Bsp:

\$result = createfolder ("%publication%", "%page%/%publication%/", "company", "brown");

Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des neuen Ordners)

\$foldernew Name des neuen Ordners

\$user Benutzername

globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Konnte der neue Ordner angelegt werden)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[folder] Name des Ordners

### 3.5.2 deletefolder

#### Syntax:

deletefolder (\$site, \$location, \$folder, \$user)

## Beschreibung:

Entfernt einen bestehenden Ordner. Der Ordner wird nur dann entfernt, wenn er keine Objekte mehr beinhaltet. Alle Objekte müssen daher zuvor mit deleteobject entfernt werden.

Bsp

\$result = deletefolder ("%publication%", "%page%/%publication%/", "company", "brown");

## Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des neuen Ordners)

\$folder Name des zu entfernenden Ordners

\$user Benutzername

### globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

# Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Konnte der Ordner entfernt werden)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung \$result[folder] Name des bestehenden Ordners bei Misserfolg, ansonst leer

### 3.5.3 renamefolder

#### Syntax:

renamefolder (\$site, \$location, \$folder, \$foldernew, \$user)

# Beschreibung:

Benennt einen bestehenden Ordner um.

Bsp:

\$result = renamefolder ("%publication%", "%page%/%publication%/", "company", "news",
"brown");

# Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Ordners)

\$folder Alter Name des Ordners \$foldernew Neuer Name des Ordners

\$user Benutzername

# globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

# Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Konnte der Ordner umbenannt werden)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[folder] Name des Ordners

# 3.5.4 createobject

#### Syntax:

createobject (\$site, \$location, \$object, \$template, \$user)

#### Beschreibung:

Erzeugt eine neue Seite oder Komponente auf Basis einer Vorlage. Bitte beachten Sie das die Position (\$location) auch die Kategorie des Objektes (Seite/Komponente) bestimmt. Dies bedingt weiters, dass es sich beim Wert des Parameters \$template um eine gültige Seitenbzw. Komponentenvorlage handeln muss.

#### Bsp

\$result = createobject ("%publication%", "%page%/%publication%/", "index", "page\_main",
"Miller");

## Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Name des neuen Objektes (Seite oder Komponente)

\$template Name der zu verwendenden Seiten- oder Komponentenvorlage

(Name der Vorlage oder Dateiname)

\$user Benutzername

# globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

# Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

# 3.5.5 deleteobject

#### Syntax:

deleteobject (\$site, \$location, \$object, \$user)

#### Beschreibung:

Entfernt eine bestehende Seite, Datei oder Komponente.

Bsp:

\$result = deleteobject ("%publication%", "%page%/%publication%/", "sales.doc", "Miller");

Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Name des Objektes \$user Benutzername

## globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[publication] Name der Publikation bzw. Mandant in dem das Objekt existiert

\$result[location] absoluter Pfad im Filesystem (Position des Objektes)

# 3.5.6 renameobject

#### Syntax:

renameobject (\$site, \$location, \$object, \$objectnew, \$user)

### Beschreibung:

Umbenennen eine bestehender Seite, Datei oder Komponente.

Bsp:

\$result = renameobject ("%publication%", "%page%/%publication%/", "sales.doc",
"best.doc", "Miller");

## Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Alter Name des Objektes

\$objectnew Neuer Name des Objektes (ohne Dateiendung)

\$user Benutzername

## globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

Output:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[publication] Name der Publikation bzw. Mandant in dem das Objekt existiert

\$result[location] absoluter Pfad im Filesystem (Position des Objektes)

# 3.5.7 cutobject

# Syntax:

cutobject (\$site, \$location, \$object, \$user)

### Beschreibung:

Ausschneiden eine bestehender Seite, Datei oder Komponente.

Bsp:

\$result = cutobject ("%publication%", "%page%/%publication%/", "index.php", "Miller");

### Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Alter Name des Objektes

\$user Benutzername

# globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

### Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[object] Dateiname der Seite, Datei oder Komponente \$result[objectname] Name der Seite, Datei oder Komponente \$result[objecttype] Filetype bzw. File Extension der Datei

\$result[clipboard] temporärer Eintrag im Clipboard (kann als globale Variable

\$clipboard der Funktion pasteobject übergeben werden, diese muss somit keinen Lesezugriff auf die temporäre Datei ausführen)

# 3.5.8 copyobject

#### Syntax:

copyobject (\$site, \$location, \$object, \$user)

#### Beschreibung:

Kopieren eine bestehender Seite, Datei oder Komponente.

Bsp:

\$result = copyobject ("%publication%", "%page%/%publication%/", "index.php", "Miller");

Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Alter Name des Objektes

\$user Benutzername

## globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[object] Dateiname der Seite, Datei oder Komponente \$result[objectname] Name der Seite, Datei oder Komponente \$result[objecttype] Filetype bzw. File Extension der Datei

\$result[clipboard] temporärer Eintrag im Clipboard (kann als globale Variable

\$clipboard der Funktion pasteobject übergeben werden, diese muss somit keinen Lesezugriff auf die temporäre Datei ausführen)

# 3.5.9 copyconnectedobject

#### Syntax:

copyconnectedobject (\$site, \$location, \$object, \$user)

### Beschreibung:

Kopieren eine bestehender Seite, Datei oder Komponente auf Basis des gleichen Content Containers.

Bsp:

\$result = copyconnectedobject ("%publication%", "%page%/%publication%/", "index.php",
"Miller");

# Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Alter Name des Objektes

\$user Benutzername

## globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

#### Output:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[object] Dateiname der Seite, Datei oder Komponente \$result[objectname] Name der Seite, Datei oder Komponente \$result[objecttype] Filetype bzw. File Extension der Datei

\$result[clipboard] temporärer Eintrag im Clipboard (kann als globale Variable

\$clipboard der Funktion pasteobject übergeben werden, diese muss somit keinen Lesezugriff auf die temporäre Datei ausführen)

# 3.5.10 pasteobject

## Syntax:

pasteobject (\$site, \$location, \$user)

### Beschreibung:

Einfügen einer bestehender Seite, Datei oder Komponente.

Bsp:

\$result = pasteobject ("%publication%", "%page%/%publication%/", "Miller");

Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$user Benutzername

\$clipboard globale Varibale mit dem temporären Eintrag im Clipboard (Damit

ist ein Lesezugriff auf die temporäre Datei nicht notwendig.)

## globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

\$result[publication] Name der Publikation bzw. Mandant in dem das Objekt existiert

\$result[location] absoluter Pfad im Filesystem (Position des Objektes)

# 3.5.11 lockobject

#### Syntax:

lockobject (\$site, \$location, \$object, \$user)

#### Beschreibung:

Sperren einer oder mehrerer bestehender Seiten oder Komponenten die auf den gleichen Content Container beruhen für die exklusive Nutzung eines Benutzers.

Bsp

\$result = lockobject ("%publication%", "%page%/%publication%/", "index.php","Miller");

## Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Name des Objektes \$user Benutzername

### globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

#### **Output:**

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

# 3.5.12 unlockobject

#### Syntax:

unlockobject (\$site, \$location, \$object, \$user)

### Beschreibung:

Entsperren einer oder mehrerer bestehender Seiten oder Komponenten die auf den gleichen Content Container beruhen für die gemeinsame Nutzung durch alle Benutzer.

Bsp

\$result = unlockobject ("%publication%", "%page%/%publication%/", "index.php", "Miller");

## Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Name des Objektes \$user Benutzername

# globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

# Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

# 3.5.13 publishobject

#### Syntax:

publishobject (\$site, \$location, \$object, \$user)

### Beschreibung:

Publizieren einer Seite oder Komponente. Alle gebundenen Kopien des Objektes bzw. dessen Content Containers werden ebenfalls publiziert. Gestattet die Berechtigung eines im Einsatz befindlichen Workflows die Publizierung nicht, so wird das Objekt auch nicht publiziert.

Bsp:

\$result = publishobject ("%publication%", "%page%/%publication%/", "index.php", "Miller");

Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Name des Objektes \$user Benutzername

## globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

Output:

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

## 3.5.14 unpublishobject

#### Syntax:

unpublishobject (\$site, \$location, \$object, \$user)

#### Beschreibung:

Entpublizieren einer Seite oder Komponente. Link und Task Management werden automatisch ausgeführt. Alle gebundenen Kopien des Objektes bzw. dessen Content Containers werden ebenfalls entpubliziert.

Bsp:

\$result = unpublishobject ("%publication%", "%page%/%publication%/", "index.php",
"Miller");

#### Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Name des Objektes \$user Benutzername

## globale Input-Parameter:

Die folgenden globalen Input Parameter sind ebenfalls der Funktion zu übergeben: \$lang Spracheinstellung bzw. Sprachkürzel, z.B. "en", "de"

**Output:** 

Array \$result das folgende Informationen beinhaltet:

\$result[result] True/False (Erfolg der Aktion)

\$result[add\_onload] JavaScript Code für das onLoad Event

\$result[message] Nachricht über den Erfolg der Aktion bzw. Fehlermeldung

## 3.5.15 getlinkedobject

#### Syntax:

getlinkedobject (\$site, \$location, \$object, \$cat)

#### Beschreibung:

Diese Funktion extrahiert alle Objekte, die auf das gegebene Objekt zeigen. Dies können Seiten-Links oder auch Komponenten-Links sein. Ist das übergebene Objekt eine Seite, so werden alle Objekte ermittelt die einen Seiten-Link auf das Objekt besitzen. Ist das übergebene Objekt eine Komponente, so werden alle Objekte gefunden die einen Komponenten-Link zu dem Objekt besitzen.

Bsp:

\$result = getlinkedobject ("%publication%", "%page%/%publication%/", "index.php",
"page");

Input-Parameter:

\$site Name der Publikation

\$location absoluter Pfad (Position des Objektes)

\$object Name des Objektes

\$cat optional: Objekt Kategorie [page, comp]

Output:

Array \$result das folgende Informationen beinhaltet:

\$result False (Aktion fehlgeschlagen)

\$result[publication] Name der Publikation bzw. Mandant in dem das Objekt existiert

\$result[location] absoluter Pfad im Filesystem (Position des Objektes)

\$result[object] Name des Objektes

\$result[category] Kategorie des Objektes [page, comp]

## 3.5.16 getconnectedobject

## Syntax:

getconnectedobject (\$site, \$container)

## Beschreibung:

Diese Funktion ermittelt alle Objekte, die auf dem gleichen Content Container basieren. Der Name des Content Containers eines Objektes kann mittels der Funktion "getfilename" ermittelt werden.

Bsp:

\$result = getconnectedobject ("%publication%", "0000127.xml");

Input-Parameter:

\$site Name der Publikation

\$container Name des Content Containers

**Output:** 

Array \$result das folgende Informationen beinhaltet:

\$result False (Aktion fehlgeschlagen)

\$result[publication] Name der Publikation bzw. Mandant in dem das Objekt existiert

\$result[location] absoluter Pfad im Filesystem (Position des Objektes)

\$result[object] Name des Objektes

\$result[category] Kategorie des Objektes [page, comp]

## 3.5.17 getobjectcontainer

#### Syntax:

getobjectcontainer (\$site, \$location, \$object, \$user)

#### Beschreibung:

Diese Funktion lädt den Content Container (XML-String) eines bestimmten Objektes. Das Objekt kann eine Seite, Datei, Komponente oder ein Ordner sein.

Die gewünschten Daten können mittels der Funktionen "getcontent" oder "selectcontent" aus dem XML-String ermittelt werden.

#### Bsp

```
$xmldata = getobjectcontainer ("%publication%", "%page%/%publication%/Home/",
"index.php", "demouser");
```

#### Input-Parameter:

\$site Name der Publikation

\$location Pfad im Filesystem (Position des Objektes)

\$object Name des Objektes \$user Benutzername

**Output:** 

XML-String Rückgabe des geladenen Content Containers

False Fehler aufgetreten

## 3.6 Bearbeiten von Inhalten

Die programmatische Bearbeitung der Inhalte eines Objektes wird anhand des folgenden Beispiels gezeigt. Zu beachten ist die Funktion settext, die dazu verwendet wird Texte eines Objektes zu manipulieren, für nähere Details siehe die Set API Funktionsbibliothek.

```
// load object file information
$objectinfo = getobjectinfo ("%publication%", "%page%/%publication%/Home/",
"index.php", "demouser", $container_version="");
// load content container (work status)
$contentdata = loadcontainer ($objectinfo['container_id'], "work", "demouser");
// set a new text
$text = array();
$type = array();
$textuser = array();
$text['Title'] = "My new title";
type[Title'] = u''
$textuser['Title'] = "demouser";
$text['Description'] = "My new description";
$type['Description'] = "f";
$textuser['Description'] = "demouser";
$containerdata = settext ("%publication%", $contentdata, $objectinfo['container'], $text,
$type, "no", $textuser, "demouser");
// save working xml content container file
if (!empty ($containerdata)) $result = savecontainer ($objectinfo['container id'], "work",
$containerdata, "demouser");
```

## 3.7 Bibliothek File Operation

Die folgenden Funktionen für File-Operationen sollten keinesfalls benutzt werden, um Objekte (Seiten, Komponenten oder Dateien) zu laden oder zu speichern.

Sie können diese Funktionen jedoch zum Laden und Speichern von XML-Content-Container verwenden, sollten Sie dies für die Entwicklung von Erweiterungen oder Anwendungen benötigen.

#### 3.7.1 loadfile

#### Syntax:

loadfile (\$abs\_path, \$filename)

## Beschreibung:

Mit hilde dieser Funktion können Dateien geladen werden. Es müssen der Absolutpfad, als auch der Dateiname selbst als Parameter übergeben werden. Die Funktion wartet bis zu 3 Sekunden lang beim Laden von gesperrten Dateien. Wird der User-Parameter \$user gesetzt, so kann die Funktion auch gesperrte Dateien des gegebenen Benutzers lesen.

Bsp

\$data = loadfile ("%page%/%publication%/home/", "index.php");

#### Input-Parameter:

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$filename Dateiname

**Output:** 

Dateinhalt Funktion wurde fehlerfrei ausgeführt und liefert den Inhalt der Datei

False Fehler aufgetreten

#### 3.7.2 savefile

#### Syntax:

savefile (\$abs\_path, \$filename, \$filedata)

#### Beschreibung:

Mit savefile werden Dateien gespeichert. Hierfür müssen der Absolutpfad, der gewünschte Dateiname, als auch der Inhalt, die in die Datei geschrieben werden soll als Parameter übergeben werden. Ist die Datei gesperrt, so wird nicht gespeichert und False retourniert.

Bsp:

\$result = savefile ("%page%/%publication%/home/", "index.php", "file content");

## Input-Parameter:

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$filename Dateiname

\$filedata Inhalt, der in die Datei geschrieben werden soll

Output:

True Funktion wurde fehlerfrei ausgeführt

#### 3.7.3 loadlockfile

#### Syntax:

loadlockfile (\$user, \$abs\_path, \$filename)

#### Beschreibung:

Damit können Dateien wie mit loadfile geladen werden, es wird aber zusätzlich ein Sperr-Mechanismus ausgelöst.

Diese Funktion sollte nur dann genutzt werden, wenn Daten manipuliert und wieder gespeichert werden sollen. Damit wird sichergestellt, dass keine anderen Schreibzugriffe eines anderen Users erfolgen können. Beim Speichern muss die Funktion "savelockfile" benutzt werden, um den Inhalt wieder freizugeben.

Es müssen der Benutzer, der absolute Pfad als auch der Dateiname selbst als Parameter übergeben werden.

Bsp

\$data = loadlockfile ("Miller", "%page%/%publication%/home/", "index.php");

#### Input-Parameter:

\$user Benutzer der die Datei sperrt

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$filename Dateiname

Output:

Dateinhalt Funktion wurde fehlerfrei ausgeführt und liefert den Inhalt der Datei

False Fehler aufgetreten

## 3.7.4 savelockfile

#### Syntax:

savelockfile (\$user, \$abs\_path, \$filename, \$filedata)

#### Beschreibung:

Mit savelockfile werden Dateien gespeichert und entsperrt, die vorher mit loadlockfile geöffnet wurden. Hierfür müssen der Benutzer, der Absolutpfad, der gewünschte Dateiname, als auch der Inhalt, die in die Datei geschrieben werden soll als Parameter übergeben werden.

Bsp:

savelockfile ("Miller", "%page%/%publication%/home/", "index.php", "file content");

#### Input-Parameter:

\$user Benutzer der die Datei sperrt

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$filename Dateiname

\$filedata Inhalt, der in die Datei geschrieben werden soll

Output:

True Funktion wurde fehlerfrei ausgeführt

#### 3.7.5 lockfile

#### Syntax:

lockfile (\$user, \$abs\_path, \$filename)

#### Beschreibung:

Mit lockfile werden Dateien von einem bestimmten Benutzer gesperrt und stehen für dessen exklusive Nutzung zur Verfügung. Hierfür müssen der Benutzer, der Absolutpfad, der gewünschte Dateiname als Parameter übergeben werden.

Bsp:

lockfile ("Miller", "%page%/myPublication/home/", "index.php");

### Input-Parameter:

\$user Benutzer der die Datei sperrt

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$filename Dateiname

Output:

True Funktion wurde fehlerfrei ausgeführt

False Fehler aufgetreten

#### 3.7.6 unlockfile

#### Syntax:

unlockfile (\$user, \$abs\_path, \$filename)

#### Beschreibung:

Mit unlockfile werden Dateien entsperrt, die vorher mit lockfile gesperrt oder mit loadlockfile geöffnet wurden. Hierfür müssen der Benutzer, der Absolutpfad, der gewünschte Dateiname als Parameter übergeben werden.

Bsp:

unlockfile ("Miller", "%page%/%publication%/home/", "index.php");

#### Input-Parameter:

\$user Benutzer der die Datei sperrt

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$filename Dateiname

Output:

True Funktion wurde fehlerfrei ausgeführt

#### 3.7.7 deletefile

#### Syntax:

deletefile (\$location, \$file, \$recursive)

#### Beschreibung:

Mit deletefile können Dateien und (leere) Ordner gelöscht werden. Es wird der Pfad der gewünschten Datei übergeben, der Dateiname, und ein Parameter "Rekursiv", der entweder (0) oder (1) beträgt. Wenn recursive 1 gesetzt wurde, wird der gesamte Inhalt des Ordners behandelt, also auch Unterverzeichnisse und deren Dateien, bei 0 werden nur die Dateien des angesprochenen Ordners (falls leer) entfernt.

#### Bsp:

deletefile ("%page%/%publication%/home/", "index.php", 0);

#### Input-Parameter:

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$file Dateiname

\$recursive 0 oder 1, je nachdem ob sich der Vorgang auch auf Unterverzeichnisse

auswirken soll

### Output:

True Funktion wurde fehlerfrei ausgeführt

False Fehler aufgetreten

## 3.7.8 appendfile

### Syntax:

append (\$abs\_path, \$filename, \$filedata)

### Beschreibung:

Mit appendfile können Inhalte an Dateien angefügt werden. Die Funktion arbeitet wie savefile, der Unterschied besteht allerdings darin, dass bereits vorhandene Daten nicht überschrieben, sondern ergänzt werden. Hierfür müssen der Absolutpfad, der gewünschte Dateiname, als auch der Inhalt, die in die Datei geschrieben werden soll als Parameter übergeben werden.

#### Bsp:

appendfile ("%page%/%publication%/home/", "index.php", "© 2003 ...");

#### Input-Parameter:

\$abs\_path absoluter Pfad zur gewünschten Datei, %page% und %comp% können in der

Pfadangabe verwendet werden

\$filename Dateiname

\$filedata Inhalt, der an die Datei angefügt werden soll

#### Output:

True Funktion wurde fehlerfrei ausgeführt

## 3.8 XML Bibliothek

Die folgenden Funktionen bieten Ihnen die Möglichkeit Inhalte aus XML-Content-Container zu lesen und zu schreiben. Sie können optional auch mit anderen Technologien, die mit XML umgehen können, die Inhalte der Container abfragen. Die Bibliothek Edit Content bietet Ihnen jedoch eine sehr einfache als auch performante Methode hierfür.

### 3.8.1 setxmlparameter

#### Syntax:

setxmlparameter (\$xmldata, \$parameter, \$value)

#### Beschreibung:

Setzt den Wert eines bestimmten Parameters innerhalb der XML-Deklaration (1.Zeile).

Bsp

\$xmldata = setxmlparameter (\$xmldata, "encoding", "UTF-8");

#### Input-Parameter:

\$xmldata XML-String der übergeben und manipuliert werden soll \$parameter Name des Parameter dessen Wert geändert werden soll

\$value Wert des Paramaters

Output:

XML-String Rückgabe des manipulierten XML-Strings

False Fehler aufgetreten

#### 3.8.2 getcontent

## Syntax:

getcontent (\$xmldata, \$tag)

## Beschreibung:

Holt den XML-Content aus dem Content Container, der sich innerhalb der Tags \$tag befindet. Ein Array mit allen gefundenen Inhalten bzw. Childs wird zurückgegeben und kann in einer Array-Variable gespeichert und weiterverwendet werden.

#### Bsp:

// hole alle text-childs aus Content Container
\$text\_array = getcontent (\$xmldata, "<text>");

// ausgeben aller Text-Childs
foreach (\$text\_array as \$text) echo \$text;

#### Input-Parameter:

\$xmldata XML-String der übergeben und durchsucht werden soll \$tag XML-Tag der die Information bzw. Childs umschliesst

Output:

Array Mrray mit allen gefunden Inhalten, der erste Wert/Inhalt kann mit Array[0]

angesprochen werden

## 3.8.3 getxmlcontent

#### Syntax:

getxmlcontent (\$xmldata, \$tag)

#### Beschreibung:

Holt den XML-Content aus dem Content Container, der sich innerhalb der Tags \$tag befindet und belässt im Unterschied zu getcontent die Tags im Rückgabewert (Array). Ein gesamter Node (well-formed) wird daher zurückgeliefert.

Ein Array mit allen gefundenen Inhalten bzw. Childs wird zurückgegeben und kann in einer Variable vom Typ Array gespeichert und weiterverwendet werden.

#### Bsp:

```
$text_array = getxmlcontent ($xmldata, "<text>");
foreach ($text_array as $text) echo $text;
```

#### Input-Parameter:

\$xmldata XML-String der übergeben und durchsucht werden soll \$tag XML-Tag der die Information bzw. Childs umschliesst

#### Output:

Array Marray mit allen gefunden Inhalten, der erste Wert/Inhalt kann mit Array[0]

angesprochen werden

False Fehler aufgetreten

#### 3.8.4 selectcontent

#### Syntax:

selectcontent (\$xmldata, \$parenttag, \$childtag, \$childvalue)

#### Beschreibung:

Holt jenen XML-Content bestimmt durch \$parenttag aus dem Content-Container, der innerhalb des Childtags \$childtag einen bestimmten Wert \$childvalue aufweist. Ein Array mit allen gefundenen Inhalten wird zurückgegeben und kann in einer Array-Variable gespeichert und weiterverwendet werden.

#### Bsp:

```
Auszug aus dem Content Container:
```

```
<text>
  <text_id>summary</text_id>
  <textuser>editor1</textuser>
  <textcontent>This is my summary!</textcontent>
  </text>

// hole alle Text-Childs mit der id=summary
$text_array = selectcontent ($xmldata, "<text>", "<text_id>", "summary");

// extrahiere das Summary aus dem gefundenen Inhalt
foreach ($text_array as $text)
{
  $summary = getcontent ($text, "<textcontent>");
}
```

#### Input-Parameter:

\$xmldata XML-String der übergeben und durchsucht werden soll \$parenttag XML-Tag der die Information bzw. das Child beinhaltet

\$childtag optional: XML-Tag der die Information umschliesst, die einen gewissen Wert

besitzen muss

\$childvalue optional: Wert der Bedingung, das WildCard Zeichen \* kann am Anfang

und/oder am Ende des Ausdruckes verwendet werden und ist Platzhalter für

beliebige weitere Zeichen.

Output:

Array Mrray mit allen gefunden Inhalten, der erste Wert/Inhalt kann mit Array[0]

angesprochen werden

False Fehler aufgetreten

#### 3.8.5 selectxmlcontent

#### Syntax:

selectxmlcontent (\$xmldata, \$parenttag, \$childtag, \$childvalue)

#### Beschreibung:

Holt jenen XML-Content definiert durch \$parenttag aus dem Content-Container, der innerhalb eines Childtags \$childtag einen bestimmten Wert \$childvalue aufweist. Im Unterschied zu getcontent werden die Parent-Tags im Rückgabewert (Array) belassen.

Ein Array mit allen gefundenen Inhalten wird zurückgegeben und kann in einer Array-Variable gespeichert und weiterverwendet werden.

#### Bsp:

```
Auszug aus dem Content Container:
```

```
<text>
    <text_id>summary</text_id>
    <textuser>editor1</textuser>
    <textcontent>This is my summary!</textcontent>
</text>

// hole alle Text-Childs mit der id=summary
$text_array = selectxmlcontent ($xmldata, "<text>", "<text_id>", "summary");

// extrahiere das Summary aus dem gefundenen Inhalt
foreach ($text_array as $text)
{
    $summary = getcontent ($text, "<textcontent>");
}
```

#### Input-Parameter:

\$xmldata XML-String der übergeben und durchsucht werden soll \$parenttag XML-Tag der die Information bzw. das Child beinhaltet

\$childtag optional: XML-Tag der die Information umschliesst, die einen gewissen Wert

besitzen muss

\$childvalue optional: Wert der Bedingung, das WildCard Zeichen \* kann am Anfang

und/oder am Ende des Ausdruckes verwendet werden und ist Platzhalter für

beliebige weitere Zeichen.

#### Output:

Array Array mit allen gefunden Inhalten, der erste Wert/Inhalt kann mit Array[0]

angesprochen werden

#### 3.8.6 deletecontent

#### Syntax:

deletecontent (\$xmldata, \$tagname, \$condtag, \$condvalue)

#### Beschreibung:

Löscht den gesamten XML-Content definiert durch den Tag \$tagname. Als Kriterium für die Auswahl der zu löschenden Childs wird das entsprechende XML-Childtag \$condtag und die umschlossene Information \$condvalue als Bedingung mitgeschickt.

#### Bsp:

Auszug aus dem Content Container:

```
<text>
  <text-id>bedingung</text_id>
  <textuser>editor1</textuser>
  <textcontent>This is my summary!</textcontent>
</text>
.....
```

\$xmldata = deletecontent (\$xmldata, "<text>", "<text\_id>", "bedingung");

### Input-Parameter:

\$xmldata XML-String der übergeben wird

\$parenttag XML-Tag der die Information bzw. Childs umschliesst, die aus dem

Content Container entfernt werden sollen

\$condtag optional: Name des Parameters (XML-Child) das der Bedingung

unterliegt

\$condvalue optional: Wert der Bedingung, die erfüllt werden muss

Output:

XML-String Rückgabe des manipulierten XML-Strings

## 3.8.8 setcontent

## Syntax:

setcontent (\$xmldata, \$parenttagname, \$tagname, \$contentnew, \$condtag, \$condvalue)

#### Beschreibung:

Ein XML-String wird übergeben und innerhalb eines bestimmten Parent Nodes (\$parenttagname) wird überprüft, ob ein bestimmter Parameter (\$condtag) existiert und einen bestimmter Wert (\$condvalue) aufweist. Ist die Bedingung erfüllt, wird der Wert des Parameters \$tagname durch einen neuen Wert \$contentnew ersetzt.

#### Bsp:

Auszug aus dem Content Container:

\$xmldata = setcontent (\$xmldata, "<text>", "<textcontent>", "This is my new value!",
"<text\_id>", "bedingung");

#### Input-Parameter:

\$xmldata XML-String der übergeben und modifiziert werden soll

\$parenttagname optional: XML-Parenttag

\$tagname optional: XML-Childtag, dessen Wert ersetzt werden soll (wenn

Bedingung erfüllt)

\$contentnew Neuer Wert für den XML-Childtag \$tagmame

\$condtag optional: Name des Parameters der die Bedingung erfüllen muss

\$condvalue optional: Wert des Parameters für die Bedingung

**Output:** 

XML-String Rückgabe des manipulierten XML-Strings

## 3.8.10 updatecontent

### Syntax:

updatecontent (\$xmldata, \$xmlnode, \$xmlnodenew)

#### Beschreibung:

Alle XML-String \$xmlnode wird durch einen neuen String \$xmlnodenew in \$xmldata ersetzt. Diese Methode ist schneller als setcontent, wenn der aktualisierende XML Node bereits aus dem Container extrahiert wurde.

### Bsp:

Auszug aus dem Content Container:

```
<text>
<text|id>bedingung</text_id>
<textuser>editor1</textuser>
<textcontent>This is old content!<textcontent>
</text>
</text>
```

\$xmldata = updatecontent (\$xmldata, "<textcontent>This is old content!<textcontent> ",
"<textcontent>This is my new content!<textcontent>");

### Input-Parameter:

\$xmldata XML-String der übergeben und modifiziert werden soll

\$xmlnode zu ersetzender XML-String (Node bzw. Substring von \$xmldata) \$xmlnodenew optional: neuer XML-String, wenn leer, so wird der bestehende XML-

String entfernt.

#### **Output:**

XML-String Rückgabe des manipulierten XML-Strings

## 3.8.11 insertcontent

#### Syntax:

insertcontent (\$xmldata, \$insertxmldata, \$tagname)

#### Beschreibung:

Fügt einen XML-String (Child Node) vor dem Ende des übergebenen XML-Parenttags ein. Der modifizierte XML-String wird zurückgegeben.

#### Bsp:

```
Auszug aus dem Content Container:
```

\$xmldata = insertcontent (\$xmldata, \$insertxmldata, "<articletextlist>");

## Input-Parameter:

\$xmldata XML-String der übergeben und modifiziert werden soll

\$insertxmldata XML-String der eingesetzt wird

\$tagname optional: XML-Parenttag an dessen Ende eingesetzt werden soll

Output:

XML-String Rückgabe des manipulierten XML-Strings

### 3.8.12 addcontent

#### Syntax:

addcontent (\$xmldata, \$sub\_xmldata, \$grandtagname, \$condtag, \$condvalue, \$parenttagname, \$tagname, \$contentnew)

#### Beschreibung:

\$tagname \$contentnew

Output:

XML-String False

Innerhalb eines Parent Nodes wird ein Child Node hinzugefügt, sofern ein Wert im darüberliegenden Grandparent Node die Bedingung erfüllt. Im Child Node kann auf Wunsch gleichzeitig ein Wert gesetzt werden. Der modifizierte XML-String wird zurückgegeben.

```
Auszug aus dem Content Container:
<article>
 <article_id>art1</article_id>
 <articletitle></articletitle>
 <articledatefrom></articledatefrom>
 <articledateto></articledateto>
 <articlestatus>active</articlestatus>
 <articleuser></articleuser>
 <articletextlist>
  <text>
    <text id>art1:summary</text id>
   <textuser>editor1</textuser>
    <textcontent>This is my summary!</textcontent>
----- hier wird ein Child Node eingefügt -----
  <text>
   <text_id>art1:longtext</text_id>
   <textuser>editor1</textuser>
   <textcontent>This is my summary!</textcontent>
  </text>
                 </articletextlist>
</article>
$xmldata = addcontent ($xmldata, $sub_xmldata, "<article>", "<article_id>", "art1",
"<articletextlist>", "<text_id>", "art1:longtext");
Input-Parameter:
                          XML-String der übergeben und modifiziert werden soll
$xmldata
                          XML-String der eingebettet werden soll
$sub_xmldata
                         Enthält den XML-Childtag, in dem $sub_xmldata eingebettet
$grandtagname
                         werden soll
                         optional: Name des Parameters der überprüft werden soll
$condtag
$condvalue
                          optional: Wert des Parameters der überprüft werden soll
$parenttagname
                         optional: XML-Childtag, in dem $sub_xmldata eingebettet
                         werden soll
```

optional: Childtag des eingebetteten XML-String

optional: Content für den Tag \$tagname

Rückgabe des manipulierten XML-Strings

Fehler aufgetreten

## 3.9 Bibliothek Meta Data Generator

Diese Funktionsbibliothek ermöglicht Ihnen Keyword-Listen, die Description aus einem Inhalt zu erzeugen. Dies kann zur automatischen Erzeugung bzw. Befüllung von Metadaten verwendet werden.

Es können Meta Daten aus Multimedia-Dateien ausgelesen und im Container eines Objektes gespeichert werden.

## 3.9.1 getmetakeywords

#### Syntax:

getkeywords (\$text, \$language, \$charset)

#### Beschreibung:

Der Funktion wird der Inhalt übergeben. Damit werden alle Keywords aus dem Text ermittelt und als Keyword-Liste zurückgegeben.

Bsp

\$keywords = getkeywords ("This is just a short text.", "en", "UTF-8");

## Input-Parameter:

\$text Content als String

\$language optional: Sprache [en, de], Standard ist "en" \$charset optional: Character Set, Standard ist "UTF-8"

Output:

Keywords Komma-getrennte Liste aller Keywords

False Fehler aufgetreten

## 3.9.2 getmetadescription

## Syntax:

getdescription (\$text, \$charset)

#### Beschreibung:

Dieser Funktion wird der Inhalt übergeben. Daraufhin wird eine Kurzbeschreibung aus dem Text ermittelt und zurückgegeben.

Bsp:

\$keywords = getdescription ("This is just a short text.", "UTF-8");

#### Input-Parameter:

\$text Content als String

\$charset optional: Character Set, Standard ist "UTF-8"

Output:

Keywords Kurzbeschreibung des Inhaltes

### 3.10 Bibliothek Notifications

Diese Funktionsbibliothek versendet automatisierte Nachrichten an einen Benutzer anhand von Grenzwerten eines bestimmten Feldes.

Der Benutzer erhält eine vorformatierte Nachricht mit Information (Links) zu allen Objekten, die in den Suchbereich (Datumsober und -untergrenze) fallen.

## 3.10.1 licensenotification

#### Syntax:

licensenotification (\$site, \$cat, \$folderpath, \$text\_id, \$date\_begin, \$date\_end, \$user)

#### Beschreibung:

Der Funktion ermittelt alle Objekte aufgrund des vorgegebenen Suchbereiches (Lokation und Datumsgrenzwerte) und versendet eine E-Mail an einen bestimmten Benutzer mit den Links zu allen betroffenen Objekten.

#### Bsp:

// set language for mail message
\$lang = "en";

// send mail to Miller

\$result = licensenotification ("%publication%", "%comp%/%publication%/images/", "comp",
"valid\_date", "2012-09-01", "2012-09-30", "Miller");

#### Input-Parameter:

\$site Name der Publikation

\$cat Objekt Kategorie [page, comp]

\$folderpath Pfad für die Defintion des Suchbereiches

\$text\_id Text ID des Feldes auf das die Suche angewendet werden soll

\$date\_begin Startdatum für die Suche (YYYY-MM-DD) \$date\_end Endedatum für die Suche (YYYY-MM-DD)

\$user Benutzername

### Output:

True Mail wurde erfolgreich gesendet

# 4 Komponenten und Applikationen

Wenn Anwendungen in Komponenten integriert werden und Variablen aus einer Seite an eine Komponente übergeben werden müssen, so ist auf folgendes zu achten: Die Komponenten müssen über das Dateisystem eingebunden werden (nicht via HTTP). Alle Variablen die an die Komponente zu übergeben sind, sind in der Komponente als global zu definieren.

#### Bsp:

Eine Seite übergibt eine Variable an eine Komponente.

Hier der Code der Seite:

```
<html>
<head>
<title>page</title>
<head>
<body>
<?php $test="This is just a test!"; ?>
[hyperCMS:components id='component']
</body>
</html>
```

Der Code der Komponente muss wie folgt aussehen:

```
<?php
global $test;
echo $test;
?>
```

Im Beispiel wird die Variable \$test bzw. dessen Wert "This is just a test!" von der Komponente übernommen und in der Präsentation angezeigt.

# 5 Database Connectivity

Die Database Connectivity des hyper Content & Digital Asset Management Servers erlaubt die Anbindung von diversen Datenbanken zur Speicherung und Entnahme von Inhalten. Damit können z.B. relationale Datenbanken als externes Content Repository genutzt werden. Zu diesem Zweck ist je Template der entsprechende hyperCMS-Tag für die Database Connectivity einzufügen, der auf ein DB-Connect File verweißt.

In diesem File werden Funktionen hinterlegt, die hyperCMS aufruft, sofern das Template auf die Funktionsdatei zeigt.

Die Inhalte werden aus der Datenbank gelesen und dem Redakteur angezeigt. Verändert der Redakteur die Inhalte, so können diese auch wieder in die Datenbank geschrieben werden. Es können für Lese- und Schreibzugriffe auch verschiedene Datenbanken aufgerufen werden. Die Funktionen im DB-Connect File bieten nur die Hülle bzw. standardisierte Schnittstelle zu hyperCMS, die durch den Programmierer befüllt werden muss.

Das Thema der Datenbankintegration ist komplex und individuell zu behandeln, da auch bereits bestehende Datenbanken und deren Informationen integriert werden können. hyperCMS gibt kein ER-Modell vor bzw. legt sich auf keine speziellen Datenbank-Produkte fest. Generell kann gesagt werden, dass alle Möglichkeiten von PHP ausgeschöpft werden können, um sich zu diversen Datenquellen zu verbinden.

Neben den notwendigen Parameter für Queries auf relationale Datenbanken wird auch der gesamte Content Conatiner als XML-String übergeben. Damit könnten Dokumente bzw. Inhalte aus den Content Repository auch als Node in XML-Datenbanken abgelegt werden.

Sie selbst bestimmen, wohin Sie Ihre Daten speichern bzw. woher Sie diese holen. Mit PHP besitzen eine mächtige Sprache, die Ihnen Zugriff auf alle gängigen Datenbanken bietet.

Mehr Information zu den Funktionen von PHP finden Sie unter: http://www.php.net

## 5.1 Erstellen einer Database Connectivity

Möchten Sie eine Database Connectivity erstellen, so erstellen Sie eine Kopie des Files db\_connect\_default.php, dieses finden Sie in dem gewählten Root-Verzeichnis für die Ablage der Management Daten unter dem folgenden weiterführenden Pfad: /data/db\_connect/ Die Kopie des Files nennen Sie z.B. nach der Datenbank, die Sie anbinden möchten.

Danach öffnen Sie die Datei und erhalten Einsicht in die Funktionen. Im Source Code finden Sie auch eine Beschreibung der Funktionen und der übergebenen Parameter als auch des Outputs.

Exemplarisch soll hier ein Lesezugriff auf eine MySQL Datenbank für einen Text-Inhalt dargestellt werden. Wir gehen davon aus, dass in einem Table "TextContent" die Inhalte mit dem Primary Key "container\_id" und "text\_id", dem Text-Inhalt "Text" sowie dem Text-Typ "Type" vorliegen. Der User sowie die Artikel ID wird nicht gesondert gespeichert, dies ist für die Eindeutigkeit des Inhalts auch nicht notwendig, denn die ID des Content Containers als auch die ID des Elements reichen als Primärschlüssel aus.

```
// ============== db connect ================================
// this file allows you to access a database using the full PHP functionality.
// you can read or write data from or into a database:
// the following parameter values are passed to each function for
// retrieving data from the database:
// name of the site: $site [string]
// name of the content container: $container_id [string] (is unique
// inside hyperCMS over all sites)
// content container: $container_content [XML-string]
// identification name: $id [string]
// ------ text ------
// if content is text
function db_read_text ($site, $content_id, $container_content, $id, $art_id, $user)
  // input variables: $id [string], optional: $artid [string], $user [string]
  // return value: $text [array]
                  the array must exactly look like this:
  //
                       $text[text], optional: $text[type]
                  constraints/accepted values for article type, see note below
  //
  // note: special characters in $text are escaped into
  // their html/xml equivalents.
             you can decide between unformatted, formatted and
  //
          optional text using $type:
unformatted text: $text[type] = textu
   //
   //
   //
              formatted text: $text[type] = textf
  //
              text option: $text[type] = textl
   //-----
   $user = "username";
   $password = "password";
   $database = "database";
   // connect to database
   mysql_connect ("localhost", $user, $password);
   @mysql_select_db ($database) or die ("Unable to select database");
   // fire SQL-query
   $result = mysql_query ("SELECT Text, Type FROM TextContent WHERE
                container_id=$container_id AND text_id=$id);
   // count returned rows, must be 1 if unique
   $num_of_rows = mysql_num_rows ($result);
   // get the result into an array namend $row
  if (\sum_{i=1}^{n} 
       $row = mysql_fetch_row ($result);
       // set values
       \text{stext[text]} = \text{srow[0]};
       \text{text[type]} = \text{row[1]};
   else $text = false;
   // close connection
  mysql_close ();
   // return result
  return $text;
```

# 6 Event System

Der hyper Content & Digital Asset Management Server beinhaltet ein Event System, das eine automatisierte Ausführung von Aktionen passierend auf Ereignissen im System ermöglicht. Damit lassen sich z.B. manuelle Vorgänge automatisieren.

Events werden meist durch den Benutzer durch Wahl einer Aktion gestartet, z.B. das Publizieren einer Seite. Ist der entsprechende Event aktiviert, so wird nach erfolgreicher Ausführung des Publikationsprozesses der Seite das Event "onpublishobject" aufgerufen. Die darin definierten Funktionen werden sodann ausgeführt.

Die Events des Event Systems können in der Datei "hypercms\_eventsys.inc.php" definiert werden. Diese befindet sich im internen Repository im Ordner "eventsystem". In dieser Datei befinden sich auch weitere wichtige Hinweise, die bei der Ausführung von Events zu beachten sind.

Das Event System ist innerhalb des gesamten Management Systems über alle Publikationen gültig. Das System ist Bestandteil des hyperCMS APIs und wird somit bei jedem Aufruf einer Funktion des APIs ausgeführt.

Events lassen sich in der Datei "hypercms\_eventsys.inc.php" aktivieren als auch deaktivieren, sodass der Einsatz der darin definierten Events leicht gesteuert werden kann.

Bei allen Events wird zwischen PRE- und POST-Events unterschieden. Das PRE-Event wird vor der eigentlichen Ausführung der aufgerufenen Aktion gestartet, während das POST-Event nach der erfolgreichen Ausführung der Aktion aufgerufen wird.

#### Bsp:

Beim Publizieren eines Objektes soll automatisch auch die Seite "index.php" die sich an der gleichen Position befindet publiziert werden, da diese z.B. ein über ein hyperCMS Script generiertes Verzeichnis aller Objekte des gleichen Ordners beinhaltet.

# 7 Liste der hyperCMS API Funktionen

Die Dokumentation aller API Funktionen sind auch auf unserer Website hypercms.com in der aktuellen Version verfügbar. Sie können die Dokumentation ihrer installierten Version als Hilfe und im Browser anzeigen. Nutzen Sie hierzu das ?-Icon im Template Editor um die Referenz aller hyperCMS Tags und API Funcktionen einzusehen.

## 7.1 Main API Functions

#### 7.1.1 correctnumber

#### **Syntax**

correctnumber (\$number)

## Input parameters

• \$number ... formated number [string]

## global input parameters

• \$mgmt\_config

## Output

correct mathematical number / false on error

## 7.1.2 cleancontent

#### Description

Removes all HTML tags, scripts and other special characters from the content in order to create a plain text

#### **Syntax**

cleancontent (\$text, \$charset="UTF-8")

## Input parameters

- \$text ... text [string or array]
- \$charset ... character set [string] (optional)

### global input parameters

• \$mgmt\_config

#### **Output**

cleaned text / false on error

## 7.1.3 remove\_utf8\_bom

### **Description**

Remove UTF-8 BOM sequences

#### **Syntax**

remove\_utf8\_bom (\$text)

## Input parameters

• \$text ... text [string]

#### Output

cleaned text / false on error

#### 7.1.4 convert\_utf8

#### **Syntax**

convert\_utf8 (\$in)

## Input parameters

• \$in ... expression [string or array]

## Output

• UTF-8 converted expression / original expression on error

#### 7.1.5 convertchars

#### **Syntax**

convertchars (\$expression, \$charset\_from="UTF-8", \$charset\_to="UTF-8")

#### Input parameters

- \$expression ... expression [string or array]
- \$charset\_from ... input character set [string] (optional)
- \$charset\_to ... output character set [string] (optional)

## global input parameters

• \$mgmt\_config

## Output

• converted expression / original expression on error

## 7.1.6 specialchr

#### Description

Tests if an expression includes special characters (true) or does not (false). Allow characters through including them in \$accept (e.g. #\$...)

## **Syntax**

specialchr (\$expression, \$accept="")

#### Input parameters

- \$expression ... expression [string]
- \$accept ... list of characters to be excluded from search [string] (optional)

### Output

• true/false

## 7.1.7 specialchr\_encode

#### **Description**

Renames all special characters for file names to an expression according to given rules

#### **Syntax**

specialchr\_encode (\$expression, \$remove="no")

#### Input parameters

- \$expression ... expression [string]
- \$remove ... remove all special characters [yes, no]

#### global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

#### Output

• expression without special characters (for file names)

## 7.1.8 specialchr\_decode

#### **Description**

This is the decode function for function specialchr\_encode

#### **Syntax**

specialchr\_decode (\$expression)

#### Input parameters

• \$expression ... expression [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

• expression with special characters (for file names) / false

#### 7.1.9 convertdate

#### **Description**

This function converts a date to a different time zone and format.

#### **Syntax**

convertdate (\$date, \$timezone1, \$dateformat1="Y-m-d H:i:s", \$timezone2, \$dateformat2="Y-m-d H:i:s")

## Input parameters

- \$date ... date and time [string]
- \$timezone1 ... time zone source [string]
- \$dateformat1 ... source date format [string] (optional)
- \$timezone2 ... time zone target [string]
- \$dateformat2 ... target date format [string] (optional)

## Output

• converted date as tring / false

## 7.1.10 offsettime

#### **Description**

This function calculates the offset time from UTC (Coordinated Universal Time).

#### **Syntax**

offsettime ()

#### Input parameters

#### Output

offset time in hh: mm from UTC

## 7.1.11 object\_exists

## Description

This function verifies if an object exists already.

#### **Syntax**

object\_exists (\$path)

#### Input parameters

• \$path ... path to an object [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

• true / false

## 7.1.12 is\_utf8

## Description

This function is an alternative to mb\_check\_encoding (which requires an extra PHP module). It is not failsave!

## **Syntax**

is\_utf8 (\$str)

## Input parameters

• \$str ... expression [string]

#### Output

• if string is utf-8 encoded true / false otherwise

## 7.1.13 is\_latin1

## Description

This function is an alternative to mb\_check\_encoding (which requires an extra PHP module). It is not failsave!

#### **Syntax**

is\_latin1 (\$str)

#### Input parameters

• \$str ... expression [string]

## Output

• if string is latin 1 encoded true / false otherwise

## 7.1.14 makestring

### **Syntax**

makestring (\$array)

## Input parameters

• \$array ... (multidimensional) array

## Output

• string including all array values / false on error

## 7.1.15 splitstring

## **Syntax**

splitstring (\$string)

## Input parameters

• \$string ... string with ";" or ", " as seperator [string]

## Output

• array with string splitted into array / false on error

## 7.1.16 is\_folder

## Description

Checks if the provided path to an object is a folder

#### **Syntax**

is\_folder (\$path)

## Input parameters

• \$path ... path to any object [string]

## global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.1.17 is\_emptyfolder

### **Description**

Checks if a directory/folder is empty (has no published objects or other files)

#### Syntax

is\_emptyfolder (\$dir)

### Input parameters

• \$dir ... path to folder [string]

## global input parameters

\$mgmt\_config

## Output

true / false

## 7.1.18 is\_supported

#### Description

This function determines if a certain file type by its file extension is supported by the systems media conversion

## **Syntax**

is\_supported (\$preview\_array, \$file)

## Input parameters

- \$preview\_array ... preview array holding the supported file extensions as key and references to executables as value [array]
- \$file ... file name or file extension [string]

## Output

true / false

## 7.1.19 is\_cloudstorage

#### **Description**

This function determines if a cloud storage has been defined in the main configuration or for a specific publication

#### **Syntax**

is\_cloudstorage (\$site="")

## Input parameters

• \$site ... publication name [string] (optional)

## global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.1.20 is\_cloudobject

### **Description**

This function verifies if an object/file is available in the cloud storage

#### **Syntax**

is\_cloudobject (\$file)

## Input parameters

• \$file ... path to media file or media file name [string]

## global input parameters

• \$mgmt\_config

## Output

true / false

## 7.1.21 is\_date

#### **Description**

This function determines if a string represents a valid date format

#### Syntax

is\_date (\$date, \$format="Y-m-d")

#### Input parameters

- \$date ... date [string]
- \$format ... date format [string] (optional)

#### Output

• true / false

## 7.1.22 is\_tempfile

## Description

This function checks if the provided file name is a temporary file

## **Syntax**

is\_tempfile (\$path)

## Input parameters

• \$path ... file name or path [string]

## Output

• if file is a temp file true / false on error

## 7.1.23 is\_keyword

### Description

This function checks if the provided expression can be used as a keyword

#### **Syntax**

is\_keyword (\$keyword)

## Input parameters

• \$keyword ... keyword [string]

## Output

• if expression can be used as a keyword true / false on error

## 7.1.24 is\_thumbnail

#### Description

This function checks if the provided file name is a thumbnail file

#### **Syntax**

is\_thumbnail (\$media, \$images\_only=true)

## Input parameters

- \$media ... file name or path [string]
- \$images\_only ... only thumbnail images should be considered as thumbnail [boolean]

## Output

• if file is a thumbnail file true / false on error

## 7.1.25 is\_config

## Description

This function checks if the provided file name is a config file

## **Syntax**

is\_config (\$media)

### Input parameters

• \$media ... file name or path [string]

## Output

• if file is a config file true / false if not

## 7.1.26 is\_encryptedfile

## Description

This function checks if the provided file is encrypted

#### **Syntax**

is\_encryptedfile (\$location, \$file)

### Input parameters

- \$location ... path to file [string]
- \$file ... file name [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

• true / false

## 7.1.27 is\_document

## Description

This function determines if a certain file is a document (binary and text based)

## **Syntax**

is\_document (\$file)

## Input parameters

• \$file ... file name or file extension [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

## Output

• true / false

## 7.1.28 is\_image

## Description

This function determines if a certain file is an image

#### **Syntax**

is\_image (\$file)

#### Input parameters

• \$file ... file name or file extension [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

## Output

true / false

## 7.1.29 is\_rawimage

## Description

This function determines if a certain file is a raw image

## **Syntax**

is\_rawimage (\$file)

## Input parameters

• \$file ... file name or file extension [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

## Output

• true / false

## 7.1.30 is\_aiimage

## Description

This function determines if a certain file is a vector-based Adobe Illustrator (AI) or AI-compatible EPS file

## **Syntax**

is\_aiimage (\$file)

## Input parameters

• \$file ... file name or file extension [string]

## Output

• true / false

## 7.1.31 is\_video

### **Description**

This function determines if a certain file is a video

#### **Syntax**

is\_video (\$file)

## Input parameters

• \$file ... file name or file extension [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

## Output

• true / false

## 7.1.32 is\_rawvideo

#### Description

This function determines if a certain file is a RAW video

## **Syntax**

is\_rawvideo (\$file)

## Input parameters

• \$file ... file name or file extension [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

## Output

• true / false

## 7.1.33 is\_audio

### Description

This function determines if a certain file is an audio file

### **Syntax**

is\_audio (\$file)

## Input parameters

• \$file ... file name or file extension [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

## Output

• true / false

## 7.1.34 is\_mobilebrowser

## Description

Detects mobile browsers (smartphones and tablets)

## **Syntax**

is\_mobilebrowser ()

## Input parameters

## global input parameters

- \$user
- \$mgmt\_config

## Output

• true / false

## 7.1.35 is\_iOS

## Description

Detects if a mobile browser is an iPhone, iPad or IPod

## **Syntax**

is\_iOS ()

## Input parameters

## global input parameters

- \$user
- \$mgmt\_config

## Output

• true / false

## 7.1.36 is\_activelanguage

## Description

This function determines if a language has been enabled for automatic translation in the publication settings

## **Syntax**

is\_activelanguage (\$site, \$langcode)

### Input parameters

- \$site ... publication name [string]
- \$langcode ... 2-digits language code [string]

## global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.1.37 copyrecursive

### Description

This function copyies all directories and files from source to destination directory

#### **Syntax**

copyrecursive (\$src, \$dst)

## Input parameters

- \$src ... source directory [string]
- \$dst ... destination directory [string]

#### Output

true/false

## 7.1.38 array\_iunique

### Description

This function is the case-insensitive form of PHPs array\_unique function

#### **Syntax**

array\_iunique (\$array)

#### Input parameters

• \$array ... array [array]

## Output

• unique array / false

# 7.1.39 in\_array\_substr

## Description

This function is supporting the search of substrings in the array values compared to PHPs in\_array function

# **Syntax**

in\_array\_substr (\$search, \$array)

# Input parameters

- \$search ... search expression [string]
- \$array ... array [array]

# Output

• true / false

# 7.1.40 createfilename

# Description

Creates a valid file name without special characters that does not exceed the maximum file name length

# **Syntax**

createfilename (\$filename)

# Input parameters

• \$filename ... path to file or directory [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• new filename/false

# 7.1.41 correctfile

# **Syntax**

correctfile (\$abs\_path, \$filename, \$user="")

- \$abs\_path ... path to file or directory [string]
- \$filename ... file or directory name [string]
- \$user ... user name [string]

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• correct filename/false

# 7.1.42 correctpath

# **Syntax**

correctpath (\$path, \$slash="/")

# Input parameters

- \$path ... path to folder [string]
- \$slash ... directory seperator [string] (optional)

# Output

correct path/false

# 7.1.43 convertpath

### **Description**

This function replaces object pathes of the content management config with %page% and %comp% path variables

## **Syntax**

convertpath (\$site, \$path, \$cat="")

# Input parameters

- \$site ... publication name [string]
- \$path ... content management path to folder or object [string]
- \$cat ... object category [page, comp]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

• converted path or URL / false on error

# 7.1.44 convertlink

## Description

This function replaces pathes of the publication management config with %page% and %comp% path variables.

## **Syntax**

convertlink (\$site, \$path, \$cat)

### Input parameters

- \$site ... publication name [string]
- \$path ... publication management path to folder or object [string]
- \$cat ... object category [page, comp]

## global input parameters

- \$user
- \$mgmt\_config
- \$publ\_config
- \$hcms\_lang
- \$lang

## Output

• converted path or URL / false on error

# 7.1.45 deconvertpath

# Description

This function replaces all %page% and %comp% path variables with the path of the content management config.

It converts the path only on content management side not for the publication target. It optionally transform special characters as well.

BE AWARE: The input path must not provide template data since valid\_publicationname might return false.

#### **Syntax**

deconvertpath (\$objectpath, \$type="file", \$specialchr\_transform=true)

## Input parameters

- \$objectpath ... string including path to folder or object [string]
- \$type ... convert to file system path or URL [file, url] (optional)
- \$specialchr\_transform ... transform special characters using specialchr\_encode [boolean] (optional)

#### global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

deconverted path/false

## 7.1.46 deconvertlink

## Description

This function deconverts the path only for the publication target.

It should be used for page linking, otherwise the function will return the absolute link including the host for component links.

## **Syntax**

deconvertlink (\$path, \$type="url")

## Input parameters

- \$path ... path to folder or object [string]
- \$type ... convert to file system path or URL [file, url]

# global input parameters

- \$user
- \$mgmt\_config
- \$publ\_config
- \$hcms\_lang
- \$lang

## Output

• converted absolute link without host/false

# 7.1.47 mediapublicaccess

#### **Description**

Is the media file public accessible. Has it been published or has the setting 'publicdownload' in the main configuration been enabled.

This function does not include direct links to the media files (used in websites).

# **Syntax**

mediapublicaccess (\$mediafile)

## Input parameters

• \$mediafile ... media file name [string]

# global input parameters

\$mgmt\_config

## Output

• true / false

## 7.1.48 createviewlink

## **Description**

The view link is mainly used inside the system in order to reference and load a multimedia file.

The database is not required since the object hash or ID is not needed to create the view link.

## **Syntax**

createviewlink (\$site, \$mediafile, \$name="", \$force\_reload=false, \$type="wrapper")

## Input parameters

- \$site ... publication name [string]
- \$mediafile ... media file name [string]
- \$name ... media name [string] (optional)
- \$force\_reload ... force reload [boolean] (optional)
- \$type ... link type [wrapper, download] (optional)

# global input parameters

- \$user
- \$mgmt\_config

## **Output**

• URL for download of the multimedia file / false on error

# 7.1.49 createportallink

# Description

The portal access link is used to provide public access without logon based on a certain user profile and user hash that is connected with the portal.

#### **Syntax**

createportallink (\$site, \$portal)

# Input parameters

- \$site ... publication name [string]
- \$portal ... portal name [string]

## global input parameters

• \$mgmt\_config

## Output

• URL for download of the multimedia file / false on error

# 7.1.50 createaccesslink

## Description

Creates an access link to any object based on the permissions of the provided user account.

# **Syntax**

createaccesslink (\$site, \$location="", \$object="", \$cat="", \$object\_id="", \$login, \$type="al", \$lifetime=0, \$formats="")

### Input parameters

- \$site ... publication name [string]
- \$location ... location [string] (optional)
- \$object ... object [string] (optional)
- \$cat ... category [page, comp] (optional)
- \$object\_id ... object-ID [string] (optional)
- \$login ... user name of the user account to be used for access [string]
- \$type ... link type [al, dl] (optional)
- \$lifetime ... token lifetime in seconds [integer] (optional)
- \$formats ... formats defined in main configuration [JSON-string] (optional)

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

URL for access to given object / false on error

# 7.1.51 createobjectaccesslink

## **Description**

Creates an access link to any object based on the permissions of the user account defined in the publication settings.

# **Syntax**

```
createobjectaccesslink ($site="", $location="", $object="", $cat="", $object_id="", $container_id="")
```

# Input parameters

- \$site ... publication name [string] (optional)
- \$location ... location [string] (optional)
- \$object ... object [string] (optional)
- \$cat ... category [page, comp] (optional)
- \$object\_id ... object ID [string] (optional)
- \$container\_id ... container-ID or repository media file [string] (optional)

## global input parameters

\$user

- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

• URL for download of the multimedia file of the given object or folder / false on error

# 7.1.52 createwrapperlink

# Description

In order to track and include external user IDs in the daily statistics you need to manually add the 'user' parameter to the link in the form of: &user=[user-ID]

#### Syntax

```
createwrapperlink ($site="", $location="", $object="", $cat="", $object_id="",
$container_id="", $type="", $mediaconfig="")
```

## Input parameters

- \$site ... publication name [string] (optional)
- \$location ... location [string] (optional)
- \$object ... object [string] (optional)
- \$cat ... category [page, comp] (optional)
- \$object\_id ... object ID [string] (optional)
- \$container\_id ... container-ID or repository media file [string] (optional)
- \$type ... media file extension or type based on main config settings [string] (optional)
- \$mediaconfig ... media configuration based on main config settings [string] (optional)

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

URL for download of the multimedia file of the given object or folder / false on error

## 7.1.53 createdownloadlink

#### Description

In order to track and include external user IDs in the daily statistics you need to manually add the 'user' parameter to the link in the form of: &user=[user-ID]

### **Syntax**

```
\label{location} $$\operatorname{createdownloadlink} (\$site="", \$location="", \$object="", \$cat="", \$object\_id="", \$container\_id="", \$type="", \$mediaconfig="")$
```

# Input parameters

• \$site ... publication name [string] (optional)

- \$location ... location [string] (optional)
- \$object ... object [string] (optional)
- \$cat ... category [page, comp] (optional)
- \$object\_id ... object ID [string] (optional)
- \$container\_id ... container-ID or repository media file [string] (optional)
- \$type ... media file extension or type based on main config settings [string] (optional)
- \$mediaconfig ... media configuration based on main config settings [string] (optional)

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• URL for download of the multimedia file of the given object or folder / false on error

## 7.1.54 createmultiaccesslink

### **Description**

Creates an access link to any object based on the permissions of the provided user account.

## Syntax

createmultiaccesslink (\$multiobject, \$login, \$type="al", \$lifetime=0, \$formats="")

### Input parameters

- \$multiobject ... multiobject [path1|path2|path3] or [array]
- \$login ... user name of the user account to be used for access [string]
- \$type ... link type [al, dl] (optional)
- \$lifetime ... token lifetime in seconds [integer] (optional)
- \$formats ... formats [string] (optional)

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

URL for access to the requested objects / false on error

## 7.1.55 createmultidownloadlink

#### Description

Generates a download link of a selectio of media objects. Pages and components will be ignored.

There is a difference in the file conversion functionality:

Case 1: multiobject (min. 2 objects or object is a folder) without the support of file conversion Case 2: multiobject with only one object (must not be a folder) with support of file conversion

# **Syntax**

createmultidownloadlink (\$site, \$multiobject, \$name="", \$user, \$type="", \$mediacfg="", \$linktype="download", \$flatzip=false)

## Input parameters

- \$site ... publication name [string]
- \$multiobject ... multiobject using | as seperator [string] or [array]
- \$name ... presentation name [string] (optional)
- \$user ... user name [string]
- \$type ... conversion type example: jpg [string]
- \$mediacfg ... media configuration used for conversion (e.g.: 1024x768px) [string]
- \$linktype ... link type [wrapper, download] (optional)
- \$flatzip ... flat hierarchy means no directories [boolean] (optional)

## global input parameters

- \$mgmt\_config
- \$mgmt\_compress
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$globalpermission
- \$setlocalpermission
- \$hcms\_lang
- \$lang

# Output

• URL for download of the requested objects / false on error

#### 7.1.56 cleandomain

#### Description

Returns the URL notation without the protocoll://domain.

# **Syntax**

cleandomain (\$path)

# Input parameters

• \$path ... string to clean from http(s)://domain [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• cleanded string / false on error

## 7.1.57 fileversion

# Description

Creates a version file name

## **Syntax**

fileversion (\$file)

# Input parameters

• \$file ... file name [string]

# Output

• versioned file name [string] / false on error

# 7.1.58 createversion

### **Description**

Creates a new version of a multimedia file and container

#### Syntax

createversion (\$site, \$file, \$user="sys")

## Input parameters

- \$site ... publication name [string]
- \$file ... media file name or container name [string]
- \$user ... user name [string] (optional)

# global input parameters

- \$mgmt\_config
- \$mgmt\_mediaoptions
- \$mgmt\_docoptions
- \$hcms\_ext
- \$user

## Output

true / false

# 7.1.59 rollbackversion

#### **Description**

Makes an older object version to the current version

## **Syntax**

rollbackversion (\$site, \$location, \$page, \$container\_version, \$user="sys")

## Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$container\_version ... container version name [string]
- \$user ... user name [string] (optional)

## global input parameters

- \$mgmt\_config
- \$mgmt\_mediaoptions
- \$mgmt\_docoptions
- \$hcms\_ext
- \$hcms\_lang
- \$lang

# Output

result\_array

# 7.1.60 deleteversion

# Description

Removes the version of an object

#### **Syntax**

deleteversion (\$site, \$container\_version, \$user="sys")

## Input parameters

- \$site ... publication name [string]
- \$container\_version ... location [string]
- \$user ... object name [string]

# global input parameters

• \$mgmt\_config

## **Output**

• true / false

# 7.1.61 deleteversions

## Description

Removes all versions of all objects or templates

#### Syntax

deleteversions (\$type, \$report, \$user="sys")

# Input parameters

- \$type ... type [content, template] or valid path in filesystem
- \$report ... report [yes, no]
- \$user ... user name [string] (optional)

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

- true [report=no] or report [report=yes]
- false on error

# 7.1.62 loadfile\_header

## Description

Loads the file header, represented by a defined header size.

#### Syntax

loadfile\_header (\$abs\_path, \$filename)

# Input parameters

- \$abs\_path ... path to file [string]
- \$filename ... file name [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

file content

# 7.1.63 loadfile\_fast

## Description

This functions is identical to loadfile, but it does not wait for locked files to be unlocked again. It should only be used on files that won't be locked by the system. It is therefore recommended to use loadfile.

## **Syntax**

loadfile\_fast (\$abs\_path, \$filename)

# Input parameters

- \$abs\_path ... path to file [string]
- \$filename ... file name [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

file content

# 7.1.64 loadfile

### **Description**

This function loads a file and waits up to 3 seconds for locked files to be unlocked

#### Syntax

loadfile (\$abs\_path, \$filename)

## Input parameters

- \$abs\_path ... path to file [string]
- \$filename ... file name [string]

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

• file content

# 7.1.65 loadlockfile

## **Description**

This function loads and locks a file for a sepecific user. It waits up to 3 seconds for locked files to be unlocked.

Function loadlockfile and savelockfile includes a locking mechanismen for files.

Every time you want to lock a file during your operations use loadlockfile.

It is important to use savelockfile to save and unlock the file again.

savelockfile requires the file to be opened by loadlockfile before.

# **Syntax**

loadlockfile (\$user, \$abs\_path, \$filename, \$force\_unlock=3)

### Input parameters

- \$user ... user name [string]
- \$abs\_path ... path to file [string]
- \$filename ... file name [string]
- \$force\_unlock ... force unlock of file after x seconds [integer]

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• file content

# 7.1.66 savefile

# Description

This function saves content to a file

## **Syntax**

savefile (\$abs\_path, \$filename, \$filedata)

# Input parameters

- \$abs\_path ... path to file [string]
- \$filename ... file name [string]
- \$filedata ... file content [string]

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

true/false

## 7.1.67 savelockfile

## Description

Saves content to a locked file. It requires the file to be opened by loadlockfile. Function loadlockfile and savelockfile includes a locking mechanismen for files. Every time you want to lock a file during your operations use loadlockfile. It is important to use savelockfile to save and unlock the file again. savelockfile requires the file to be opened by loadlockfile before.

#### **Syntax**

savelockfile (\$user, \$abs\_path, \$filename, \$filedata)

# Input parameters

- \$user ... user name [string]
- \$abs\_path ... path to file [string]
- \$filename ... file name [string]
- \$filedata ... file content [string]

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

true/false

# 7.1.68 appendfile

# Description

Appends data to a file but cannot create a new file! Waits up to 3 seconds for locked files to be unlocked again. Files won't be unlocked if the file is already locked.

#### **Syntax**

appendfile (\$abs\_path, \$filename, \$filedata)

## Input parameters

- \$abs\_path ... path to file [string]
- \$filename ... file name [string]
- \$filedata ... file content [string]

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

true/false

## 7.1.69 lockfile

## Description

This functions lockes a file for a specific user

## **Syntax**

lockfile (\$user, \$abs\_path, \$filename)

# Input parameters

- \$user ... user name [string]
- \$abs\_path ... path to file [string]
- \$filename ... file name [string]

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

true/false

# 7.1.70 unlockfile

## Description

This functions unlockes a file for a specific user

# **Syntax**

unlockfile (\$user, \$abs\_path, \$filename)

## Input parameters

- \$user ... user name [string]
- \$abs\_path ... path to file [string]
- \$filename ... file name [string]

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

true/false

# 7.1.71 deletefile

## Description

Deletes a file or directory. If parameter recursive is et to true all items of a directory will be removed as well.

## **Syntax**

deletefile (\$abs\_path, \$filename, \$recursive=false)

# Input parameters

- \$abs\_path ... path to file [string]
- \$filename ... file or directory name [string]
- \$recursive ... delete all files in directory recursively including symbolic links [boolean]

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

true/false

# 7.1.72 restoremediafile

## Description

Moves an exported media file back to the media repository.

## **Syntax**

restoremediafile (\$site, \$mediafile)

# Input parameters

- \$site ... publication name [string]
- \$mediafile ... media file name [string]

# global input parameters

• \$mgmt\_config

# Output

result array

# 7.1.73 preparemediafile

# Description

Prepares a media file for use in the system (load from cloud, decrypt content)

## **Syntax**

preparemediafile (\$site, \$medialocation, \$mediafile, \$user="")

- \$site ... publication name [string]
- \$medialocation ... media file location [string]
- \$mediafile ... media file name [string]

• \$user ... user name [string] (optional)

## global input parameters

\$mgmt\_config

# Output

• result array / false on error

## 7.1.74 deletemediafiles

### Description

Deletes all derivates (thumbnails, config files, converted versions of the file) of a specific media file resource. Deletes the original media file optionally.

# **Syntax**

deletemediafiles (\$site, \$mediafile, \$delete\_original=false)

## Input parameters

- \$site ... publication name [string]
- \$mediafile ... mediafile name [string]
- \$delete\_original ... delete original media file [boolean] (optional)

## global input parameters

- \$user
- \$mgmt\_config
- \$mgmt\_mediaoptions
- \$mgmt\_docoptions
- \$hcms\_ext
- \$hcms\_lang
- \$lang

## **Output**

true/false

## 7.1.75 avoidfilecollision

## Description

Appending data to a file ensures that the previous write process is finished (required due to issue when editing encrypted files)

#### **Syntax**

avoidfilecollision (\$data="tempdata", \$force=false)

- \$data ... data string [string] (optional)
- \$force ... force execution [boolean]

- \$mgmt\_config
- \$site

# Output

true / false on error

# 7.1.76 substr\_in\_array

# Description

Searches for substring in array

## **Syntax**

substr\_in\_array (\$search, \$array)

## Input parameters

- \$search ... search-string [string]
- \$array ... array [array]

# Output

• array with found values / false

# 7.1.77 downloadobject

## Description

This functions provides an object via http for viewing, not suitable for multimedia objects!

#### Syntax

downloadobject (\$location, \$object, \$container="", \$lang="en", \$user="")

# Input parameters

- \$location ... location [string]
- \$object ... object name [string]
- \$container ... content container [string]
- \$lang ... language [string] (optional)
- \$user ... user name [string] (optional)

## global input parameters

- \$mgmt\_config
- \$eventsystem
- \$hcms\_lang
- \$lang

# Output

• stream of file content / false on error

## 7.1.78 downloadfile

### **Description**

This functions provides a file via http for view or download

### **Syntax**

downloadfile (\$filepath, \$name, \$force="wrapper", \$user="")

## Input parameters

- \$filepath ... path to file [string]
- \$name ... file name to show for download via http [string]
- \$force ... force file wrapper or download or no file headers for WebDAV [download, wrapper, noheader]
- \$user ... user name [string] (optional)

# global input parameters

- \$mgmt\_config
- \$eventsystem
- \$hcms\_lang
- \$lang
- \$is\_iphone

## Output

• stream of file content / false on error

# 7.1.79 loadcontainer

## **Description**

This functions loads a content container

#### **Syntax**

loadcontainer (\$container, \$type="work", \$user)

# Input parameters

- \$container ... container file name or container id (working container will be loaded by default) [string]
- \$type ... optional container type [published, work, version]
- \$user ... user name [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

XML content of container / false on error

#### 7.1.80 savecontainer

## Description

Saves data into existing content container by default. Only if \$init is set to true it will initally save a non existing container.

## **Syntax**

savecontainer (\$container, \$type="work", \$data, \$user, \$init=false)

## Input parameters

- \$container ... container file name or container id (working container will be loaded by default) [string]
- \$type ... container type [published, work, version] (optional)
- \$data ... container content [XML]
- \$user ... user name [string]
- \$init ... save container initally [boolean] (optional)

## global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

• true / false on error

## 7.1.81 checkworkflow

#### **Description**

Help function for function buildview to evaluate the workflow of an object and return the manipulated view store, view name, workflow ID, workflow role and the encrypted workflow token.

Workflow roles:

```
0 ... user is not a member of workflow (no permissions)
```

1 ... read

2 ... read + edit

3 ... read + publish

4 ... read + edit + publish

5 ... no workflow (users permissions apply)

# **Syntax**

```
checkworkflow ($site, $location, $page, $cat="", $contentfile="", $contentdata="", $buildview="cmsview", $viewstore="", $user)
```

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$cat ... category [page, comp] (optional)
- \$contentfile ... container name [string] (optional)

- \$contentdata ... container [XML string] (optional)
- \$buildview ... view name [string] (optional)
- \$viewstore ... view store [string] (optional)
- \$user ... user name [string]

\$mgmt\_config

## Output

result array

# 7.1.82 inherit\_db\_load

# Description

This function loads and locks the inheritance database.

Each record of the inherit management database has the following design:

xml-content container : | absolute path to 1-n objects : | 1-m inherits used by 1-n objects Important: The inherit management database needs to be saved or closed after loading it

## **Syntax**

inherit\_db\_load (\$user)

# Input parameters

• \$user ... %

## global input parameters

- \$siteaccess
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

• inheritance database [2 dim. array]/false

# 7.1.83 inherit\_db\_read

## Description

This function loads the inheritance database for reading

#### **Syntax**

inherit\_db\_read ()

# Input parameters

## global input parameters

• \$user

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• inheritance database [2 dim. array]/false

# 7.1.84 inherit\_db\_close

# Description

Closes and unlocks the inheritance management database

## **Syntax**

inherit\_db\_close (\$user)

# Input parameters

• \$user ... %

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• true/false

# 7.1.85 inherit\_db\_save

# Description

This function saves und unlocks the inheritance management database

## **Syntax**

inherit\_db\_save (\$inherit\_db, \$user)

# Input parameters

- \$inherit\_db ... inherit database [array]
- \$user

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

true/false

# 7.1.86 inherit\_db\_getparent

# **Syntax**

inherit\_db\_getparent (\$inherit\_db, \$child)

## Input parameters

- \$inherit\_db ... inherit database [2 dim. array]
- \$child ... child [string]

# Output

• all parents of given child [1 dim. array] / false

# 7.1.87 inherit\_db\_getchild

# Syntax

inherit\_db\_getchild (\$inherit\_db, \$parent)

# Input parameters

- \$inherit\_db ... parent [string]
- \$parent

# Output

• all childs of given parent [1 dim. array] / false

# 7.1.88 inherit\_db\_setparent

#### **Description**

This function updates and insert all references from a child an its parents

#### Syntax

inherit\_db\_setparent (\$inherit\_db, \$child, \$parent\_array)

## Input parameters

- \$inherit\_db ... inherit database [2 dim. array]
- \$child ... child [string]
- \$parent\_array ... parents [array]

## **Output**

• inherit database [2 dim. array]

# 7.1.89 inherit\_db\_insertparent

## **Syntax**

inherit\_db\_insertparent (\$inherit\_db, \$parent, \$child\_array)

# Input parameters

- \$inherit\_db ... inherit database [2 dim. array]
- \$parent ... parent [string]
- \$child\_array ... childs [array]

# Output

• inherit database [2 dim. array]

# 7.1.90 inherit\_db\_deleteparent

# **Syntax**

inherit\_db\_deleteparent (\$inherit\_db, \$parent)

# Input parameters

- \$inherit\_db ... inherit database [2 dim. array]
- \$parent ... parent [string]

# Output

• inherit database [2 dim. array]

## 7.1.91 createinstance

### **Description**

This function creates a new instance with all its files and the mySQL database

## **Syntax**

createinstance (\$instance\_name, \$settings, \$user="sys")

# Input parameters

- \$instance\_name ... instance name [string]
- \$settings ... settings array [array]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.92 editinstance

## Description

This function saves the instance configuration in the config file

## **Syntax**

editinstance (\$instance\_name, \$content, \$user="sys")

## Input parameters

- \$instance\_name ... instance name [string]
- \$content ... content [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

## 7.1.93 deleteinstance

## **Description**

This function creates a new instance with all its files and the mySQL database

## **Syntax**

deleteinstance (\$instance\_name, \$user="sys")

# Input parameters

- \$instance\_name ... instance name [string]
- \$user ... settings [array]

## global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

result array

# 7.1.94 createpublication

## Description

This function creates a new publication with all its files

### **Syntax**

createpublication (\$site\_name, \$user="sys")

## Input parameters

- \$site\_name ... publication name [string]
- \$user ... user name [string] (optional)

#### global input parameters

- \$siteaccess
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

#### **Output**

result array

#### 7.1.95 editpublication

## Description

```
This function saves all settings of a publication. It is a good advice to load the settings of a
publication and manipulate the values in order to provide all settings as input.
Settings (keys for settings array):
inherit_comp ... inherit components [boolean]
inherit_tpl ... inherit templates [boolean]
youtube_token ... Youtube token [string]
registration ... enable registration of new users [boolean]
registration_group ... assign new users to the group [string]
registration_notify ... notify the users whenever a new user registered [string]
site_admin0 ... enable publication management [true]
url_path_page ... URL to page root on management server [string]
abs_path_page .... absolute path to page root on management server [string]
exclude_folders ... exlude folders from the system [string]
allow_ip ... only enable access for the provided IP addresses [string]
webdav ... enable WebDAV access [boolean]
webdav dl ... enable download links for WebDAV [boolean]
webday al ... enable access links for WebDAV [boolean]
default_codepage ... deafult charcter set of the publication [string]
sendmail ... enable send mail [boolean]
mailserver ... mailserver name [string]
portalaccesslink ... enable portal access via public link [boolean]
accesslinkuser ... user to be used for access links [string]
watermark_image ... watermark settings for images (-wm
/home/hypercms/public_html/logo_watermark.png->topleft->10) [string]
watermark video ... watermark settings for videos (-wm
/home/hypercms/public_html/logo_watermark.png->topleft->10) [string]
sharesociallink ... enable social media link sharing [boolean]
youtube ... enbale Youtube upload [boolean]
theme ... standard design theme of the publication [string]
translate ... languges that can be used for automated translation (en, fr, de) [string]
```

```
ocr ... languges that can be used for OCR (en, de, ...) [string]
crypt_content ... encrypt content [boolean]
connector_rest ... Enable RESTful API [boolean]
connector soap ... enable SOAP API [boolean]
storage_limit ... storage limit in MB [integer]
gs_access_json ... Google Cloud service JSON access code [string]
gs_analyze_image ... Enable automatted image tagging [boolean]
gs_analyze_video ... Enable automatted video tagging [boolean]
gs_speech2text ... Enable automatted speech to text translation for video and audio files
[boolean]
gs_speech2text_langcode ... language code to be used for Google Speech2Text Cloud service
(en-US) [string]
url_publ_page ... URL to page root on publication server [string]
abs_publ_page ... absolute path to page root on publication server [string]
url_publ_rep ... URL to repository root on publication server [string]
abs_publ_rep ... absolute path to repository root on publication server [string]
abs_publ_app ... absolute path to application root on publication server [string]
publ_os ... operating system used (UNIX or WIN) [string]
remoteclient ... URL to remote client on remote webserver [string]
```

#### Syntax

editpublication (\$site\_name, \$setting, \$user="sys")

### Input parameters

- \$site\_name ... publication name [string]
- \$setting ... publication settings with setting name as key and parameter as value [array]
- \$user ... user name [string] (optional)

### global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.96 editpublicationsetting

## Description

This function can be used to edit a single setting of a publication

#### Syntax

editpublicationsetting (\$site\_name, \$setting, \$user="sys")

- \$site\_name ... publication name [string]
- \$setting ... publication settings with setting name as key and setting parameter as value (see publication config file for details) [array]
- \$user ... user name [string] (optional)

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.97 deletepublication

## Description

This function deletes a publication with all its files

## **Syntax**

deletepublication (\$site\_name, \$user="sys")

## Input parameters

- \$site\_name ... publication name [string]
- \$user ... user name [string] (optional)

# global input parameters

- \$mgmt\_config
- \$eventsystem
- \$hcms\_lang
- \$lang

## Output

result array

# 7.1.98 createpersonalization

## Description

This function creates a new customer personalization tracking or profile

## **Syntax**

createpersonalization (\$site, \$pers\_name, \$cat)

## Input parameters

- \$site ... publication name [string]
- \$pers\_name ... personalization profile or tracking name [string]
- \$cat ... category [profile, tracking]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

### Output

result array

# 7.1.99 deletepersonalization

## Description

This function deletes a customer personalization tracking or profile

# **Syntax**

deletepersonalization (\$site, \$pers\_name, \$cat)

# Input parameters

- \$site ... publication name [string]
- \$pers\_name ... personalization profile or tracking name [string]
- \$cat ... category [profile, tracking]

## global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.100 loadtemplate

# Description

This function loads templates by given name.

Based on the inheritance settings of the publication the template will be loaded with highest priority from the own publication and if not available from a parent publication. If the parent publications have double entries the sort mechanism will define the priority. First priority have numbers, second are upper case letters and last priority have lower case letters.

### **Syntax**

loadtemplate (\$site, \$template)

- \$site ... publication name [string]
- \$template ... template file name [string]

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

- array (template content [XML string]
- publication
- result[true/false]) / false on error

# 7.1.101 createtemplate

# Description

This function creates a new template

# **Syntax**

createtemplate (\$site, \$template, \$cat)

# Input parameters

- \$site ... publication name [string]
- \$template ... template name [string]
- \$cat ... category [page, comp, meta, inc]

## global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.102 edittemplate

# Description

This function edites a template

# **Syntax**

edittemplate (\$site, \$template, \$cat, \$user, \$content="", \$extension="", \$application="")

- \$site ... publication name [string]
- \$template ... template file name [string]
- \$cat ... category [page, comp, meta, inc]

- \$user ... user name [string]
- \$content ... template content [string] (optional)
- \$extension ... template extension [string] (optional)
- \$application ... template application [string] (optional)

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.103 deletetemplate

## Description

This function deletes a template

# **Syntax**

deletetemplate (\$site, \$template, \$cat)

# Input parameters

- \$site ... publication name [string]
- \$template ... template file name [string]
- \$cat ... category [page, comp, meta, inc]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.104 createportal

#### Description

This function creates a new portal template

# **Syntax**

createportal (\$site, \$template)

- \$site ... publication name [string]
- \$template ... portal template name [string]

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.105 editportal

## Description

This function edites the settings of a portal.

#### **Syntax**

editportal (\$site, \$template, \$portaluser, \$design="day", \$primarycolor="", \$global\_files=array(), \$formats="", \$user="sys")

# Input parameters

- \$site ... publication name [string]
- \$template ... template name or file name [string]
- \$portaluser ... portal user name [string]
- \$design ... design theme name [string] (optional)
- \$primarycolor ... primary color as hex code [string] (optional)
- \$global\_files ... PHP global FILES variable for file upload/remove [array] (optional)
- \$formats ... download formats [JSON-string] (optional)
- \$user ... user name [string] (optional)

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

result array

# 7.1.106 deleteportal

## Description

This function deletes a portal

# **Syntax**

deleteportal (\$site, \$template)

### Input parameters

- \$site ... publication name [string]
- \$template ... template file name [string]

## global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.107 createuser

## Description

This function creates a new user. Use \*Null\* for publication name to remove access to all publications.

# **Syntax**

createuser (\$site="", \$login, \$password, \$confirm\_password, \$user="sys")

## Input parameters

- \$site ... publication name [string] (optional)
- \$login ... user login name [string]
- \$password ... password [string]
- \$confirm\_password ... confirmed password [string]
- \$user ... user name [string] (optional)

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$mgmt\_lang\_shortcut\_default
- \$hcms\_lang
- \$lang

## **Output**

result array

## 7.1.108 edituser

## Description

This function edits a user. Use \*Leave\* as input if a value should not be changed. Use \*Null\*

for publication name to remove access to all publications. Use \*Null\* for user group to remove user from all user groups of the publication.

## **Syntax**

```
edituser ($site="", $login, $old_password="", $password="", $confirm_password="", $superadmin="0", $realname="*Leave*", $language="en", $timezone="*Leave*", $theme="*Leave*", $signature="*Leave*", $susergroup="*Leave*", $usersite="*Leave*", $validdatefrom="*Leave*", $validdatefrom="*Leave*", $validdateto="*Leave*", $
```

# Input parameters

- \$site ... publication name [string]
- \$login ... user login name [string]
- \$old\_password ... new login name [string] (optional)
- \$password ... password [string] (optional)
- \$confirm\_password ... confirmed password [string] (optional)
- \$superadmin ... super administrator [0, 1] (optional)
- \$realname ... real name [string] (optional)
- \$language ... language setting [en, de, ...] (optional)
- \$timezone ... time zone [string] (optional)
- \$theme ... theme name (optional)
- \$email ... email [string] (optional)
- \$phone ... phone [string] (optional)
- \$signature ... signature [string] (optional)
- \$usergroup ... member of usergroup string [group1|group2] (optional)
- \$usersite ... member of publications string [site1|site2] (optional)
- \$validdatefrom ... valid date from [date] (optional)
- \$validdateto ... valid date to [date] (optional)
- \$user ... user name [string] (optional)

### global input parameters

- \$eventsystem
- \$login\_cat
- \$group
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

result array

# 7.1.109 deleteuser

#### Description

This function removes a user

#### **Syntax**

deleteuser (\$site, \$login, \$user="sys")

- \$site ... publication where the user should be removed [\*Null\*] for all publications [string]
- \$login ... login name of the account that will be removed [string]
- \$user ... user name [string]

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.110 creategroup

## **Description**

This function creates a new user group

## **Syntax**

creategroup (\$site, \$groupname, \$user="sys")

# Input parameters

- \$site ... publication name [string]
- \$groupname ... group name [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.111 editgroup

# Description

This function edits the settings of a user group. The following permissions can be used: desktopglobal desktopsetting desktoptaskmgmt desktopcheckedout desktoptimetravel userglobal

usercreate

userdelete

useredit

groupglobal

groupcreate

groupdelete

groupedit

siteglobal

sitecreate

sitedelete

siteedit

persglobal

perstrack

perstrackcreate

perstrackdelete

perstrackedit

persprof

persprofcreate

persprofdelete

persprofedit

workflowglobal

workflowproc

workflowproccreate

workflowprocdelete

workflowprocedit

workflowprocfolder

workflowscript

workflowscriptcreate

workflowscriptdelete

workflowscriptedit

templateglobal

tpl

tplcreate

tpldelete

tpledit

tplmedia

tplmediacatcreate

tplmediacatdelete

tplmediacatrename

tplmediaupload

tplmediadelete

componentglobal

compupload

compdownload

compsendlink

compfoldercreate

compfolderdelete

compfolderrename

compcreate

compdelete

comprename

comppublish

pageglobal

pagesendlink

pagefoldercreate

pagefolderdelete

pagefolderrename

pagecreate

pagedelete

pagerename

pagepublish

The value of each parameter can be 1 for granted permission or 0 for no permission. If you need further explanation about the permissions, please have a look at the Administrators Guide.

### **Syntax**

editgroup (\$site, \$groupname, \$pageaccess, \$compaccess, \$permission, \$user)

# Input parameters

- \$site ... publication name [string]
- \$groupname ... group name [string]
- \$pageaccess ... page folder access array [array]
- \$compaccess ... component folder access array [array]
- \$permission ... permissions with permission name as key and value of 1 or 0 [array]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

result array

# 7.1.112 deletegroup

#### Description

This function removes a user group

#### **Syntax**

deletegroup (\$site, \$groupname, \$user)

# Input parameters

- \$site ... publication name [string]
- \$groupname ... group name [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

#### **Output**

result array

# 7.1.113 renamegroupfolder

# Description

This function renames a workgroup folder

#### **Syntax**

renamegroupfolder (\$site, \$cat, \$folder\_curr, \$folder\_new, \$user)

# Input parameters

- \$site ... publication name [string]
- \$cat ... category [page, comp]
- \$folder\_curr ... old location [string]
- \$folder\_new ... new location [string]
- \$user ... user name [string]

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• true / false on error

# 7.1.114 deletegroupfolder

# Description

This function removes a group folder.

#### Syntax

deletegroupfolder (\$site, \$cat, \$folderpath, \$user)

# Input parameters

- \$site ... publication name [string]
- \$cat ... category [page, comp]
- \$folderpath ... path to the folder [string]
- \$user ... user name [string]

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• true / false on error

# 7.1.115 renameworkflowfolder

### Description

This function renames a workgroup folder

### **Syntax**

renameworkflowfolder (\$site, \$cat, \$folder\_curr, \$folder\_new, \$user)

# Input parameters

- \$site ... publication name [string]
- \$cat ... category [page, comp]
- \$folder\_curr ... old location [string]
- \$folder\_new ... new location [string]
- \$user ... user name [string]

#### global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• true / false on error

# 7.1.116 deleteworkflowfolder

### **Description**

This function removes a workgroup folder

#### Syntax

deleteworkflowfolder (\$site, \$cat, \$folderpath, \$user)

# Input parameters

- \$site ... publication name [string]
- \$cat ... category [page, comp]
- \$folderpath ... location of folder [string]
- \$user ... user name [string]

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• true / false on error

# 7.1.117 createmediacat

### **Description**

Creates a new media category in the template media index file. Only used for template media.

#### **Syntax**

createmediacat (\$site, \$mediacat\_name)

#### Input parameters

- \$site ... publication name [string]
- \$mediacat\_name ... media category name [string]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

Array with onload JS-code and message

# 7.1.118 renamemediacat

### Description

Renames a new media category in the template media index file

#### Syntax

renamemediacat (\$site, \$mediacat\_name\_curr, \$mediacat\_name)

# Input parameters

- \$site ... publication name [string]
- \$mediacat\_name\_curr ... old media category name [string]
- \$mediacat\_name ... new media category name [string]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

Array with onload JS-code and message

# 7.1.119 deletemediacat

# Description

Deletes a new media category in the template media index file

#### **Syntax**

deletemediacat (\$site, \$mediacat\_name)

# Input parameters

- \$site ... publication name [string]
- \$mediacat\_name ... media category name [string]

#### global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

Array with onload JS-code and message

# 7.1.120 uploadtomediacat

#### **Description**

Uploads a media file into a given template media category

#### **Syntax**

uploadtomediacat (\$site, \$mediacat\_name, \$global\_files)

# Input parameters

- \$site ... publication name [string]
- \$mediacat\_name ... media category name [string]
- \$global\_files ... PHP global FILES variable [array]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

Array with onload JS-code and message

# 7.1.121 deletefrommediacat

### Description

Deletes a media file from the template media category index

#### **Syntax**

deletefrommediacat (\$site, \$mediafile)

# Input parameters

- \$site ... publication name [string]
- \$mediafile ... media file name [string]

### global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

Array with onload JS-code and message

#### 7.1.122 createfolder

#### **Description**

This function creates a new folder. The folder name must not match any temp file pattern.

#### **Syntax**

createfolder (\$site, \$location, \$folder, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$folder ... folder name [string]
- \$user ... user name [string]

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

result array

# 7.1.123 createfolders

# Description

This function creates all folders recursively

#### Syntax

createfolders (\$site, \$location, \$folder, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$folder ... folder name [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.124 collectfolders

#### Description

Help function to create the collection of folders

#### **Syntax**

collectfolders (\$site, \$location, \$folder)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$folder ... folder name [string]

#### global input parameters

\$user

- \$mgmt\_config
- \$hcms\_lang
- \$lang

result array / false

# 7.1.125 copyfolders

# Description

This function copies/creates all folders of the source location using mkdir (only directories will be created!). Used by pasteobject function.

#### Syntax

copyfolders (\$site, \$location, \$locationnew, \$folder, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location (source) [string]
- \$locationnew ... new location (destination) [string]
- \$folder ... folder name [string]
- \$user ... user name [string]

#### global input parameters

- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

# Output

· result array equal to createfolder

#### 7.1.126 deletefolder

# Description

This function removes a folder. The folder must be empty in order to be removed from the system.

#### Syntax

deletefolder (\$site, \$location, \$folder, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]

- \$folder ... folder name [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

### Output

result array

# 7.1.127 renamefolder

#### **Description**

This function renames a folder

#### Syntax

renamefolder (\$site, \$location, \$folder, \$foldernew, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$folder ... folder name [string]
- \$foldernew ... new folder name [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

# **Output**

result array

# 7.1.128 correct container name

### Description

This function adds zeros to the container ID to create the correct file name of the content container.

#### **Syntax**

correctcontainername (\$container\_id)

#### Input parameters

\$container\_id ... container ID [string]

# Output

corrected name / false on error

# 7.1.129 createobject

#### Description

This function creates a new page or component.

## **Syntax**

createobject (\$site, \$location, \$page, \$template, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name without file extension [string]
- \$template ... template name [string]
- \$user ... user name [string]

### global input parameters

- \$eventsystem
- \$mgmt\_config
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang\$lang

### Output

result array

# 7.1.130 uploadfile

# Description

This function manages all file uploads, like unzip files, zip a collection of files, create media objects and resize images.

The container name will be extracted from the media file name for updating an existing multimedia file.

# **Syntax**

uploadfile (\$site, \$location, \$cat, \$global\_files, \$page="", \$unzip="", \$createthumbnail=0, \$imageresize="", \$imagepercentage="", \$user="sys", \$checkduplicates=true, \$versioning=false, \$zipfilename="", \$zipfilecount=0)

#### Input parameters

- \$site ... publication name [string]
- \$location ... destination location [string]
- \$cat ... category [page, comp]
- \$global\_files ... uploaded file (array as defined by PHP autoglobale \$\_FILES) [array]
- \$page ... unzip/zip [%, unzip, zip]
- \$unzip ... object name (only for media file update of existing object) [string]
- \$createthumbnail ... create only a new thumbnail from the media file [1, 0] (optional)
- \$imageresize ... resize image [percentage, null] (optional)
- \$imagepercentage ... image resize percentage value [integer] (optional)
- \$user ... user name [string] (optional)
- \$checkduplicates ... check for duplicates [boolean] (optional)
- \$versioning ... versioning of file [boolean] (optional)
- \$zipfilename ... name of zip file [string] (optional)
- \$zipfilecount ... number of files to be compressed [integer] (optional)

#### global input parameters

- \$mgmt\_config
- \$mgmt\_uncompress
- \$mgmt\_compress
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions
- \$mgmt\_maxsizepreview
- \$mgmt parser
- \$eventsystem
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$localpermission
- \$hcms\_lang
- \$lang

# **Output**

result array

#### 7.1.131 createmediaobject

# Description

This function creates an asset (multimedia object) by reading a given source file. The file name must not match any temp file pattern.

The metadata template is based on the template of the folder the objects resides in.

### **Syntax**

createmediaobject (\$site, \$location, \$file, \$path\_source\_file, \$user, \$imagepercentage=0, \$leavefile=false)

### Input parameters

- \$site ... publication name [string]
- \$location ... destination location [string]
- \$file ... file name [string]
- \$path\_source\_file ... path to source multimedia file (uploaded file in temp directory) [string]
- \$user ... user name [string]
- \$imagepercentage ... resize original image (100%) by percentage [integer] (optional)
- \$leavefile ... leave file in the directory and create a symbolic link to the file [boolean] (optional)

### global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions
- \$mgmt\_maxsizepreview
- \$mgmt\_mediametadata
- \$mgmt\_parser
- \$mgmt\_imagepreview
- \$mgmt\_uncompress
- \$hcms\_ext
- \$eventsystem
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.132 createmediaobjects

### Description

This function creates media objects by reading all media files from a given source location (used after unzipfile).

The file name must not match any temp file pattern.

#### **Syntax**

createmediaobjects (\$site, \$location\_source, \$location\_destination, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location\_source ... source location [string]

- \$location\_destination ... destination location [string]
- \$user ... user name [string]

## global input parameters

- \$mgmt\_config
- \$mgmt\_imageoptions
- \$eventsystem
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

### Output

result array with all objects created / false

# 7.1.133 editmediaobject

#### **Description**

This function mainly uses function createmedia to render the objects media, but at the same time takes care of versioning and the object name, if the file extension has been changed

#### **Syntax**

editmediaobject (\$site, \$location, \$page, \$format="jpg", \$type="thumbnail", \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$format ... format (file extension w/o dot) [string] (optional)
- \$type ... type of image/video/audio file [thumbnail, origthumb(thumbail made from original video/audio), original, any other string present in \$mgmt\_imageoptions] (optional)
- \$mediadata ... base64 encoded media data as alternative to server-side conversion using createmedia [string] (optional)
- \$user ... user name [string]

- \$wf\_token
- \$mgmt\_config
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions
- \$mgmt\_maxsizepreview
- \$mgmt\_mediametadata
- \$hcms\_ext
- \$hcms\_lang
- \$lang

- result array / false on error (saves original or thumbnail media file of an object
- for thumbnail only jpeg format is supported as output)
- user name

# 7.1.134 manipulateobject

# Description

This function removes, unpublishs, renames and pastes objects and is used by other functions which works as a shell for this function

#### **Syntax**

manipulateobject (\$site, \$location, \$page, \$pagenew, \$user, \$action, \$clipboard\_array=array())

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$pagenew ... new object name (exkl. extension except for action "file\_rename") [string]
- \$user ... user name [string]
- \$action ... action [page\_delete
- \$clipboard\_array ... page\_rename

# global input parameters

- \$wf\_token
- \$eventsystem
- \$mgmt\_config
- \$mgmt\_mediaoptions
- \$mgmt\_docoptions
- \$hcms\_ext
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$cat
- \$hcms\_lang
- \$lang

# Output

array

# 7.1.135 deletemarkobject

#### **Description**

This function marks a page, asset, or component as deleted.

#### **Syntax**

deletemarkobject (\$site, \$location, \$page, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]

# global input parameters

- \$wf\_token
- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.136 deleteunmarkobject

### Description

This function unmarks a page, asset, or component as deleted.

# **Syntax**

deleteunmarkobject (\$site, \$location, \$page, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]

- \$wf\_token
- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

result array

# 7.1.137 deleteobject

#### **Description**

This function removes a page, asset, or component by calling the function manipulateobject.

#### Syntax

deleteobject (\$site, \$location, \$page, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

#### **Output**

result array

# 7.1.138 renameobject

# Description

This function renames a page, component or asset and calls the function manipulateobject

#### **Syntax**

renameobject (\$site, \$location, \$page, \$pagenew, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$pagenew ... new object name without file extension [string]
- \$user ... user name [string]

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

result array

#### 7.1.139 renamefile

#### Description

This function renames a file (NOT a page, component or asset) and calls the function manipulateobject.

This function renames the file name including the extension and not only the name of an object.

The event that will be executed in the event system is the same as for renameobject.

#### **Syntax**

renamefile (\$site, \$location, \$page, \$pagenew, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$pagenew ... new object including file extension [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

#### Output

result array

# 7.1.140 cutobject

#### Description

This function cuts a page, component or asset.

#### **Syntax**

cutobject (\$site, \$location, \$page, \$user, \$clipboard\_add=false, \$clipboard\_session=true)

### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]
- \$clipboard\_add ... add to existing clipboard entries [boolean] (optional)
- \$clipboard\_session ... save clipboard in session [boolean] (optional)

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.141 copyobject

### Description

This function copies a page, component or asset.

#### **Syntax**

copyobject (\$site, \$location, \$page, \$user, \$clipboard\_add=false, \$clipboard\_session=true)

### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]
- \$clipboard\_add ... add to existing clipboard entries [boolean] (optional)
- \$clipboard\_session ... save clipboard in session [boolean] (optional)

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$hcms\_lang
- \$lang

#### **Output**

result array

# 7.1.142 copyconnectedobject

### Description

This function makes a connected copy of a page, component or asset.

#### **Syntax**

copyconnectedobject (\$site, \$location, \$page, \$user, \$clipboard\_add=false, \$clipboard\_session=true)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]
- \$clipboard\_add ... add to existing clipboard entries [boolean] (optional)
- \$clipboard\_session ... save clipboard in session [boolean] (optional)

### global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.143 pasteobject

### Description

This function pastes an object by calling and calls the function manipulateobject

### **Syntax**

pasteobject (\$site, \$location, \$user, \$clipboard\_array=array())

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$user ... user name [string]
- \$clipboard\_array ... clipboard entries [array] (optional)

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking

- \$hcms\_lang
- \$lang

result array

# 7.1.144 lockobject

# Description

This function locks an object for a specific user

#### **Syntax**

lockobject (\$site, \$location, \$page, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.145 unlockobject

#### **Description**

This function unlocks an object of a specific user

#### **Syntax**

unlockobject (\$site, \$location, \$page, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]

#### global input parameters

• \$eventsystem

- \$mgmt\_config
- \$cat
- \$hcms\_lang
- \$lang

array

# 7.1.146 publishobject

### Description

This function publishes a page, component or asset

#### Syntax

publishobject (\$site, \$location, \$page, \$user)

# Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name (full name incl. extension) [string]
- \$user ... user name [string]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$ctrlreload
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

### Output

result array

# 7.1.147 publishlinkedobject

### Description

This function publishes all linked objects of a given object.

All objects with component links (references) to the given object will be published. This funtion is only used by publishobject.

#### Syntax

publishlinkedobject (\$site, \$location, \$page, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]

### global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$ctrlreload
- \$hcms\_lang
- \$lang

# Output

array

# 7.1.148 unpublishobject

### Description

This function unpublishes a page, component, or asset and calls the function manipulateobject

#### **Syntax**

unpublishobject (\$site, \$location, \$page, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$user ... user name [string]

### global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$ctrlreload
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.149 processobjects

#### **Description**

Publish, unpublish or delete all objects recursively, and send mails stored in the queue. This function is used by the job 'minutely' to process all objects of the queue.

In order to process all objects recursively a folder name need to be provided and not the .folder file.

This function should not be used for the graphical user interface since it does not provide feedback about the process state!

## **Syntax**

processobjects (\$action, \$site, \$location, \$file, \$published\_only=false, \$user)

### Input parameters

- \$action ... action [publish, unpublish, delete]
- \$site ... publication name [string]
- \$location ... location [string]
- \$file ... object name or mail ID [string]
- \$published\_only ... only published objects [boolean]
- \$user ... user name [string]

#### global input parameters

- \$eventsystem
- \$mgmt\_config
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$hcms\_lang
- \$lang

# Output

true/false

# 7.1.150 collectobjects

# Description

Help function used to create a list of all objects inside a folder

#### **Syntax**

collectobjects (\$root\_id, \$site, \$cat, \$location, \$published\_only=false)

#### Input parameters

- \$root\_id ... root ID [string]
- \$site ... publication name [string]
- \$cat ... category [page, comp]
- \$location ... location [string]
- \$published\_only ... collect only published objects [boolean]

- \$user
- \$pageaccess
- \$compaccess
- \$mgmt\_config
- \$hiddenfolder
- \$hcms\_lang
- \$lang

result array / false

# 7.1.151 manipulateallobjects

#### Description

This function is used to perform actions on multiple objects and is mainly used by popup\_status.php.

This function should only be used in connection with the GUI of the system.

#### **Syntax**

manipulateallobjects (\$action, \$objectpath\_array, \$method="", \$force="start", \$published\_only=false, \$user, \$tempfile="", \$maxitems=10)

#### Input parameters

- \$action ... action [publish
- \$objectpath\_array ... unpublish
- \$method ... deletemark
- \$force ... deleteunmark/restore
- \$published\_only ... emptypin
- \$user ... delete
- \$tempfile ... paste]
- \$maxitems ... objectpath [array]

# global input parameters

- \$eventsystem
- \$mgmt\_config
- \$cat
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_lang
- \$lang

# Output

true/false

# 7.1.152 createqueueentry

#### Description

Creates a new item in the queue

### **Syntax**

createqueueentry (\$action, \$object, \$date, \$published\_only, \$data="", \$user)

#### Input parameters

- \$action ... action [publish, unpublish, delete, mail]
- \$object ... object path [string] or object ID [integer]
- \$date ... date and time [YYY-MM-DD HH:MM]
- \$published\_only ... publish only published objects [boolean]
- \$data ... data to be saved in queue [array] (optional)
- \$user ... user name [string]

### global input parameters

• \$mgmt\_config

### Output

true / false

# 7.1.153 savemessage

#### Description

Saves the data of a sent e-mail message.

# **Syntax**

savemessage (\$data, \$type="mail", \$user)

#### Input parameters

- \$data ... data to be saved in queue [array]
- \$type ... message type [mail, chat] (optional)
- \$user ... user name [string]

# global input parameters

\$mgmt\_config

#### Output

• true / false

#### 7.1.154 remoteclient

# Description

Sends data to remote client via http post

#### **Syntax**

remoteclient (\$action, \$root, \$site, \$location, \$locationnew, \$page, \$pagenew)

#### Input parameters

- \$action ... action [save, copy, delete, rename, get]
- \$root ... root [abs\_path\_link, abs\_path\_media, abs\_path\_comp, abs\_path\_page, abs\_path\_rep]
- \$site ... publication name [string]
- \$location ... location [string]
- \$locationnew ... new location [string]
- \$page ... object name [string]
- \$pagenew ... new object name [string]

### global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• http answer [string] or false

# 7.1.155 HTTP\_Post

## Description

Sends data via http post and returns response

#### **Syntax**

HTTP\_Post (\$URL, \$data, \$contenttype="application/x-www-form-urlencoded", \$charset="UTF-8", \$referrer="")

## Input parameters

- \$URL ... URL [string]
- \$data ... data (raw data) [array]
- \$contenttype ... content-type [application/x-www-form-urlencoded, multipart/form-data]
- \$charset ... character set [string]
- \$referrer

#### Output

• http response [string] / false on error

# 7.1.156 HTTP\_Get

#### Description

Sends data via http get and returns response

#### **Syntax**

HTTP\_Get (\$URL, \$data="", \$contenttype="application/x-www-form-urlencoded", \$charset="UTF-8")

#### Input parameters

- \$URL ... URL [string]
- \$data ... data (raw data) [array] (optional)
- \$contenttype ... content-type [string excl. charset] (optional)
- \$charset ... character set [string] (optional)

• http response [string] / false on error

# 7.1.157 HTTP\_Proxy

#### **Description**

Sends all global POST/GET and FILES data via http post and returns response

#### Syntax

HTTP\_Proxy (\$URL, \$enable\_file=false)

# Input parameters

- \$URL ... URL [string]
- \$enable\_file ... enable post of files [boolean] (optional)

# global input parameters

• \$mgmt\_config

#### Output

• http response [string] / false on error

#### 7.1.158 loadbalancer

#### Description

Balances the load by sending all global POST/GET and FILES to one service ressource of a given array of service ressources.

Don't define and use the same server ressources in \$mgmt\_config['url\_path\_service'], this can lead to an infinite loop.

# **Syntax**

loadbalancer (\$type)

# Input parameters

• \$type ... type [renderimage, rendervideo, uploadfile]

# global input parameters

\$mgmt\_config

# Output

• http response [string] / false on error or if disabled

# 7.1.159 savelog

# Description

Adds new entries to log file.

An error entry must be formed like:

date[YYYY-MM-DD hh: mm] | name of scipt file | error type: "error", "warning" or "information" | unique error code in script file | error message

# **Syntax**

savelog (\$error, \$logfile="event")

#### Input parameters

- \$error ... error log entries [array]
- \$logfile ... name of log file without extension [string] (optional)

# global input parameters

- \$user
- \$login
- \$site
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• true / false on error

# 7.1.160 loadlog

# Description

Loads a log file an returns the data as string or array for all log records.

# **Syntax**

loadlog (\$logfile="event", \$return\_type="array")

# Input parameters

- \$logfile ... name of log file without extension [string] (optional)
- \$return\_type ... return type [string, array] (optional)

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

• true / false on error

# 7.1.161 deletelog

# Description

Deletes a log file.

#### **Syntax**

deletelog (\$logname="")

# Input parameters

• \$logname ... log name [string] (optional)

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.1.162 debuglog

# Description

Writes code lines into debug file in data/log/debug.log

# **Syntax**

debuglog (\$code)

# Input parameters

• \$code ... code to write to debug file [string]

# global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• true / false

# 7.1.163 notifyusers

### Description

Notifies all users based on the given event and location

#### **Syntax**

notifyusers (\$site, \$location, \$object, \$event, \$user\_from)

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$object ... object name [string]
- \$event ... event name [oncreate, onedit, onmove, ondelete]
- \$user\_from ... user name [string]

#### global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

# Output

true / false on error

# 7.1.164 sendlicensenotification

#### Description

Searches for objects with a date in a defined text field that has to be between the defined date limits and sends a message to the defined users.

This is a helper function for function licensenotification.

### **Syntax**

sendlicensenotification (\$site, \$cat, \$folderpath, \$text\_id, \$date\_begin, \$date\_end, \$user, \$format="%Y-%m-%d")

# Input parameters

- \$site ... publication name [string]
- \$cat ... category [page, comp]
- \$folderpath ... folder path [string]
- \$text\_id ... text ID for text field [string]
- \$date\_begin ... search from date [YYYY-MM-DD]
- \$date\_end ... search till date [YYYY-MM-DD]
- \$user ... user name [string or array] (optional)
- \$format ... date format (optional)

- \$eventsystem
- \$mgmt\_config

- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

• true / false on error

# 7.1.165 licensenotification

# Description

This function reads the license notification configuration and looks up all objects with a date in a defined text field

that has to be between the defined date limits and sends a message to the defined users.

#### **Syntax**

licensenotification ()

# Input parameters

# global input parameters

- \$eventsystem
  - \$mgmt\_config
  - \$hcms\_lang\_codepage
  - \$hcms\_lang
  - \$lang

# Output

• true / false on error

# 7.1.166 sendresetpassword

# Description

Send a new password to the users e-mail address.

# **Syntax**

sendresetpassword (\$login, \$link=false, \$instance="")

# Input parameters

- \$login ... user name [string]
- \$link ... provide logon link [boolean] (optional)
- \$instance ... instance name [string] (optional)

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

message as string

# 7.1.167 html\_diff

#### **Description**

Paul's Simple Diff Algorithm v 0.1

Function html\_diff is a wrapper for the diff command, it takes two strings and returns the differences in HTML. The tags used are <ins> and <del>, which can easily be styled with CSS.

# **Syntax**

html\_diff (\$old, \$new)

# Input parameters

- \$old ... old text [string]
- \$new ... new text [string]

#### Output

• result text showing deleted and inserted words/differences / false on error

#### 7.1.168 createfavorite

### **Syntax**

createfavorite (\$site="", \$location="", \$page="", \$id="", \$user)

# Input parameters

- \$site ... publication name [string] (optional)
- \$location ... location [string] (optional)
- \$page ... object name [string] (optional)
- \$id ... identifier (object ID
- \$user ... object hash) [string] (optional)

#### global input parameters

\$mgmt\_config

# Output

true / false

# 7.1.169 deletefavorite

### **Syntax**

deletefavorite (\$site="", \$location="", \$page="", \$id="", \$user)

# Input parameters

- \$site ... publication name [string] (optional)
- \$location ... location [string] (optional)
- \$page ... object name [string] (optional)
- \$id ... identifier (object ID
- \$user ... object hash) [string] (optional)

# global input parameters

• \$mgmt\_config

#### Output

true / false

# 7.1.170 rewrite\_targetURI

# **Syntax**

rewrite\_targetURI (\$site, \$text\_id, \$uri, \$exclude\_dir\_esc="", \$rewrite\_type="include")

#### Input parameters

- \$site ... publication name [string]
- \$text\_id ... text ID array (text-ID as key and URL parameters as value) [string]
- \$uri ... requested URI [string]
- \$exclude\_dir\_esc ... exclude path [array] (optional)
- \$rewrite\_type ... rewrite type [none, forward, include] (optional)

# global input parameters

- \$mgmt\_config
- \$publ\_config

#### Output

• HTTP header with target URL as location / false on error

# 7.1.171 rewrite\_homepage

#### Description

Uses the page root directory of the publication configuration and forwards to the default index page. No page include supported!

#### **Syntax**

rewrite\_homepage (\$site, \$rewrite\_type="forward")

#### Input parameters

- \$site ... publication name [string]
- \$rewrite\_type ... rewrite type [none, forward] (optional)

- \$mgmt\_config
- \$publ\_config

HTTP header with target URL as location / false on error

# 7.1.172 load\_csv

### **Description**

Analyzes the content from the CSV file and detects delimiter and enclosure characters if left empty. On success the data will be returned as array starting with row index of 1.

#### **Syntax**

load\_csv (\$file, \$delimiter=";", \$enclosure=""', \$charset\_from="utf-8", \$charset\_to="utf-8")

#### Input parameters

- \$file ... path to CSV file [string]
- \$delimiter ... delimiter [string] (optional)
- \$enclosure ... enclosure [string] (optional)
- \$charset\_from ... character set of source data [string] (optional)
- \$charset\_to ... character set of output data [string] (optional)

# global input parameters

- \$mgmt\_config
- \$eventsystem

#### **Output**

• array / false on error

### 7.1.173 create\_csv

#### **Description**

Creates a CSV file from an associative data array and returns the file as download or writes the file to the file system if a valid path to a directory has been provided.

For support of MS Excel the encoding should be UTF-16LE in older versions or an UTF-8 BOM need to be added for newer versions of Excel.

#### **Syntax**

create\_csv (\$assoc\_array, \$filename="export.csv", \$filepath="php://output", \$delimiter=";", \$enclosure="'", \$charset\_from="utf-8", \$charset\_to="utf-8", \$add\_bom=false)

#### Input parameters

- \$assoc\_array ... associative data with row-id and column name as keys [array]
- \$filename ... file name [string] (optonal)
- \$filepath ... file path for saving the CSV file [string] (optional)
- \$delimiter ... delimiter [string] (optional)

- \$enclosure ... enclosure [string] (optional)
- \$charset\_from ... character set of input data [string] (optional)
- \$charset\_to ... character set of output data [string] (optional)
- \$add\_bom ... add UTF-8 BOM [boolean] (optional)

true / false on error

# 7.1.174 sendmessage

### Description

Sends a message via e-mail to a user.

#### **Syntax**

sendmessage (\$from\_user="", \$to\_user, \$title, \$message, \$object\_id="", \$site="")

#### Input parameters

- \$from\_user ... from user name [string] (optional)
- \$to\_user ... to user name [string]
- \$title ... title [string]
- \$message ... message [string]
- \$object\_id ... object ID or object path [string] (optional)
- \$site ... publication name [string] (optional)

#### global input parameters

- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

#### **Output**

true/false

# 7.1.175 linking\_valid

#### Description

Verifies if a valid access linking exists.

#### **Syntax**

linking\_valid ()

#### Input parameters

- \$mgmt\_config
- \$hcms\_linking

true/false

## 7.1.176 linking\_objects

### Description

Returns the all objects of an access link as an array.

#### Syntax

linking\_objects (\$return\_text\_id=array())

#### Input parameters

• \$return\_text\_id ... %

## global input parameters

- \$mgmt\_config
- \$hcms\_linking

### Output

• result array / false on error

# 7.1.177 linking\_inscope

#### **Description**

Verifies if the provided location path is in the scope of the access linking.

#### **Syntax**

linking\_inscope (\$site="", \$location, \$page="", \$cat="")

### Input parameters

- \$site ... publication name [string] (optional)
- \$location ... location [string]
- \$page ... object name [string] (optional)
- \$cat ... object category [comp, page] (optional)

### global input parameters

- \$mgmt\_config
- \$hcms\_linking

### Output

true/false

### 7.1.178 savecontent

#### **Description**

Saves the provided content for a specific object. Only the provided content based on its ID will be saved. Existing content with a different ID will not be deleted.

```
Example of a page content array as content input:
array(
array(
"pagetitle" = > "My Page",
"pageauthor" = > "Thomas Tester",
"pagedescription"=>"Just an example"
),
array(
"id"=>"MyText",
"textu"=>"I am a text"
array(
"id"=>"MyImage",
"mediaobject" = > "%comp%/myPublication/image.jpg",
"mediaalttext"=>"This is my image",
"mediaalign"=>"top",
"mediawidth"=>"260"
"mediaheight"=>"140",
),
array(
"id"=>"MyLink",
"linkhref" = > "http://www.hypercms.com",
"linktarget" = > "_SELF",
"linktext"=>"hyperCMS Home"
),
array(
"id" = > "MyComponent",
"componentm"=>"%comp%/comp_1.html|%comp%/comp_2.html",
"condition"=>""
)
)
```

#### **Syntax**

savecontent (\$site, \$location, \$page, \$content, \$charset="UTF-8", \$user, \$db\_connect="")

### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$content ... content array with 1st key as index number and 2nd keys as id or name according to the template tags [array]
- \$charset ... character set [string] (optional)
- \$user ... user name [string]
- \$db\_connect ... DB connectivity file name [string] (optional)

## global input parameters

- \$mgmt\_config
- \$lang
- \$hcms\_lang
- \$eventsystem

- \$rootpermission
- \$globalpermission
- \$localpermission
- \$siteaccess
- \$pageaccess
- \$compaccess
- \$adminpermission
- \$hiddenfolder

true/false

## 7.2 Get API Functions

## 7.2.1 getserverload

#### **Syntax**

getserverload (\$interval=0)

### Input parameters

• \$interval ... intervall for average system load can be 1

## Output

- Returns the average system load (the number of processes in the system run queue) over the last minute
- the number of CPU cores
- and the memory usage as array

### 7.2.2 getconfigvalue

#### Description

Help function for createinstance

#### Syntax

getconfigvalue (\$config, \$in\_key="")

## Input parameters

- \$config ... settings [array]
- \$in\_key ... value/substring in array key [string] (optional)

#### **Output**

value of setting

## 7.2.3 getsession

# Syntax

getsession (\$variable, \$default="")

#### Input parameters

- \$variable ... session variable name [string]
- \$default ... default session value [string] (optional)

### Output

session value

### 7.2.4 getrequest

#### **Description**

Returns the value of a POST, GET or COOKIE request, or a default value if not valid.

### **Syntax**

getrequest (\$variable, \$force\_type=false, \$default="")

#### Input parameters

- \$variable ... request variable name [string]
- \$force\_type ... must be of certain type [numeric, array, publicationname, locationname, objectname, url, bool] (optional)
- \$default ... default value [string] (optional)

## Output

request value

## 7.2.5 getrequest\_esc

#### Description

Returns the escaped value in order to prevent XSS from POST, GET or COOKIE variables. Returns a default value if not valid.

#### **Syntax**

getrequest\_esc (\$variable, \$force\_type=false, \$default="", \$js\_protection=false)

#### Input parameters

- \$variable ... request variable name [string]
- \$force\_type ... must be of certain type [numeric, array, publicationname, locationname, objectname] (optional)
- \$default ... default value [string] (optional)
- \$js\_protection ... remove characters to avoid JS injection [boolean] (optional)

# Output

request value

#### 7.2.6 getuserip

#### **Description**

Retrieves the IP address of the client/user.

#### **Syntax**

getuserip ()

#### Input parameters

### Output

IP address of client / false on error

# 7.2.7 getobjectlistcells

#### **Syntax**

getobjectlistcells (\$viewportwidth, \$is\_mobile=0)

#### Input parameters

- \$viewportwidth ... width of viewport or window in pixels [integer]
- \$is\_mobile ... is mobile device [0, 1] (optional)

#### Output

• number of table cells/rows for the gallery view of object lists

## 7.2.8 getlanguageoptions

## **Syntax**

getlanguageoptions ()

## Input parameters

### global input parameters

\$mgmt\_config

### **Output**

 array with 2-digit language code as key and language name in English as value / false on error

## 7.2.9 getlanguagefile

#### **Syntax**

getlanguagefile (\$lang="en")

#### Input parameters

• \$lang ... language code [string] (optional)

### global input parameters

• \$mgmt\_config

• language file name

## 7.2.10 getcodepage

## **Syntax**

getcodepage (\$lang="en")

### Input parameters

• \$lang ... language code [string] (optional)

### global input parameters

- \$mgmt\_config
- \$hcms\_lang\_codepage

#### Output

• code page (character set)

## 7.2.11 getcalendarlang

#### **Syntax**

getcalendarlang (\$lang="en")

### Input parameters

• \$lang ... language code [string] (optional)

# global input parameters

• \$mgmt\_config

### Output

• supported language code for calendar

# 7.2.12 getscaytlang

#### **Syntax**

getscaytlang (\$lang="en")

### Input parameters

• \$lang ... 2-digits language code [string] (optional)

### global input parameters

• \$mgmt\_config

### Output

• supported language locale for CKEditor scayt plugin

# 7.2.13 getescapedtext

### Description

Returns the synonyms of a word.

#### Syntax

getescapedtext (\$text, \$charset="", \$lang="")

### Input parameters

- \$text ... word [string]
- \$charset ... 2-digit language code [string] (optional)
- \$lang

## global input parameters

• \$mgmt\_config

### Output

• array holding all synonyms including the provided word / false on error

# 7.2.14 getsearchhistory

#### **Syntax**

getsearchhistory (\$user="")

# Input parameters

• \$user ... user name [string] (optional)

### global input parameters

• \$mgmt\_config

## Output

 array holding all expressions (in single quotes) of the search history of a user / false on error

## 7.2.15 gettaxonomy\_sublevel

#### **Description**

Returns sorted keywords of a taxonomy level (multilingual support based on taxonomies). Global variable \$taxonomy can be used to pass the taxonomy as array.

#### **Syntax**

gettaxonomy\_sublevel (\$site, \$lang="en", \$tax\_id="0")

#### Input parameters

- \$site ... publication name [string]
- \$lang ... language code [string] (optional)
- \$tax\_id ... taxonomy parent ID [string] (optional)

### global input parameters

- \$mgmt\_config
- \$taxonomy

#### **Output**

• array holding all keywords of the next taxonomy level / false on error

# 7.2.16 gettaxonomy\_childs

#### Description

Returns keywords based on taxonomy defintion and synonyms if expression is a keyword (multilingual support based on taxonomies and synonyms).

The expression can be a taxonomy path in the form of %taxonomy%/site/language-code/taxonomy-ID/taxonomy-child-levels (use "all" for all languages and "0" for all taxonomy-IDs on first level).

Global variable \$taxonomy can be used to pass the taxonomy as array.

#### **Syntax**

gettaxonomy\_childs (\$site="", \$lang="", \$expression, \$childlevels=1, \$id\_only=true)

#### Input parameters

- \$site ... publication name [string] (optional)
- \$lang ... language code [string] (optional)
- \$expression ... taxonomy ID or expression or taxonomy path in the form %taxonomy%/publication-name or 'default'/language-code/taxonomy-ID/taxonomy-child-levels [string]
- \$childlevels ... taxonomy child levels [integer] (optional)
- \$id\_only ... only return taxonomy IDs without language and keyword information [boolean] (optional)

## global input parameters

- \$mgmt\_config
- \$taxonomy

array holding all taxonomy IDs / false on error

## 7.2.17 gethierarchy\_defintion

#### **Description**

Reads the metadata/content hierarchy defintion and returns a multidimensinal array.

#### Syntax

gethierarchy\_defintion (\$site, \$selectname="")

#### Input parameters

- \$site ... publication name [string]
- \$selectname ... hierarchy name [string] (optional)

### global input parameters

• \$mgmt\_config

### Output

• hierarchy array in form of array[name][level][text-id][language] = label / false on error

## 7.2.18 gethierarchy\_sublevel

### Description

Returns sorted values of a metadata/content hierarchy level.

#### Syntax

gethierarchy\_sublevel (\$hierarchy\_url)

#### Input parameters

• \$hierarchy\_url ... hierarchy URL in form of %hierarchy%/publication-name/hierarchy-name/hierarchy-level-of-last-element/text-ID-1=value-1/text-ID-2=value-2/text-ID-3 [string]

#### global input parameters

- \$mgmt\_config
- \$lang

#### Output

 array holding all hierarchy URLs as key and text content or label as value / false on error

## 7.2.19 getkeywords

#### **Description**

Generates an array holding all keywords and the number as value and keyword ID as key.

#### **Syntax**

getkeywords (\$site="")

## Input parameters

• \$site ... publication name [string] (optional)

#### global input parameters

• \$mgmt\_config

## Output

keywords as array / false on error

## 7.2.20 getmetakeywords

#### **Description**

Generates a keyword list from a plain text. Stop word lists are defined in data/include/stopwords.inc.php

#### **Syntax**

getmetakeywords (\$text, \$language="en", \$charset="UTF-8")

## Input parameters

- \$text ... text [string]
- \$language ... language to be used for stop word list [de, en, ...] (optional)
- \$charset ... character set [string] (optional)

### global input parameters

• \$mgmt\_config

#### Output

keywords as array /false on error

# 7.2.21 getmetadescription

#### **Description**

Generates a description from a text, to be used as meta information.

#### **Syntax**

getmetadescription (\$text, \$charset="UTF-8")

#### Input parameters

- \$text ... text [string]
- \$charset

cleanded description of provided text /false on error

## 7.2.22 getgooglesitemap

#### **Description**

Generates a google sitemap xml-output

#### **Syntax**

getgooglesitemap (\$site, \$dir, \$url, \$getpara=array(), \$permalink=array(), \$chfreq="weekly", \$prio="", \$ignore=array(), \$filetypes=array('cfm', 'htm', 'html', 'xhtml', 'asp', 'aspx', 'jsp', 'php', 'pdf'), \$show\_freq=true, \$show\_prio=true)

### Input parameters

- \$site ... publication name [string]
- \$dir ... directory path [string]
- \$url ... URL to directory [string]
- \$getpara ... GET parameters to use for new versions of the URL as array (optional)
- \$permalink ... permanent links text-ID to use for location [array] (optional)
- \$chfreq ... frequency of google scrawler [never, weekly, daily] (optional)
- \$prio ... priority [1 or less] (optional)
- \$ignore ... ignore file names [array] (optional)
- \$filetypes ... allowed file types [array] (optional)
- \$show\_freq ... include frequenzy tag [boolean] (optional)
- \$show\_prio ... include priority tag [boolean] (optional)

### global input parameters

- \$mgmt\_config
- \$publ\_config

### Output

xml sitemap / false on error

# 7.2.23 getgoogleanalytics

#### Description

Generates a google analytics code segement for embedding.

#### **Syntax**

getgoogleanalytics (\$google\_analytics\_key)

#### Input parameters

• \$google\_analytics\_key ... google analytics key publication name [string]

### global input parameters

• \$mgmt\_config

### Output

• JS code as string / false on error

## 7.2.24 getlistelements

#### Syntax

getlistelements (\$list\_sourcefile)

#### Input parameters

• \$list\_sourcefile ... content attribute value of list or keyword tag

### global input parameters

- \$mgmt\_config
- \$lang

#### Output

• string with list/keyword elements sperated by commas / false

## 7.2.25 getmetadata

## **Syntax**

getmetadata (\$location, \$object, \$container="", \$seperator="\r\n", \$template="")

### Input parameters

- \$location ... location [string]
- \$object ... object name (both optional if container is given) [string]
- \$container ... container name/ID or container content [string] (optional)
- \$seperator ... seperator of meta data fields [any string, array] (optional)
- \$template ... publication name/template name to extract label names [string] (optional)

## global input parameters

• \$mgmt\_config

#### Output

• string with all metadata from given object based on container / false

# 7.2.26 getmetadata\_multiobjects

#### **Description**

Extracts all metadata including media information for a provided list of objects. This function is used for the CSV export in the objectlist views and also evaluates the access permissions of the user.

### **Syntax**

getmetadata\_multiobjects (\$multiobject\_array, \$user)

### Input parameters

- \$multiobject\_array ... converted path of multiple objects [array]
- \$user ... user name [string]

### global input parameters

- \$mgmt\_config
- \$siteaccess
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$adminpermission
- \$localpermission

### Output

assoziatve array with all text content and meta data / false

# 7.2.27 getmetadata\_container

#### Description

Extracts container, media, and metadata information of a container. This function is used for the presentation of metadata for objectlist views.

## **Syntax**

getmetadata\_container (\$container\_id, \$text\_id\_array)

### Input parameters

- \$container\_id ... container ID [string]
- \$text\_id\_array ... array of text IDs [array]

# global input parameters

- \$mgmt\_config
- \$labels

### Output

assoziatve array with all text content and meta data / false

## 7.2.28 getobjectlist

#### **Description**

Get all objects of a location. This is a simplified wrapper for function rdbms\_searchcontent.

#### **Syntax**

getobjectlist (\$site="", \$location="", \$folderhash="", \$objectlistcols=array())

#### Input parameters

- \$site ... publication name [string] (optional)
- \$location ... location [string] (optional)
- \$folderhash ... folder hash code [string] (optional)
- \$objectlistcols ... text IDs to be returned e.g. text: Title [array] (optional)

## global input parameters

• \$mgmt\_config

### **Output**

result array / false on error

# 7.2.29 getobjectcontainer

#### Description

Loads the content container of a given object (page, component, folder).

#### **Syntax**

getobjectcontainer (\$site, \$location, \$object, \$user, \$type="work")

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$object ... object name [string]
- \$user ... user name [string]
- \$type ... container type [work, published] (optional)

### global input parameters

• \$mgmt\_config

#### **Output**

• Content Container [XML]/false

# 7.2.30 getcontainer

#### **Description**

Obsolete function used as an alias for the loadcontainer function without the possibility to load locked containers

#### **Syntax**

getcontainer (\$containerid, \$type)

## Input parameters

- \$containerid ... container name or container ID [string]
- \$type ... container type [published, work]

### global input parameters

• \$mgmt\_config

#### Output

• Contant Container [XML]/false

# 7.2.31 getwallpaper

#### **Description**

Provides a wallpaper image or video used for the logon and home screen.

#### Syntax

getwallpaper (\$theme="", \$version="")

#### Input parameters

- \$theme ... design theme name [string] (optional)
- \$version ... version number for the wallpaper service [string] (optional)

## global input parameters

• \$mgmt\_config

#### **Output**

• URL of wallpaper image / false

# 7.2.32 getcontainername

#### **Syntax**

getcontainername (\$container)

### Input parameters

• \$container ... container name (e.g. 0000112.xml.wrk) or container ID [string]

### global input parameters

• \$mgmt\_config

 Array with file name of the working content container (locked or unlocked!) and username if locked

# 7.2.33 getlocationname

#### **Syntax**

getlocationname (\$site, \$location, \$cat, \$source="path")

## Input parameters

- \$site ... publication name [string]
- \$location ... location path (as absolute path or converted path) [string]
- \$cat ... category [page, comp]
- \$source ... source for name [path, name]

### global input parameters

- \$mgmt\_config
- \$lang
- \$hcms\_lang\_codepage

### Output

• location with readable names instead of directory and file names / false on error

## 7.2.34 getthemes

#### Description

Returns all design theme names as values and the techical names (path) as key of the result array.

#### **Syntax**

getthemes (\$site\_array=array())

#### Input parameters

• \$site\_array ... publication name as string or array [string, array] (optional)

#### global input parameters

• \$mgmt\_config

### Output

• all design theme names as array / false

## 7.2.35 getthemelocation

#### **Description**

Returns the absolute path (URL) of the theme (css and images).

If the main configuration setting \$mgmt\_config['theme'] defines a theme, this theme will be mandatory in case it exists.

#### **Syntax**

getthemelocation (\$theme="")

## Input parameters

• \$theme ... theme name [string] (optional)

# global input parameters

\$mgmt\_config

## Output

• path to theme / false

## 7.2.36 getcategory

### Description

Evaluates the category ['page, comp'] of a location

#### **Syntax**

getcategory (\$site="", \$location)

### Input parameters

- \$site ... publication name [string] (optional)
- \$location ... location path [string]

### global input parameters

- \$mgmt\_config
- \$publ\_config

### Output

- category ['page
- comp'] / false on error

# 7.2.37 getpublication

#### Description

Extract the publication name of a location path

## **Syntax**

getpublication (\$path)

### Input parameters

• \$path ... converted location path [string]

### Output

• publication name

## 7.2.38 getlocation

### Description

Extract the location excluding object or folder of a location path

#### **Syntax**

getlocation (\$path)

### Input parameters

• \$path ... location path [string]

## Output

• location (without object or folder)

## 7.2.39 getobject

#### **Description**

Extract the object or folder of a location path

#### **Syntax**

getobject (\$path)

## Input parameters

• \$path ... location path [string]

### Output

• object or folder name

# 7.2.40 getmediacontainername

#### **Description**

Extract the container name from a multimedia file name by using the hcm-ID

#### **Syntax**

getmediacontainername (\$file)

#### Input parameters

• \$file ... file name [string]

• container name / false on error

### 7.2.41 getmediafileversion

### Description

Extracts the name from the multimedia file by container name or ID in order to get the media file of older content versions.

if the result is false, there is no older media file version.

#### **Syntax**

getmediafileversion (\$container)

## Input parameters

• \$container ... container name or container ID [string]

## global input parameters

- \$mgmt\_config
- \$user

### Output

• media file name / false on error

## 7.2.42 getobjectid

#### Description

Converts the object path to the object ID of any object

## **Syntax**

getobjectid (\$objectlink)

### Input parameters

• \$objectlink ... converted object path or pathes separated by | [string]

#### Output

object ID

# 7.2.43 getobjectpath

#### **Description**

Returns the location path of an object as string. This function is an alias for function rdbms\_getobject in DB Connect.

#### **Syntax**

getobjectpath (\$object\_identifier)

### Input parameters

\$object\_identifier ... object identifier (object hash OR object ID OR access hash)
 [string]

#### global input parameters

• \$mgmt\_config

### Output

object path / false

## 7.2.44 getobjectlink

#### Description

Converts the object ID to the object path of any object

#### **Syntax**

getobjectlink (\$objectid)

### Input parameters

• \$objectid ... converted object ID or IDs separated by | [string]

### Output

• converted object link

### 7.2.45 getcontainerversions

### **Syntax**

getcontainerversions (\$container)

#### Input parameters

• \$container ... container ID or container name [string]

## global input parameters

\$mgmt\_config

### Output

• array of all versions (array[version-extension] = file-name) / false

# 7.2.46 getlocaltemplates

### Description

This function returns a list of all templates of a publication without inherited templates from other publications.

### **Syntax**

getlocaltemplates (\$site, \$cat="all")

#### Input parameters

- \$site ... publication name [string]
- \$cat ... template category [all, page, comp, meta, inc, portal] (optional)

### global input parameters

• \$mgmt\_config

#### Output

• array with all template names / false

# 7.2.47 gettemplates

### Description

This function returns a list of all templates for pages or components.

Based on the inheritance settings of the publication the template will be loaded with highest priority from the own publication and if not available from a parent publication.

Portal templates are not supoported by the template inheritance due to the fact that the portal access link permission is connected to a specific publication.

#### **Syntax**

gettemplates (\$site, \$cat="all")

#### Input parameters

- \$site ... publication name [string]
- \$cat ... object category [all, page, comp, meta] (optional)

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• template file name list as array / false on error

## 7.2.48 gettemplateversions

#### **Syntax**

gettemplateversions (\$site, \$template)

#### Input parameters

- \$site ... publication name [string]
- \$template ... template name [string]

#### global input parameters

\$mgmt\_config

## Output

• array of all versions (array['YYYY-MM-DD HH:MM:SS'] = file-name) / false

## 7.2.49 getfileinfo

#### Description

defines file properties based on the file extension and returns file info as an array:

\$result['file']: file name without hypercms management extension

\$result['name']: readable file name without hypercms management extension

\$result['filename']: file name without file extensions

\$result['icon']: file name of the file icon

\$result['type']: file type

\$result['ext']: file extension incl. dot in lower case

\$result['published']: if page or component is published (true) or not (false), true in all other

cases

\$result['deleted']: if file is deleted = true else = false

#### **Syntax**

getfileinfo (\$site, \$file, \$cat="comp")

#### Input parameters

- \$site ... publication name [string] (optional)
- \$file ... file name incl. extension [string]
- \$cat ... category [page, comp] (optional)

#### global input parameters

\$mgmt\_config

#### **Output**

array/false

# 7.2.50 getobjectinfo

#### **Description**

Get all file pointers (container, media, template) and object name from object file and collect info from container version, if provided

### **Syntax**

getobjectinfo (\$site, \$location, \$object, \$user="sys", \$container\_version="")

#### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$object ... object name [string]
- \$user ... user name [string] (optional)
- \$container\_version ... container version [string] (optional)

#### global input parameters

• \$mgmt\_config

## Output

result array / false on error

## 7.2.51 getfilesize

#### Description

This function won't give you a proper result of the file size of multimedia components, if there is no Database installed.

#### **Syntax**

getfilesize (\$file)

### Input parameters

• \$file ... converted path to file or directory [string]

### global input parameters

• \$mgmt\_config

### Output

result array with file size in kB and file count / false on error

## 7.2.52 getmimetype

### Description

Gets the mime-type of the file by its extension.

If file has a version file extension the next file extension will be used.

## **Syntax**

getmimetype (\$file)

### Input parameters

• \$file ... file name incl. extension [string]

### global input parameters

• \$mgmt\_config

### Output

• mime\_type

## 7.2.53 getbase64fileextension

### Description

Returns the file extension based on the base64 encoded file content.

#### Syntax

getbase64fileextension (\$base64)

#### Input parameters

• \$base64 ... base 64 encoded file content [string]

### global input parameters

• \$mgmt\_config

### Output

• file extension

# 7.2.54 getfiletype

#### **Syntax**

getfiletype (\$file\_ext)

#### Input parameters

• \$file\_ext ... file extension or file name [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

### Output

• file type to be saved in database based on file extension

# 7.2.55 getpreviewwidth

### Description

Returns the default preview/annotation width in pixel of a document, image, or video

#### **Syntax**

getpreviewwidth (\$site, \$filepath, \$width\_orig="")

#### Input parameters

- \$site ... publication name [string] (optional)
- \$filepath ... path to file or file name [string]
- \$width\_orig ... original width [string] (optional)

#### global input parameters

- \$mgmt\_config
- \$hcms\_ext

### Output

result array with width and height / false on error

# 7.2.56 getimagecolorkey

#### **Description**

Extracts the color key for an image that represents the 5 mostly used colors:

K...black

W...white

E...grey

R... red

G...green

B...blue

C...cyan

M...magenta

Y...yellow

O...orange

P...pink

N...brown

#### **Syntax**

getimagecolorkey (\$image)

## Input parameters

• \$image ... image resource [resource]

#### global input parameters

• \$mgmt\_config

#### **Output**

• color key of image / false on error

# 7.2.57 getimagecolors

#### **Description**

Uses the thumbnail image to calculate the mean color (red, green, blue), defines the colorkey (5 most commonly used colors) and the image type (landscape, portrait, square)

### **Syntax**

getimagecolors (\$site, \$file)

### Input parameters

- \$site ... publication name [string]
- \$file ... media file name [string]

## global input parameters

- \$mgmt\_config
- \$user

## Output

result array / false on error

# 7.2.58 getmediasize

#### **Syntax**

getmediasize (\$filepath)

#### Input parameters

• \$filepath ... path to media file [string]

## global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$user

# Output

Array with media width and height / false on error

# 7.2.59 getimageinfo

### **Syntax**

getimageinfo (\$filepath)

#### Input parameters

\$filepath ... path to media file [string]

### global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$user

### Output

- Array with image information like md5 hash
- file type
- file size
- width
- height
- colors / false on error

# 7.2.60 getpdfinfo

#### Description

Extracts width and height in pixel of a PDF file based on the MediaBox in the files content or ImageMagick as fallback

### **Syntax**

getpdfinfo (\$filepath, \$box="MediaBox")

## Input parameters

- \$filepath ... path to PDF file [string]
- \$box ... box attribute [BleedBox, CropBox, MediaBox] (optional)

### global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$user

## Output

- result array with MD5 hash
- file type
- file size
- last modfied date and time
- width
- height / false on error

# 7.2.61 getvideoinfo

#### **Description**

Extract video metadata from video file.

#### **Syntax**

getvideoinfo (\$filepath)

# Input parameters

• \$filepath ... path to video file [string]

### global input parameters

- \$mgmt\_config
- \$mgmt\_mediapreview
- \$user

## Output

• video file information as result array / false on error

## 7.2.62 getbrowserinfo

#### **Syntax**

getbrowserinfo ()

### Input parameters

#### Output

• client browser and version as array / false on error

# 7.2.63 getcontentlocation

#### **Description**

Gets the content location based on the given container id.

The use of various directories is necessary since the number of directories is limited by the filesystem, e.g. Linux ext3 is limited to 32000.

#### **Syntax**

getcontentlocation (\$container\_id, \$type="abs\_path\_content")

### Input parameters

- \$container\_id ... container id [string]
- \$type ... type [url\_path\_content, abs\_path\_content]

#### global input parameters

• \$mgmt\_config

### Output

• location of the container file / false on error

# 7.2.64 getmedialocation

#### **Description**

Gets the media repsitory location from \$mgmt\_config array. The function supports up to 10 media repositories.

Any other rules for splitting the media files on multiple devices can be implemented as well by the function getmedialocation\_rule.

If the file resides outside the repository (symbolic link is used in the repository), the full path including the file name can be returned.

### **Syntax**

getmedialocation (\$site, \$file, \$type, \$resolve\_symlink=false)

### Input parameters

- \$site ... publication name [string]
- \$file ... multimedia file name (including hcm-ID) [string]
- \$type ... type [url\_path\_media, abs\_path\_media, url\_publ\_media, abs\_publ\_media]
- \$resolve\_symlink ... resolve symbolik links [boolean] (optional)

## global input parameters

- \$mgmt\_config
- \$publ\_config

### Output

• location of the multimedia file / false on error

# 7.2.65 getlockedfileinfo

#### Description

Finds the locked file and returns the name and user as array

#### **Syntax**

getlockedfileinfo (\$location, \$file)

#### Input parameters

- \$location ... location to file [string]
- \$file ... file name [string]

## global input parameters

• \$mgmt\_config

#### Output

Array holding file name incl. lock extension and user name / false on error

## 7.2.66 getfavorites

#### **Syntax**

getfavorites (\$user, \$output="path", \$return\_text\_id=array())

#### Input parameters

- \$user ... user name [string]
- \$output ... output format [path, id] (optional)
- \$return\_text\_id ... text IDs to be returned if output=path [array] (optional)

# global input parameters

\$mgmt\_config

### Output

• object info or object id array of users favorites / false

## 7.2.67 getclipboard

#### **Syntax**

getclipboard (\$output="path", \$return\_text\_id=array())

#### Input parameters

- \$output ... output format [path, id] (optional)
- \$return\_text\_id ... text IDs to be returned if output=path [array] (optional)

### global input parameters

• \$mgmt\_config

#### Output

• object info or object id array of the users clipboard objects / false

# 7.2.68 gethomeboxes

#### **Syntax**

gethomeboxes (\$site\_array=array())

#### Input parameters

• \$site\_array ... pupblication name [array] (optional)

#### global input parameters

• \$mgmt\_config

 All home boxes as array with technical name as key and readable name as value / false

# 7.2.69 getuserboxes

#### **Syntax**

getuserboxes (\$user)

## Input parameters

• \$user ... user name [string]

### global input parameters

• \$mgmt\_config

#### Output

 selected home box of a user as array with technical name as key and readable name as value / false

## 7.2.70 getusersonline

## **Syntax**

getusersonline (\$sites=array())

#### Input parameters

• \$sites ... publication names [array] (optional)

### global input parameters

- \$mgmt\_config
- \$siteaccess

## Output

• Array of online user names / false

# 7.2.71 getchatstate

### **Syntax**

getchatstate (\$register=true)

### Input parameters

• \$register ... register stat in session [true/false] (optional)

# global input parameters

\$mgmt\_config

### Output

• state of chat / false on error

### 7.2.72 getimagelib

### **Syntax**

getimagelib ()

#### Input parameters

### global input parameters

• \$mgmt\_imagepreview

## Output

- name of image library used [GD
- ImageMagick] / false on error

# 7.2.73 getfilename

#### **Description**

Extracts the file name of the content and template pointer tags of an object file

#### **Syntax**

getfilename (\$filedata, \$tagname)

## Input parameters

- \$filedata ... file content [string]
- \$tagname ... hyperCMS tag name in page or component [string]

#### **Output**

• file name

# 7.2.74 gethypertag

### Description

Finds the hyperCMS tag start and end position and returns an array of the whole tags including all information.

Offset value must be integer value and is used to skip search for hyperCMS tag till offset position of filedata.

#### **Syntax**

gethypertag (\$filedata, \$tagname, \$offset=0)

## Input parameters

- \$filedata ... file content [string]
- \$tagname ... full/partly hyperCMS tag name (with or without hyperCMS:) [string]
- \$offset ... offset position [integer]

### Output

• full hyperCMS tag array [array]/false on error

# 7.2.75 gethypertagname

#### **Description**

Reads the name of the hyperCMS tag

#### **Syntax**

gethypertagname (\$tagdata)

#### Input parameters

\$tagdata ... full hyperCMS tag [string]

## Output

• full hyperCMS tag name/false on error

### 7.2.76 gethtmltag

#### **Description**

Finds the first html tag start and end position of a nested hyperCMS tag and returns the whole tag including all information.

Works also if other script tags are nested in the HTML-tag.

This function is not case sensitive!

#### **Syntax**

gethtmltag (\$filedata, \$tag)

#### Input parameters

- \$filedata ... file content [string]
- \$tag ... full hyperCMS tag (or other identifier) [string]

#### **Output**

• full html tag/false on error

### 7.2.77 gethtmltags

#### Description

Finds the nearest html tag start and end position of a nested hyperCMS tag and returns the whole tag including all information.

This functions works also for html-tag pairs like <a href></a>, <div></div> and so on.

#### **Syntax**

gethtmltags (\$filedata, \$tag)

## Input parameters

- \$filedata ... file content [string]
- \$tag ... full hyperCMS tag or other identifier in html tag [string]

### Output

• string from html tag start to end tag/false on error

# 7.2.78 getattribute

### Description

Get the value of a certain attribute out of a string (...attributname=value....)

#### Svntax

getattribute (\$string, \$attribute, \$secure=true)

#### Input parameters

- \$string ... string including attributes [string]
- \$attribute ... attribute name [string]
- \$secure ... secure attribute value reg. XSS [boolean] (optional)

## Output

• attribute value/false on error

## 7.2.79 getoption

#### **Description**

Get the value of a certain option out of a string (-c:v value -ar 44100)

#### Syntax

getoption (\$string, \$option)

#### Input parameters

- \$string ... string including options [string]
- \$option ... option name [string]

#### Output

• option value / false on error

# 7.2.80 getcharset

#### **Description**

Extract the content-type definition and the character set from the template (1st priority), content container (2nd priority) or publication settings (3rd priority)

## **Syntax**

getcharset (\$site, \$data)

## Input parameters

- \$site ... publication name [string]
- \$data ... data from template or content container [string]

## global input parameters

\$mgmt\_config

### Output

• array with content-type and charset / false on error

# 7.2.81 getartid

#### **Description**

Extract the article ID from the tag ID

### **Syntax**

getartid (\$id)

### Input parameters

• \$id ... string including id [string]

## Output

• article id/false on error

## 7.2.82 getelementid

## Description

Extract the element ID from the tag ID

#### **Syntax**

getelementid (\$id)

### Input parameters

• \$id ... string including id [string]

### Output

• element id/false on error

## 7.2.83 getfirstkey

#### **Syntax**

getfirstkey (\$array)

### Input parameters

• \$array ... array [array]

#### Output

• array key of first element in array if \$value is not empty / false on error

## 7.2.84 getdirectoryfiles

### **Syntax**

getdirectoryfiles (\$dir, \$pattern="")

#### Input parameters

- \$dir ... path to directory [string]
- \$pattern ... pattern as string [string] (optional)

### Output

• sorted array of all files matching the pattern / false on error

## 7.2.85 getuserinformation

### Description

This function creates an assoziative array with user information, e.g. for a user select box.

### **Syntax**

getuserinformation (\$login="")

### Input parameters

• \$login ... user name [string] (optional)

### global input parameters

- \$mgmt\_config
- \$user

## Output

 assoziative array with basic user information [publication->username->attribute] / false

# 7.2.86 getworkflowitem

### **Syntax**

getworkflowitem (\$site, \$workflow\_file, \$workflow, \$user)

### Input parameters

- \$site ... publication name [string]
- \$workflow\_file ... location [string]
- \$workflow ... object name [string]
- \$user ... workflow file name [string]

#### global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

workflow item [XML-string]

## 7.3 Set API Functions

#### 7.3.1 setsession

#### **Syntax**

setsession (\$variable, \$content="", \$write=false)

#### Input parameters

- \$variable ... temporary hyperCMS variable name [string or array]
- \$content ... value [string or array] (optional)
- \$write ... write session data for load balancer [boolean] (optional)

## Output

• true / false on error

## 7.3.2 settemplate

#### **Description**

This function sets the template for a single folder/object or all objects in a folder.

#### **Syntax**

settemplate (\$site, \$location, \$object, \$template, \$recursive=false)

- \$site ... publication name [string]
- \$location ... location [string]
- \$object ... object [string]

- \$template ... template name [string]
- \$recursive ... recursive [boolean] (optional)

• \$mgmt\_config

#### **Output**

true/false

# 7.3.3 settaxonomy

## Description

Analyzes the content regarding all taxonomy keywords, saves results in database and returns an array (multilingual support based on taxonomies).

#### **Syntax**

settaxonomy (\$site, \$container\_id, \$langcode="", \$taxonomy="")

#### Input parameters

- \$site ... publication name [string]
- \$container\_id ... container ID [string]
- \$langcode ... 2-digit language code [string] (optional)
- \$taxonomy ... taxonomy definition [array] (optional)

#### global input parameters

\$mgmt\_config

## Output

result array / false on error

## 7.3.4 setarticle

## Description

Set article content in container. The content container will be returned and not saved.

## **Syntax**

setarticle (\$site, \$contentdata, \$contentfile, \$arttitle=array(), \$artstatus=array(), \$artdatefrom=array(), \$artdateto=array(), \$artuser=array(), \$user="sys")

- \$site ... publication name [string]
- \$contentdata ... container (XML) [string]
- \$contentfile ... container name [string]
- \$arttitle ... article title [array]
- \$artstatus ... article status [array]
- \$artdatefrom ... article beginn date [array] (optional)

- \$artdateto ... article end date [array] (optional)
- \$artuser ... article user name [array or string] (optional)
- \$user ... user name [string] (optional)

\$mgmt\_config

### Output

- updated content container (XML)
- false on error

#### 7.3.5 settext

## Description

Set text content in container and database. The content container will be returned and not saved.

### **Syntax**

settext (\$site, \$contentdata, \$contentfile, \$text=array(), \$type=array(), \$art="no", \$textuser=array(), \$user="sys", \$charset="", \$addmicrotime=false)

#### Input parameters

- \$site ... publication name [string]
- \$contentdata ... container (XML) [string]
- \$contentfile ... container name [string]
- \$text ... text with tag Id as key and text as value [array]
- \$type ... text type [array or string] [u, f, I, c, d, k]
- \$art ... article [array or string] [yes, no] (optional)
- \$textuser ... text user [array or string] (optional)
- \$user ... user name [string] (optional)
- \$charset ... character set of text content [string] (optional)
- \$addmicrotime ... add microtime to ID used for comments [boolean] (optional)

## global input parameters

- \$mgmt\_config
- \$publ\_config

#### Output

- updated content container (XML)
- false on error

#### 7.3.6 setmedia

#### Description

Set media content in container and database. The content container will be returned and not saved.

### **Syntax**

setmedia (\$site, \$contentdata, \$contentfile, \$mediafile=array(), \$mediaobject=array(), \$mediaalttext=array(), \$mediaalign=array(), \$mediawidth=array(), \$mediaheight=array(), \$art="no", \$mediauser="", \$user="sys", \$charset="")

#### Input parameters

- \$site ... publication name [string]
- \$contentdata ... container (XML) [string]
- \$contentfile ... container name [string]
- \$mediafile ... media files with tag ID as key and reference as value [array] (optional)
- \$mediaobject ... new media object references with tag ID as key and reference as value [array]
- \$mediaalttext ... media alternative text [array] (optional)
- \$mediaalign ... media alignment [array] (optional)
- \$mediawidth ... media width [array] (optional)
- \$mediaheight ... media height [array] (optional)
- \$art ... article [array or string] [yes, no] (optional)
- \$mediauser ... content user [array or string] (optional)
- \$user ... user name [string] (optional)
- \$charset ... character set of text content [string] (optional)

### global input parameters

\$mgmt\_config

#### **Output**

- updated content container (XML)
- false on error

## 7.3.7 setpagelink

### **Description**

Set link content in container and database. The content container will be returned and not saved.

#### **Syntax**

setpagelink (\$site, \$contentdata, \$contentfile, \$linkhref=array(), \$linktarget=array(), \$linktext=array(), \$art="no", \$linkuser=array(), \$user="sys", \$charset="")

- \$site ... publication name [string]
- \$contentdata ... container (XML) [string]
- \$contentfile ... container name [string]
- \$linkhref ... new link with tag ID as key and link reference as value [array]
- \$linktarget ... link target [array] (optional)
- \$linktext ... link text [array] (optional)
- \$art ... article [array or string] [yes, no] (optional)
- \$linkuser ... content user [array or string] (optional)
- \$user ... user name [string] (optional)
- \$charset ... character set of text content [string] (optional)

\$mgmt\_config

### Output

- updated content container (XML)
- false on error

## 7.3.8 setcomplink

#### **Description**

Set component link content in container and database. The content container will be returned and not saved.

#### **Syntax**

setcomplink (\$site, \$contentdata, \$contentfile, \$component=array(), \$condition=array(),
\$art="no", \$compuser=array(), \$user="sys")

#### Input parameters

- \$site ... publication name [string]
- \$contentdata ... container (XML) [string]
- \$contentfile ... container name [string]
- \$component ... new components with tag ID as key and component reference as value [array]
- \$condition ... conditions [array] (optional)
- \$art ... article [array or string] [yes, no] (optional)
- \$compuser ... content user [array or string] (optional)
- \$user ... user name [string] (optional)

#### global input parameters

\$mgmt\_config

## Output

- updated content container (XML)
- false on error

#### 7.3.9 sethead

#### **Description**

Only used for content in general head information of container.

## **Syntax**

sethead (\$site, \$contentdata, \$contentfile, \$headcontent=array(), \$user="sys", \$charset="")

- \$site ... publication name [string]
- \$contentdata ... container (XML) [string]

- \$contentfile ... container name [string]
- \$headcontent ... head content with tagname as ID and text as value [array]
- \$user ... user name [string] (optional)
- \$charset ... character set of text content [string] (optional)

\$mgmt\_config

### **Output**

- updated content container (XML)
- false on error

#### 7.3.10 setrelation

## Description

This function sets a relationship between two objects by adding the reference as a multi component link to the specified tag ID of both objects.

#### **Syntax**

setrelation (\$site, \$location\_1, \$object\_1, \$id\_1="Related", \$location\_2, \$object\_2, \$id\_2="Related", \$user)

### Input parameters

- \$site ... publication name [string]
- \$location\_1 ... location path 1 [string]
- \$object\_1 ... object name 1 for component link reference 2 [string]
- \$id\_1 ... tag/content ID 1 for component reference to object 2 [string] (optional)
- \$location\_2 ... location path 2 [string]
- \$object 2 ... object name 2 for component link reference 2 [string]
- \$id\_2 ... tag/content ID 2 for component reference to object 1 [string] (optional)
- \$user ... user name [string]

# global input parameters

• \$mgmt\_config

#### **Output**

• true / false on error

#### 7.3.11 setfilename

#### Description

Sets or creates the file name of the hyperCMS content file, template file, media file or file name pointer

#### **Syntax**

setfilename (\$filedata, \$tagname, \$value)

## Input parameters

- \$filedata ... file content [string]
- \$tagname ... hyperCMS tag name in page or component [content, template, media, name]
- \$value ... new value [string]

## Output

filedata/false on error

## 7.3.12 setuserboxes

### **Syntax**

setuserboxes (\$name\_array, \$user)

## Input parameters

- \$name\_array ... home box file names [array or string]
- \$user ... user name [string]

#### global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.3.13 setguiview

### **Syntax**

setguiview (\$objectview, \$explorerview, \$sidebar, \$user)

#### Input parameters

- \$objectview ... object view name [formedit, cmsview, inlineview]
- \$explorerview ... explorer view name [detail, small, medium, large]
- \$sidebar ... show sidebar [true=1, false=0]
- \$user ... user name [string]

## global input parameters

• \$mgmt\_config

#### **Output**

true / false

# 7.4 Connect API Functions

# 7.4.1 ftp\_userlogon

### Description

This function connects and performs logon to an FTP server.

### **Syntax**

ftp\_userlogon (\$server, \$user, \$passwd, \$ssl=false)

# Input parameters

- \$server ... FTP servername or IP [string]
- \$user ... user name [string]
- \$passwd ... password [string]
- \$ssl ... SSL [boolean] (optional)

## global input parameters

• \$mgmt\_config

### Output

• true / false on error

## 7.4.2 ftp\_userlogout

## Description

This function disconnects from an FTP server.

# **Syntax**

ftp\_userlogout (\$conn\_id)

## Input parameters

• \$conn\_id ... FTP connection [resource]

## global input parameters

• \$mgmt\_config

## Output

• true / false on error

# 7.4.3 ftp\_getfile

#### Description

This function gets a file from the FTP server.

## **Syntax**

ftp\_getfile (\$conn\_id, \$remote\_file, \$local\_file, \$passive=true)

### Input parameters

- \$conn\_id ... FTP connection [resource]
- \$remote\_file ... path to file on FTP server [string]
- \$local\_file ... passive mode [boolean] (optional)
- \$passive

### global input parameters

\$mgmt\_config

#### Output

• true / false on error

# 7.4.4 ftp\_putfile

#### Description

This function puts a file to the FTP server.

#### Syntax

ftp\_putfile (\$conn\_id, \$local\_file, \$remote\_file, \$passive=true)

#### Input parameters

- \$conn\_id ... FTP connection [resource]
- \$local\_file ... path to local file [string]
- \$remote\_file ... path to file on FTP server [string]
- \$passive ... passive mode [boolean] (optional)

#### global input parameters

• \$mgmt\_config

### Output

true / false on error

# 7.4.5 ftp\_deletefile

#### Description

This function deletes a file from the FTP server.

#### **Syntax**

ftp\_deletefile (\$conn\_id, \$remote\_file, \$passive=true)

- \$conn\_id ... FTP connection [resource]
- \$remote\_file ... path to file on FTP server [string]

• \$passive ... passive mode [boolean] (optional)

# global input parameters

• \$mgmt\_config

## Output

• true / false on error

## 7.4.6 ftp\_filelist

#### Description

This function gets a file/directory listing of the FTP server.

## **Syntax**

ftp\_filelist (\$conn\_id, \$path=".", \$passive=true)

## Input parameters

- \$conn\_id ... FTP connection [resource]
- \$path ... path to remote directory [string] (optional)
- \$passive ... passive mode [boolean] (optional)

## global input parameters

• \$mgmt\_config

## Output

• result array / false on error

## 7.4.7 createsharelink\_facebook

#### **Syntax**

createsharelink\_facebook (\$site, \$url)

## Input parameters

- \$site ... URL to share [string]
- \$url

### global input parameters

• \$mgmt\_config

## Output

• Share URL / false on error

# 7.4.8 createsharelink\_twitter

### **Syntax**

createsharelink\_twitter (\$site, \$url, \$text)

# Input parameters

- \$site ... URL to share [string]
- \$url ... message to share [string]
- \$text

# global input parameters

• \$mgmt\_config

## Output

• Share URL / false on error

# 7.4.9 createsharelink\_googleplus

### **Syntax**

createsharelink\_googleplus (\$site, \$url)

### Input parameters

- \$site ... URL to share [string]
- \$url

## global input parameters

• \$mgmt\_config

#### Output

• Share URL / false on error

## 7.4.10 createsharelink\_linkedin

#### **Syntax**

createsharelink\_linkedin (\$site, \$url, \$title, \$summary, \$source)

- \$site ... URL to share [string]
- \$url ... title [string]
- \$title ... summary [string] (optional)
- \$summary ... source [string] (optional)
- \$source

• \$mgmt\_config

## Output

• Share URL / false on error

## 7.4.11 createsharelink\_pinterest

### Syntax

createsharelink\_pinterest (\$site, \$image\_url, \$title, \$description)

### Input parameters

- \$site ... image URL to share [string]
- \$image\_url ... title [string]
- \$title ... description [string] (optional)
- \$description

## global input parameters

\$mgmt\_config

## Output

• Share URL / false on error

# 7.5 Security API Functions

# 7.5.1 rootpermission

### Description

Deseralizes the permission string and and returns the root permission array

#### Syntax

rootpermission (\$site\_name, \$site\_admin, \$permission\_str)

#### Input parameters

- \$site\_name ... publication name [string]
- \$site\_admin ... publication admin [boolean]
- \$permission\_str ... permission string from group [string]

#### global input parameters

- \$rootpermission
- \$mgmt\_config

# Output

global permission array/false

## 7.5.2 global permission

### Description

Deseralizes the permission string and returns the global permission array

#### Syntax

globalpermission (\$site\_name, \$permission\_str)

### Input parameters

- \$site\_name ... publication name [string]
- \$permission\_str ... permission string from group [string]

## Output

global permission array/false

# 7.5.3 localpermission

### Description

Deseralizes the permission string and returns the local permission array

### **Syntax**

localpermission (\$site\_name, \$permission\_str)

## Input parameters

- \$site\_name ... publication name [string]
- \$permission\_str ... permission string from group [string]

### **Output**

local permission array/false

## 7.5.4 accessgeneral

#### Description

Checks general access to certain system folders, publications and returns true if access is granted

### **Syntax**

accessgeneral (\$site, \$location, \$cat)

- \$site ... publication name [string]
- \$location ... location (path to folder) [string]
- \$cat ... object category [page, comp]

- \$mgmt\_config
- \$hiddenfolder
- \$siteaccess

#### Output

true/false

## 7.5.5 accesspermission

## Description

Evaluates page and component access permissions and returns group(s). Since version 8.0.0 this function does not evaluate the access based on access links anymore since explorer\_objectlist verifies the access linking.

#### Syntax

accesspermission (\$site, \$location, \$cat)

### Input parameters

- \$site ... location (path to folder) [string]
- \$location ... object category [page, comp]
- \$cat

### global input parameters

- \$user
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$mgmt\_config

## Output

group with access permissions as array / false on error

# 7.5.6 setlocal permission

## Description

Sets local permissions of a user group for a specific publication

## **Syntax**

setlocalpermission (\$site, \$group\_array, \$cat)

- \$site ... publication name [string]
- \$group\_array ... group name [array]
- \$cat ... object category [page, comp]

\$localpermission

## Output

• local permission array / false on error

# 7.5.7 checkpublicationpermission

#### Description

Checks the access to a publication based on the site access and inheritance settings

### Syntax

checkpublicationpermission (\$site, \$strict=true)

## Input parameters

- \$site ... publication name [string]
- \$strict ... strictly limited to siteaccess only without inheritance [boolean] (optional)

### global input parameters

- \$mgmt\_config
- \$siteaccess

## Output

 "direct" for direct access via group permission / "inherited" for access through inheritance / false

# 7.5.8 checkadminpermission

#### **Description**

Checks the super admin permission

#### **Syntax**

checkadminpermission ()

#### Input parameters

## global input parameters

• \$adminpermission

## Output

true/false

# 7.5.9 checkrootpermission

### **Description**

Checks the root permissions

#### **Syntax**

checkrootpermission (\$name)

## Input parameters

• \$name ... permission name [string]

## global input parameters

• \$rootpermission

# Output

true/false

# 7.5.10 checkglobalpermission

#### **Description**

Checks global permission for a publication

#### Syntax

checkglobalpermission (\$site, \$name)

#### Input parameters

- \$site ... publication name [string]
- \$name ... permission name [string]

## global input parameters

• \$globalpermission

### Output

true/false

# 7.5.11 checklocalpermission

## Description

Checks local permissions of a user group for a specific publication

#### Syntax

checklocalpermission (\$site, \$group, \$name)

## Input parameters

\$site ... publication name [string]

- \$group ... user group name [string]
- \$name ... permission name [string]

• \$\$localpermission

#### Output

true/false

## 7.5.12 checklanguage

## **Syntax**

checklanguage (\$language\_array, \$language\_value)

### Input parameters

- \$language\_array ... language array with all valid values [array]
- \$language\_value ... language value of attribute in template tag [string]

### Output

• true if language array holds the given language value / false if not found

# 7.5.13 checkgroupaccess

## Description

Verifies if a user has access to the tags content based on the group membership.

### **Syntax**

checkgroupaccess (\$groupaccess, \$usergroup\_array)

#### Input parameters

- \$groupaccess ... group access from template group-tag attribute [string]
- \$usergroup\_array ... user group membership names [array]

#### Output

true if the current user group has access / false if not

## 7.5.14 userlogin

#### Description

Login of user by sending user and password using the variables: \$sentuser, \$sentpasswd This procedure will register the user in the hypercms session and in the php session. The procedure will return true or false using the variable \$result.

#### Syntax

```
userlogin ($user="", $passwd="", $hash="", $objref="", $objcode="", $ignore_password=false, $locking=true, $portal="")
```

#### Input parameters

- \$user ... user name [string] (optional if hash code is used for logon)
- \$passwd ... password [string] (optional if hash code is used for logon)
- \$hash ... hash code of user [string] (optional)
- \$objref ... object reference for hcms linking (object ID) [string] (optional)
- \$objcode ... object code for hcms linking (crypted object ID) [string] (optional)
- \$ignore\_password ... ignore passwordcheck needed for WebDAV or access link [boolean] (optional)
- \$locking ... lock IP after 10 failed attempts to login [boolean] (optional)
- \$portal ... portal name in the form of publication.portal or publication/portal [string] (optional)

## global input parameters

- \$mgmt\_config
- \$eventsystem
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

## Output

result array

# 7.5.15 setportalpermissions

#### **Description**

Sets the permissions for a portal user by reducing the standard permissions.

#### Svntax

setportalpermissions (\$login\_result)

#### Input parameters

• \$login\_result ... result from function userlogin [array]

#### global input parameters

• \$mgmt\_config

## Output

result array / false

# 7.5.16 registerinstance

#### Description

Registers the instance in the users session.

### **Syntax**

registerinstance (\$instance, \$load\_config=true)

#### Input parameters

- \$instance ... instance name [string]
- \$load\_config ... load main config of instance [boolean] (optional)

## global input parameters

• \$mgmt\_config

### Output

true/false

## 7.5.17 registeruser

#### Description

Registers all user related paramaters in the session. Access links can be provided with the login result or alternatively as the seperate accesslink parameter.

### **Syntax**

registeruser (\$instance="", \$login\_result, \$accesslink=false, \$hcms\_objformats=false, \$is\_mobile=0, \$is\_iphone=0, \$html5support=1)

#### Input parameters

- \$instance ... instance name [string] (optional)
- \$login\_result ... result array of function userlogin [array]
- \$accesslink ... access link [array] (optional)
- \$hcms\_objformats ... download formats of access link provided by function rdbms\_getaccessinfo [array] (optional)
- \$is\_mobile ... mobile browser result of client [0, 1] (optional)
- \$is\_iphone ... is iOS browser result of client [0, 1] (optional)
- \$html5support ... HTML5 file support result of client [0, 1] (optional)

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array / false on error

# 7.5.18 registerassetbrowser

#### Syntax

registerassetbrowser (\$userhash, \$objecthash="")

- \$userhash ... user hash [string]
- \$objecthash ... object hash [string] (optional)

• \$mgmt\_config

#### Output

true/false

### 7.5.19 createchecksum

## Description

Creates the checksum of the user permissions.

#### **Syntax**

createchecksum (\$permissions="")

## Input parameters

• \$permissions ... array or empty [array]

## Output

• MD5 checksum

#### 7.5.20 writesession

## Description

Writes hyperCMS specific session data of a user.

#### **Syntax**

writesession (\$user, \$passwd, \$checksum, \$siteaccess=array())

## Input parameters

- \$user ... user name [string]
- \$passwd ... password [string]
- \$checksum ... checksum [string]
- \$siteaccess ... publicaion access [array]

## global input parameters

• \$mgmt\_config

## Output

true / false on error

## 7.5.21 writesessiondata

### **Description**

Serializes and writes all session data of a user.

### **Syntax**

writesessiondata ()

#### Input parameters

### global input parameters

• \$mgmt\_config

## Output

• true / false on error

## 7.5.22 createsession

## Description

Checks if session data of a user is available. This function does access session variables directly.

### **Syntax**

createsession ()

## Input parameters

# global input parameters

• \$mgmt\_config

# Output

true

# 7.5.23 killsession

#### **Description**

Destroys session data of a user.

## **Syntax**

killsession (\$user="", \$destroy\_php=true, \$remove=false)

# Input parameters

- \$user ... user name for hyperCMS session [string] (optional)
- \$destroy\_php ... destroy php session [boolean] (optional)
- \$remove ... remove session file of the user [boolean] (optional)

## global input parameters

• \$mgmt\_config

# Output

• true

# 7.5.24 checkdiskkey

## Description

Checks the disc key of the installation.

### **Syntax**

checkdiskkey (\$users="", \$site="")

## Input parameters

- \$users ... users XML [string] (optional)
- \$site ... publication names (use | as seperator) [string] (optional)

## global input parameters

• \$mgmt\_config

## Output

• true / false

# 7.5.25 checkpassword

## Description

This function checks the strength of a password and return the error messages or true.

#### **Syntax**

checkpassword (\$password, \$user="")

## Input parameters

- \$password ... password [string]
- \$user ... user name [string] (optional for password history)

## global input parameters

- \$mgmt\_config
- \$lang

## Output

• true if passed / error message as string

# 7.5.26 loguserip

### **Syntax**

loguserip (\$client\_ip, \$user="sys")

## Input parameters

- \$client\_ip ... client IP address [string]
- \$user ... user logon name [string] (optional)

# global input parameters

• \$mgmt\_config

### Output

true / false on error

# 7.5.27 checkuserip

## **Syntax**

checkuserip (\$client\_ip, \$user="", \$timeout=0)

#### Input parameters

- \$client\_ip ... client IP address [string]
- \$user ... user logon name [string] (optional)
- \$timeout ... timeout in minutes [integer] (optional)

## global input parameters

• \$mgmt\_config

#### Output

• true if IP is not locked / false if IP is locked or on error

## 7.5.28 checkuserrequests

#### Description

Provides security for Cross-Site Request Forgery.

#### Syntax

checkuserrequests (\$user="sys")

#### Input parameters

• \$user ... user name [string] (optional)

### global input parameters

• \$mgmt\_config

# Output

• true / false if a certain amount of reguests per minute is exceeded

#### 7.5.29 recreateusersession

#### **Description**

Recreates the users session data in case it is missing (due to issues with Android Chrome and the Mobile Edition).

Recreates the session data only if the session ID is still available.

#### **Syntax**

recreateusersession ()

### Input parameters

## global input parameters

• \$mgmt\_config

# Output

• true / false requires config.inc.php

### 7.5.30 checkusersession

### Description

Checks if the session data of a user is valid. This function does access session variables directly.

#### **Syntax**

checkusersession (\$user="sys", \$CSRF\_detection=true)

# Input parameters

- \$user ... user name [string] (optional)
- \$CSRF\_detection ... include CSRF detection [boolean]

## global input parameters

• \$mgmt\_config

# Output

• true / html-output followed by termination requires config.inc.php

# 7.5.31 allowuserip

#### **Description**

Verifies if the client IP is in the range of valid IPs and logs IP addresses with no access.

# **Syntax**

allowuserip (\$site)

## Input parameters

• \$site ... publication name [string]

## global input parameters

• \$mgmt\_config

# Output

• true / false requires config.inc.php

# 7.5.32 valid\_objectname

## Description

Checks if an object name includes forbidden characters in order to prevent directory browsing.

### **Syntax**

valid\_objectname (\$variable)

## Input parameters

• \$variable ... variable [string or array]

## Output

• true / false

# 7.5.33 valid\_locationname

#### Description

Checks if an location includes forbidden characters in order to prevent directory browsing.

### **Syntax**

valid\_locationname (\$variable)

## Input parameters

• \$variable ... variable [string or array]

# Output

• true / false

# 7.5.34 valid\_publicationname

### Description

Checks if a publication name includes forbidden characters in order to prevent directory browsing.

Optionally verifies if the publication name is included in the siteaccess variable.

## **Syntax**

valid\_publicationname (\$variable)

### Input parameters

• \$variable ... variable [string or array]

## global input parameters

\$siteaccess

#### **Output**

• true / false

## 7.5.35 html\_encode

#### Description

This function encodes certain characters (&, <, >, ", ') into their HTML character entity equivalents to protect against XSS.

Converts a string into the html equivalents (also used for XSS protection).

Supports multibyte character sets like UTF-8 as well based on the ASCII value of the character.

#### **Syntax**

html\_encode (\$expression, \$encoding="", \$js\_protection=false)

#### Input parameters

- \$expression ... variable [string or array]
- \$encoding ... conversion of all special characters based on given character set or to ASCII [string] (optional)
- \$js\_protection ... remove characters to avoid JS injection [boolean] (optional)

## Output

html encoded value as array or string / false on error

## 7.5.36 html decode

#### Description

This function decodes all characters which have been converted by html\_encode.

#### **Syntax**

html\_decode (\$expression, \$encoding="")

## Input parameters

- \$expression ... epxression [string or array]
- \$encoding ... conversion of all special characters based on character set [string] (optional)

### Output

• html decoded value as array or string / false on error

# 7.5.37 scriptcode\_encode

### Description

This function escapes all script tags.

This function must be used to clean all user input in the CMS by removing all server side scripts tags.

#### **Syntax**

scriptcode\_encode (\$content)

### Input parameters

• \$content ... content [string]

## global input parameters

• \$mgmt\_config

### **Output**

escaped content as string / false on error

## 7.5.38 scriptcode\_extract

#### **Description**

This function extracts the script code of a given content.

#### Syntax

scriptcode\_extract (\$content, \$identifier\_start="<?", \$identifier\_end="?>")

#### Input parameters

- \$content ... content [string]
- \$identifier\_start ... identifier of script begin [string]
- \$identifier\_end ... identifier of script end [string]

#### **Output**

• script code as array / false on error or if noting was found

# 7.5.39 scriptcode\_clean\_functions

### Description

This function removes all dangerous PHP functions.

#### **Syntax**

scriptcode\_clean\_functions (\$content, \$type=4, \$application="PHP")

## Input parameters

- \$content ... content [string]
- \$type ... cleaning level type: no cleaning = 0; basic set of disabled functions = 1; 1 + file access functions = 2; 2 + include functions = 3; 3 + hyperCMS API file functions = 4; No server side script allowed = 5 [0, 1, 2, 3, 4, 5] (optional)
- \$application ... application [PHP, ASP, JSP] (optional)

### global input parameters

• \$mgmt\_config

### Output

• result array / false on error

# 7.5.40 sql\_clean\_functions

### Description

This function checks SQL statements for write operations.

## **Syntax**

sql\_clean\_functions (\$content)

### Input parameters

• \$content ... SQL statement [string]

#### global input parameters

• \$mgmt\_config

### Output

result array / false on error

## 7.5.41 url\_encode

### **Description**

This function encodes all characters.

#### **Syntax**

url\_encode (\$variable)

## Input parameters

\$variable ... variable [string or array]

## global input parameters

• \$mgmt\_config

## Output

• urlencoded value as array or string / false on error

## 7.5.42 url\_decode

# Description

This function decodes all characters which have been converted by url\_encode or urlencode (PHP).

#### **Syntax**

url\_decode (\$variable)

#### Input parameters

• \$variable ... variable [string or array]

## global input parameters

• \$mgmt\_config

#### Output

• urldecoded value as array or string / false on error

# 7.5.43 shellcmd\_encode

#### Description

This function encodes/escapes characters to secure the shell comand.

#### Svntax

shellcmd\_encode (\$variable, \$type="")

### Input parameters

- \$variable ... variable [string or array]
- \$type ... type [%, strict] (optional)

# Output

encoded value as array or string / false on error

# 7.5.44 hcms\_crypt

### Description

Unidrectional encryption using crc32 and urlencode. Used to create tokens for simple view links in the system.

The tokens can be verified by calculating the hash of the media file name and comparing the hash values.

Don't use this function to secure any string or for password hashing.

#### **Syntax**

hcms\_crypt (\$string, \$start=0, \$length=0)

#### Input parameters

- \$string ... string to encode [string]
- \$start ... start position [integer]
- \$length ... length for string extraction [integer]

### global input parameters

\$mgmt\_config

## Output

• encoded string / false on error

# 7.5.45 hcms\_encrypt

#### **Description**

Encryption of a string. Only strong encryption is binary-safe.

#### Syntax

hcms\_encrypt (\$string, \$key="", \$crypt\_level="", \$encoding="url")

#### Input parameters

- \$string ... string to encode [string]
- \$key ... key of length 16 or 24 or 32 [string] (optional)
- \$crypt\_level ... crypt strength level [weak, standard, strong] (optional)
- \$encoding ... encoding [base64, url, none] (optional)

### global input parameters

\$mgmt\_config

#### Output

• encoded string / false on error

## 7.5.46 hcms\_decrypt

#### **Description**

Decryption of a string. Only strong encryption is binary-safe.

#### **Syntax**

hcms\_decrypt (\$string, \$key="", \$crypt\_level="", \$encoding="url")

#### Input parameters

- \$string ... hash-string to decode [string]
- \$key ... key of length 16 or 24 or 32 [string] (optional)
- \$crypt\_level ... crypt strength level [weak, standard, strong] (optional)
- \$encoding ... encoding [base64, url, none] (optional)

### global input parameters

• \$mgmt\_config

#### Output

decoded string / false on error

# 7.5.47 createtimetoken

#### **Syntax**

createtimetoken (\$lifetime=0, \$secret=4)

#### Input parameters

- \$lifetime ... token lifetime in seconds [integer] (optional)
- \$secret ... secret value [integer] (optional)

# global input parameters

• \$mgmt\_config

#### **Output**

• token / false on error

#### 7.5.48 checktimetoken

#### **Syntax**

checktimetoken (\$token, \$secret=4)

# Input parameters

- \$token ... token [string]
- \$secret ... secret value [integer] (optional)

# global input parameters

\$mgmt\_config

# Output

• true / false

# 7.5.49 createtoken

## **Syntax**

createtoken (\$user="sys", \$lifetime=0, \$secret=4)

### Input parameters

- \$user ... user name [string] (optional)
- \$lifetime ... token lifetime in seconds [integer] (optional)
- \$secret ... secret value [integer] (optional)

## global input parameters

• \$mgmt\_config

# Output

• token / false on error

## 7.5.50 checktoken

## **Syntax**

checktoken (\$token, \$user="sys", \$secret=4)

#### Input parameters

- \$token ... token [string]
- \$user ... user name [string] (optional)
- \$secret ... secret value [integer] (optional)

## global input parameters

• \$mgmt\_config

# Output

• true / false

## 7.5.51 createuniquetoken

#### **Syntax**

createuniquetoken (\$length=16)

## Input parameters

• \$length ... token length [integer] (optional)

\$mgmt\_config

## Output

• token as string / false

## 7.5.52 createpassword

## **Syntax**

createpassword (\$length=10)

## Input parameters

• \$length ... password length [integer] (optional)

## global input parameters

• \$mgmt\_config

## Output

• password as string / false

# 7.5.53 rand\_secure

#### **Syntax**

rand\_secure (\$min=1000, \$max=9999999999)

#### Input parameters

- \$min ... min and max value [integer] (optional)
- \$max

#### Output

• secure random number / false

# 7.6 Media API Functions

# 7.6.1 ocr\_extractcontent

#### Description

This function extracts the text content of multimedia objects using OCR and returns the text. It is a helper function for function indexcontent.

#### **Syntax**

ocr\_extractcontent (\$site, \$location, \$file)

#### Input parameters

- \$site ... publication name [string]
- \$location ... path to multimedia file [string]
- \$file ... multimedia file name (file to be indexed) [string]

### global input parameters

- \$mgmt\_config
- \$mgmt\_parser
- \$mgmt\_imagepreview
- \$hcms\_lang
- \$lang

#### Output

· extracted content as text string / false

#### 7.6.2 indexcontent

### Description

This function extracts the text content of multimedia objects and writes it the text to the container.

The given charset of the publication (not set by default), container or publication (not set by default) will be used.

The default character set of default.meta.tpl is UTF-8, so all content should be saved in UTF-8.

#### **Syntax**

indexcontent (\$site, \$location, \$file, \$container="", \$container\_content="", \$user, \$return content=false)

### Input parameters

- \$site ... publication name [string]
- \$location ... path to multimedia file [string]
- \$file ... multimedia file name (file to be indexed) [string]
- \$container ... container name or ID [string] (optional)
- \$container\_content ... container XML-content [string] (optional)
- \$user ... user name [string]
- \$return\_content ... return the content without saving it in the system [boolean] (optonal)

#### global input parameters

- \$mgmt\_config
- \$mgmt\_parser
- \$mgmt\_imagepreview
- \$mgmt\_uncompress
- \$hcms\_ext
- \$hcms\_lang
- \$lang

## Output

• true / false

## 7.6.3 unindexcontent

### Description

This function removes media objects from the container

#### Syntax

unindexcontent (\$site, \$location, \$file, \$container, \$container\_content, \$user)

#### Input parameters

- \$site ... publication name [string]
- \$location ... file location [string]
- \$file ... file name [string]
- \$container ... multimedia file to index [string]
- \$container\_content ... container name or ID [string]
- \$user ... container XML-content [string]

# global input parameters

- \$mgmt\_config
- \$mgmt\_parser
- \$hcms\_lang
- \$lang

#### Output

• true / false

#### 7.6.4 reindexcontent

### Description

Reindexes all media files of a publication. Optionally only for specific containers.

#### Syntax

reindexcontent (\$site, \$container\_id\_array="")

## Input parameters

- \$site ... publication name [string]
- \$container\_id\_array ... container IDs [array] (optional)

# global input parameters

• \$mgmt\_config

#### Output

• true / false

## 7.6.5 createthumbnail\_indesign

#### Description

Creates a thumbnail by extracting the thumbnail from an indesign file and transferes the generated image via remoteclient.

For good results, InDesign Preferences must be set to save preview image and at extra large size.

#### **Syntax**

createthumbnail\_indesign (\$site, \$location\_source, \$location\_dest, \$file)

### Input parameters

- \$site ... publication name [string]
- \$location\_source ... path to source dir [string]
- \$location\_dest ... path to destination dir [string]
- \$file ... file name [string]

### global input parameters

- \$mgmt\_config
- \$user

#### **Output**

- new file name / false on error (saves only thumbnail media file in destination location
- only jpeg format is supported as output)

## 7.6.6 createthumbnail\_video

#### **Description**

Creates a thumbnail picture of a video frame. Saves only the thumbnail media file in destination location. Only jpeg format is supported as output.

#### **Syntax**

createthumbnail\_video (\$site, \$location\_source, \$location\_dest, \$file, \$frame, \$autorotate=false)

#### Input parameters

- \$site ... publication name [string]
- \$location\_source ... path to source dir [string]
- \$location\_dest ... path to destination dir [string]
- \$file ... file name [string]
- \$frame ... frame of video in seconds or hh:mm:ss[.xxx]
- \$autorotate ... autorotate [boolean] (optional)

#### global input parameters

- \$mgmt\_config
- \$mgmt\_mediapreview

- \$mgmt\_mediaoptions
- \$user

• new file name / false on error

## 7.6.7 createimages\_video

### **Description**

Creates and saves images of video screen size from a video to a directory.

## **Syntax**

createimages\_video (\$site, \$location\_source, \$location\_dest, \$file, \$name="", \$fs=1, \$format="jpg", \$width="", \$height="")

#### Input parameters

- \$site ... publication name [string]
- \$location\_source ... path to source dir [string]
- \$location\_dest ... path to destination dir [string]
- \$file ... file name [string]
- \$name ... name for image files [string] (optional)
- \$fs ... frames per second to create from the video [number] (optional)
- \$format ... image format [jpg, png, bmp] (optional)
- \$width ... image width in pixel [integer] (optional)
- \$height ... image height in pixel [integer] (optional)

# global input parameters

- \$mgmt\_config
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$user

### Output

true / false on error

## 7.6.8 createmedia

#### **Description**

Creates an new image or video from the original file or creates a thumbnail and transferes the generated image via remoteclient.

Saves original or thumbnail media file in destination location, for thumbnail only jpeg format is supported as output.

### **Syntax**

createmedia (\$site, \$location\_source, \$location\_dest, \$file, \$format="", \$type="thumbnail", \$force\_no\_encrypt=false)

#### Input parameters

- \$site ... publication name [string]
- \$location\_source ... path to source dir [string]
- \$location\_dest ... path to destination dir [string]
- \$file ... file name [string]
- \$format ... format (file extension w/o dot) [string] (optional)
- \$type ... type of image/video/audio file [thumbnail(for thumbnails of images), origthumb(thumbnail made from original video/audio), original(to overwrite original video/audio file), annotation(for annotation images), any other string present in \$mgmt\_imageoptions/\$mgmt\_mediaoptions, temp(for temporary files)] (optional)
- \$force\_no\_encrypt ... force the file to be not encrypted even if the content of the publication must be encrypted [boolean] (optional)

# global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$mgmt mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions
- \$mgmt\_maxsizepreview
- \$mgmt\_mediametadata
- \$hcms\_ext
- \$user

### Output

new file name / false on error

## 7.6.9 splitmedia

#### Description

Splits a video or audio file in segments measured in seconds. Used for synchronous Google Cloud Speech Service that only supports max. 1 minute audio files.

### **Syntax**

splitmedia (\$site, \$location\_source, \$location\_dest, \$file, \$sec=60, \$format="",
\$force\_no\_encrypt=false)

### Input parameters

- \$site ... publication name [string]
- \$location\_source ... path to source dir [string]
- \$location\_dest ... path to destination dir [string]
- \$file ... file name [string]
- \$sec ... seconds of a segment [integer] (optional)
- \$format ... target format (file extension w/o dot) of destination file [string] (optional)
- \$force\_no\_encrypt ... force the file to be not encrypted even if the content of the publication must be encrypted [boolean] (optional)

#### global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview

- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions
- \$mgmt\_maxsizepreview
- \$mgmt\_mediametadata
- \$hcms\_ext
- \$user

• array of new file names / false on error

#### 7.6.10 convertmedia

# Description

Converts and creates a new image/video/audio or document from original. This is a wrapper function for createmedia, createimages\_video and createdocument.

#### **Syntax**

convertmedia (\$site, \$location\_source, \$location\_dest, \$mediafile, \$format, \$media\_config="", \$force\_no\_encrypt=false)

#### Input parameters

- \$site ... publication name [string]
- \$location\_source ... path to source dir [string]
- \$location\_dest ... path to destination dir [string]
- \$mediafile ... file name [string]
- \$format ... target format (file extension w/o dot) of destination file [string]
- \$media\_config ... media configuration to be used [string] (optional)
- \$force\_no\_encrypt ... force the file to be not encrypted even if the content of the publication must be encrypted [boolean] (optional)

## global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions
- \$mgmt\_maxsizepreview
- \$mgmt\_mediametadata
- \$mgmt\_compress
- \$hcms\_ext

## Output

new file name / false on error

# 7.6.11 convertimage

#### Description

Converts and creates a new image from original. The new image keeps will be resized and cropped to fit width and height.

This is a wrapper function for createmedia.

### **Syntax**

convertimage (\$site, \$file\_source, \$location\_dest, \$format="jpg", \$colorspace="RGB", \$iccprofile="", \$width="", \$height="", \$slug=0, \$units="px", \$dpi=72, \$quality="")

#### Input parameters

- \$site ... publication name [string]
- \$file\_source ... path to source image file [string]
- \$location\_dest ... path to destination dir [string]
- \$format ... format (file extension w/o dot) of destination file [string] (optional)
- \$colorspace ... colorspace of new image [CMY, CMYK, Gray, HCL, HCLp, HSB, HSI, HSL, HSV, HWB, Lab, LCHab, LCHuv, LMS, Log, Luv, OHTA, Rec601YCbCr, Rec709YCbCr, RGB, scRGB, sRGB, Transparent, XYZ, YCbCr, YCC, YDbDr, YIQ, YPbPr, YUV] (optional)
- \$iccprofile ... width in pixel/mm/inch [integer] (optional)
- \$width ... height in pixel/mm/inch [integer] (optional)
- \$height ... slug in pixel/mm/inch [integer] (optional)
- \$slug ... units for width [string]
- \$units ... height and slug [px, mm, inch] (optional)
- \$dpi ... dpi [integer] (optional)
- \$quality ... image quality [1 to 100]

## global input parameters

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions
- \$mgmt\_maxsizepreview
- \$mgmt\_mediametadata
- \$hcms\_ext
- \$user

#### **Output**

new file name / false on error

## 7.6.12 rotateimage

#### Description

Rotates an image (must be jpg, png or gif) using GD library. not used if ImageMagick is available

#### **Syntax**

rotateimage (\$site, \$filepath, \$angle, \$imageformat)

#### Input parameters

- \$site ... publication name [string]
- \$filepath ... path to source media file [string]
- \$angle ... rotation angle [integer]
- \$imageformat ... destination image format [jpg, png, gif]

# global input parameters

- \$mgmt\_config
- \$user

# Output

new image file name / false on error

# 7.6.13 hex2rgb

## **Syntax**

hex2rgb (\$hex)

## Input parameters

• \$hex ... image color as hex-code [string]

#### Output

• RGB-color as array / false on error

# 7.6.14 rgb2hex

#### **Syntax**

rgb2hex (\$red, \$green, \$blue)

#### Input parameters

- \$red ... image color in RGB [string]
- \$green
- \$blue

## Output

• hex-color as string / false on error

# 7.6.15 readmediaplayer\_config

### **Syntax**

readmediaplayer\_config (\$location, \$configfile)

# Input parameters

- \$location ... path to media config file [string]
- \$configfile ... config file name [string]

## global input parameters

• \$mgmt\_config

• \$user

### Output

config array / false on error

# 7.6.16 savemediaplayer\_config

#### **Syntax**

savemediaplayer\_config (\$location, \$configfile, \$mediafiles, \$width=320, \$height=240, \$rotation="", \$filesize="", \$duration="", \$videobitrate="", \$audiobitrate="", \$audiofrequenzy="", \$audiochannels="", \$video\_codec="", \$audio\_codec="")

### Input parameters

- \$location ... path to media config file [string]
- \$configfile ... media config file name [string]
- \$mediafiles ... media file name [array or string]
- \$width ... width in px [integer] (optional)
- \$height ... height in px [integer] (optional)
- \$rotation ... rotation in degree [integer] (optional)
- \$filesize ... file size in kB [integer] (optional)
- \$duration ... duration [hh:mmm:ss] (optional)
- \$videobitrate ... video bitrate in kb/s [string] (optional)
- \$audiobitrate ... audio bitrate in kb/s [string] (optional)
- \$audiofrequenzy ... audio frequenzy in Hz [string] (optional)
- \$audiochannels ... audio channels [mono, stereo] (optional)
- \$video\_codec ... video codec name [string] (optional)
- \$audio\_codec ... audio codec name [string] (optional)

#### global input parameters

- \$mgmt\_config
- \$user

#### **Output**

true / false on error

## 7.6.17 createdocument

#### Description

Creates a new multimedia file of given format at source destination using UNOCONV and saves it as a thumbnail file in the destination location

#### **Syntax**

createdocument (\$site, \$location\_source, \$location\_dest, \$file, \$format="",
\$force\_no\_encrypt=false)

#### Input parameters

- \$site ... publication name [string]
- \$location\_source ... path to source location [string]

- \$location\_dest ... path to destination location [string]
- \$file ... file name [string]
- \$format ... destination file format (extension w/o dot) [string]
- \$force\_no\_encrypt ... force the file to be not encrypted even if the content of the publication must be encrypted [boolean] (optional)

### global input parameters

- \$mgmt\_config
- \$mgmt\_docpreview
- \$mgmt\_docoptions
- \$mgmt\_docconvert
- \$mgmt\_maxsizepreview
- \$hcms ext
- \$hcms\_lang
- \$lang
- \$user

#### Output

new file name / false on error

# 7.6.18 unzipfile

## Description

Unpacks ZIP file and creates media files in destination location for components or unzips files directly for pages (not recommended due to securoty risks by uplaoding unsecured files).

#### **Syntax**

unzipfile (\$site, \$zipfilepath, \$location, \$filename, \$cat="comp", \$user)

## Input parameters

- \$site ... publication name [string]
- \$zipfilepath ... path to source zip file [string]
- \$location ... path to destination location [string]
- \$filename ... category [page, comp]
- \$cat ... name of file for extraction [string]
- \$user ... user name [string]

#### global input parameters

- \$mgmt\_config
- \$mgmt\_uncompress
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions

#### **Output**

result array with all object paths / false

## 7.6.19 clonefolder

### **Description**

Help function for function zipfiles that reads all multimedia files from their multimedia objects and copies them to the same folder structure using the object names.

#### **Syntax**

clonefolder (\$site, \$source, \$destination, \$user, \$activity="")

### Input parameters

- \$site ... publication name [string]
- \$source ... source location [string]
- \$destination ... destination location [string]
- \$user ... user name [string]
- \$activity ... activity that need to be set for daily stats [download] (optional)

## global input parameters

- \$mgmt\_config
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$globalpermission
- \$setlocalpermission

# Output

container IDs as array / false

# 7.6.20 zipfiles\_helper

### Description

Compresses all files and includes their folder structure in a ZIP file. This function does not support multimedia objects and is only a helper function for native file system operations.

#### **Syntax**

zipfiles\_helper (\$source, \$destination, \$zipfilename, \$remove=false)

# Input parameters

- \$source ... source directory [string]
- \$destination ... destination directory [string]
- \$zipfilename ... name of ZIP-file [string]
- \$remove ... remouse all files from source [boolean] (optional)

#### global input parameters

- \$mgmt\_config
- \$mgmt\_compress

true/false

## 7.6.21 zipfiles

#### Description

Compresses all media files and includes their folder structure in a ZIP file.

#### Syntax

zipfiles (\$site, \$multiobject\_array, \$destination="", \$zipfilename, \$user, \$activity="", \$flatzip=false)

### Input parameters

- \$site ... publication name [string]
- \$multiobject\_array ... array with path to source files [array]
- \$destination ... destination location (if this is null then the \$location where the zip-file resists will be used) [string]
- \$zipfilename ... name of ZIP-file [string]
- \$user ... user name [string]
- \$activity ... activity that need to be set for daily stats [download] (optional)
- \$flatzip ... flat hierarchy means no directories [boolean] (optional)

# global input parameters

- \$mgmt\_config
- \$mgmt\_compress
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$globalpermission
- \$setlocalpermission
- \$hcms\_lang
- \$lang

# Output

• true/false

# 7.6.22 px2mm

#### Description

Convert mm to pixel

#### **Syntax**

px2mm (\$pixel, \$dpi=72)

### Input parameters

- \$pixel ... pixel [integer]
- \$dpi ... dpi [integer] (optional)

• pixel / false

7.6.23 px2inch

## Description

Convert pixel to inches

#### **Syntax**

px2inch (\$pixel, \$dpi=72)

## Input parameters

- \$pixel ... pixel [integer]
- \$dpi ... dpi [integer] (optional)

## Output

• inch / false

# 7.6.24 inch2px

## Description

Convert inches to pixel

# **Syntax**

inch2px (\$inch, \$dpi=72)

## Input parameters

- \$inch ... pixel [integer]
- \$dpi ... dpi [integer] (optional)

# Output

pixel / false

## 7.6.25 sec2time

#### Description

Convert seconds to time format hh: mm: ss.mmm

### **Syntax**

sec2time (\$input)

## Input parameters

• \$input ... time in seconds [float]

# Output

• time in hh: mm: ss.mmm / false

### 7.6.26 mediasize2frame

#### Description

Calculates the width and height of a media to fit into a given frame size.

#### **Syntax**

mediasize2frame (\$mediawidth, \$mediaheight, \$framewidth="", \$frameheight="", \$keepmaxsize=true)

## Input parameters

- \$mediawidth ... media width [integer]
- \$mediaheight ... media height [integer]
- \$framewidth ... frame width [integer] (optional)
- \$frameheight ... frame height [integer] (optional)
- \$keepmaxsize ... keep maximum media size based on original dimensions of media without stretching [boolean] (optional)

## Output

• width and height as array / false

## 7.6.27 vtt2array

### **Description**

Converts VTT string to array

#### **Syntax**

vtt2array (\$vtt)

## Input parameters

• \$vtt ... video text track [string]

#### **Output**

· array / false

# 7.6.28 html2pdf

#### Description

Converts html to pdf using WKHTMLTOPDF and XSERVER. The CSS media print style will be applied.

For full support you might want to install the package provided from WKHTMLTOPDF directly (patched QT).

See the event log in case the function does not create a proper result since you are not using a patched QT version.

See also: https://wkhtmltopdf.org/usage/wkhtmltopdf.txt

#### **Syntax**

html2pdf (\$source, \$dest, \$cover="", \$toc=false, \$page\_orientation="Portrait", \$page\_size="A4", \$page\_margin=10, \$image\_dpi=144, \$image\_quality=95,

\$smart\_shrinking=true, \$options="")

#### Input parameters

- \$source ... URLs or pathes to html source files [array]
- \$dest ... path of pdf destination output file [string]
- \$cover ... cover page html file [string] (optional)
- \$toc ... create TOC table of contents [boolean] (optional)
- \$page\_orientation ... page orientation [Landscape, Portrait] (optional)
- \$page\_size ... page size like A4 or Letter [string] (optional)
- \$page\_margin ... page margin in mm [integer] (optional)
- \$image\_dpi ... image DPI [integer] (optional)
- \$image\_quality ... image quality 1-100 [integer] (optional)
- \$smart\_shrinking ... use smart shrinking of the content so it can fit in the page [boolean] (optional)
- \$options ... additional WKHMTLTOPDF options [string] (optional)

# global input parameters

\$mgmt\_config

# Output

• true / false on error

# 7.6.29 mergepdf

### Description

Merges pdf files into one pdf file. Do NOT USE special characters in file names. See also: https://www.pdflabs.com/docs/pdftk-man-page/

#### **Syntax**

mergepdf (\$source, \$dest)

#### Input parameters

- \$source ... pathes to pdf source files [array]
- \$dest ... path of pdf destination output file [string]

## global input parameters

• \$mgmt\_config

#### **Output**

• true / false on error

## 7.7 Metadata API Functions

## 7.7.1 importmetadata

## Description

Imports metadata form CSV file for various assets linked by name or conatiner ID. Empty rows or rows without a delimiter will be ignored.

In order to identify an asset the file name as "Name" or the container ID as "containerID" must be provided in the first row before the content rows.

#### **Syntax**

importmetadata (\$site, \$location, \$file, \$user, \$type="", \$delimiter=";", \$enclosure='"', \$charset="utf-8")

### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$file ... path to CSV file [string]
- \$user ... user name [string]
- \$type ... type array or string [u, f, I, c, d, k] (optional)
- \$delimiter ... delimiter [string] (optional)
- \$enclosure ... enclosure [string] (optional)
- \$charset ... character set [string] (optional)

### global input parameters

- \$mgmt\_config
- \$eventsystem

#### **Output**

• true / false

#### 7.7.2 loadtaxonomy

#### **Description**

Generates an array from a taxonomy definition file located in data/include/ to be used for presentation or CSV export.

### **Syntax**

loadtaxonomy (\$site, \$start=1, \$perpage=100000)

## Input parameters

- \$site ... publication name [string]
- \$start ... return rows starting with row number [integer] (optional)
- \$perpage ... return number of rows [integer] (optional)

### global input parameters

• \$mgmt\_config

• true / false

### 7.7.3 savetaxonomy

#### Description

Generates an array from a taxonomy definition file located in data/include/ to be used for presentation or CSV export.

#### **Syntax**

savetaxonomy (\$site, \$taxonomy, \$saveindex\_start, \$saveindex\_stop)

## Input parameters

- \$site ... publication name [string]
- \$taxonomy ... taxonomy with rows and languages as keys [array]
- \$saveindex\_start ... replace rows starting with row number [integer]
- \$saveindex\_stop ... replace rows ending with row number [integer]

### global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.7.4 createtaxonomy

#### **Description**

Generates an array from a taxonomy defintion file (CSV) and saves the PHP file in data/include/publication-name.taxonomy.inc.php.

Recreates the taxonomy for all objects if the taxonomy defintion has been uodated.

#### Syntax

createtaxonomy (\$site\_name="", \$recreate=false)

#### Input parameters

- \$site\_name ... publication name [string] (optional)
- \$recreate ... recreate taxonomy file [boolean] (optional)

#### global input parameters

\$mgmt\_config

## Output

true / false

## 7.7.5 splitkeywords

### **Description**

Generates a keyword list from a text by splitting and transforming the comma separated string.

#### **Syntax**

splitkeywords (\$keywords, \$charset="UTF-8")

### Input parameters

- \$keywords ... comma seperated keywords [string]
- \$charset ... character set [string] (optional)

## Output

keywords as array / false on error

# 7.7.6 copymetadata

## Description

Copies all meta data from source to destination file using EXIFTOOL

#### Syntax

copymetadata (\$file\_source, \$file\_dest)

## Input parameters

- \$file\_source ... path to source file [string]
- \$file\_dest ... path to destination file [string]

#### global input parameters

- \$mgmt\_config
- \$mgmt\_mediametadata
- \$user

#### Output

true / false

## 7.7.7 extractmetadata

### **Description**

Extracts all meta data from a file using EXIFTOOL

#### **Syntax**

extractmetadata (\$file)

## Input parameters

• \$file ... path to image file [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$mgmt\_mediametadata

# Output

• result array / false on error

# 7.7.8 xmlobject2array

## Description

Converts an xmlobject to an array, provided by xaviered at gmail dot com

### **Syntax**

xmlobject2array (\$obj, \$namespace="")

## Input parameters

- \$obj ... XML [object]
- \$namespace ... namespace [array] (optional)

## Output

• result array / false

# 7.7.9 id3\_getdata

### Description

Requires getID3 library since EXIFTOOL cannot write ID3 tags so far

#### **Syntax**

id3\_getdata (\$file)

## Input parameters

• \$file ... path to audio file [string]

## global input parameters

- \$mgmt\_config
- \$hcms\_ext

## Output

result array / false on error

## 7.7.10 id3\_writefile

### Description

Writes ID3 tags into audio file for supported file types and keeps the existing ID3 tags

#### **Syntax**

id3\_writefile (\$file, \$id3, \$keep\_data=true, \$movetempfile=true)

## Input parameters

- \$file ... abs. path to audio file [string]
- \$id3 ... ID3 tag [array]
- \$keep\_data ... keep existing ID3 data of file [boolean] (optional)
- \$movetempfile ... move tempoarary file from unecrypted to encrypted [boolean] (optional)

#### global input parameters

- \$user
- \$mgmt\_config
- \$mgmt\_mediametadata
- \$hcms\_ext

### Output

true / false on error

## 7.7.11 id3\_create

## Description

Defines ID3 tag array based on the media mapping of a publication.

### **Syntax**

id3\_create (\$site, \$text)

## Input parameters

- \$site ... publication name [string]
- \$text ... text from content container [array]

## global input parameters

\$mgmt\_config

## Output

• ID3 tag array / false on error

## 7.7.12 xmp\_getdata

## Syntax

xmp\_getdata (\$file)

## Input parameters

• \$file ... path to image file [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_ext

### Output

• result array / false on error

## 7.7.13 xmp\_writefile

#### Description

Writes XMP tags into image file for supported file types and keeps the existing XMP tags

#### Syntax

xmp\_writefile (\$file, \$xmp, \$keep\_data=true, \$movetempfile=true)

## Input parameters

- \$file ... abs. path to image file [string]
- \$xmp ... XMP tag [array]
- \$keep\_data ... keep existing XMP data of file [boolean] (optional)
- \$movetempfile ... move tempoarary file from unecrypted to encrypted [boolean] (optional)

## global input parameters

- \$user
- \$mgmt\_config
- \$mgmt\_mediametadata
- \$hcms\_ext

### Output

• true / false on error

## 7.7.14 xmp\_create

## Description

Defines XMP tag array based on the media mapping of a publication

#### **Syntax**

xmp\_create (\$site, \$text)

#### Input parameters

- \$site ... publication name [string]
- \$text ... text from content container [array]

## global input parameters

• \$mgmt\_config

## Output

XMP tag array / false on error

# 7.7.15 geo2decimal

## **Syntax**

geo2decimal (\$coordinate, \$hemisphere)

## Input parameters

- \$coordinate ... GPS location [degrees, minutes, seconds]
- \$hemisphere ... hemisphere [N, O, S, W]

## Output

• decimal result / false

# 7.7.16 exif\_getdata

### **Syntax**

exif\_getdata (\$file)

## Input parameters

• \$file ... path to image file [string]

## global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_ext

# Output

· result array / false

# 7.7.17 iptc\_getdata

#### **Syntax**

iptc\_getdata (\$file)

## Input parameters

• \$file ... path to image file [string]

### global input parameters

- \$user
- \$mgmt\_config
- \$hcms\_ext

## Output

result array / false

## 7.7.18 iptc\_getcharset

### **Description**

Copied from MediaWiki!

Warning, this function does not (and is not intended to) detect all iso 2022 escape codes. In practise, the code for utf-8 is the only code that seems to have wide use. It does detect that code.

According to iim standard, charset is defined by the tag 1:90.

in which there are iso 2022 escape sequences to specify the character set.

the iim standard seems to encourage that all necessary escape sequences are in the 1:90 tag, but says it doesn't have to be.

This is in need of more testing probably. This is definitely not complete.

however reading the docs of some other iptc software, it appears that most iptc software only recognizes utf-8. If 1:90 tag is not present content is

usually ascii or iso-8859-1 (and sometimes utf-8), but no guarantee.

This also won't work if there are more than one escape sequence in the 1:90 tag or if something is put in the G2, or G3 charsets, etc. It will only reliably recognize utf-8. This is just going through the charsets mentioned in appendix C of the iim standard.

### **Syntax**

iptc\_getcharset (\$tag)

### Input parameters

\$tag ... iptc tag that holds character set information [string]

### Output

character set as string / false on error

# 7.7.19 iptc\_maketag

#### **Description**

Convert the IPTC tag to binary code

### **Syntax**

iptc\_maketag (\$record=2, \$tag, \$value)

## Input parameters

\$record ... type of tag (e.g. 2) [integer]

- \$tag ... code of tag (e.g. 025) [string]
- \$value ... value of tag [string]

· binary IPTC tag / false on error

## 7.7.20 iptc\_writefile

# Description

Writes IPTC tags into image file for supported file types and keeps the existing IPTC tags

## **Syntax**

iptc\_writefile (\$file, \$iptc, \$keep\_data=true, \$movetempfile=true)

## Input parameters

- \$file ... abs. path to image file [string]
- \$iptc ... IPTC tag [array]
- \$keep\_data ... keep existing IPTC data of file [boolean] (optional)
- \$movetempfile ... move tempoarary file from unecrypted to encrypted [boolean] (optional)

# global input parameters

- \$user
- \$mgmt\_config
- \$mgmt\_mediametadata

#### **Output**

true / false on error

## 7.7.21 iptc\_create

#### Description

Defines IPTC tag array based on the media mapping of a publication

#### **Syntax**

iptc\_create (\$site, \$text)

## Input parameters

- \$site ... publication name [string]
- \$text ... text from content container [array]

### global input parameters

• \$mgmt\_config

#### **Output**

• IPTC tag array / false on error

# 7.7.22 createmapping

### **Description**

Prepares the PHP mapping array from the provided mapping definition and saves media mapping file

### **Syntax**

createmapping (\$site, \$mapping)

## Input parameters

- \$site ... publication name [string]
- \$mapping ... mapping definition [string]

### global input parameters

• \$mgmt\_config

## Output

• true / false on error

# 7.7.23 getmapping

#### **Description**

Load the mapping file of the provided publication.

#### **Syntax**

getmapping (\$site)

#### Input parameters

• \$site ... publication name [string]

#### global input parameters

• \$mgmt\_config

# Output

• mapping code for display / false

### 7.7.24 metadata\_exists

## Description

Verifies if the content of a specific text ID that triggers a Cloud API call exists already. This function is used to reduce/trigger Cloud API calls in case the content exists already and the media file does not need to be analyzed by a cloud service.

#### **Syntax**

metadata\_exists (\$mapping, \$text\_array)

#### Input parameters

- \$mapping ... mapping [array:metadata-tag-name => text-id]
- \$text\_array ... text [array:metadata-text-id => content]

## Output

true / false

## 7.7.25 setmetadata

### **Description**

Saves meta data of a multimedia file using a provided mapping in the proper fields of the content container.

If no mapping is given a default mapping will be used.

#### **Syntax**

```
setmetadata ($site, $location="", $object="", $mediafile="", $mapping="", $containerdata="", $user, $savecontainer=true)
```

### Input parameters

- \$site ... publication name [string]
- \$location ... location path [string] (optional)
- \$object ... object name [string] (optional)
- \$mediafile ... media file name [string] (optional)
- \$mapping ... mapping [array: metadata-tag-name => text-id] (optional)
- \$containerdata ... container content as XML [string] (optional)
- \$user ... user name [string]
- \$savecontainer ... save content container [boolean] (optional)

### global input parameters

- \$eventsystem
- \$mgmt\_config
- \$hcms\_ext

## Output

container content as XML string / false

# 7.8 Link API Functions

### 7.8.1 link db restore

### Description

This function restores a given or all link management index files

## **Syntax**

link db restore (\$site="")

## Input parameters

• \$site ... publication name [string] (optional)

## global input parameters

\$mgmt\_config

## Output

• true / false on error

## 7.8.2 link\_db\_load

## Description

This function loads and locks the link management database each record of the link management database has the following design: xml-content container: | absolute path to 1-n objects: | 1-m links used by 1-n objects important: the link management database has to saved or closed after loading it.

### **Syntax**

link\_db\_load (\$site, \$user)

### Input parameters

- \$site ... publication name [string]
- \$user ... user name [string]

#### global input parameters

• \$mgmt\_config

# Output

• link database [2 dim. array] or true / false on error

## 7.8.3 link\_db\_read

#### **Description**

This function loads the link management database for reading without locking

# **Syntax**

link\_db\_read (\$site)

## Input parameters

• \$site ... publication name [string]

#### global input parameters

• \$mgmt\_config

# Output

• link database [2 dim. array] or true / false on error

# 7.8.4 link\_db\_close

## Description

closes and unlocks the link management database.

### **Syntax**

link\_db\_close (\$site, \$user)

### Input parameters

- \$site ... publication name [string]
- \$user ... user name [string]

## global input parameters

• \$mgmt\_config

## Output

• true/false

# 7.8.5 link\_db\_save

## Description

This function saves und unlocks the link management database

#### **Syntax**

link\_db\_save (\$site, \$link\_db, \$user)

## Input parameters

- \$site ... link database [array]
- \$link\_db ... publication name [string]
- \$user ... user name [string]

## global input parameters

• \$mgmt\_config

## Output

• true/false on error

## 7.8.6 link\_db\_update

# Description

This function inserts, updates and removes objects and their links from the link management database (add or update a link)

depending on which link is left empty:

link\_curr = "": add new link (just one link matching given category)

link\_new = "": delete current link in use (just one link matching given category)

link\_curr & link\_new are not empty and not equal: update current link with the new one

## **Syntax**

link\_db\_update (\$site, \$link\_db, \$attribute, \$contentfile="", \$cat="", \$link\_curr="", \$link\_new="", \$option)

## Input parameters

- \$site ... publication name [string]
- \$link\_db ... link database [2 dim. array]
- \$attribute ... attribute [object, link]
- \$contentfile ... content container [string] (optional)
- \$cat ... link category [comp, page] (optional)
- \$link\_curr ... current link must be an URL or absolute/relative path [string] (optional)
- \$link\_new ... new link must be an URL or absolute/relative path [string] (optional)
- \$option ... update option [all, unique]

## global input parameters

\$mgmt\_config

## Output

• link database [array] or true if link index database is not used / false on error

# 7.8.7 link\_db\_insert

## Description

This function inserts a new record in the link management database optionally the created object can be also inserted

# **Syntax**

link\_db\_insert (\$site, \$link\_db, \$contentfile, \$cat, \$object="")

## Input parameters

- \$site ... publication name [string]
- \$link\_db ... link database [2 dim. array]
- \$contentfile ... content container name [string]
- \$cat ... link category [comp, page]
- \$object ... object name (optional)

#### global input parameters

\$mgmt\_config

• link database [2 dim. array] or true / false

## 7.8.8 link\_db\_delete

### Description

This function deletes a record in the link management database

#### Syntax

link\_db\_delete (\$site, \$link\_db, \$contentfile)

#### Input parameters

- \$site ... link database [2 dim. array]
- \$link\_db ... content container name [string]
- \$contentfile

# global input parameters

• \$mgmt\_config

# Output

• link database [2 dim. array] or true / false on error

## 7.8.9 link\_db\_getobject

#### Description

This function splits the object string into an array of objects.

#### **Syntax**

link\_db\_getobject (\$multiobject)

## Input parameters

\$multiobject ... link database attribut (references to objects seperated by |) [string]

# global input parameters

\$mgmt\_config

## Output

objects [array] / false on error

# 7.8.10 link\_update

#### **Description**

This function updates the link of the published and working content container and link file

#### **Syntax**

link\_update (\$site, \$container, \$link\_old, \$link\_new)

## Input parameters

- \$site ... publication name [string]
- \$container ... container name [string]
- \$link\_old ... old link (converted) [string]
- \$link\_new ... new link (converted) [string]

### global input parameters

- \$user
- \$mgmt\_config

#### Output

true/false

# 7.8.11 getlinkedobject

#### **Description**

This function gets all objects which link to the given object. works with pages (page links) and components (component links) if link management is enabled.

## **Syntax**

getlinkedobject (\$site, \$location, \$page, \$cat)

## Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object (name and extension) [string]
- \$cat ... category [page, comp] (optional)

### global input parameters

• \$mgmt\_config

### Output

objects which link to the given object [array] or true / false

# 7.8.12 getconnectedobject

#### **Description**

This function gets all objects which use the same content container and are therefore connected.

## **Syntax**

getconnectedobject (\$container, \$type="work")

#### Input parameters

- \$container ... container name [string]
- \$type ... container type [work, published, version] (optional)

## global input parameters

- \$mgmt\_config
- \$user

## Output

connected objects[array]

## 7.8.13 extractlinks

## Description

This function extracts all links based on it's identifier from a text and returns an array of all links

#### **Syntax**

extractlinks (\$textcontent, \$identifier)

#### Input parameters

- \$textcontent ... text content [string]
- \$identifier ... link identifiert ["href" for hyperreferences, "src" for image references or embed references (flash), "value" for paramter (flash)]

## global input parameters

• \$mgmt\_config

## Output

object links [array] / false on error

# 7.9 Plugin API Functions

## 7.9.1 plugin\_getdefaultconf

## **Syntax**

plugin\_getdefaultconf ()

## Input parameters

#### **Output**

default value as array

## 7.9.2 plugin\_readmenu

### **Description**

Reads Menupoints and menugroups from the xml data.

Be carefull with nesting, function getcontent is used and you can't nest groups inside of groups as a subpoint!

Input parameter \$pluginFolder contains the directory of the plugin.

Returns an Array containing every group and menupoint with its configuration.

### **Syntax**

plugin\_readmenu (\$xml, \$pluginFolder)

### Input parameters

- \$xml ... plugin xml [string]
- \$pluginFolder ... plugin directory [string]

## global input parameters

• \$mgmt\_config

## Output

· menu point array used by navigator

# 7.9.3 plugin\_parse

#### **Description**

Reads the plugin configurations from the file system.

Checks the folder defined in mgmt\_config and searched for plugins and their configurations files

It either takes needed values from the configuration, from the \$oldData or defaultConfiguration.

#### **Syntax**

plugin\_parse (\$oldData=array())

# Input parameters

• \$oldData ... mgmt\_plugin [array] (optional)

### global input parameters

\$mgmt\_config

#### Output

mgmt\_plugin as array

## 7.9.4 plugin\_generatedefinition

## Description

Generates the Array definition used in php for \$array with the name of \$arrayName. Run recursively through the array and supports boolean, numeric and string types for the key and value.

## **Syntax**

plugin\_generatedefinition (\$arrayName, \$array)

### Input parameters

- \$arrayName ... name of array holding the plugin definitions [string]
- \$array ... configuration containing the values and keys [array]

### global input parameters

• \$mgmt\_config

### Output

• plugin array / false on error

## 7.9.5 plugin\_saveconfig

#### **Description**

Saves the plugin configuration \$configuration into the configuration file. The configuration file is located in the data/config directory and is named plugin.conf.php.

#### **Syntax**

plugin\_saveconfig (\$configuration)

#### Input parameters

• \$configuration ... configuration [array]

## global input parameters

• \$mgmt\_config

#### **Output**

• true / false on error

# 7.9.6 plugin\_generatelink

#### Description

Generates a link to be used when linking to other pages inside of a plugin

#### Syntax

plugin\_generatelink (\$plugin, \$page, \$control=false, \$additionalGetParameters=false)

# Input parameters

• \$plugin ... plugin name [string]

- \$page ... plugin page (relative reference to the plugins main page) [string]
- \$control ... control (relative reference to the plugins control page) [string]
- \$additionalGetParameters ... additional GET parameters [string]

## global input parameters

\$mgmt\_config

## Output

• plugin link

# 7.10 User Interface API Functions

## 7.10.1 windowwidth

## Description

Returns the width of the object window when editing/opening an object

### **Syntax**

windowwidth (\$type="object")

### Input parameters

\$type ... type [string] (optional)

## global input parameters

• \$mgmt\_config

#### Output

• window width in pixels

# 7.10.2 windowheight

#### Description

Returns the height of the object window when editing/opening an object

#### **Syntax**

windowheight (\$type="object")

#### Input parameters

• \$type ... type [string] (optional)

#### global input parameters

• \$mgmt\_config

• window height in pixels

## 7.10.3 toggleview

## Description

Set explorer objectlist view parameter

#### **Syntax**

toggleview (\$view)

## Input parameters

• \$view ... view [detail, small, medium, large]

# global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.10.4 togglesidebar

## Description

Enables or disables the sidebar

### **Syntax**

togglesidebar (\$view)

# Input parameters

• \$view ... view [boolean]

## global input parameters

• \$mgmt\_config

# Output

• true / false

## 7.10.5 setfilter

## Description

Set filter settings for object view in session

## **Syntax**

setfilter (\$filter\_set)

#### Input parameters

 \$filter\_set ... set of filters as array with keys [comp, image, document, video, audio] and value [0, 1]

## global input parameters

• \$mgmt\_config

# Output

true / false

## 7.10.6 objectfilter

#### **Description**

If an object name is passing the filter-test. One or more filters need to be set in the session "hcms\_objectfilter".

### **Syntax**

objectfilter (\$file)

#### Input parameters

• \$file ... file name [string]

#### global input parameters

- \$mgmt\_config
- \$hcms\_ext

# Output

true / false

# 7.10.7 showdate

#### Description

Prepares the date and time for the display in the users time zone and format.

# **Syntax**

showdate (\$date, \$sourceformat="Y-m-d H:i", \$targetformat="Y-m-d H:i", \$timezone=true)

## Input parameters

- \$date ... date and time [string
- \$sourceformat ... date input format [string]
- \$targetformat ... date output format [string]
- \$timezone ... correct time zone [boolean] (optional)

### global input parameters

• \$mgmt\_config

## Output

date and time

#### 7.10.8 showshorttext

#### Description

Reduce the length of a string and add "..." at the end

#### Syntax

showshorttext (\$text, \$length=0, \$linebreak=false, \$charset="UTF-8")

### Input parameters

- \$text ... text [string]
- \$length ... max. length of text (minus length starting from the end) [integer] (optional)
- \$linebreak ... line break instead of cut [boolean] only if length is positive (optional)
- \$charset ... character set for encoding [string] (optional)

## Output

- shortened text if possible
- or orignal text

# 7.10.9 showtopbar

#### **Description**

Returns the standard top bar with or without close button

### **Syntax**

showtopbar (\$show, \$lang="en", \$close\_link="", \$close\_target="", \$individual\_button="", \$id="bar")

#### Input parameters

- \$show ... message [string]
- \$lang ... language code [string] (optional)
- \$close\_link ... close button link [string] (optional)
- \$close\_target ... link target [string] (optional)
- \$individual\_button ... individual button [string] (optional)
- \$id ... ID of div-layer [string] (optional)

## global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang

top bar box / false on error

## 7.10.10 showtopmenubar

#### **Description**

Returns the menu top bar with or without close button

#### Syntax

showtopmenubar (\$show, \$menu\_array, \$lang="en", \$close\_link="", \$close\_target="", \$id="bar")

## Input parameters

- \$show ... message [string]
- \$menu\_array ... menu [array:name => properties/events]
- \$lang ... language code [string] (optional)
- \$close\_link ... close button link [string] (optional)
- \$close\_target ... link target [string] (optional)
- \$id ... ID of div-layer [string] (optional)

#### global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang

### Output

• top bar box / false on error

#### 7.10.11 showhomeboxes

### **Description**

Returns the file path to the home boxes

#### **Syntax**

showhomeboxes (\$homebox\_array)

#### Input parameters

\$homebox\_array ... home box names [array:file name => readable name]

## global input parameters

• \$mgmt\_config

### Output

path to home boxes as array / false on error

# 7.10.12 showmessage

## Description

Returns the standard message box with close button

### **Syntax**

showmessage (\$show, \$width="580px", \$height="70px", \$lang="en", \$style="", \$id="hcms\_messageLayer")

#### Input parameters

- \$show ... message [string]
- \$width ... width in pixel [integer] (optional)
- \$height ... height in pixel [integer] (optional)
- \$lang ... language code [string] (optional)
- \$style ... additional style definitions of div-layer [string] (optional)
- \$id ... ID of div-layer [string] (optional)

# global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang

# Output

message box / false on error

# 7.10.13 showinfopage

### Description

Returns a full html info page

## **Syntax**

showinfopage (\$show, \$lang="en", \$onload="")

# Input parameters

- \$show ... message [string]
- \$lang ... language code [string] (optional)
- \$onload ... on load JS events [string] (optional)

# global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang\_codepage
- \$hcms\_lang

# Output

• message on html info page / false on error

# 7.10.14 showinfobox

## Description

Returns the infobox as long as it has not been closed. Saves the close event in localstorage of browser.

## **Syntax**

showinfobox (\$show, \$lang="en", \$style="", \$id="hcms\_infoboxLayer")

#### Input parameters

- \$show ... message [string]
- \$lang ... language code [string] (optional)
- \$style ... additional style definitions of div-layer [string] (optional)
- \$id ... ID of div-layer [string] (optional)

#### global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang\_codepage
- \$hcms\_lang

# Output

message in div layer / false on error

### 7.10.15 showsharelinks

# Description

Returns the presenation of share links of social media platforms

# **Syntax**

showsharelinks (\$link, \$mediafile, \$lang="en", \$style="", \$id="hcms\_shareLayer")

# Input parameters

- \$link ... link to share [string]
- \$mediafile ... media file name [string]
- \$lang ... language code [string] (optional)
- \$style ... additional style definitions of div-layer [string] (optional)
- \$id ... ID of div-layer [string] (optional)

# global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang\_codepage
- \$hcms\_lang

# Output

• message in div layer / false on error

### 7.10.16 showmetadata

# **Syntax**

showmetadata (\$data, \$lang="en", \$class\_headline="hcmsRowData2")

## Input parameters

- \$data ... metadata [array]
- \$lang ... 2 digits language code [string]
- \$class\_headline ... CSS-class with background-color for headlines [string] (optional)

## global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang\_codepage
- \$hcms\_lang

## Output

• result as HTML unordered list / false on error

# 7.10.17 showobject

## **Syntax**

showobject (\$site, \$location, \$page, \$cat="", \$name="")

### Input parameters

- \$site ... publication name [string]
- \$location ... location [string]
- \$page ... object name [string]
- \$cat ... category [page, comp] (optional)
- \$name ... object name [string] (optional)

# global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang
- \$hcms\_lang\_date
- \$lang
- \$user

# Output

html presentation / false

# 7.10.18 showmedia

## Description

This function requires site, location and cat to be set as global variable in order to validate the access permission of the user

### **Syntax**

showmedia (\$mediafile, \$medianame, \$viewtype, \$id="", \$width="", \$height="", \$class="hcmsImageItem")

# Input parameters

- \$mediafile ... mediafile (publication/filename) [string]
- \$medianame ... name of mediafile for display [string]
- \$viewtype ... view type [template, media\_only, preview, preview\_download, preview\_no\_rendering]
- \$id ... ID of the HTML media tag [string]
- \$width ... width in px [integer] (optional)
- \$height ... height in px [integer] (optional)
- \$class ... CSS class [string] (optional)

# global input parameters

- \$site
- \$mgmt\_config
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imagepreview
- \$mgmt\_docpreview
- \$mgmt\_docoptions
- \$mgmt\_docconvert
- \$mgmt\_maxsizepreview
- \$hcms\_charset
- \$hcms\_lang\_codepage
- \$hcms\_lang\_date
- \$hcms\_lang
- \$lang
- \$site
- \$location
- \$cat
- \$page
- \$user
- \$pageaccess
- \$compaccess
- \$downloadformats
- \$hiddenfolder
- \$hcms\_linking
- \$setlocalpermission
- \$mgmt\_imageoptions
- \$is\_mobile
- \$is\_iphone

# Output

html presentation of any media asset / false

# 7.10.19 showcompexplorer

## Description

Creates component explorer including the search form

# **Syntax**

```
showcompexplorer ($site, $dir, $location_esc="", $page="", $compcat="multi", $search_expression="", $search_format="", $mediatype="", $lang="en", $callback="", $scalingfactor="1", $view="list", $thumbsize=100)
```

# Input parameters

- \$site ... publication name [string]
- \$dir ... current explorer location [string]
- \$location\_esc ... object location [string] (optional)
- \$page ... object name [string] (optional)
- \$compcat ... component category [single, multi, media] (optional)
- \$search\_expression ... search expression [string] (optional)
- \$search\_format ... search format [object, document, image, video, audio, watermark] (optional)
- \$mediatype ... media-type [audio, video, text, flash, image, compressed, binary] (optional)
- \$lang ... view tpye [list, gallery] (optional)
- \$callback ... thumbnail size in pixel [integer] callback of CKEditor [string] (optional)
- \$scalingfactor ... saclingfactor for images [integer] (optional)
- \$view
- \$thumbsize

## global input parameters

- \$mgmt\_config
- \$siteaccess
- \$pageaccess
- \$compaccess
- \$rootpermission
- \$globalpermission
- \$localpermission
- \$hiddenfolder
- \$html5file
- \$temp\_complocation
- \$hcms\_charset
- \$hcms\_lang
- \$user

#### Output

explorer with search / false on error

### 7.10.20 showeditor

#### Description

Returns the rich text editor code

#### Svntax

showeditor (\$site, \$hypertagname, \$id, \$contentbot="", \$sizewidth=600, \$sizeheight=300,

\$toolbar="Default", \$lang="en", \$dpi=72)

#### Input parameters

- \$site ... publication name [string]
- \$hypertagname ... hypertag name [string]
- \$id ... hypertag id [string]
- \$contentbot ... content [string]
- \$sizewidth ... width of the editor [integer]
- \$sizeheight ... height of the editor [integer]
- \$toolbar ... toolbar set [string]
- \$lang ... 2 digit language code [string]
- \$dpi ... dpi for scaling images [integer]

# global input parameters

- \$mgmt\_config
- \$publ\_config

# Output

rich text editor code / false on error

# 7.10.21 showinlineeditor\_head

#### Description

Returns the rich text editor code (JS, CSS) for include into the html head section

#### **Syntax**

showinlineeditor\_head (\$lang)

### Input parameters

• \$lang ... 2 digit language code [string]

### global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang

## **Output**

rich text editor code for html head section / false on error

# 7.10.22 showinlinedatepicker\_head

#### **Description**

Returns the date picker code (JS, CSS) for include into the html head section

### **Syntax**

showinlinedatepicker\_head ()

#### Input parameters

# global input parameters

• \$mgmt\_config

# Output

date picker code for html head section / false on error

# 7.10.23 showinlineeditor

## **Description**

shows the rich text inline editor

### **Syntax**

```
showinlineeditor ($site, $hypertag, $id, $contentbot="", $sizewidth=600, $sizeheight=300, $toolbar="Default", $lang="en", $contenttype="", $cat="", $location_esc="", $page="", $contentfile="", $db_connect=0, $token="")
```

#### Input parameters

- \$site ... publication name [string]
- \$hypertag ... hypertag [string]
- \$id ... hypertag id [string]
- \$contentbot ... content [string]
- \$sizewidth ... width of the editor [integer]
- \$sizeheight ... height of the editor [integer]
- \$toolbar ... toolbar set [string]
- \$lang ... 2 digit language code [string]
- \$contenttype ... content-type [string]
- \$cat ... category [page, comp]
- \$location\_esc ... converted location [string]
- \$page ... object name [string]
- \$contentfile ... container name [string]
- \$db\_connect ... DB-connect file name [string]
- \$token ... security token [string]

### global input parameters

- \$mgmt\_config
- \$publ\_config
- \$hcms\_charset
- \$hcms\_lang

# Output

rich text editor code / false on error

# 7.10.24 showvideoplayer

# Description

Generates a html segment for the video player code

#### **Syntax**

showvideoplayer (\$site, \$video\_array, \$width=854, \$height=480, \$logo\_url="", \$id="", \$title="", \$autoplay=true, \$fullscreen=true, \$loop=false, \$muted=false, \$controls=true, \$iframe=false, \$force\_reload=false)

### Input parameters

- \$site ... video array containing the different html sources [array]
- \$video\_array ... width of the video in pixel [integer]
- \$width ... height of the video in pixel [integer]
- \$height ... link to the logo which is displayed before you click on play (If the value is null the default logo will be used) [string]
- \$logo\_url ... ID of the video (will be generated when empty) [string]
- \$id ... title for this video [string]
- \$title ... autoplay video on load (true)
- \$autoplay ... default is false [boolean]
- \$fullscreen ... view the video in full screen [boolean]
- \$loop ... play loop [boolean] (optional)
- \$muted ... muted/no sound [boolean] (optional)
- \$controls ... player controls [boolean] (optional)
- \$iframe ... use video in iframe [boolean] (optional)
- \$force\_reload ... reload video sources to prevent the browser cache to show the same video even if it has been changed [boolean] (optional)

# global input parameters

• \$mgmt\_config

# Output

HTML code of the video player / false on error

# 7.10.25 showvideoplayer\_head

#### **Syntax**

showvideoplayer\_head (\$secureHref=true, \$fullscreen=true)

### Input parameters

- \$secureHref ... secure hyperreferences by adding 'hypercms\_' [boolean] (optional)
- \$fullscreen ... is it possible to view the video in fullScreen [boolean] (optional)

# global input parameters

\$mgmt\_config

# **Output**

• head for video player / false on error

# 7.10.26 showaudioplayer

## Description

Generates the html segment for the video player code

# **Syntax**

showaudioplayer (\$site, \$audioArray, \$width=320, \$height=320, \$logo\_url="", \$id="", \$autoplay=false, \$loop=false, \$controls=true, \$force\_reload=false)

#### Input parameters

- \$site ... publication name [string]
- \$audioArray ... audio files [array]
- \$width ... ID of the tag [string] (optional)
- \$height ... width of the video in pixel [integer]
- \$logo\_url ... height of the video in pixel [integer]
- \$id ... link to the logo which is displayed before you click on play (If the value is null the default logo will be used) [string]
- \$autoplay ... ID of the video (will be generated when empty) [string]
- \$loop ... autoplay (optional) [boolean]
- \$controls ... play loop (optional) [boolean]
- \$force\_reload ... player controls (optional) [boolean]

# global input parameters

• \$mgmt\_config

### **Output**

• code of the HTML5 player / false

# 7.10.27 showaudioplayer\_head

#### **Syntax**

showaudioplayer\_head (\$secureHref=true)

# Input parameters

• \$secureHref ... secure hyperreferences by adding 'hypercms\_' [boolean] (optional)

### global input parameters

• \$mgmt\_config

# Output

head for audio player

# 7.10.28 debug\_getbacktracestring

## Description

Returns the current backtrace as a good readable string.

Ignores debug and debug\_getbacktracestring.

#### **Syntax**

debug\_getbacktracestring (\$valueSeparator, \$rowSeparator, \$ignoreFunctions=array())

### Input parameters

- \$valueSeparator ... separator for arguments [string]
- \$rowSeparator ... separator for a row on screen/file [string]
- \$ignoreFunctions ... functionnames to be ignored [array]

# Output

• debug message

### 7.10.29 showAPIdocs

# Description

Generates the documentation of an API file

#### **Syntax**

showAPIdocs (\$file, \$return="html", \$html\_hr=true, \$html\_description=true, \$html\_input=true, \$html\_globals=true, \$html\_output=true)

## Input parameters

- \$file ... path to API file [string]
- \$return ... return result as HTML or array [html, array] (optional)
- \$html\_hr ... use horizontal rule as separator in HTML output [boolean] (optional) display description [boolean] (optional)
- \$html\_description ... display input parameters [boolean] (optional)
- \$html\_input ... display global variables [boolean] (optional)
- \$html\_globals ... display output [boolean] (optional)
- \$html\_output

### global input parameters

 $\bullet$  = array()

# Output

HTML output of documentation / false on error

# 7.10.30 readnavigation

# Description

Reads the content from the container and collects information about a single navigation item

#### **Syntax**

readnavigation (\$site, \$docroot, \$object, \$view="publish", \$user="sys")

- \$site ... publication name [string]
- \$docroot ... location [string]
- \$object ... object name [string]
- \$view ... view name (see view parameters of function buildview) [string] (optional)
- \$user ... user name [string] (optional)

#### global input parameters

- \$mgmt\_config
- \$navi\_config

#### **Output**

navigation item array / false

## 7.10.31 createnavigation

## Description

```
Generates an associative array (item => nav-item, sub => array with sub-items).
Example
$navi_config = array();
document root definitions
$navi_config['root_path'] = "%abs_page%/";
$navi_config['root_url'] = "%url_page%/";
HTML / CSS class defintions
$navi_config['attr_ul_top'] = "class=\"nav navbar-nav\"";
$navi_config['attr_ul_dropdown'] = "class=\"dropdown-menu\"";
$navi_config['attr_li_active'] = "class=\"active\"";
$navi_config['attr_li_dropdown'] = "class=\"dropdown\"";
$navi_config['attr_href_dropdown'] = "class=\"dropdown-toggle\" data-
toggle=\"dropdown\"";
$navi_config['tag_li'] = "<a href=\"%link%\"</pre>
%attr_href%>%title%</a>%sub%\n";
$navi_config['tag_ul'] = "%list%\n";
Language definitions
Session variable name that holds the language setting
$navi_config['lang_session'] = "langcode";
2nd key = langcode & value = text_id of textnode
$navi_config['lang_text_id']['DE'] = "Titel_DE";
$navi_config['lang_text_id']['EN'] = "Titel_EN";
PermaLink definitions
2nd key = langcode & value = text_id of textnode
$navi config['permalink text id']['DE'] = "PermaLink DE";
$navi_config['permalink_text_id']['EN'] = "PermaLink_EN";
Hide navigation item (any value or empty) and use sort order (number or empty)
$navi_config['hide_text_id'] = "NavigationHide";
$navi_config['sort_text_id'] = "NavigationSortOrder";
Use only index file of directory as navigation item, e.g. index.html or index.php (Keep empty
if all objects of a folder should be included)
$navi_config['index_file'] = "";
$navigation = createnavigation ("%publication%", $navi_config['root_path'],
$navi_config['root_url'], "%view%", "%abs_location%/%object%");
echo shownavigation ($navigation);
```

#### **Syntax**

createnavigation (\$site, \$docroot, \$urlroot, \$view="publish", \$currentobject="",

\$recursive=true)

#### Input parameters

- \$site ... publication name [string]
- \$docroot ... document root for navigation [string]
- \$urlroot ... URL root for navigation [string]
- \$view ... view name (see view parameters of function buildview) [string]
- \$currentobject ... path to current object [string] (optional)
- \$recursive ... recursive [boolean] (optional)

# global input parameters

- \$mgmt\_config
- \$navi\_config

# Output

navigation array / false

# 7.10.32 shownavigation

#### **Description**

```
display navigation as HTML code.
The following example configures the navigation:
$navi config = array();
document root definitions:
$navi_config['root_path'] = "%abs_page%/";
$navi_config['root_url'] = "%url_page%/";
HTML / CSS class defintions (names between percentage signs are placeholders):
$navi_config['attr_ul_top'] = "class=\"nav navbar-nav\"";
$navi config['attr ul dropdown'] = "class=\"dropdown-menu\"";
$navi_config['attr_li_active'] = "class=\"active\"";
$navi_config['attr_li_dropdown'] = "class=\"dropdown\"";
$navi_config['attr_href_dropdown'] = "class=\"dropdown-toggle\" data-
togale=\"dropdown\"";
$navi_config['tag_li'] = "<a href=\"%link%\"</pre>
%attr_href%>%title%</a>%sub%\n";
$navi_config['tag_ul'] = "%list%\n";
language definitions
Session variable name that holds the language setting
$navi_config['lang_session'] = "langcode";
note: key = langcode & value = text_id of textnode
$navi_config['lang_text_id']['DE'] = "Titel_DE";
$navi_config['lang_text_id']['EN'] = "Titel_EN";
PermaLink defintions
note: key = langcode & value = text_id of textnode
$navi_config['permalink_text_id']['DE'] = "PermaLink_DE";
$navi_config['permalink_text_id']['EN'] = "PermaLink_EN";
Navigation hide and sort order defintions
$navi_config['hide_text_id'] = "NavigationHide";
$navi_config['sort_text_id'] = "NavigationSortOrder";
Use the first object of a folder for the main navigation item and display all following objects as
sub navigation items [boolean]
$navi_config['use_1st_folderitem'] = false;
```

#### **Syntax**

shownavigation (\$navigation, \$level=1)

# Input parameters

- \$navigation ... navigation (created by function readnavigation) [array]
- \$level ... level [integer] (optional)

#### global input parameters

- \$mgmt\_config
- \$navi\_config

# Output

navigation HTML presentation / false

## 7.10.33 showselect

#### **Syntax**

showselect (\$value\_array, \$only\_text=false, \$selected\_value="", \$id="", \$attributes="")

# Input parameters

- \$value\_array ... values array (array-key = value
- \$only\_text ... array-value = text) [array]
- \$selected\_value ... use values of array as option value and text [boolean] (optional)
- \$id ... selected value [string] (optional)
- \$attributes ... attributes of select tags like name or id or events [string] (optional)

### **Output**

HTML select box presentation / false

### 7.10.34 showtranslator

#### **Syntax**

showtranslator (\$site, \$id, \$type, \$charset="UTF-8", \$lang="en", \$style="")

#### Input parameters

- \$site ... publication name [string]
- \$id ... editor/text-tag ID [string]
- \$type ... unformatted or formatted texttag-type [u, f]
- \$charset ... character set [string] (optional)
- \$lang ... 2 digit language code [string] (optional)
- \$style ... style of div tag [string] (optional)

# global input parameters

\$mgmt\_config

\$hcms\_lang

# Output

HTML translator box presentation / false

# 7.10.35 showmapping

### **Description**

Present the mapping form of the provided publication.

#### **Syntax**

showmapping (\$site, \$lang="en")

# Input parameters

- \$site ... publication name [string]
- \$lang ... 2 digit language code [string] (optional)

# global input parameters

- \$mgmt\_config
- \$hcms\_charset
- \$hcms\_lang

# Output

• table with form fields for display / false

# 7.10.36 showgallery

#### Description

Presents all objects in a gallery with their thumbnails.

# **Syntax**

showgallery (\$multiobject, \$thumbsize=100, \$openlink=false, \$user="sys")

# Input parameters

- \$multiobject ... multiobjects represented by their path or object ID [array]
- \$thumbsize ... thumbnail size in pixels [integer] (optional)
- \$openlink ... open object on click [boolean] (optional)
- \$user ... user name [string] (optional)

# global input parameters

- \$mgmt\_config
- \$pageaccess
- \$compaccess
- \$hiddenfolder
- \$hcms\_linking
- \$globalpermission

- \$setlocalpermission
- \$hcms\_lang
- \$lang

## Output

gallery view / false

## 7.10.37 showthumbnail

# Description

Presents the thumbnail of a single media file that is optionally base64 encoded an can embedded in HTML pages or e-mails.

#### **Syntax**

showthumbnail (\$site, \$mediafile, \$name="", \$thumbsize=120, \$base64=false, \$style="", \$theme="standard")

## Input parameters

- \$site ... publication name [string]
- \$mediafile ... media file name [string]
- \$name ... display name [string] (optional)
- \$thumbsize ... thumbnail size in pixels [integer] (optional)
- \$base64 ... base64 encoding [boolean] (optional)
- \$style ... CSS style for image [string] (optional) design theme name for icons [string] (optional)
- \$theme

# global input parameters

\$mgmt\_config

### Output

• thumbnail view / false

# 7.10.38 showtaxonomytree

#### Description

Displays the requested taxonomy tree structure or sub branch with checkboxes for the keywords.

## **Syntax**

showtaxonomytree (\$site="", \$container\_id, \$text\_id, \$tagname="textk", \$taxonomy\_lang="en", \$expression, \$width=600, \$height=500)

- \$site ... publication name [string] (optional)
- \$container\_id ... container ID [integer][array]
- \$text\_id ... text ID [string]
- \$tagname ... language code [string] (optional)

- \$taxonomy\_lang ... taxonomy ID or expression or taxonomy path in the form %taxonomy%/publication-name or 'default'/language-code/taxonomy-ID/taxonomy-child-levels [string]
- \$expression ... width in pixel [integer] (optional)
- \$width ... height in pixel [integer] (optional)
- \$height

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang
- \$taxonomy

# Output

taxonomy tree view / false

# 7.10.39 showworkflowstatus

### Description

Displays the workflow status information table.

# **Syntax**

showworkflowstatus (\$site, \$location, \$page)

## Input parameters

- \$site ... publication name [string]
- \$location ... location path [string]
- \$page ... object name [string]

# global input parameters

- \$mgmt\_config
- \$publ\_config
- \$hcms\_charset
- \$hcms\_lang
- \$lang
- \$user

### Output

workflow status view / false

# 7.11 Template Engine API Functions

## 7.11.1 transformlink

### **Syntax**

transformlink (\$viewstore)

# Input parameters

• \$viewstore ... view of object

# global input parameters

- \$site
- \$location\_esc
- \$page
- \$ctrlreload
- \$mgmt\_config

# Output

· view with transformed links for easyedit mode

### 7.11.2 followlink

### **Syntax**

followlink (\$site, \$follow)

### Input parameters

- \$site ... publication name
- \$follow ... link to follow

# global input parameters

• \$mgmt\_config

# Output

• prepared input (location plus page) for easyedit mode (buildview) / false on error

### 7.11.3 errorhandler

### **Syntax**

errorhandler (\$source\_code, \$return\_code, \$error\_identifier)

# Input parameters

- \$source\_code ... source code
- \$return\_code ... return code
- \$error\_identifier ... error identifier

# Output

• error message and view of the code with line identifiers

# 7.11.4 viewinclusions

### **Syntax**

viewinclusions (\$site, \$viewstore, \$hypertag, \$view, \$application, \$charset="UTF-8")

### Input parameters

- \$site ... view of object
- \$viewstore ... hypertag to create view of inlcuded objects
- \$hypertag ... view parameter
- \$view ... application
- \$application ... character set used (optional) view-parameter explanation: "template or any other word": the standard text (in table) will be included for the view "preview": preview of the content of the included file "publish": view the content of the included file as it is (for publishing)
- \$charset

# global input parameters

- \$user
- \$mamt config
- \$location
- \$hcms\_lang
- \$lang

### **Output**

• view of the content including the content of included objects

### 7.11.5 buildview

#### Description

buildview parameter may have the following values:

"formedit": use form for content editing

"formmeta": use form for content viewing only for meta informations (tag-type must be meta)

"formlock": use form for content viewing

"cmsview": view of page based on template, includes hyperCMS specific code (buttons)

"inlineview": view of page based on template, includes hyperCMS specific code (buttons) and inline text editing

"publish": view of page for publishing based on template without CMS specific code (editing)

"unpublish": execution of the code for unpublishing an object

"preview": view of page based on template for preview (inactive hyperlinks) without CMS specific code (buttons)

"template": view of template based on template for preview (inactive hyperlinks) without CMS specific code (buttons)

#### **Syntax**

buildview (\$site, \$location, \$page, \$user, \$buildview="template", \$ctrlreload="no", \$template="", \$container="", \$force\_cat="", \$execute\_code=true)

- \$site ... publication name [string]
- \$location ... location [string]

- \$page ... object name [string]
- \$user ... user name [string]
- \$buildview ... view parameter [string] (optional)
- \$ctrlreload ... reload workplace control frame and add html & body tags if missing [yes, no] (optional)
- \$template ... template name [string] (optional)
- \$container ... container name [string] (optional)
- \$force\_cat ... force category to use different location path [page, comp] (optional)
- \$execute\_code ... execute\_code [boolean] (optional)

# global input parameters

- \$container\_collection
- \$eventsystem
- \$db\_connect
- \$mgmt\_config
- \$siteaccess
- \$adminpermission
- \$setlocalpermission
- \$token
- \$is\_mobile
- \$is\_iphone
- \$viewportwidth
- \$mgmt\_lang\_shortcut\_default
- \$hcms\_charset
- \$hcms\_lang\_name
- \$hcms\_lang\_shortcut
- \$hcms\_lang\_codepage
- \$hcms\_lang\_date
- \$hcms\_lang
- \$lang

# Output

result array with view of the content / false on error

# 7.11.6 unescapeview

## **Syntax**

unescapeview (\$viewstore, \$application="php")

# Input parameters

- \$viewstore ... code [string]
- \$application ... application name [string] (optional)

# Output

unescaped code / false on error

### 7.11.7 buildsearchform

#### **Syntax**

buildsearchform (\$site="", \$template="", \$report="", \$ownergroup="", \$css\_display="inline-

block", \$css\_width\_field="90%", \$empty\_values=true, \$title="")

#### Input parameters

- \$site ... publication name [string] (optional for report)
- \$template ... template name [string] (optional)
- \$report ... or report name [string] (optional)
- \$ownergroup ... group access [array] (optional)
- \$css\_display ... CSS display value for label tag [string] (optional)
- \$css\_width\_field ... CSS field width (optional)
- \$empty\_values ... allow empty values [boolean] (optional)
- \$title ... display title [string] (optional)

## global input parameters

- \$user
- \$siteaccess
- \$mgmt\_config
- \$mgmt\_lang\_shortcut\_default
- \$hcms\_charset
- \$hcms\_lang\_name
- \$hcms\_lang\_shortcut
- \$hcms\_lang\_codepage
- \$hcms lang date
- \$hcms\_lang
- \$lang

#### Output

• form view / false on error

#### 7.11.8 buildbarchart

## **Syntax**

```
\label{lem:buildbarchart} buildbarchart ($paper_name, $paper_width=600, $paper_height=300, $paper_top=10, $paper_left=40, $x_axis, $y1_axis, $y2_axis="", $y3_axis="", $paper_style="", $bar1_style="", $bar2_style="", $bar3_style="", $show_value=false)
```

- \$paper\_name ... name/id of paper [string]
- \$paper\_width ... width of paper in pixel [integer]
- \$paper\_height ... height of paper in pixel [integer]
- \$paper\_top ... top space in pixel [integer]
- \$paper\_left ... left space in pixel [integer]
- \$x\_axis ... x-axis values [array]
- \$y1\_axis ... y1-axis values [array]
- \$y2 axis ... y2-axis values [array] (optional)
- \$y3\_axis ... y3-axis values [array] (optional)
- \$paper\_style ... paper CSS style [string]
- \$bar1\_style ... 1st bar chart CSS style [string]
- \$bar2\_style ... 2nd bar chart CSS style [string]
- \$bar3\_style ... 3rd bar chart CSS style [string]
- \$show\_value ... show y-value in bar [boolean]

# global input parameters

- \$lang
- \$mgmt\_config

# Output

bar chart view / false on error

# 7.12 XML API Functions

# 7.12.1 valid\_tagname

## **Description**

Verifies a tag name

## **Syntax**

valid\_tagname (\$tagname)

### Input parameters

• \$tagname ... tag name [string]

# Output

• true / false on error

# 7.12.2 setxmlparameter

# Description

Set parameter values in XML declaration (e.g. encoding): encoding="UTF-8"

#### **Syntax**

setxmlparameter (\$xmldata, \$parameter, \$value)

# Input parameters

- \$xmldata ... XML content container [string]
- \$parameter ... paramater name [string]
- \$value ... paramater value [string]

# Output

• XML content container / false on error

# 7.12.3 getcontent

### Description

<tagname>content</tagname>

Extracts the content between the given \$starttagname xml-tags.

Only this function will decode special characters (&, <, >) in the content and removes CDATA.

Function getcontent will only decode values if they are non-xml and non\_html. so content inside child nodes including tags won't be decoded.

Wild card character "\*" can be used at the end of \$starttagname.

#### **Syntax**

getcontent (\$xmldata, \$starttagname)

## Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name [string]

### Output

result array with the content of the requested XML node (tag) / false on error

# 7.12.4 geticontent

### **Description**

CASE-Insensitive version (XML parser are however always case-sensitive!)

<tagname>content</tagname>

Extracts the content between the given \$starttagname xml-tags.

Only this function will decode special characters (&, <, >) in the content and removes CDATA. getcontent will only decode values if they are non-xml and non\_html. so content inside child nodes including tags won't be decoded.

Wild card character "\*" can be used at the end of \$starttagname

#### Syntax

geticontent (\$xmldata, \$starttagname)

## Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name [string]

### Output

• result array with the content of the requested XML node (tag) / false on error

# 7.12.5 getxmlcontent

#### Description

<tagname>content</tagname>

Extracts the content together with the \$starttagname xml tags.

This function will NOT decode special characters like function getcontent! Wild card character "\*" can be used at the end of \$starttagname.

#### Svntax

getxmlcontent (\$xmldata, \$starttagname)

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name [string]

# Output

result array with the content of the requested XML node (tag) / false on error

# 7.12.6 getxmlicontent

#### **Description**

CASE-Insensitive version (XML parser are always case-sensitive!) <tagname>content</tagname> Extracts the content together with the \$starttagname xml tags. This function will NOT decode special characters like function getcontent! Wild card character "\*" can be used at the end of \$starttagname.

#### **Syntax**

getxmlicontent (\$xmldata, \$starttagname)

#### Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name [string]

### Output

• result array with the content of the requested XML node (tag) / false on error

# 7.12.7 selectcontent

#### Description

```
<tagname>
......
<condtag>condvalue</condtag>
.......
</tagname>
```

Extracts the content between the given \$starttagname xml tags where the child xml tag \$startcondtag value is equal with the target value \$condvalue.

Wild card character "\*" can be used at the end of \$starttagname.

Wild card character "\*" can be used at begin and end of \$condvalue.

Be Aware: \$startcondtag must be a child of \$starttagname!

# **Syntax**

selectcontent (\$xmldata, \$starttagname, \$startcondtag, \$condvalue)

### Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name of requested XML node [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]

### **Output**

result array with the content of the requested XML node (tag) / false on error

# 7.12.8 selecticontent

## Description

```
CASE-Insensitive version (XML parser are always case-sensitive!) <tagname>
......
<condtag>condvalue</condtag>
.......
</tagname>
```

Extracts the content between the given \$starttagname xml tags where the child xml tag \$startcondtag value is equal with the target value \$condvalue.

Wild card character "\*" can be used at the end of \$starttagname.

Wild card character "\*" can be used at begin and end of \$condvalue.

Be Aware: \$startcondtag must be a child of \$starttagname!

### **Syntax**

selecticontent (\$xmldata, \$starttagname, \$startcondtag, \$condvalue)

#### Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name of requested XML node [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]

# Output

result array with the content of the requested XML node (tag) / false on error

#### 7.12.9 selectxmlcontent

#### Description

```
<tagname>
......
<condtag>condvalue</condtag>
......
</tagname>
```

Extracts the content between the given \$starttagname xml tags where the child xml tag \$startcondtag value is equal with the target value \$condvalue

Wild card character "\*" can be used at begin and end of \$condvalue.

Be Aware: \$startcondtag must be a child of \$starttagname!

#### Syntax

selectxmlcontent (\$xmldata, \$starttagname, \$startcondtag, \$condvalue)

# Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name of requested XML node [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagnamev
- \$condvalue ... conditional value [string]

#### Output

• result array with the content of the requested XML node (tag) / false on error

#### 7.12.10 selectxmlicontent

### Description

```
CASE-Insensitive version (XML parser are always case-sensitive!)
<tagname>
. . . . . . .
```

<condtag>condvalue</condtag>

</tagname>

Extracts the content between the given \$starttagname xml tags where the child xml tag \$startcondtag value is equal with the target value \$condvalue.

Wild card character "\*" can be used at begin and end of \$condvalue.

Be Aware: \$startcondtag must be a child of \$starttagname!

# **Syntax**

selectxmlicontent (\$xmldata, \$starttagname, \$startcondtag, \$condvalue)

# Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name of requested XML node [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]

### **Output**

result array with the content of the requested XML node (tag) / false on error

#### 7.12.11 deletecontent

#### **Description**

<tagname>

<condtag>condvalue</condtag>

</tagname>

Deletes the whole xml content including <tagname>.

Wild card character "\*" can be used at begin and end of \$condvalue.

#### **Syntax**

deletecontent (\$xmldata, \$starttagname, \$startcondtag="", \$condvalue="")

#### Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name of requested XML node [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string] (optional)
- \$condvalue ... conditional value [string] (optional)

## Output

XML content container / false on error

# 7.12.12 deleteicontent

## **Description**

CASE-Insensitive version (XML parser are always case-sensitive!)

<tagname>

<condtag>condvalue</condtag>

</tagname>

Deletes the whole xml content including <tagname>.

Wild card character "\*" can be used at begin and end of \$condvalue.

## **Syntax**

deleteicontent (\$xmldata, \$starttagname, \$startcondtag="", \$condvalue="")

#### Input parameters

- \$xmldata ... XML content container [string]
- \$starttagname ... tag name of requested XML node [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string] (optional)
- \$condvalue ... conditional value [string] (optional)

# Output

XML content container / false on error

#### 7.12.13 setcontent

# Description

<parenttagname>

<condtag>condvalue</condtag>

<tagname>contentnew</tagname>

</parenttagname>

\$xmldata = data string to be parsed

\$startparenttagname = name of the tag that is a parent node of starttagname (necessary if condition has been set!)

\$starttagname = name of the tag (child node)

\$contentnew = the content that will be inserted between the child tags \$starttagname

\$startcondtag = child xml tag where condition will be set

\$condvalue = value of the condition

Wild card character "\*" can be used at begin and end of \$condvalue.

#### **Syntax**

setcontent (\$xmldata, \$startparenttagname, \$starttagname, \$contentnew, \$startcondtag="", \$condvalue="")

- \$xmldata ... XML content container [string]
- \$startparenttagname ... parent tag name [string]
- \$starttagname ... tag name of XML node for the new content [string]
- \$contentnew ... new XML node to be inserted
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]

## **Output**

XML content container / false on error

## 7.12.14 seticontent

### Description

CASE-Insensitive version (XML parser are always case-sensitive!)

- <parenttagname>
- <condtag>condvalue</condtag>
- <tagname>contentnew</tagname>
- </parenttagname>

\$xmldata = data string to be parsed

\$startparenttagname = name of the tag that is the parent node of starttagname (necessary if condition has been set!)

\$starttagname = name of the tag (child node)

\$contentnew = the content that will be inserted between the child tags \$starttagname

\$startcondtag = child xml tag where condition will be set

\$condvalue = value of the condition

Wild card character "\*" can be used at begin and end of \$condvalue.

#### **Syntax**

seticontent (\$xmldata, \$startparenttagname, \$starttagname, \$contentnew, \$startcondtag, \$condvalue)

#### Input parameters

- \$xmldata ... XML content container [string]
- \$startparenttagname ... parent tag name [string]
- \$starttagname ... tag name of XML node for the new content [string]
- \$contentnew ... new XML node to be inserted [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]

#### **Output**

• XML content container / false on error

## 7.12.15 setcontent\_fast

#### Description

function designed for link management, extremely fast but with limitations (only CASE-Sensitive!)

- <parenttagname>
- <condtag>condvalue</condtag>
- <tagname>contentnew</tagname>
- </parenttagname>

\$xmldata = data string to be parsed

\$startparenttagname = name of the tag that is the parent node of starttagname (necessary if condition has been set!)

\$starttagname = name of the tag (child node)

\$contentnew = the content that will be inserted between the child tags \$starttagname

\$startcondtag = child xml tag where condition will be set

\$condvalue = value of the condition

Wild card character "\*" can be used at begin and end of \$condvalue.

#### **Syntax**

setcontent\_fast (\$xmldata, \$startparenttagname, \$starttagname, \$contentnew, \$startcondtag="", \$condvalue="")

### Input parameters

- \$xmldata ... XML content container [string]
- \$startparenttagname ... parent tag name [string]
- \$starttagname ... tag name of XML node for the new content [string]
- \$contentnew ... new XML node to be inserted
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]

### **Output**

XML content container / false on error

# 7.12.16 updatecontent

# Description

Updates a given xml string \$xmlnode in \$xmldata with the content \$xmlnodenew. This method provides a faster way to update xml nodes when the node was selected before.

# **Syntax**

updatecontent (\$xmldata, \$xmlnode, \$xmlnodenew)

### Input parameters

- \$xmldata ... XML content container [string]
- \$xmlnode ... XML node to be replaced [string]
- \$xmInodenew ... new XML node [string]

### **Output**

• XML content container / false on error

# 7.12.17 insertcontent

# 

Inserts \$insertxmldata string at the end of all child between the parent \$tagname .

### **Syntax**

insertcontent (\$xmldata, \$insertxmldata, \$starttagname)

# Input parameters

- \$xmldata ... XML content container [string]
- \$insertxmldata ... XML node to be inserted in starttagname [string]
- \$starttagname ... tag name of the parent XML node [string]

#### **Output**

XML content container / false on error

#### 7.12.18 inserticontent

#### **Description**

#### Svntax

inserticontent (\$xmldata, \$insertxmldata, \$starttagname)

# Input parameters

- \$xmldata ... XML content container [string]
- \$insertxmldata ... XML node to be inserted in starttagname [string]
- \$starttagname ... tag name of the parent XML node [string]

### **Output**

XML content container / false on error

# 7.12.19 addcontent

### **Description**

\$condvalue (optional) = value of the condition

\$startparenttagname (optional) = name of the parent xml tag where the xml subschema should be added (list)

\$starttagname (optional) = name of the tag (child)

\$contentnew (optional) = the content that will be inserted between the child tags

#### **Syntax**

addcontent (\$xmldata, \$sub\_xmldata, \$startgrandtagname, \$startcondtag, \$condvalue, \$startparenttagname, \$starttagname, \$contentnew)

# Input parameters

- \$xmldata ... XML content container [string]
- \$sub\_xmldata ... xml node to be inserted [string]
- \$startgrandtagname ... grandparent tag name [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]
- \$startparenttagname ... parent tag name [string]
- \$starttagname ... tag name of XML node for the new content [string]
- \$contentnew ... new XML node to be inserted [string]

## Output

• XML content container / false on error

#### 7.12.20 addicontent

#### Description

```
CASE-Insensitive version (XML parser are always case-sensitive!)
<grandtagname>
<condtag>condvalue</condtag>
<parenttagname> <- list start</pre>
<tagname>contentnew</tagname> } <- sub xmldata
.....}
</parenttagname> <- list end
</grandtagname>
$xmldata = data string to be parsed
$sub_xmldata = xml subschema to be inserted
$startgrandtagname (optional) = name of the grand xml tag of parent xml tag where (article)
$startcondtag (optional) = xml tag inside the parent xml tags where condition will be set
$condvalue (optional) = value of the condition
$startparenttagname (optional) = name of the parent xml tag where the xml subschema
should be added (list)
$starttagname (optional) = name of the tag (child)
$contentnew (optional) = the content that will be inserted between the child tags
```

### **Syntax**

addicontent (\$xmldata, \$sub\_xmldata, \$startgrandtagname, \$startcondtag, \$condvalue, \$startparenttagname, \$starttagname, \$contentnew)

### Input parameters

• \$xmldata ... XML content container [string]

- \$sub\_xmldata ... xml node to be inserted [string]
- \$startgrandtagname ... grandparent tag name [string]
- \$startcondtag ... tag holding the conditional value inside the given starttagname [string]
- \$condvalue ... conditional value [string]
- \$startparenttagname ... parent tag name [string]
- \$starttagname ... tag name of XML node for the new content [string]
- \$contentnew ... new XML node to be inserted [string]

# Output

• XML content container / false on error

# 7.13 Report API Functions

# 7.13.1 createreport

# Description

This function creates a new report

# **Syntax**

createreport (\$report\_name)

# Input parameters

\$report\_name ... report name [string]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## **Output**

result array

# 7.13.2 editreport

## Description

This function saves the configuration of a report.

## **Syntax**

editreport (\$report\_name, \$config)

- \$report\_name ... report name [string]
- \$config ... report configuration [array]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

result array

# 7.13.3 loadreport

# Description

This function loads the report configuration file and provides the data as array.

#### Syntax

loadreport (\$report\_name)

# Input parameters

• \$report\_name ... report name [string]

# global input parameters

- \$user
- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

# Output

• result array / false

# 7.13.4 deletereport

# Description

This function deletes a report

# **Syntax**

deletereport (\$report\_name)

# Input parameters

\$report\_name ... report name [string]

# global input parameters

• \$user

- \$eventsystem
- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

result array

# 7.13.5 analyzeSQLselect

#### **Description**

This function analyzes an SQL Select statement and return its parts in an array

#### Syntax

analyzeSQLselect (\$sql)

# Input parameters

• \$sql ... SQL statement [string]

# Output

result array

# 7.13.6 showpiechart

# Description

This function creates the Google Chart Code for a pie chart. The Google Chart API need to be loaded first!

# **Syntax**

showpiechart (\$title="", \$x\_title, \$x\_value, \$y\_title, \$y\_value, \$data\_array, \$width="100%", \$height="100%", \$id="hcmsPieChart", \$suffix="", \$loadAPI=true)

#### Input parameters

- \$title ... chart title [string]
- \$x\_title ... chart x-axis title [string]
- \$x\_value ... chart x-axis array key name holding the values [string]
- \$y\_title ... chart y-axis title [string]
- \$y\_value ... chart y-axis array key name holding the values [string]
- \$data\_array ... assoz. data array [array]
- \$width ... chart width [string] (optional)
- \$height ... chart height [string] (optional)
- \$id ... ID of chart [string] (optional)
- \$suffix ... function name suffix [string] (optional)
- \$loadAPI ... load Google Chart API [boolean] (optional)

### global input parameters

- \$mgmt\_config
- \$hcms\_lang

- \$lang
- \$user

# Output

• Google Chart code / false

#### 7.13.7 showcolumnchart

# **Description**

This function creates the Google Chart Code for a column chart. The Google Chart API need to be loaded first!

## **Syntax**

```
showcolumnchart ($title="", $x_title, $x_value, $y1_title, $y1_value, $y2_title="", $y2_value="", $y3_title="", $y3_value="", $data_array, $width="100%", $height="100%", $id="hcmsColumnChart", $suffix="", $loadAPI=true)
```

### Input parameters

- \$title ... chart title [string]
- \$x\_title ... chart x-axis title [string]
- \$x\_value ... chart x-axis array key name holding the values [string]
- \$y1\_title ... chart y1-axis title [string]
- \$y1\_value ... chart y1-axis array key name holding the values [string]
- \$y2\_title ... chart y2-axis title [string]
- \$y2\_value ... chart y2-axis array key name holding the values [string]
- \$y3\_title ... chart y3-axis title
- \$y3\_value ... chart y3-axis array key name holding the values [string]
- \$data\_array ... assoz. data array [array]
- \$width ... chart width [string] (optional)
- \$height ... chart height [string] (optional)
- \$id ... ID of chart [string] (optional)
- \$suffix ... function name suffix [string] (optional)
- \$loadAPI

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang
- \$user

#### **Output**

• Google Chart code / false

### 7.13.8 showareachart

### Description

This function creates the Google Chart Code for an area chart. The Google Chart API need to be loaded first!

#### **Syntax**

showareachart (\$title="", \$x\_title, \$x\_value, \$y1\_title, \$y1\_value, \$y2\_title="", \$y2\_value="", \$y3\_title="", \$y3\_value="", \$data\_array, \$width="100%", \$height="100%", \$id="hcmsAreaChart", \$suffix="", \$loadAPI=true)

#### Input parameters

- \$title ... chart title [string]
- \$x\_title ... chart x-axis title [string]
- \$x\_value ... chart x-axis array key name holding the values [string]
- \$y1\_title ... chart y1-axis title [string]
- \$y1\_value ... chart y1-axis array key name holding the values [string]
- \$y2\_title ... chart y2-axis title [string]
- \$y2\_value ... chart y2-axis array key name holding the values [string]
- \$y3\_title ... chart y3-axis title
- \$y3\_value ... chart y3-axis array key name holding the values [string]
- \$data\_array ... assoz. data array [array]
- \$width ... chart width [string] (optional)
- \$height ... chart height [string] (optional)
- \$id ... ID of chart [string] (optional)
- \$suffix ... function name suffix [string] (optional)
- \$loadAPI

# global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang
- \$user

#### **Output**

Google Chart code / false

#### 7.13.9 showtimelinechart

#### Description

This function creates the Google Chart Code for a timeline chart. The Google Chart API need to be loaded first!

#### **Syntax**

showtimelinechart (\$title="", \$y\_title, \$y\_value, \$x1\_title, \$x1\_value, \$x2\_title="", \$x2\_value="", \$data\_array, \$width="100%", \$height="100%", \$id="hcmsTimelineChart", \$suffix="", \$loadAPI=true)

- \$title ... chart title [string]
- \$y title ... chart y-axis title [string]
- \$y\_value ... chart y-axis array key name holding the values [string]
- \$x1\_title ... chart x1-axis title
- \$x1\_value ... chart x1-axis array key name holding the values [string]
- \$x2\_title ... chart x2-axis title [string]
- \$x2\_value ... chart x2-axis array key name holding the values [string]
- \$data\_array ... assoz. data array [array]
- \$width ... chart width [string] (optional)

- \$height ... chart height [string] (optional)
- \$id ... ID of chart [string] (optional)
- \$suffix ... function name suffix [string] (optional)
- \$loadAPI ... load Google Chart API [boolean] (optional)

#### global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang
- \$user

# **Output**

Google Chart code / false

# 7.13.10 showgeolocationchart

## Description

This function creates the Google Maps Code for a geolocation chart. The Google Maps API need to be loaded first!

# **Syntax**

showgeolocationchart (\$title="", \$marker\_value, \$lat\_value, \$lng\_value, \$link\_value, \$data\_array, \$width="100%", \$height="100%", \$id="hcmsGeolocationChart", \$suffix="", \$loadAPI=true)

#### Input parameters

- \$title ... chart title [string]
- \$marker\_value ... array key name holding the value for the marker title [string]
- \$lat\_value ... array key name holding the value for the latitude of the marker [string]
- \$Ing\_value ... array key name holding the value for the longitude of the marker [string]
- \$link\_value ... array key name holding the value for the marker link [string]
- \$data\_array ... assoz. data array [array]
- \$width ... chart width [string] (optional)
- \$height ... chart height [string] (optional)
- \$id ... ID of chart [string] (optional)
- \$suffix ... function name suffix [string] (optional)
- \$loadAPI ... load Google Maps API [boolean] (optional)

## global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang
- \$user

### Output

Google Chart code / false

## 7.14 Project API Functions

## 7.14.1 createproject

#### **Description**

This function creates a new project.

#### **Syntax**

createproject (\$subproject\_id=0, \$object\_id="", \$user, \$projectname, \$description="")

## Input parameters

- \$subproject\_id ... ID of main project (only if the project is a subproject) [integer]
- \$object\_id ... object ID or path to object [string] (optional)
- \$user ... user name of sub/project owner [string]
- \$projectname ... project name [string]
- \$description ... project description [string] (optional)

## global input parameters

- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

### Output

result array

## 7.14.2 editproject

#### Description

This function saves data of an exitsing project.

#### **Syntax**

editproject (\$project\_id, \$subproject\_id=0, \$object\_id="", \$user="", \$projectname="", \$description="")

## Input parameters

- \$project\_id ... project ID [integer]
- \$subproject\_id ... ID of main project (only if project is a subproject) [integer]
- \$object\_id ... object ID or path to object [string] (optional)
- \$user ... user name of sub/project owner [string] (optional)
- \$projectname ... project name [string] (optional)
- \$description ... project description [string] (optional)

- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

result array

## 7.14.3 deleteproject

## Description

This function removes projects.

#### **Syntax**

deleteproject (\$project\_id)

#### Input parameters

• \$project\_id ... project ID or array of project IDs to be deleted [string or array]

## global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

## Output

result array

## 7.14.4 getprojectstructure

## Description

This function creates an associative array presenting the project structure (project -> subprojects -> tasks).

## **Syntax**

getprojectstructure (\$project\_id, \$user="")

## Input parameters

- \$project\_id ... project ID [integer]
- \$user ... projects for specific user name [string] (optional)

## global input parameters

• \$mgmt\_config

## Output

associative result array / false

## 7.14.5 showprojectrecord

#### Description

This function creates a table row for the projects presentation.

#### **Syntax**

showprojectrecord (\$project\_record, \$masterproject\_id)

#### Input parameters

- \$project\_record ... project record as array (project/subproject/task) [array]
- \$masterproject\_id ... ID of master project [integer]

### global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang
- \$siteaccess
- \$user\_array

#### Output

html presentation of the record / false

## 7.14.6 showganttchart

#### Description

This function creates the Google Chart Code for a Gantt chart. The Google Chart API need to be loaded first.

#### **Syntax**

showganttchart (\$title="", \$task\_title, \$task\_value, \$resource\_title="", \$resource\_value="", \$start\_title, \$start\_value, \$end\_title="", \$end\_value="", \$status\_title="", \$status\_value="", \$data\_array, \$width="100%", \$height="100%", \$id="hcmsTimelineChart", \$suffix="", \$loadAPI=true)

#### Input parameters

- \$title ... chart title [string]
- \$task\_title ... task title [string]
- \$task\_value ... task array key name holding the values [array]
- \$resource\_title ... resouce title [string] (optional)
- \$resource\_value ... resource array key name holding the values [string] (optional)
- \$start\_title ... task start date title [string]
- \$start\_value ... task start date array key name holding the values [string]
- \$end\_title ... task finish date title [string]
- \$end\_value ... task finish date array key name holding the values [string]
- \$status\_title ... work status title [string] (optional)
- \$status\_value ... work status array key name holding the values [string] (optional)
- \$data\_array ... assoz. data array [array]
- \$width ... chart width [string] (optional)
- \$height ... chart height [string] (optional)
- \$id ... ID of chart [string] (optional)
- \$suffix ... function name suffix [string] (optional)

• \$loadAPI ... load Google Chart API [boolean] (optional)

### global input parameters

- \$mgmt\_config
- \$hcms\_lang
- \$lang

#### **Output**

· Google Chart code / false

## 7.15 Task API Functions

#### 7.15.1 createtask

#### **Description**

Creates a new user task and send optional e-mail to user. Since verion 5.8.4 the data will be stored in RDBMS instead of XML files.

#### **Syntax**

createtask (\$site="", \$from\_user, \$from\_email="", \$to\_user, \$to\_email="", \$startdate="", \$finishdate="", \$category="", \$object\_id="", \$taskname, \$message="", \$sendmail=true, \$priority="low", \$project\_id=0, \$planned="")

#### Input parameters

- \$site ... publication name [string] (optional)
- \$from\_user ... from\_user name [string]
- \$from\_email ... from\_email [email-address] (optional)
- \$to\_user ... to\_user name [string]
- \$to\_email ... to\_email [email-address] (optional)
- \$startdate ... start date [yyyy-mm-dd] (optional)
- \$finishdate ... finish date [yyyy-mm-dd] (optional)
- \$category ... category [link, user, workflow] (optional)
- \$object\_id ... object ID or object path [string]
- \$taskname ... task name [string]
- \$message ... message [string] (optional)
- \$sendmail ... sendmail [boolean]
- \$priority ... priority [high, medium, low] (optional)
- \$project\_id ... project/subproject ID if the task should be assigned to a project [integer] (optional)
- \$planned ... planned effort in taskunit [integer] (optional)

#### global input parameters

- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

#### Output

result array

#### 7.15.2 edittask

### Description

Saves data of a user task and send optional e-mail to user. Since verion 5.8.4 the data will be stored in RDBMS instead of XML files.

#### **Syntax**

```
edittask ($task_id, $object_id="", $to_user="", $startdate="", $finishdate="", $taskname="", $message="", $sendmail=true, $priority="", $status="", $planned="", $actual="", $project_id=0)
```

#### Input parameters

- \$task\_id ... task ID [integer]
- \$object\_id ... object ID pr path to object [string] (optional)
- \$to\_user ... to\_user name [string] (optional)
- \$startdate ... start date [yyyy-mm-dd] (optional)
- \$finishdate ... finish date [yyyy-mm-dd] (optional)
- \$taskname ... name of task [string] (optional)
- \$message ... task message/description [string] (optional)
- \$sendmail ... sendmail [true/false]
- \$priority ... priority [high, medium, low] (optional)
- \$status ... status in percent [0-100] (optional)
- \$planned ... planned effort in taskunit [integer] (optional)
- \$actual ... actual effort in taskunit [integer] (optional)
- \$project\_id ... project/subproject ID the task belongs to [integer] (optional)

### global input parameters

- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

#### **Output**

result array

#### 7.15.3 deletetask

#### Description

Deletes user tasks.

#### **Syntax**

deletetask (\$task\_id)

#### Input parameters

• \$task\_id ... task ID or array of task IDs to be deleted [integer]

- \$mgmt\_config
- \$hcms\_lang
- \$lang

• true/false

## 7.15.4 tasknotification

## Description

Sends e-mail notifications to users if a task starts or ends on the given date.

#### **Syntax**

tasknotification (\$date)

## Input parameters

• \$date ... date [yyyy-mm-dd]

## global input parameters

- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

## Output

true/false

## 7.16 Workflow API Functions

## 7.16.1 deleteworkflow

## Description

This function deletes a workflow.

#### Syntax

deleteworkflow (\$site, \$wf\_name, \$cat)

#### Input parameters

- \$site ... publication name [string]
- \$wf\_name ... worfklow name [string]
- \$cat ... category [man, script]

- \$user
- \$eventsystem
- \$mgmt\_config

- \$hcms\_lang
- \$lang

result array

#### 7.16.2 buildworkflow

## **Syntax**

buildworkflow (\$workflow\_data)

### Input parameters

• \$workflow\_data ... workflow [XML]

## Output

workflow items as array

## 7.16.3 workflowaccept

## **Syntax**

workflowaccept (\$site, \$location, \$object, \$workflow, \$item\_id, \$user, \$message="", \$sendmail=true, \$priority="medium")

#### Input parameters

- \$site ... publication name [string]
- \$location ... location name [string]
- \$object ... object name [string]
- \$workflow ... workflow [XML-string]
- \$item\_id ... item id [string]
- \$user ... user name of executing user [string]
- \$message ... task message [string] (optional)
- \$sendmail ... sendmail [boolean] (optional)
- \$priority ... priority [high, medium, low] (optional)

## global input parameters

- \$mgmt\_config
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

## Output

workflow [XML-string] / false

## 7.16.4 acceptobject

#### **Description**

Accepts an object that is managed by a workflow.

#### **Syntax**

acceptobject (\$site, \$location, \$object, \$item\_id, \$user, \$message="", \$sendmail=true, \$priority="medium")

#### Input parameters

- \$site ... publication name [string]
- \$location ... location name [string]
- \$object ... object name [string]
- \$item\_id ... workflow item id [string]
- \$user ... user name of executing user [string]
- \$message ... task message [string] (optional)
- \$sendmail ... sendmail [boolean] (optional)
- \$priority ... priority [high, medium, low] (optional)

#### global input parameters

- \$mgmt\_config
- \$contentfile
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

## Output

result array

## 7.16.5 workflowreject

#### **Description**

Rejects an object that is managed by a workflow.

## **Syntax**

workflowreject (\$site, \$location, \$object, \$workflow, \$item\_id, \$user, \$message="",
\$sendmail=true, \$priority="medium")

#### Input parameters

- \$site ... publication name [string]
- \$location ... location name [string]
- \$object ... object name [string]
- \$workflow ... workflow [XML-string]
- \$item\_id ... workflow item id [string]
- \$user ... user name of executing user [string]
- \$message ... task message [string] (optional)
- \$sendmail ... send mail [boolean] (optional)
- \$priority ... priority [high, medium, low] (optional)

- \$mgmt\_config
- \$hcms\_lang

\$lang

## Output

• workflow [XML-string] / false

## 7.16.6 rejectobject

#### **Description**

Rejects an object that is managed by a workflow.

#### **Syntax**

rejectobject (\$site, \$location, \$object, \$item\_id, \$user, \$message="", \$sendmail=true, \$priority="medium")

## Input parameters

- \$site ... publication name [string]
- \$location ... location name [string]
- \$object ... object name [string]
- \$item\_id ... workflow item id [string]
- \$user ... user name of executing user [string]
- \$message ... task message [string] (optional)
- \$sendmail ... send mail [boolean] (optional)
- \$priority ... priority [high, medium, low]

#### global input parameters

- \$mgmt\_config
- \$contentfile
- \$hcms\_lang\_codepage
- \$hcms\_lang
- \$lang

### Output

result array

## 7.17 Cloud Storage API Functions

## 7.17.1 loadcloudobject

## Description

This functions load/streams an object/file from the cloud storage and saves it the local media repository on request

#### **Syntax**

loadcloudobject (\$site, \$location, \$file, \$user="", \$save=true, \$directoutput=false)

## Input parameters

- \$site ... publication name [string]
- \$location ... media file location [string]

- \$file ... media file name [string]
- \$user ... user name [string] (optional)
- \$save ... save file in local media repository or return content as result [true, false] (optional)
- \$directoutput ... direct output of the streamed content [true, false] (optional)

### global input parameters

\$mgmt\_config

#### Output

data / false on error

## 7.17.2 savecloudobject

#### **Description**

This function saves an object/file in the cloud storage if no daily cloud snyc has been defined, see main configuration setting \$mgmt\_config['storage\_dailycloudsnyc']

#### **Syntax**

savecloudobject (\$site, \$location, \$file, \$user="")

#### Input parameters

- \$site ... publication name [string]
- \$location ... media file location [string]
- \$file ... media file name [string]
- \$user ... user name [string] (optional)

#### global input parameters

\$mgmt\_config

## Output

• true / false on error

## 7.17.3 copycloudobject

## Description

This functions renames an object/file in the cloud storage

#### Syntax

copycloudobject (\$site, \$location, \$file\_old, \$file\_new, \$user="")

### Input parameters

- \$site ... publication name [string]
- \$location ... media file location [string]
- \$file\_old ... source media file name [string]
- \$file\_new ... destination media file name [string]

• \$user ... user name [string] (optional)

### global input parameters

• \$mgmt\_config

## Output

• true / false on error

## 7.17.4 renamecloudobject

#### Description

This functions renames an object/file in the cloud storage

#### **Syntax**

renamecloudobject (\$site, \$location, \$file\_old, \$file\_new, \$user="")

#### Input parameters

- \$site ... publication name [string]
- \$location ... media file location [string]
- \$file\_old ... old media file name [string]
- \$file\_new ... new media file name [string]
- \$user ... user name [string] (optional)

## global input parameters

\$mgmt\_config

### **Output**

true / false on error

## 7.17.5 deletecloudobject

## Description

This function deletes an object/file and its data from the cloud storage

#### Syntax

deletecloudobject (\$site, \$location, \$file, \$user="")

## Input parameters

- \$site ... publication name [string]
- \$location ... media file location [string]
- \$file ... media file name [string]
- \$user ... user name [string] (optional)

• \$mgmt\_config

## Output

• true / false on error

## 7.17.6 synccloudobjects

## Description

This function snychronizes all local objects/files with the cloud storage. See also main configuration settings \$mgmt\_config['storage\_dailycloudsnyc'] and \$mgmt\_config['storage\_type'].

#### **Syntax**

synccloudobjects (\$user="")

## Input parameters

• \$user ... user name [string] (optional)

## global input parameters

• \$mgmt\_config

## Output

• true / false on error

## 7.17.7 GCanalyzevideo

## Description

Analyzes a video and finds labels, based on Google Video Intelligence.

#### Syntax

GCanalyzevideo (\$site, \$path)

#### Input parameters

- \$site ... publication name [string]
- \$path ... path or URI to a video file [string]

#### global input parameters

• \$mgmt\_config

#### Output

• result array / false on error

## 7.17.8 GCanalyzeimage

#### **Description**

Analyzes an image and finds labels, based on Google Vision.

#### **Syntax**

GCanalyzeimage (\$site, \$path)

#### Input parameters

- \$site ... publication name [string]
- \$path ... path or URI to a video file [string]

### global input parameters

\$mgmt\_config

## Output

result array / false on error

## 7.17.9 GCspeech2text

#### **Description**

Analyzes a video or audio and extracts the text from the audio stream, based on Google Cloud Speech.

Google Speech supports the following language codes:

af-ZA, am-ET, hy-AM, az-AZ, id-ID, ms-MY, bn-BD, bn-IN, ca-ES, cs-CZ, da-DK, de-DE, en-AU, en-CA, en-GH, en-GB, en-IN, en-IE, en-KE, en-NZ, en-NG, en-PH, en-ZA, en-TZ, en-US, es-AR, es-BO, es-CL, es-CO, es-CR, es-EC, es-SV, es-ES, es-US, es-GT, es-HN, es-MX, es-NI, es-PA, es-PY, es-PE, es-PR, es-DO, es-UY, es-VE, eu-ES, fil-PH, fr-CA, fr-FR, gl-ES, ka-GE, gu-IN, hr-HR, zu-ZA, is-IS, it-IT, jv-ID, kn-IN, km-KH, lo-LA, lv-LV, lt-LT, hu-HU, ml-IN, mr-IN, nl-NL, ne-NP, nb-NO, pl-PL, pt-BR, pt-PT, ro-RO, si-LK, sk-SK, sl-SI, su-ID, sw-TZ, sw-KE, fi-FI, sv-SE, ta-IN, ta-SG, ta-LK, ta-MY, te-IN, vi-VN, tr-TR, ur-PK, ur-IN, el-GR, bg-BG, ru-RU, sr-RS, uk-UA, he-IL, ar-IL, ar-JO, ar-AE, ar-BH, ar-DZ, ar-SA, ar-IQ, ar-KW, ar-MA, ar-TN, ar-OM, ar-PS, ar-QA, ar-LB, ar-EG, fa-IR, hi-IN, th-TH, ko-KR, cmn-Hant-TW, yue-Hant-HK, ja-JP, cmn-Hans-HK, cmn-Hans-CN

#### Syntax

GCspeech2text (\$site, \$path, \$langcode="en-US")

#### Input parameters

- \$site ... publication name [string]
- \$path ... path or URI to a video file [string]
- \$langcode ... language code [string] (optional)

- \$mgmt\_config
- \$mgmt\_imagepreview
- \$mgmt\_mediapreview
- \$mgmt\_mediaoptions
- \$mgmt\_imageoptions

- \$mgmt\_maxsizepreview
- \$mgmt\_mediametadata
- \$mgmt\_compress
- \$hcms\_ext

• result array / false on error

# 7.18 Import/Export API Functions

## 7.18.1 exportobjects

## Description

Executes the export job.

## **Syntax**

exportobjects ()

## Input parameters

## global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.18.2 importobjects

#### Description

Executes the import job.

#### **Syntax**

importobjects ()

## Input parameters

## global input parameters

• \$mgmt\_config

## Output

• true / false

## 7.18.3 importmediafiles

#### Description

This function imports all directories and files from import directory to location.

## **Syntax**

importmediafiles (\$importdir, \$location, \$createfolders=false, \$leavefiles=false, \$deletefiles=false, \$report=true, \$user="sys")

### Input parameters

- \$importdir ...
- \$location
- \$createfolders
- \$leavefiles
- \$deletefiles
- \$report
- \$user

## global input parameters

\$mgmt\_config

#### **Output**

true/false

## 7.18.4 importxmlfiles

## Description

Import of content and media files based on the XML import schema.

### **Syntax**

importxmlfiles (\$importdir, \$createfolders=false, \$ignoremissinglinks=false, \$leavefiles=false, \$deletefiles=false, \$report=true, \$user="sys")

#### Input parameters

- \$importdir ... path of the import directory [string]
- \$createfolders ... create folder [boolean] (optional)
- \$ignoremissinglinks ... ignore or keep links to missing objects [boolean] (optional)
- \$leavefiles ... leave the files in the import directory and create symbolic link to the file [boolean] (optional)
- \$deletefiles ... delete files after successful import [boolean] (optional)
- \$report ... print report [boolean] (optional)
- \$user ... user name [string] (optional)

#### global input parameters

• \$mgmt\_config

## Output

true / false

## 7.18.5 calculatedate

### **Syntax**

calculatedate (\$days)

#### Input parameters

• \$days ... number of days [integer]

#### Output

date based on number of days in the past from today

## 7.18.6 exportxmlfiles

#### **Description**

Export of content and media files based on the XMLexport schema.

#### **Syntax**

exportxmlfiles (\$location, \$object="", \$exportdir, \$recursive=false, \$preserve=false, \$symlink=false, \$delete=false, \$createdays=0, \$editdays=0, \$accessdays=0, \$filesize=0, \$contentrules="", \$report=true, \$user="sys")

#### Input parameters

- \$location ... location [string]
- \$object ... object name [string] (optional)
- \$exportdir ... path of the export directory or FTP server path [string]
- \$recursive ... export all items in subfolders recursively [boolean] (optional)
- \$preserve ... preserve container ID [boolean] (optional)
- \$symlink ... export only the media files and use a symbolic link to the file [boolean] (optional)
- \$delete ... delete files after successful export [boolean] (optional)
- \$createdays ... age in days after creation of the object [integer] (optional)
- \$editdays ... age in days after last modification of the object [integer] (optional)
- \$accessdays ... age in days after last access of the object [integer] (optional)
- \$filesize ... minimum file size of the asset in MB [integer] (optional)
- \$contentrules ... content rules/conditions for text content based on SQL Syntax [string]
- \$report ... print report [boolean] (optional)
- \$user ... user name [string] (optional)

## global input parameters

• \$mgmt\_config

#### Output

true / false

# 8 Rechtliche Hinweise / Impressum

## 8.1 Fragen und Anregungen

Sollten Sie weitergehende Fragen oder Anregungen zum Produkt haben, so wenden Sie sich bitte an den Support. Wir stehen Ihnen auch gerne für Fragen bezüglich unseres Reseller-Programms und Partner-Programms zur Verfügung. Zugriff auf die erweitere Online-Demo des hyper Content & Digital Asset Management Servers können sie ebenfalls über den Support beantragen.

#### hyperCMS Support:

support@hypercms.com http://www.hypercms.com

## 8.2 Impressum

Verantwortlich für den Inhalt:

hyperCMS Content Management Solutions GmbH Rembrandtstr. 35/6 A-1020 Wien – Austria

office@hypercms.com http://www.hypercms.com

## 8.3 Rechtliche Hinweise

Vorliegendes Benutzerhandbuch basiert auf der zum Zeitpunkt der Verfassung des Dokumentes verfügbaren Programmversion.

Der Hersteller behält sich Programmänderungen und -Verbesserungen vor.

Fehler und Irrtümer vorbehalten.

© 2020 by hyperCMS Content Management Solutions