

ZYVORAI LABS · CUSTOMER DOCUMENTATION



## Admin Basics

2026-08-29

| Topic     | Detail                                                                                                              |
|-----------|---------------------------------------------------------------------------------------------------------------------|
| Config    | <code>/etc/netevd/netevd.yaml</code> (see <code>config/netevd.example.yaml</code> )                                 |
| Hooks     | <code>/etc/netevd/{carrier,no-carrier,configured,degraded,routable,activated,disconnected,manager,routes}.d/</code> |
| Unit      | <code>netevd.service</code> — <code>systemctl enable --now netevd</code>                                            |
| Logs      | <code>journalctl -u netevd -f</code>                                                                                |
| REST      | <code>api.bind_address</code> + <code>api.port</code> (default <code>127.0.0.1:9090</code> )                        |
| Metrics   | <code>metrics.port</code> (default <code>9091</code> )                                                              |
| Backend   | <code>system.backend</code> : <code>systemd-networkd</code> · <code>NetworkManager</code> · <code>dhclient</code>   |
| Privilege | Drops to <code>netevd</code> user; retains <code>CAP_NET_ADMIN</code> ; hooks inherit no caps                       |
| Dry-run   | <code>netevd --dry-run ...</code> skips script execution / mutations                                                |
| Validate  | <code>netevd validate</code> against the config file                                                                |
| Reload    | <code>netevd reload</code> (API) or <code>systemctl restart netevd</code> after YAML/hook changes                   |
| Security  | See repo <code>SECURITY.md</code> ; restrict YAML permissions ( <code>chmod 640</code> )                            |

## Hook environment (common)

| Variable                 | Content                                      |
|--------------------------|----------------------------------------------|
| <code>\$LINK</code>      | Interface name                               |
| <code>\$LINKINDEX</code> | Kernel ifindex                               |
| <code>\$STATE</code>     | Normalized event state                       |
| <code>\$BACKEND</code>   | Source backend                               |
| <code>\$ADDRESSES</code> | Address / gateway / DNS summary              |
| <code>\$JSON</code>      | Full payload (systemd-networkd when enabled) |
| <code>\$DHCP_*</code>    | dhclient lease fields                        |

## Operate from CLI

---

1. **Config check:** `netevd validate && netevd status`
2. **Hook inventory:** `ls -la /etc/netevd/routable.d/ && netevd list scripts`
3. **Live debug:** `netevd events -f` + `journalctl -u netevd -f`
4. **Policy routing:** `netevd list rules` and `ip rule list`
5. **Remote API (tunnel):** `ssh -L 9090:127.0.0.1:9090 root<host>` then `curl http://127.0.0.1:9090/health`
6. **Metrics scrape:** `curl http://<host>:9091/metrics | grep netevd_info`

Use `<host>` in runbooks — never hard-code lab IPs.

# Support

[GitHub issues](#) · [Contact Zyvor](#) for Enterprise