

ZYVORAI LABS · CUSTOMER DOCUMENTATION



Admin Basics

2026-08-29

Topic	Detail
Config	<code>/etc/netevd/netevd.yaml</code> (see <code>config/netevd.example.yaml</code>)
Hooks	<code>/etc/netevd/{carrier,no-carrier,configured,degraded,routable,activated,disconnected,manager,routes}.d/</code>
Unit	<code>netevd.service</code> — <code>systemctl enable --now netevd</code>
Logs	<code>journalctl -u netevd -f</code>
REST	<code>api.bind_address</code> + <code>api.port</code> (default <code>127.0.0.1:9090</code>)
Metrics	<code>metrics.port</code> (default <code>9091</code>)
Backend	<code>system.backend</code> : <code>systemd-networkd</code> · <code>NetworkManager</code> · <code>dhclient</code>
Privilege	Drops to <code>netevd</code> user; retains <code>CAP_NET_ADMIN</code> ; hooks inherit no caps
Dry-run	<code>netevd --dry-run ...</code> skips script execution / mutations
Validate	<code>netevd validate</code> against the config file
Reload	<code>netevd reload</code> (API) after config/hook changes when supported
Security	See repo <code>SECURITY.md</code> ; restrict YAML permissions

Hook environment (common)

Variable	Content
<code>\$LINK</code>	Interface name
<code>\$LINKINDEX</code>	Kernel ifindex
<code>\$STATE</code>	Normalized event state
<code>\$BACKEND</code>	Source backend
<code>\$ADDRESSES</code>	Address / gateway / DNS summary
<code>\$JSON</code>	Full payload (systemd-networkd when enabled)
<code>\$DHCP_*</code>	dhclient lease fields

Support

[GitHub issues](#) · [Contact Zyvor](#) for Enterprise