

1 Preliminary

Condensed notes from references,

- The Implementation of Functional Programming Languages [1]
- Implementing Lazy Functional Languages on Stock Hardware: The Spineless Tagless G-machine [2]

, focusing on abstract machine operational semantics.

Notation:

```

 $\rho \equiv \text{local env}$ 
 $\rho' = \rho[x \mapsto y] \equiv \text{new env with the old env } \rho$ 
 $\text{plus additional mapping } x \mapsto y$ 
 $\rho[x \mapsto y] \equiv \text{env } \rho \text{ with mapping } x \mapsto y$ 
 $\text{present (eg: read the env only)}$ 

 $\text{val } \rho \sigma k = k, k \text{ is a literal}$ 
 $\text{val } \rho \sigma k = \rho[k], k \text{ is in } \rho$ 
 $\text{val } \rho \sigma k = \sigma[k], k \text{ is in } \sigma$ 
 $\text{val } \rho \sigma ks = [(\text{val } \rho \sigma k) \text{ for } k \text{ in } ks]$ 

 $\rho a \equiv \text{query env } \rho \text{ with key } a$ 
 $\rho as \equiv [\rho a \text{ for } a \text{ in } as]$ 
 $h a \equiv \text{query heap } h \text{ with key(address) } a$ 
 $h as \equiv [h a \text{ for } a \text{ in } as]$ 

 $(\text{vs } \backslash n \text{ xs} \mapsto e) \text{ ws\_f} \equiv \text{closure that is non-}$ 
 $\text{updatable, with parameters xs and free}$ 
 $\text{variable parameters vs bound with}$ 
 $\text{values ws\_f; note: closure with len(xs)}$ 
 $> 0 \implies \text{it is non-updatable}$ 
 $(\text{vs } \backslash u \{ \} \mapsto e) \text{ ws\_f} \equiv \text{closure that is}$ 
 $\text{updatable}$ 

```

2 Machine State

a tuple of:

- code
- $as \equiv$ argument stack: for actual arguments of lambdas
- $rs \equiv$ return stack: for continuations
- $us \equiv$ update stack: for updatable closure / thunk
- $h \equiv$ heap: for locals, closures
- $\sigma \equiv$ globals: for top-level variables/binders

initial state:

```

(eval (main { }) { },
 [],
 [],
 [],
 { ...;  $a_i \mapsto (vs_i \backslash \pi_i \text{ xs} \mapsto e_i) (\sigma \text{ vs}_i)$ ; },
 { ...; main = addr  $a_{main}$  })

```

3 Code Forms

eval $e \rho$: uses local env. ρ and accesses argument stack

enter a : accesses the argument stack for applying the closure at address a on the heap

ReturnCon $c \text{ ws}$: constructor c applied to ws ; return it to continuation

ReturnInt k : return primitive type int k to continuation

4 Operational Semantics

state transitions of STG

4.1 eval function application

eval $(f \text{ xs}) \rho, as, rs, us, h, \sigma$

where:

val $\rho \sigma f = \text{addr } a$

$\implies$

```

enter a,
(val  $\rho \sigma \text{ xs}$ ) ++ as,
rs,
us,
h,
 $\sigma$ 

```

note: ρ is discarded

4.2 intermediate state: enter non-updatable closure

```

enter a,
as,
rs,
us,
h[a  $\mapsto (\text{vs } \backslash n \text{ xs} \mapsto e) \text{ ws\_f}$ ],
 $\sigma$ 

```

where:

len(as) $\geq$ len(xs)

$\implies$

eval $e \rho, as', rs, us, h, \sigma$

(eval body e of closure, in local env ρ)

where:

$ws_a ++ as' = as$ // partition into 2,
where ws_a are the actual arguments
bound to formal parameters xs

len(xs) = len(ws_a)

$\rho = [\text{vs} \mapsto \text{ws_f}, \text{xs} \mapsto \text{ws_a}]$

(augmented local env., where free
variables vs are bound to ws_f , xs
are bound to arguments)

heap h is unchanged after transition

4.3 eval let expression

allocate closures on the heap for let bindings, extend local env with let binding heap addresses, then evaluate the body of the let expression

```
eval (let x1 = vs1 \π1 xs1 ↦ e1; ...; in e)
  ρ,
  as,
  rs,
  us,
  h,
  σ
```

⇒

```
eval e ρ', as, rs, us, h', σ
```

where:

```
ρ' = ρ[x1 ↦ addr a1, ...]
```

```
h' = h[a1 ↦ (vs1 \π1 xs1 ↦ e1)
      (ρrhs vs1);
      ...]
```

```
ρrhs = ρ
```

note:

```
this step converts static variable names
into runtime values for free variable
payload via (ρrhs vs1); this is where
heap allocation occurs
```

4.4 eval letrec expression

same as eval let expression, except $\rho_{rhs} = \rho'$

4.5 eval case expression

push continuation onto return stack and evaluate scrutinee expression; after evaluation, continue execution at continuation (pick which alternative to execute)

```
eval (case e of alts) ρ, as, rs, us, h, σ
```

⇒

```
eval e ρ, as, (alts, ρ):rs, us, h, σ
```

note: ρ provides context for evaluating chosen alternative

4.6 eval constructor

eval of an expression that is specifically a constructor

use of an intermediate state: ReturnCon which pops and resumes continuation(s) from return stack

```
eval (c xs) ρ, as, rs, us, h, σ
```

⇒

```
ReturnCon c (val ρ σ xs), as, rs, us, h, σ
```

4.7 intermediate state: ReturnCon

choose which alternative to resume execution from the return stack based on matching constructor

```
ReturnCon c ws,
  as,
  (...; c vs ↦ e; ..., ρ):rs,
  us,
  h,
  σ
```

⇒

```
eval e ρ[vs ↦ ws], as, rs, us, h, σ
```

note:

```
args to c are bound to vs in local env
```

```
continuations are pushed onto the return
stack earlier
```

handling default alternative for ReturnCon:

```
ReturnCon c ws,
  as,
  (c1 vs1 ↦ e1; ...; default ↦ ed, ρ):rs,
  us,
  h,
  σ
```

where:

```
c ≠ ci, (∀i)
```

⇒

```
eval ed ρ, as, rs, us, h, σ
```

handling match all variable binder pattern for ReturnCon:

```
ReturnCon c ws,
  as,
  (c1 vs1 ↦ e1; ...; v ↦ ed, ρ):rs, us, h, σ
```

where:

```
c ≠ ci, (∀i)
```

⇒

```
eval ed ρ[v ↦ a], as, rs, us, h', σ
```

where:

```
// introduce closure for constructor
h' = h[a ↦ (vs \n {} ↦ c vs) ws]
vs = newly introduced params/vars
a = newly introduced address
len(vs) = len(ws)
```

note: if there is no match to any of the above, then raise error

4.8 eval literal

similar logic as constructor

use of intermediate state: ReturnInt

```
eval k ρ, as, rs, us, h, σ
⇒
ReturnInt k, as, rs, us, h, σ
```

eval of a variable bound to a primitive value:

```
eval (f {}) ρ[f ↦ Int k], as, rs, us, h, σ
⇒
ReturnInt k, as, rs, us, h, σ
```

4.9 intermediate state: ReturnInt

purpose: search for a continuation on return stack to continue execution

```
ReturnInt k,
as,
(...; k ↦ e; ..., ρ):rs,
us,
h,
σ
⇒
eval e ρ, as, rs, us, h, σ
```

handling alternative with default:

```
ReturnInt k,
as,
(k1 ↦ e1; ...; default ↦ e, ρ):rs,
us,
h,
σ

where:
k ≠ ki, (∀i)
⇒
eval e ρ, as, rs, us, h, σ
```

handling alternative with match all binder variable:

```
ReturnInt k,
as,
(k1 ↦ e1; ...; x ↦ e, ρ):rs,
us,
h,
σ

where:
k ≠ ki, (∀i)
⇒
eval e ρ[x ↦ Int k], as, rs, us, h, σ
```

4.10 eval builtin operator

for example, binary operator $\oplus$ with primitive int parameters:

```
eval ⊕{x1, x2}
ρ[x1 ↦ Int i1, x2 ↦ Int i2],
as,
rs,
us,
h,
σ
⇒
ReturnInt (⊕ i1 i2), as, rs, us, h, σ
```

5 Update Mechanics

this is applicable for updatable closure / thunk

technique: implicitly detect that an update needs is required when empty return stack is encountered during constructor return, or when insufficient arguments are on argument stack when entering a function closure

2 stages:

1) updatable closure is entered

```
enter a,
as,
rs,
us,
h[a ↦ (vs \ u {} ↦ e) ws_f],
σ
```

note:

u denotes updatable closure

only closure with no arguments is ever qualified for being updatable

⇒

```
eval e ρ, [], [], (as,rs,a):us, h, σ
```

where:

$\rho = [vs \mapsto ws_f]$

arg. and return stacks are empty

similar to entering a non-updatable closure, except we push items onto the update stack

2) after eval of closure corresponding to body of original thunk/closure is done

update is triggered via either:

i) value of closure is data constructor (note: closures never evaluate to unboxed/primitive literals, so unboxed values are not stored in closures / thunks, so ReturnInt state is expected to have non-empty return stack and never triggers update):

try pop continuation from return stack, but the stack is empty
⇒ triggers update

ii) value of closure is a function:

function tries to bind arguments, but the argument stack does not have enough arguments ⇒ triggers update

5.1 update mechanics: when the updatable closure is a data constructor

evaluation of closure is data constructor: try pop continuation from return stack, but the stack is empty ⇒ triggering an update

closure referenced by the update frame is updated, where arg. stack and return stack are restored from update frame, and then try again (possibly trigger another update if return stack is still empty... until the stack is non-empty and a continuation is exposed)

```
ReturnCon c ws, [], [], (as_u, rs_u, a_u):
us, h, σ
```

note:

arg. and return stacks are empty

⇒

```
ReturnCon c ws, as_u, rs_u, us, h_u, σ
```

(updating closure a_u with a constructor closure)

where:

$h_u = h[a_u \mapsto (vs \setminus n \{\} \mapsto c \text{ vs}) \text{ ws}]$

$\text{len}(vs) = \text{len}(ws)$

$vs \equiv$ newly introduced params/vars

note:

no closure has a primitive type:
ReturnInt state won't see any empty return stack

5.2 update mechanics: when the updatable closure is a partial application

handle the case where there are not enough arguments on the argument stack for the lambda abstraction

```
enter a, as, [], (as_u, rs_u, a_u):us, h,  $\sigma$ 
```

where:

```
len(as) < len(xs)
```

```
h a = (vs \n xs  $\mapsto$  e) ws_f
```

```
len(xs) > 0  $\implies$  non-updatable closure
```

$\implies$

```
enter a, as++as_u, rs_u, us, h',  $\sigma$ 
```

(restore arg. and return stacks, update closure a_u in the heap, then retry entering a)

where:

```
h' = h[a_u  $\mapsto$  (vs++xs1 \n xs2  $\mapsto$  e) (ws_f ++ as)]
```

```
xs1 ++ xs2 = xs
```

```
len(xs1) = len(as)
```

xs1 are transferred to be free variables from original formal parameters of lambda along with arguments 'as'

xs2 are remaining formal parameters

a is referring to the closure that is originally produced from updatable closure/thunk a_u's body

h' is updated for future use: what is in closure 'a' is inlined into 'a_u' plus adjustments for partial application

a_u is the updatable thunk/closure

in order to avoid compiling code for the body, e, for every possible partial application

```
(vs++xs1 \n xs2  $\mapsto$  e)
```

, an alternative form exists that reuses closure 'a' being entered within the new updated closure:

```
enter a, as, [], (as_u, rs_u, a_u):us, h,  $\sigma$ 
```

where:

```
len(as) < len(xs)
```

```
h a = (vs \n xs  $\mapsto$  e) ws_f
```

```
len(xs) > 0
```

$\implies$

```
enter a, as++as_u, rs_u, us, h_u,  $\sigma$ 
```

where:

```
h_u = h[a_u  $\mapsto$  ((f:xs1) \n {}  $\mapsto$  f xs1) (a :as)]
```

```
xs1++xs2 = xs
```

```
len(xs1) = len(as)
```

f $\equiv$ newly introduced variable

((f:xs1) \n {} $\mapsto$ f xs1) $\equiv$ sharable code for all partial applications with the same number of arguments 'xs1' $\implies$ create a set of such code covering different arities that can be used by any partial application with matching number of arguments

References

- [1] Simon L. Peyton Jones. *The Implementation of Functional Programming Languages*. Prentice Hall, 1987.
- [2] Simon L. Peyton Jones. Implementing lazy functional languages on stock hardware: The Spineless Tagless G-machine. *Journal of Functional Programming*, 2(2):127–202, 1992.