

Contents

PBUI Wiring Intern Review	1
1. Review conclusion and reading guide	1
2. What the system is for	2
3. Architecture and ownership boundaries	4
4. Ports, bindings, evaluation, and commands	6
5. How the picture is constructed	8
6. Browser method and measured results	10
7. Findings: user impact, mechanism, and repair target	12
8. What the implementation got right, and why the tests were insufficient	20
9. Proposed repair design	22
10. Implementation plan an intern can follow	25
11. Acceptance tests and local reproduction	26
12. Source and API reading map	27
13. Screenshot and evidence catalog	29

PBUI Wiring Intern Review

1. Review conclusion and reading guide

PBUI-WIRING-1 introduced a useful visual vocabulary: tiles expose typed ports, square jacks mark connection points, and wires make dependencies visible. The semantic foundation is substantially stronger than the current visual interaction. A successful link can propagate values correctly while its wire is stale, diagonal, clipped, or difficult to interpret. The implementation should therefore be considered a working foundation with significant interaction and geometry defects, rather than a finished wiring interface.

This review evaluates the result from a user's seat. The central question is whether a person can reliably answer **what is connected, what will happen if I connect these ports, and what changed when I moved something**. The most serious failures are wires crossing a tile after resizing, wires detaching from their jacks while a divider is being dragged, and horizontal scrollbars whose only purpose is to scroll a protruding jack. These failures undermine the picture's explanatory role even when the underlying binding remains correct.

The report also serves as an onboarding guide. Sections 2–5 introduce the system and its execution paths. Sections 6–8 connect browser evidence to source code and explain why the existing validation missed the defects. Sections 9–11 propose a repair design, an implementation sequence, and meaningful acceptance tests. Section 12 is a navigable source/API map; section 13 catalogs every screenshot.

Scope and provenance. Source inspection is against PBUI commit 142b458a, on 2026-09-04. Existing Storybook instances on ports 6008 and 6012 supplied the live UI. No product source was changed for this review. The source router was separately invoked on captured browser geometry to confirm that the diagonal paths are reproducible in the checked-out implementation, rather than merely an old screenshot or a stale browser frame. Local built core packages were used for a minimal reproduction of the fixture's command refusals. The original design, nine-step diary, phase report, and the Obsidian project report informed the investigation; their conclusions were checked against current behavior.

The requested follow-up specifically called out horizontal scrollbars and asked for functional and visual assessment from a user's perspective. Section 7.3 addresses that complaint with a controlled DOM experiment. Recommendations below are proposals, not implemented fixes. The original nine implementation phases remain historical facts; completing those phases did not establish the acceptance criteria developed here.

2. What the system is for

PBUI is a presentation-based React UI system. A product can describe an object, such as an order or a port, and give its presentation common behaviors: labeling, object menus, hover information, and actions. The workbench arranges applications into tiles. Wiring lets one application consume a value produced by another without hard-coding a particular pair of components together.

Consider an orders table and an order-detail panel. The table emits an order reference when the user selects a row. The detail view declares an input that accepts orders. Following the table's output makes the detail view evaluate that output whenever its value changes. The wire is a drawing of that dependency; it does not carry the data through SVG or DOM events. Moving a tile changes the drawing without changing the dependency.

The WiringLab makes this concrete with two sources, a transform, two sinks, and a multi-port tile. Clicking **tick** in Source A emits a number and a text label. Transform reads the number and emits twice its value. A sink displays its input. After the review's tick interaction, Source A displayed 1, Transform displayed in: 1 → out: 2, Sink A displayed value: 1, and Wide displayed beta: 2. This is a useful end-to-end demonstration of the semantic path.




Figure 1: Application values after closing wiring and ticking both sources. The review verified Source A = 1, Transform = 2, Sink A = 1, and Wide beta = 2.

2.1 Vocabulary an intern needs

Term	Meaning in this system
Application manifest	Headless declaration of an app's identity, ports, and placement/binding policies.
Application presentation	React component, title, tone, and other browser-facing rendering choices.
View	Logical application instance with an ID and document bindings.
Placement / tile	A leaf in a workspace layout that displays a view. Multiple placements can show the same view.
Port	A named endpoint on a view, addressed as <code>viewId/portName</code> .
Contract	Normalized value and protocol constraints used by the planner.
Binding	Durable description of where an input gets its value.
Runtime	Ephemeral emitted values, attended values, context values, and shared-cell values.
Snapshot	Coherent set of definitions, bindings, identity facts, and runtime facts for evaluation.
Card	Visible port information and the main pointer interaction target.
Jack	Square visual anchor near the tile frame.
Wire	Currently decorative, not the drag initiator. SVG representation of a binding or identity declaration.
Carry	Browser-local state of a port drag in progress.

A view ID and a placement ID are different identities. If two tiles display the same view, they share its port IDs and bindings. A port may therefore have multiple DOM anchors. Conversely, two copies created as separate views have different port IDs even if their titles and application types match. This distinction explains both the multi-element registry and the need to keep semantic identity independent from screen position.

2.2 The expected user journey

A usable wiring interface should support a short sequence without requiring knowledge of implementation vocabulary:

1. Enter wiring and recognize the same tiles in the same workspace.
2. Find the source and the destination by readable labels and direction cues.
3. Start a connection from an obvious target; see which destinations accept it and why others do not.
4. Release and receive confirmation of the exact resulting relationship.
5. Follow a wire with the eye, inspect or remove it, and return to the application.
6. Resize or scroll without losing the relationship between the picture and the model.

The current implementation supports parts of this journey well. The cards show name, type, binding state, and documentation; the cursor changes from Follow to Hold when Shift is pressed; Escape cancels a carry before closing the mode; and the product's wire menu names both endpoints. Other parts are misleading: the jack looks draggable but does not start a

carry, the lab advertises menu behavior it has not installed, and global scrimming makes its own instructions and close button look disabled.

3. Architecture and ownership boundaries




Figure 2: Architecture: product declarations and value emission feed the headless core and link snapshot; the React shell projects the snapshot into rails and wires.

3.1 The protocol, headless core, and React shell

workbench-protocol defines the document and mutation shapes. Layout is a tree: an internal node splits an area into two children, and a leaf refers to a view. The document also records views and document payloads. This layer supplies stable transport and structural representations; it does not draw wires.

workbench-core owns semantic state, structural validation, command planning, and transaction publication. Its `createWorkbenchCore` accepts an initial document, an application catalog, policy, and optional link collaborator. `execute` returns a small success/refusal result. A refusal is data the caller must handle; issuing a command is not proof that the requested operation occurred. The core installs document and staged runtime changes before publication so subscribers do not observe half of a link transition. See core construction and transaction API and the link collaborator.

pbui-workbench is the React shell over that core. `createWorkbenchShell` binds presentation components to the core's application manifests, owns browser-local shell state, and exposes bound components such as `wb.Surface`. Its `execute` measures geometry only for commands that require layout information; a port-follow operation does not need a DOM position. Its

dispatch handles shell actions such as opening link mode. See shell construction, especially lines 54–120.

WorkbenchSurface recursively renders splits and tiles, owns the workbench root element, and mounts WireLayer while link mode is open. Keyboard ownership is scoped by focus and the number of workbench roots on the page. SplitPane temporarily owns a live drag ratio and commits a resize command on pointer release. That is a good persistence decision: it avoids writing the document for every pointer movement. It also creates an obligation for the visual geometry layer to observe layout changes that occur before a document revision. The current implementation does not fully meet that obligation. See Surface and SplitPane.

3.2 Presentation behavior is a separate extension point

The generic workbench can render a plain port or wire. A product installs richer behavior through renderPort, renderWire, and renderBadges. Ecommerce wraps port cards in a block Presentation and wire groups in an SVG Presentation; its object-menu contributions can then inspect the carried PortRef or LinkRef. block prevents a second decorative box around an already framed card. svg preserves valid SVG presentation structure. See ShopShell, lines 62–80.

This is why the ecommerce wire menu works while the lab’s right-click does nothing. WiringLab renders `<wb.Surface />` without those wrappers or a product object-menu setup. The generic SVG hit path still advertises a context-menu cursor. From an intern’s perspective, the lesson is that a visual component and its product action installation are separate obligations. From a user’s perspective, an apparent action target that does nothing is a defect regardless of which package owns the missing behavior.

3.3 Durable state versus ephemeral state

Owner	Examples	What should trigger it
Workbench document	Split ratios, views, link terms, captured hold values	Successful semantic/layout command
Link runtime	Latest emissions, attended reference, context and shared cells	Application emission or staged runtime effect
Shell store	Link mode, launcher, chooser	Browser UI action
Carry store	Pointer position, candidate target, modifiers	Pointer/key events
DOM geometry	Tile bounds, card bounds, jack positions, scroll clipping	Layout, resize, scrolling, mounting
Route result	Polyline points, label placement, hit geometry	Relevant semantic or geometry change

The existing code correctly separates many of these concerns, but does not yet have an explicit owner for a coherent geometry snapshot. Geometry is instead read and invalidated by several components. That scattered ownership explains the divider-drag failure and the scroll-related ordering fixes recorded in the original diary.

4. Ports, bindings, evaluation, and commands

4.1 The contract is more than a TypeScript type

A port's contract can be declared using a type ID shorthand such as "number". `normalizeContract` expands it into value type, semantic role, cardinality, mode, authority domain, update algebra, and lifetime. An input defaults to read mode, an output to write mode, and an inout port to read-write mode. These are runtime declarations that the link planner can inspect. They are not inferred from a React component's TypeScript props. See port types and normalization, especially lines 38-103 and 159 onward.

Following asks whether a producer can provide an acceptable value to a consumer, including direction, existing bindings, and type reachability. Sharing an identity cell is stricter: two members must agree on the full normalized contract and satisfy the identity planner's binding constraints. Merely seeing <number> on both cards does not prove identity compatibility.

An inout port has two visual sides but one semantic port ID. That is why the registry is indexed by both ID and side, and why an identity-capable demonstration should include compatible inout ports if it wants to initiate identity through the current output-card gesture.

4.2 Binding terms and the internal program

The public binding representation is a tagged union. The most relevant variants are:

```
// Abbreviated from src/presentation/links/terms.ts.  
type Binding =  
  | { kind: "ambient"; key: string }  
  | { kind: "constant"; reference: SerializableReference }  
  | { kind: "follow"; source: PortId; linkId: string }  
  | { kind: "derived"; source: Binding;  
      relationId: string; linkId: string }  
  | { kind: "hold"; reference: SerializableReference;  
      suspended: Binding }  
  | { kind: "alias"; classId: string }  
  | { kind: "unresolved"; diagnostic: Diagnostic };
```

`follow` evaluates another port. `hold` stores a captured reference while preserving the suspended relationship for resume. A derived binding applies a named relation to its source binding. An alias refers to a compiled shared cell. An unbound input may resolve its declared ambient fallback; absence of an explicit wire is not proof that an input has no effective value.

The internal expression/program representation separates evaluation concerns from the public terms. `programOf`, `effectiveProgram`, and `evaluateProgram` are useful reading points when tracing nested derived/held behavior. An intern should not add special-case data propagation to `WireLayer`; evaluation belongs in the link kernel. See terms, expression/program conversion, and evaluation.

`LinkSnapshot` combines port definitions, binding and identity state, aliases/classes, and runtime values. The core collaborator caches the snapshot by document identity and runtime revision. The shell's `useLinkSnapshot` subscribes to both document/core changes and link-runtime changes through `useSyncExternalStore`.

4.3 An end-to-end value flow

```
User clicks Source A's tick button  
  emitCount({type: "number", value: 1})  
    -> runtime.emit(viewId + "/count", reference)
```

- > runtime revision and subscriber publication
- > useLinkSnapshot reads current facts
- > evaluatePort(transform + "/in") follows source/count
- > Transform effect emits number 2
- > evaluatePort(wide + "/beta") yields number 2

WireLayer reads the same binding facts

- > linkRefsOf(snapshot)
- > draws a visual explanation
- > never performs the numeric transformation

usePort(view, name) returns the effective reference, value, evaluation, and badge. useEmit-Port(view, name) returns a function that writes to the output and any declared context or shared cell. runtime.emit is also available to product code that already owns its value in another store. See React link hooks and runtime.

4.4 An end-to-end connection gesture

PortRail.begin starts a carry only from an output-side card. The carry controller tracks pointer movement globally and reads modifiers live, including release-time modifiers. It asks the current planner about acceptability; the drop handler executes against a fresh snapshot rather than trusting a previous hover result.

pointerdown on output card

- > startPortCarry(from, acceptable, onDrop, onCancel)

pointermove

- > hit-test closest data-port-id
- > planFollow OR planIdentityAdd
- > publish over, acceptable, pointer, modifiers
- > input cards and cursor describe possible landing

pointerup

- > recheck target and modifiers
- > Ctrl/Meta: execute(identity.add)
- > otherwise: execute(port.follow)
 - if success and Shift: execute(port.pin)
- > clear carry and global listeners

The current Shift gesture performs two commands. If the follow succeeds but pin is refused because the source has no value, the result is a follow rather than the promised held relationship. PortRail checks the follow result but ignores the pin result. The lab's initial pin refusal demonstrates the same empty-value precondition. A better design should either reject the combined operation before claiming Hold, execute it atomically where supported, or explicitly explain the partial result. See PortRail lines 32-57 and planPin lines 83-92.

Escape during a carry cancels that gesture and leaves link mode open. Escape without a carry closes the mode. The review observed six rails and no cursor after canceling an incompatible drag, and zero rails after closing wiring following a successful held connection. This distinction is useful and should be preserved.

5. How the picture is constructed

5.1 Cards, jacks, and multiple mounted anchors

The carry registry is module-global: `Map<PortId, {in?: Set<Element>, out?: Set<Element>}>`. A port card's ref registers its element. `portElements` returns all elements for a side. `WireLayer.wireEnds` makes one visual wire per destination element and selects the nearest source anchor by Euclidean distance. This allows a logical view displayed in two tiles to have wires into both visible placements. See registry lines 39-83 and `wireEnds` lines 88-105.

This is a drawing heuristic, not a semantic change. Reordering or resizing duplicate placements can change which source instance is nearest. The registry currently does not filter `portElements` by `isConnected` or by the active workbench root. Its null-ref cleanup prunes disconnected elements and, if none were disconnected, clears the whole side. These details matter when reviewing duplicate mounts, multiple shells, or ref reattachment; the original design's description of connected-only lookup is stronger than the implementation.

Jacks live in an overlay inside the rail. The input jack is positioned at `left: -7px`; the output jack at `right: -7px`. Their width and height are 12px. Cards scroll inside vertical columns; a layout effect measures every card center and updates the separate jack layer. The jack layer is clipped vertically with `clip-path: inset(0 -20px)` while allowing horizontal protrusion. `anchorOf` locates a matching jack by port ID and side, then uses the input's left edge or output's right edge at its vertical center.

All points must be expressed relative to the same surface origin:

```
output anchor x = jackRect.right - surfaceRect.left
input  anchor x = jackRect.left  - surfaceRect.left
anchor y       = jackRect.top + jackRect.height/2
               - surfaceRect.top
```

This explains the earlier containing-block fix: Surface must be positioned so the absolute wire overlay is laid out against the same surface whose origin was subtracted from the measurements.

5.2 Geometry invalidation and the commit signal

`PortRail` measures on column scroll, its own `ResizeObserver`, window resize, and relevant snapshot changes. If the jack array changes, a layout effect dispatches `pbui:jacks-placed` after the jacks commit. `WireLayer` listens to that event, surface scroll in capture phase, window resize, and a `ResizeObserver` on the workbench root. It increments a local tick to force geometry to be reread.

The explicit post-commit event addresses a real ordering issue: measuring a jack in the same React batch that moves it can read the previous DOM. However, the event is tied to changes in local jack state. A frame can move horizontally while the jack's local top and bound state remain unchanged. The rail then publishes no changed jack state, and the wire layer observes only an unchanged outer root size. The live divider case falls through this gap.

5.3 Grid routing and why heading is part of the state

`routeAround` rasterizes a rectangular routing field into cells. It marks cells covered by inflated tile obstacles, frees short endpoint corridors, and searches for a low-cost path. A search state includes both cell position and travel direction. Direction is necessary because two arrivals at the same cell can have different future bend costs.




Figure 3: Current geometry flow and the missing invalidation during horizontal divider movement.

```

routeAround(from, to, obstacles, lanes, options):
  grid = rasterize(options.bounds, cell = 6px)
  block each tile inflated by margin = 3px
  free source +x corridor and destination -x corridor
  start at (sourceCell, heading = +x)

  Dijkstra over (cell, heading):
    next step costs 1
    add 10 for a change of heading
    add 8 if another wire occupied this cell
    do not immediately reverse direction
    accept destination only with heading +x

  if no route or search limit reached: return null
  reconstruct cells and mark lanes
  keep corners, snap endpoints, serialize as SVG
  
```

The caller routes longer endpoint spans first and reuses a Lanes instance for subsequent wires. Occupancy is a penalty, not an exclusion, so overlapping segments remain possible. The routing field extends 18px beyond the surface. If routing returns null, WireLayer silently draws a simpler orthogonal fallback that does not avoid obstacles. Grid limits are 400,000 cells and 600,000 popped search states. See route.ts lines 55-217 and WireLayer lines 159-176.

At 1440×1000, the captured surface plus exterior strip gives roughly 245×168 grid cells, or about 164,000 heading states per search. Each call allocates grid and search arrays. All routes are rebuilt during rendering, including renders caused by pointer carry updates. This is a source-based performance concern, not a benchmark result; the review did not measure a frame-time distribution.

5.4 SVG, styling, and interaction layers

The surface establishes an isolated stacking context in link mode. A fixed scrim washes the page; tiles paint above it; the wire overlay is at z-index 3. The application's DOM remains mounted and inert but becomes invisible. Gutters expand to the spacing token that currently yields 24px. The familiar application positions are mostly preserved, but the gutter change does alter available tile space.

Each wire group contains a transparent 10px hit stroke and a visible 2px stroke. Held links are dotted, derived links dashed and labeled, and identities use a wide outer stroke with a narrow inner stroke. Longer endpoint spans render first so shorter overlapping paths receive later hit targets. During a port carry, wire hit targets are disabled. The wire SVG is aria-hidden; link announcements and product menus must provide accessible alternatives.

The derived label is currently placed using `labelPoint(from, to, channel)`, a helper from the earlier simple router. It does not inspect the path returned by `routeAround`. This split between actual geometry and annotation geometry directly causes the detached label in section 7.5.

6. Browser method and measured results

The review used Playwright's actual browser page, pointer actions, keyboard events, native wheel scrolling, and viewport resizing. Measurements were collected after 600–700ms settling intervals except where explicitly taken during a held divider drag. These waits are observational settling intervals, not a guarantee that every intermediate animation frame is correct. No CSS was altered for the baseline screenshots.

The probe records surface and tile rectangles, jack rectangles, clipping, SVG path data, endpoint error, diagonal segments, and sampled tile intersections. All coordinates in the JSON are surface-relative CSS pixels. Endpoint error compares a path endpoint with the expected jack edge/center. Intersection detection samples the path every 2px against tile interiors inset by 2px; it is a useful diagnostic but not an exact collision proof. The source replay independently verifies the returned path points.

6.1 Window resize sweep

The same mounted lab was resized in sequence, including a return to the original size. IDs and bindings stayed in place throughout the sweep.

Viewport	Wires	Maximum settled endpoint error	Diagonal result	User-visible assessment
1440×1000	4 follows	0px	Short Source A → Transform wire	Labels readable; long empty panels; spurious scrollbars.
1280×800	4 follows	0px	Same short wire	General layout fits; defect remains.
1024×768	4 follows	0px	Same short wire	More compressed cards; endpoint alignment still correct.

Viewport	Wires	Maximum settled endpoint error	Diagonal result	User-visible assessment
768×900	4 follows	0px	Transform → Wide crosses Transform	Major routing failure; headings truncate; four horizontal bars.
390×844	4 follows	0px	None in this sample	Three squeezed columns; names/types cut off; page overflow.
1440×1000 again	4 follows	0px	Original short diagonal returns	Confirms deterministic size-dependent geometry, not accumulating drift.

Zero endpoint error is necessary but not sufficient. The 768px screenshot is an especially useful counterexample: the ends are exactly aligned, while the route between them is grossly wrong. A test that checks only path exists or end meets jack would pass it.

6.2 Divider drag and port scrolling

Dragging the first vertical separator 130px to the right at 1440×1000 changed the actual tile frames while the wire paths remained stale. A measurement taken with the pointer still down, after a 600ms pause, showed errors of 65px and 130px on affected endpoints, with a maximum of approximately 130.016px. On release, the committed resize caused endpoints to return to 0px error. This is not just a fast-drag frame artifact.

In Crowded at 1280×560, the input column had `clientHeight=185`, `scrollHeight=337`, and a maximum scroll of 152px. Before scrolling, the theta jack was clipped yet its wire still targeted its offscreen coordinates. The wire's endpoint y was 606.15625 relative to a surface only 502.375px high. After a native wheel scroll to 152px, theta became visible and the endpoint moved to 454.15625, correctly matching its jack. Resizing the scrolled view to 768×560 reproduced the large diagonal routing defect.

6.3 Connection and menu exercises

Exercise	Observed result
Tick Source A and B with wiring closed	Values propagate; transform doubles; sinks render values.
Drag text label to an anything input	Follow preview names source and target.
Press Shift while still dragging	Cursor changes to Hold before release.
Release after values exist	A held wire appears; sink holds "tick 1".
Drag text label to numeric input	Landing refused; cursor says cannot land on Sink A · value.

Exercise	Observed result
Escape during that carry	Carry canceled, six rails remain, four original wires remain.
Drag the visible square jack	No carry starts.
Right-click a wire in WiringLab	No application menu opens.
Right-click short detail wire in ecommerce	Correct detail-link menu opens, including unlink variants.

7. Findings: user impact, mechanism, and repair target

7.1 F1 — Route reconstruction can destroy orthogonality and obstacle avoidance

Priority: high. Evidence: observed in browser and reproduced from current source.

At 768×900, the cross-row path contains (504, 49.671875) → (252, 420). Both coordinates change, making a diagonal that crosses Transform. The complete path was:

```
M 501.109375 49.671875
L 504 49.671875
L 252 420
L 252 530.25
L 259.234375 530.25
```

In route.ts lines 182–201, corner extraction is followed by overwriting the first corner’s y with the source y and the last corner’s y with the destination y. This assumes those corners are safe horizontal endpoint adapters. That assumption fails when search turns immediately or a short route has too few independent corners. Moving a corner can turn the next segment diagonal or remove an essential bend. The three-point short route also writes to the same middle point twice.

For the user, this looks like a connection cutting through application content and makes the wiring layout appear arbitrary. The repair must preserve the searched path and add independently validated endpoint segments. Checking the raw grid path is insufficient: validate the final, snapped polyline for orthogonality, obstacle intersection, and correct exit/entry direction.

7.2 F2 — Divider dragging leaves the wire geometry stale

Priority: high. Evidence: observed during a paused live drag. SplitPane updates a local ratio while dragging; the workbench document is unchanged until release. WireLayer watches the surface’s size rather than each moving frame. PortRail compares only local jack top, side, ID, and bound status; a pure horizontal move can change none of them. Its post-commit jack event therefore need not fire. See SplitPane lines 56–100, PortRail line 128, and WireLayer lines 134–156.

The user loses confidence while adjusting the workspace because the lines temporarily imply different attachment points. Preserve the single document commit on release, but publish a geometry revision during the live drag. Geometry must be invalidated by position changes as well as size changes.

7.3 F3 — Decorative output jacks create horizontal scrollbars

Priority: high. Evidence: browser measurement plus controlled intervention. At 768px, Source A’s body was 236px wide with a scroll width of 243px. Transform and Wide had 228px clients and 235px scroll widths. The two input-only sinks had no horizontal overflow. Every affected tile had an output jack protruding to the right.




Figure 4: At 768px the Transform-to-Wide connection visibly cuts across the Transform tile. The endpoint measurements still report zero error.




Figure 5: The divider is still held down. Source A has widened, but its wires retain their old x positions and cross the resized frames.




Figure 6: Crowded after scrolling: theta is visible and its endpoint follows, but the multiple nested scrollbars make the interaction hard to read.




Figure 7: A genuine held connection after a source emission and Shift-drop. This case succeeds even though the lab's seed-time hold fails.




Figure 8: The ecommerce menu names the selected relationship and provides unlink, derived, and navigation actions.

Temporary DOM intervention	Source A client / scroll width	Interpretation
Baseline	236 / 243px	7px of unwanted horizontal overflow.
Hide the inert app with <code>display:none</code>	236 / 243px	Hidden application content is not the cause in this fixture.
Hide the jacks	236 / 236px	Jack protrusion is the cause.
Hide the rail	236 / 236px	Consistent with the rail/jack subtree being responsible.

All temporary style tags were removed before the subsequent interaction. Native horizontal wheel scrolling then changed Source A's `scrollLeft` to 7. This moves the rail rather than revealing useful content. The origin is public chrome tile-body { `overflow: auto` }, lines 111-117 combined with PortRail's output `jack right: -7px`. The visual clipping layer does not prevent the descendant geometry from contributing to scrollable overflow.

A user sees scrollbars under mostly empty panels and reasonably assumes there is hidden information. Scrolling instead nudges the connection surface. This adds clutter, consumes height, and damages the intended frame attachment. The repair should make the jack overlay a sibling outside the scrolling body, give the port columns sole ownership of vertical scrolling, and keep the frame coordinate system stationary. Merely hiding all horizontal overflow risks clipping the very jacks the design wants to expose and should not be accepted without geometry checks.

7.4 F4 — Scrolled-out ports still attract full wires

Priority: high. Evidence: observed in Crowded before scrolling. Jack elements remain mounted even when the jack layer clips them. `anchorOf` still measures them and `wireEnds` treats them as ordinary endpoints. A source can therefore connect to an invisible point below the viewport, making the wire appear unfinished or disappear beyond the workbench.

The current portal case handles missing mounted endpoints, not clipped-but-mounted endpoints. Define visibility explicitly: fully visible, clipped above/below, or absent. A clipped port should produce a visible rail-edge continuation with a label or reveal action, rather than a full path to a hidden coordinate. If multiple hidden ports share an edge, the continuation needs disambiguation and a count. See `anchorOf` and `wireEnds` and the raw Crowded measurements.

7.5 F5 — The derived label is unrelated to the routed path

Priority: medium. Evidence: observed in the visual-audit fixture. The derived path goes above the middle tile, but its double label sits inside that tile. Its text anchor is approximately 58px from the nearest sampled point on the wire. `labelPoint` still uses a midpoint formula for the old route, while the stroke uses the obstacle router. See `WireLayer` lines 60-64 and 196-212.

The user cannot tell whether double names the Notes tile, a port, or a transform on the wire. Choose a sufficiently long segment of the final validated polyline, place the label next to that segment, and account for its box in collision checks. The audit story injects the derived term directly and does not establish successful relation evaluation; it is useful evidence for drawing, not for end-to-end derived semantics.

7.6 F6 — The lab's claimed semantic coverage is false

Priority: high for validation and onboarding. Evidence: browser console, DOM, and command replay. The story attempts four follows, one pin, and an identity. All four follows




Figure 9: The word “double” appears inside Notes while the dashed wire routes over its top. This is annotation geometry detached from route geometry.

succeed. Pin fails with code empty because Source B has emitted nothing. Identity fails with code bound because Sink A's value already follows Source A. The story does not inspect any of these results. Its comment and earlier reports describe held/identity coverage that the current lab does not provide.

```
port.pin:
  ok: false, code: "empty"
  "sink · anything shows nothing to hold"

identity.add:
  ok: false, code: "bound"
  "sink · value is following a source; unlink it first"
```

See WiringLab lines 196–201, planning preconditions, browser console, and source replay. There are no inout ports in this lab, so its output-card Ctrl-sharing instructions also lack a valid source: the identity planner refuses output-only members. The old diary's explanation that the sinks share a cell but no wire is drawn is not supported by the current fixture; the identity declaration itself never succeeds.

Repair the fixture before using it to approve another visual iteration. Seed real values before pinning, reserve separate compatible inout ports for identity, and assert every command result and resulting term count. Use a valid product presentation installation if the lab promises badge/wire menus. Fixture correctness is part of the product review because this story is explicitly offered as the place to learn the feature.

7.7 F7 — The visible interaction vocabulary promises more than it delivers

Priority: medium. Evidence: direct pointer and keyboard inspection. A square socket is a conventional place to begin wiring, but the jack layer has `pointer-events:none` and the handler is on the card. The card is a DIV with no role and `tabIndex=-1`. The wire group is inside an `aria-hidden` SVG, and the generic lab provides no equivalent relationship editor. A live region announces changes but does not supply an accessible operation for making those changes.

The lab instructions say to right-click a badge for verbs, yet the lab installs neither product wrappers nor a menu. In contrast, ecommerce's tested menu correctly names the selected detail link. The fix is to choose and implement a coherent default: make cards and/or jacks explicit accessible connection controls, and provide a keyboard-operable connection list or command surface. Product customization can extend that default without making basic management depend on an invisible installation step.

The refused drag message is also too generic. `cannot land on Sink A · value` identifies a target but omits the available planner reason, such as text versus number or an existing hold. Surface the specific reason and a relevant next action. Do not force the user to infer it from a dimmed border.

7.8 F8 — Visual hierarchy and responsive behavior need product decisions

Priority: medium on desktop; high if narrow-screen operation is required. Evidence: screenshots and interaction. The scrim is fixed across the page and has no pointer interception. It makes the lab's buttons and instructions very faint while those controls remain clickable. This breaks the familiar convention that washed-out controls are disabled. A dedicated, readable wiring toolbar should remain above the scrim and contain a clear exit action and short legend.

At 390px, the layout retains three columns only about 100–111px wide, and every rail still reserves half its width for each direction even if one side has no ports. Titles collapse to

fragments while four header action buttons keep their width. Port names and types are clipped. The document scroll width was 394px for a 390px viewport. The absence of a diagonal in this particular size does not make the layout usable.

On wider screens, the large blank tile bodies, repeated none state labels, same-color wires, and shared stubs still require effort to read. The ink style is consistent, but consistency alone does not reveal which path belongs to which connection. Hover/focus should highlight one whole connection and both endpoints, with a persistent textual relationship description. One-sided tiles should not waste half the rail on a no inputs or no outputs placeholder. At a small width, use a consciously designed alternate view or a minimum-width canvas with explicit navigation; silently compressing every control is not an adequate policy.

7.9 F9 — Additional implementation risks to test explicitly

The following are source-backed concerns, not additional browser reproductions:

- **Global registry ownership.** The module-global anchor/carry registry and root-unfiltered lookup deserve multi-shell and duplicated-view tests. A source mounted in another shell must not be selected solely because its port ID matches.
- **Null-ref cleanup.** Clearing a side when no disconnected member is found can remove connected duplicates during ref reattachment. A disposer tied to a specific element is easier to reason about than inferring which node departed.
- **Invisible fallback.** A no-route or budget result becomes a plain route through obstacles with no diagnostic. Failed route planning must remain an explicit state in the drawing model.
- **Route churn.** Longest-span ordering and new lane occupancy on every render can cause unrelated paths to change lanes when geometry or wire count changes. The review did not quantify that churn; add a stability metric before optimizing.
- **Crowded app behavior.** Its manifest names outputs one through six, but its presentation reuses WideApp, which emits gamma. It is an overflow fixture with a mismatched application behavior, not a complete crowded-port functional demonstration.

8. What the implementation got right, and why the tests were insufficient

The division between the semantic kernel and the drawing is sound. A wire does not own propagation, and moving a placement does not redefine a port. The shared planner is reused for hover and drop, modifiers are live, the carry has a single cancellation path, and document mutation waits until a divider drag is committed. The post-commit jack event also addresses a real lifecycle ordering problem. These are useful foundations to preserve.

The review ran the existing route, connect, and identity tests: **3 files, 11 tests passed**. Those tests establish selected semantic and interaction behaviors in the current suite. They do not establish browser geometry under resizing. The three router tests use a clear field, a wall, and two nominal lane runs; they miss the fractional endpoint/short route and immediate-turn cases captured here. The lane test compares different input endpoints, so unequal paths alone are weak evidence that occupancy caused useful separation.

The identity interaction test asserts the presence of a wire group. A group can exist without a meaningful visible path. The original report's fixed-size screenshot sweeps likewise did not expose the live divider invalidation gap. Browser DOM tests, geometry invariants, and source-level router tests must complement one another. None can stand in for the others.

No complete repository build or full ecommerce e2e suite was rerun for this documentation-only review. Ecommerce's wire menu and resizing were exercised directly. Cross-browser behavior, touch input, browser zoom, large graphs, and repeated nested workbench instances remain




Figure 10: At 390px the grid persists, but names, types, and titles are no longer reliably readable. This is a failed reading experience even where geometry aligns.

untested here. The console evidence includes expected story command refusals and favicon 404s; the review does not claim a clean console.

9. Proposed repair design

9.1 Make geometry a coherent, surface-owned input

Introduce a surface-local geometry owner that measures tile frames, port cards, visibility, and endpoint attachment in one coordinate system. Both jack rendering and wire routing consume the same geometry revision. A local live layout change must invalidate geometry even when it does not change the durable document. The geometry service belongs in the React shell, not the headless link kernel.

```
// Proposed API, not current code.
type AnchorVisibility = "visible" | "above" | "below" | "absent";
interface PortAnchor {
  instanceId: string;           // exact mounted visual instance
  placementId: string;
  portId: string;
  side: "in" | "out";
  point: { x: number; y: number };
  visibility: AnchorVisibility;
}
interface WiringGeometry {
  revision: number;
  bounds: Rect;
  obstacles: readonly Rect[];
  anchors: readonly PortAnchor[];
}
```

Do not use a wire's current DOM path to derive semantics or persist this geometry. The document should continue to own only logical relationships and committed layout. Internally, a ref registration should return a disposer for the exact instance. Scope lookup to the surface's registry and keep visibility distinct from DOM attachment.

on mount/unmount, frame resize, live split change, scroll:

- mark surface geometry dirty
- schedule at most one animation-frame measurement

measurement frame:

- read all frames and card rects in a batch
- classify clipping against each port scrollport
- derive anchors in surface coordinates
- publish one geometry snapshot if it changed

render:

- render jacks from that snapshot
- route wires from that same snapshot

A ResizeObserver alone is insufficient because position can change without size. SplitPane should explicitly invalidate during live drag, and the owner should account for ancestor/root movement and scroll. Test geometry while a pointer remains down, not just after commit.




Figure 11: Proposed hierarchy: card columns own scrolling; the jack overlay is a frame sibling; jacks and wires share a geometry revision.

9.2 Move decorative geometry outside scrollable content

Move the jack layer outside tile-body's scrollable contents and anchor it to a stable frame-level positioned element. Let input and output card columns manage their vertical overflow. Keep the application mounted if preserving local React state is required, but exclude its invisible layout from the wiring scroll model by an explicit mode layout. Do not unmount applications casually: the current transform emits from a mounted effect, and local source state also lives in the component.

This change should remove the 7px scrollbar at its cause. It must also keep jacks on the physical frame while either card column scrolls, preserve top/bottom clipping semantics, and avoid clipping hit targets. A narrow view needs a separate layout decision for empty columns and header actions; the scroll ownership fix alone will not make 390px usable.

9.3 Return validated route data rather than just a string

// Proposed API, not an adapter around the old function.

```

type WireRoute =
  | { kind: "routed"; points: readonly Point[];
    labelSegment?: number }
  | { kind: "portal"; at: Point; hiddenPort: string;
    reason: "above" | "below" | "not-mounted" }
  | { kind: "unroutable";
    reason: "no-path" | "budget" | "invalid-geometry" };
  
```

Keep the grid search initially; the evidence does not require replacing Dijkstra. Repair the boundary between grid cells and exact coordinates. Build explicit endpoint connectors with known exit and entry sides, preserve interior corners, and validate the resulting path. Do not mutate an arbitrary first or last corner to fit an endpoint.

```

raw = searchGrid(endpointCorridors, obstacles)
if raw unavailable: return unroutable(reason)

points = connectExactEndpoints(raw, sourceSide, destinationSide)
points = removeDuplicateAndCollinearPoints(points)

assert each segment is horizontal or vertical
assert endpoint positions match anchor positions
assert segments avoid inflated obstacles except permitted stubs
assert exit and entry headings agree with port sides
if any check fails: return unroutable("invalid-geometry")

choose label segment from points
return routed(points, labelSegment)

```

Compute labels and hit targets from that final route. Share immutable obstacle rasterization across wires for a geometry revision where practical. Cache completed route sets on semantic endpoint/visibility facts plus geometry; pointer movement should not rebuild every settled route. Profile before adopting workers or a different routing algorithm.

9.4 Improve the user's connection workflow

Provide a visible toolbar that remains readable in wiring mode. It should state the mode, provide Exit, expose a legend when needed, and display the selected connection in text. Make a port's interactive area unambiguous. If jacks look like sockets, allow them to start the same action as the card or visibly indicate that the card is the handle.

Make refusal messages use planner diagnostics. A Hold preview should prove that a value can be captured before promising a held result. A keyboard path should let a user choose source, destination, and relation without dragging; it can invoke the same existing commands. A connection list can also reveal hidden endpoints and solve the menu-access gap for the generic shell.

Prefer highlighting one relationship and its endpoint labels on hover/focus over adding many permanent colors or thicker lines. The current monochrome visual system can remain, but it needs a clear selection state. Dense shared stubs should offer explicit disambiguation rather than relying solely on paint order.

9.5 Decision records

Decision A — Surface-owned geometry snapshot. Status: proposed. The context is multiple components observing incomplete geometry changes. Options are more ad hoc DOM events, observing every relevant element, or a surface owner with explicit live-layout invalidation. Choose the owner, using observers as inputs. It gives one coordinate and visibility contract; the cost is a new shell service and lifecycle tests.

Decision B — Frame-level jack overlay. Status: proposed. The context is proven output-jack overflow inside an auto-scrolling body. Options are hiding overflow, adding padding, or moving the overlay outside the scrollport. Choose the sibling overlay. It preserves the frame attachment without manufacturing scrollable content; the cost is a Tile/PortRail boundary change and careful clipping/hit-testing validation.

Decision C — Explicit unroutable state. Status: proposed. The context is that silent fallback can contradict obstacle avoidance. Options are retaining the simple fallback, hiding failures, or representing a failed route with explanation. Choose an explicit result and user-visible

continuation/error treatment. The consequence is that callers must handle failure instead of assuming every link yields a normal path.

Decision D — Repair the grid boundary before changing the algorithm. Status: proposed. The observed defect occurs in route reconstruction, and the live-drag failure is invalidation. Replacing Dijkstra would not by itself repair either ownership error. Preserve the search for the first repair phase, add final-geometry invariants, and use measured route cost to decide later optimization.

No backward-compatibility layer or adapter is proposed. Any public API change should be a deliberate cutover with updated callers and tests. The exact supported minimum width and embedded-scrim policy remain product decisions; the review recommends making them explicit rather than accepting accidental CSS behavior.

10. Implementation plan an intern can follow

Phase 1 — Make the evidence reproducible and the lab truthful

Start with `WiringLab.stories.tsx`. Assert each seeding command's ok result, emit before pinning, and create an independent compatible inout identity pair. Correct the Crowded app's emitter names and install the menu behavior the instructions advertise. Add a fixture assertion for the actual term kinds, rendered paths, and visible values. This phase should make later screenshots trustworthy, without changing the route algorithm.

Deliverables: valid semantic fixtures, explicit expected counts, and a small readme explaining which story covers follows, held values, identity, derived styling, overflow, and duplicate placements. Preserve the review's original evidence as a baseline.

Phase 2 — Fix final route geometry

Work in `route.ts` and `route.test.ts`. Add the captured fractional short-route and 768px cross-row cases before editing reconstruction. Use independent segment checks on the returned polyline; do not assert only a particular serialized path. Cover immediate turns, same-cell endpoints, reversed endpoints, very short gutters, obstacles at the surface edge, and no-route/budget results.

Deliverables: exact endpoint adapters, final path validation, and a result shape that makes failures explicit. Update `WireLayer` to consume it. Success means that the specific observed diagonal paths cannot be produced, and blocked routing cannot silently draw through an obstacle.

Phase 3 — Fix geometry lifecycle and scroll ownership

Introduce the geometry owner near shell geometry/context code. Wire `SplitPane` live changes into it. Move jacks to the frame-level sibling layer through `Tile` and `PortRail`; remove dependence on a local y-only state change to trigger global routing. Keep the application state mounted and semantic emissions working.

Deliverables: no 7px horizontal overflow in the lab, zero endpoint drift during a held divider drag, and a visible continuation for clipped theta. Test the first drag frame, several intermediate positions, paused pointer-down, and release. Check both column scroll and outer page scroll.

Phase 4 — Make the interaction understandable

Add the generic connection management surface, explicit controls, route-based labels, hover/focus highlighting, and actionable refusal text. Make Shift-follow-and-pin produce a

result consistent with its preview. Keep the toolbar above the scrim and decide the small-width layout policy. Ensure the ecommerce presentation hooks still supply their domain-specific menus.

Deliverables: a user can discover, create, inspect, cancel, resume, and remove a relationship with both pointer and keyboard; the lab's instructions correspond to available actions. A user should not need to know the names LinkRef, Binding, or PortCarryState to perform these tasks.

Phase 5 — Validate scaling and route stability

After correctness, measure settled-route work during pointer movement and repeated resizing. Reuse obstacle rasters and cache route sets by geometry revision. Add a dense fixture and record frame-time/long-task measurements before deciding on asynchronous routing. Track whether unrelated wires change lanes when a connection is added or a tile changes size.

Deliverables: an explicit supported density and latency target, representative browser evidence, and documented remaining limitations. Do not label an optimization successful solely because a screenshot looks unchanged.

11. Acceptance tests and local reproduction

11.1 Invariants that should define completion

Area	Meaningful acceptance condition
Endpoint geometry	Visible endpoints stay within 1 CSS pixel of their declared jack attachment, including while dragging.
Orthogonality	Every final segment has constant x or constant y within a stated numeric tolerance.
Obstacle avoidance	No final segment crosses a tile interior except explicitly permitted endpoint stubs.
Scrolling	Frame jacks do not create horizontal body overflow; scrolling a column reveals useful cards without moving the frame attachment.
Visibility	A clipped/missing endpoint has a visible, labeled continuation rather than a full route to hidden coordinates.
Semantics	Successful gestures produce expected values and term kinds; refused operations preserve prior state and explain why.
Labels	A derived label belongs to its final route and avoids unrelated tile/card content.
Identity	A valid inout identity creates a shared cell and a visible connection; duplicated/multi-shell anchors remain scoped.
Keyboard	Source, destination, cancel, inspect, and unlink are operable without a drag.
Responsive UX	At every supported width, names and action targets are readable, or an explicit alternate navigation mode is offered.

The 1px endpoint criterion is a proposed acceptance tolerance, not a claim that this browser pass sampled every frame. Performance limits also need a product target; inventing an unsupported frame budget here would not improve the design.

11.2 Commands and artifacts

Run the targeted existing tests from packages/pbui-workbench:

```
pnpm exec vitest run \
  src/components/WireLayer/route.test.ts \
  src/links/connect.test.tsx \
  src/links/identity.test.tsx
```

The result during this review was 3 files and 11 tests passed. The standalone source replay uses Node 24's TypeScript stripping to call the actual source router, reads captured rectangles, and uses built core packages to reproduce the empty/bound seed refusals:

```
# From this ticket directory:
node scripts/02-replay-route-and-seed.mjs
```

The browser replay uses the workspace's installed Playwright and an already running Storybook at port 6008. It saves the resize, divider, hold, crowded, and scrollbar experiments in a new output directory:

```
# From this ticket directory, with :6008 already running:
node scripts/03-replay-browser.mjs /tmp/pbui-wiring-review-replay
```

The review's actual captures used the Playwright MCP browser. The generated native replay script passed node --check; it was not independently run end to end. The source replay was executed successfully. If starting a new Storybook is necessary, run pnpm --filter @hyperslop-systems/pbui-workbench storybook in tmux under the repository's process guidelines; this review reused existing servers and did not start or stop them.

The probe source can also be passed as a browser evaluation function. Its measurements are diagnostic, not a full property-test implementation. The screenshots are the unmodified browser captures; the three architecture/lifecycle diagrams were generated separately from the adjacent .dot sources.

12. Source and API reading map

Paths below are relative to the PBUI repository. Line numbers refer to the inspected commit and should be refreshed after implementation changes. The reference links resolve to local repository files from this ticket.

- **R01.** src/chrome/usePortCarry.ts, 20, 39, 50, 115 — Carry state/options, multi-element registry, pointer lifecycle and cleanup.
- **R02.** PortRail.tsx, 9, 23, 32, 115, 146 — PortRailProps, planner-driven card interactions, measurement, commit event.
- **R03.** WireLayer.tsx, 9, 51, 60, 68, 88, 134, 159 — renderWire, coordinates, labels, endpoint pairing, invalidation, drawing.
- **R04.** WireLayer/route.ts, 12, 24, 37, 55, 182 — Point, Rect, RouteOptions, Lanes, search and reconstruction.
- **R05.** PortRail.module.css, 4, 18, 108 — Rail grid/scrolling and the jack overlay/negative offsets.

- **R06.** WiringLab.stories.tsx, 18, 117, 163, 176, 196 — App examples, contracts, crowded fixture, initial seeding and UI.
- **R07.** Surface.tsx, 23 — Root registration, recursive layout, shortcut, conditional wire layer.
- **R08.** SplitPane.tsx, 23, 56, 98, 113 — Live ratio versus document commit, geometry bounds, keyboard resizing.
- **R09.** createWorkbenchShell.tsx, 54, 78 — Shell construction, execute, dispatch, bound components.
- **R10.** workbench-core/createWorkbenchCore.ts, 44, 88 — Core options, execute result, state installation/publication.
- **R11.** workbench-core/links/collaborator.ts, 28, 94 — Snapshot cache, planning, lifecycle maintenance, staged effects.
- **R12.** presentation/links/types.ts, 38, 73, 135, 159 — Runtime contract fields, port declaration, ID, normalization.
- **R13.** presentation/links/terms.ts, 19, 29, 38 — Serializable references and public binding terms.
- **R14.** presentation/links/expression.ts, 5, 23, 84 — Internal binding source/expression/program representation.
- **R15.** presentation/links/evaluate.ts, 26, 45, 72, 114 — Effective binding, evaluation result and program evaluator.
- **R16.** pbui-ecommerce/ShopShell.tsx, 62, 67 — Product installation of port/wire presentation behavior.
- **R17.** pbui-workbench/links/hooks.ts, 17, 43, 65 — useLinkSnapshot, usePort, useEmitPort, badges.
- **R18.** workbench-core/links/runtime.ts, 18, 36, 98 — Runtime state, emitted/attended/context/class cells and publication.
- **R19.** presentation/links/plan.ts, 39, 83, 153 — planFollow, planPin, planIdentityAdd, refusal reasons.
- **R20.** public/chrome.css, 54, 81, 111 — Header label/badge chrome and auto-scrolling tile body.
- **R21.** Surface.module.css, 4, 25 — Coordinate containing block, fixed scrim, gutter expansion.
- **R22.** Tile.tsx, 65, 117 — Presentation slots, mounted inert app, conditional rail.
- **R23.** WireLayer.module.css, 5, 28, 35 — Overlay, hit width, styles, pointer routing.
- **R24.** WireLayer/route.test.ts, 6 — Existing three geometric tests and their coverage limits.
- **R25.** links/identity.test.tsx, 80 — Ctrl-drag fixture using valid inout ports; group-presence assertion.
- **R26.** VisualAudit.stories.tsx, 335 — Directly injected held/derived drawing fixture.
- **R27.** presentation/links/snapshot.ts, 14, 54, 99 — Port definitions, snapshot, relation definitions, dependencies.
- **R28.** LinkAnnouncer.tsx, 16 — Live-region notifications; useful feedback, not an input alternative.

The key current API calls are `defineWorkbenchApp({manifest, presentation})`, `createWorkbench({apps, initial})`, `wb.execute(command)`, `wb.dispatch(shellAction)`, `usePort(view, name)`, `useEmitPort(view, name)`, and `<wb.Surface renderPort={...} ren-`

derWire={...} />. These are local TypeScript APIs, not HTTP endpoints. No backend endpoint is required for the story interactions reviewed here. The source map above is the authoritative API reference for this analysis; proposed interfaces in section 9 are intentionally labeled as proposals.

13. Screenshot and evidence catalog

All image links below are adjacent to this review under review-assets/. Key exhibits are embedded above; the complete list preserves the rest of the browser evidence without forcing every nearly identical resize image into the main reading path.

Screenshot	What it establishes
01 initial lab	First wide inspection before the measured sweep.
01 resize 1440×1000	Measured wide baseline.
02 resize 1280×800	Intermediate desktop size.
03 resize 1024×768	Smaller desktop size.
04 resize 768×900	Large diagonal through Transform.
05 resize 390×844	Compressed unreadable columns and page overflow.
06 return to wide	Recovery of original size-dependent route.
07 live divider drag	Stale wire coordinates while pointer is held.
08 divider released	Endpoint alignment recovers after commit.
09 live values	Actual propagation with wiring closed.
10 Follow preview	Named source/destination before release.
11 Hold preview	Modifier change while carrying.
12 held connection	Held link after actual source emissions.
13 Crowded before scroll	Hidden theta still has an offscreen endpoint.
14 Crowded after scroll	Jack and wire follow the card after vertical scrolling.
15 Crowded resized/scroll	Same diagonal failure after combined scroll and resize.
16 wire-style label	Detached derived label in an unrelated tile.
17 shop wide	Product integration at desktop size.
18 shop narrow	Product integration at 768px.
19 shop wire menu	Correct relationship menu and unlink variants.
20 horizontal scroll	7px rail movement caused by decorative jack overflow.
21 incompatible target	Refusal feedback and cancellation exercise.

Raw records: resize, divider/connection interactions, Crowded, style label, ecommerce, scrollbar interventions, usability probes, source replay, and browser console.

Prior context: original design, phase report, and implementation diary. The additional vault source read was ~/code/wesen/go-go-golems/go-go-parc/Projects/2026/09/04/PROJECT REPORT - PBUI Visual Consolidation and Link-Mode Wiring - One Chip, One Shell, and Wires That Route Around Tiles.md. It was used as historical context and not overwritten.