## **USA Computing Olympiad**

**OVERVIEW** 


TRAINING

CONTESTS

HISTORY

STAFF

RESOURCES



## USACO 2014 DECEMBER CONTEST, BRONZE PROBLEM 3. COW JOG

Return to Problem List

Contest has ended.

Problem 3: Cow Jog [Mark Gordon, 2014]  The cows are out exercising their hooves again! There are N cows jogging on an infinitely-long single-lane track (1 <= N <= 100,000). Each cow starts at a distinct position on the track, and some cows jog at different speeds.  With only one lane in the track, cows cannot pass each other. When a faster cow catches up to another cow, she has to slow down to avoid running into the other cow, becoming part of the same running group.  Eventually, no more cows will run into each other. Farmer John wonders how many groups will be left when this happens. Please help him compute this number.  INPUT: (file cowjog.in)  The following N lines each contain the intiger N.  The following N lines each contain the initial position and speed of a single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input:  SAMPLE INPUT:  5  0 1  1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	Analysis mode			
Problem 3: Cow Jog [Mark Gordon, 2014]  The cows are out exercising their hooves again! There are N cows jogging on an infinitely-long single-lane track (1 <= N <= 100,000). Each cow starts at a distinct position on the track, and some cows jog at different speeds.  With only one lane in the track, cows cannot pass each other. When a faster cow catches up to another cow, she has to slow down to avoid running into the other cow, becoming part of the same running group.  Eventually, no more cows will run into each other. Farmer John wonders how many groups will be left when this happens. Please help him compute this number.  INPUT: (file cowjog.in)  The first line of input contains the integer N.  The following N lines each contain the initial position and speed of a single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input.  SAMPLE INPUT:  5  0 1  12 23 32 61  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:		English (en)	▼ .	
jogging on an infinitely-long single-lane track (1 <= N <= 100,000). Each cow starts at a distinct position on the track, and some cows jog at different speeds.  With only one lane in the track, cows cannot pass each other. When a faster cow catches up to another cow, she has to slow down to avoid running into the other cow, becoming part of the same running group.  Eventually, no more cows will run into each other. Farmer John wonders how many groups will be left when this happens. Please help him compute this number.  INPUT: (file cowjog.in)  The first line of input contains the integer N.  The following N lines each contain the initial position and speed of a single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input.  SAMPLE INPUT:  5 0 1 1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	Problem 3: Cow Jog [Mark Gordon, 2014]	<u> </u>		
faster cow catches up to another cow, she has to slow down to avoid running into the other cow, becoming part of the same running group.  Eventually, no more cows will run into each other. Farmer John wonders how many groups will be left when this happens. Please help him compute this number.  INPUT: (file cowjog.in)  The first line of input contains the integer N.  The following N lines each contain the initial position and speed of a single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input.  SAMPLE INPUT:  5  0 1  1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	jogging on an infinitely-long single-lane track (1 <= N <= 100,000). Each cow starts at a distinct position on the track, and some cows jog			
wonders how many groups will be left when this happens. Please help him compute this number.  INPUT: (file cowjog.in)  The first line of input contains the integer N.  The following N lines each contain the initial position and speed of a single cow. Position is a nonnegative integer and speed is a positive integer both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input.  SAMPLE INPUT:  5 0 1 1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	faster cow catches up to another cow, she has to slow down to avoid			
The first line of input contains the integer N.  The following N lines each contain the initial position and speed of a single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input.  SAMPLE INPUT:  5  0 1 1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	wonders how many groups will be left when this happens. Please help			
The following N lines each contain the initial position and speed of a single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input.  SAMPLE INPUT:  5 0 1 1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	<pre>INPUT: (file cowjog.in)</pre>			
single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in the input.  SAMPLE INPUT:  5 0 1 1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	The first line of input contains the integer N.			
5 0 1 1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	single cow. Position is a nonnegative integer and speed is a positive integer; both numbers are at most 1 billion. All cows start at distinct positions, and these will be given in increasing order in			
0 1 1 2 2 3 3 2 6 1  OUTPUT: (file cowjog.out)  A single integer indicating how many groups remain.  SAMPLE OUTPUT:	SAMPLE INPUT:			
A single integer indicating how many groups remain.  SAMPLE OUTPUT:	0 1 1 2 2 3 3 2			
SAMPLE OUTPUT:	OUTPUT: (file cowjog.out)			
	A single integer indicating how many groups remain.			
2	SAMPLE OUTPUT:			
	2			

Submit Solution

Language:

Source File:

С

▼

Choose File No file chosen

Note: Many issues (e.g., uninitialized variables, out-of-bounds memory access) can cause a program to product different output when run multiple times; if your program behaves in a manner inconsistent with the official contest results, you should probably look for one of these issues. Timing can also differ slightly from run to run, so it is possible for a program timing out in the official results to occasionally run just under the time limit in analysis mode, and vice versa. Note also that we have recently changed grading servers, and since our new servers run at different speeds from the servers used during older contests, timing results for older contest problems may be slightly off until we manage to re-calibrate everything properly.