

# CSC343 Worksheet 6 Solution

June 21, 2020

## 1. Exercise 6.6.1:

```
a) SET TRANSACTION READONLY;  
2 BEGIN TRANSACTION;  
3     SELECT model, price FROM PC  
4     WHERE speed = speed AND  
5         ram=ram  
6 COMMIT;  
7
```

### Notes:

- Transactions
  - is a collection of one or more operations that must be executed atomically
  - COMMIT causes the transaction to end successfully
  - ROLLBACK causes the transaction to abort. Any changes are undone
  - SET TRANSACTION READ ONLY
    - \* tells the database that it will not be modified
    - \* Must be declared before transaction
    - \* Is useful when one user is running multiple queries while other is updating the same table

### Example:

```
1 BEGIN TRANSACTION;  
2  
3 UPDATE accounts  
4 SET balance = balance - 1000  
5 WHERE account_no = 100;  
6  
7 UPDATE accounts  
8 SET balance = balance + 1000  
9 WHERE account_no = 200;  
10  
11 INSERT INTO account_changes(account_no,flag,amount,  
    changed_at)
```

```

12     VALUES (100, '-', 1000, datetime('now'));
13
14     COMMIT;
15
16     // Example - SET TRANSACTION READONLY
17     SET TRANSACTION READONLY;
18     BEGIN TRANSACTION;
19     ...
20     COMMIT;
21

```

## 2. Exercise 8.1.1:

```

a) CREATE VIEW RichExec AS
2     SELECT * FROM MovieExec
3     WHERE netWorth >= 100000000;
4

```

### Notes:

- Virtual Views
  - **Syntax:** CREATE VIEW < view-name > AS < view-definition >
  - Contrasts to database that exists in physical storage
  - Exists in RAM
  - Is created using query
  - can be used like a relation

### Notes:

```

1     CREATE VIEW ParamountMovies AS
2     SELECT title, year
3     FROM Movies
4     WHERE studioName = 'Paramount';
5

```

```

b) CREATE VIEW StudioPres AS
2     SELECT * FROM Movies
3     INNER JOIN Studio ON cert# = presC#;
4

```

```

c) CREATE VIEW ExecutiveStar AS
2     SELECT * FROM MovieExec
3     NATURAL JOIN MovieStar;
4

```

## 3. Exercise 8.1.2:

a) `SELECT name, gender FROM ExecutiveStar;`

2

b) `SELECT name FROM RichExec WHERE netWorth > 100000000;`

2

c) `SELECT name FROM StudioPres  
NATURAL JOIN ExecutiveStar  
WHERE netWorth > 50000000`

2

3

4

#### 4. Exercise 8.2.1:

*RichExec* is updatable.

##### Notes:

- Updatable View Conditions
  - The WHERE clause in CREATE VIEW must not be a subquery
  - The FROM clause has only one occurrence of R
  - The SELECT clause must include enough attributes
  - NOT NULL attributes must have default values
    - \* A solution to this is by including the attribute without default value in CREATE VIEW

##### Example:

```

1  Movies(title, year, length, genre, studioName, producerC#)
2  Suppose studioName is NOT NULL but has no default value.
   Then, a fix is:
3
4  CREATE VIEW Paramount AS
5      SELECT studioName, title, year
6      FROM Movies
7      WHERE studioName = 'Paramount';
8

```

#### 5. Exercise 8.2.2:

a) No. It is not updatable. Since,

1. studioName attribute in Movies is NOT NULL without default value

```

b) CREATE TRIGGER DisneyComediesInsert
2  INSTEAD OF INSERT ON DisneyComedies
3  REFERENCING
4      NEW ROW AS NewTuple
5  FOR EACH ROW
6  INSERT INTO Movies(title, year, length, genre, studioName)
7  VALUES(NewTuple.title, NewTuple.year, NewTuple.length, 'comedy',
8  'Disney');

```

### Notes:

- Using Trigger in VIEW
  - Uses INSTEAD OF in place of BEFORE or AFTER
  - When event causes the trigger, the trigger is done instead of the event

### Example:

```

1  CREATE VIEW ParamountMovies AS
2      SELECT title, year
3      FROM Movies
4      WHERE studioName = 'paramount';
5
6  CREATE TRIGGER ParamountInsert
7  INSTEAD OF INSERT ON ParamountMovies
8  REFERENCING NEW ROW AS NewRow
9  FOR EACH ROW
10     INSERT INTO Movies(title, year, studioName)
11     VALUES(NewRow.title, NewRow.year, 'Paramount');
12

```

```

c) CREATE TRIGGER DisneyComediesInsert
2  INSTEAD OF INSERT ON DisneyComedies
3  REFERENCING
4      NEW ROW AS NewTuple
5      OLD ROW AS OldTuple
6  FOR EACH ROW
7  UPDATE Movies
8  SET length=NewTuple.length
9  WHERE title=OldTuple.title AND year=OldTuple.year;
10

```

## 6. Exercise 8.2.3

- a) No. the view is not updatable. Because for it to be updatable, only one relation must exist in FROM

```

b) CREATE TRIGGER NewPCInsert
2  INSTEAD OF INSERT ON NewPC
3  REFERENCING

```

```
4      NEW ROW AS NewTuple
5      OLD ROW AS OldTuple
6  FOR EACH ROW
7      INSERT INTO PC(model speed, ram, hd ,price)
8      VALUES (NewTuple.model, NewTuple.speed, NewTuple.ram, NewTuple.hd
9      , NewTuple.price);
10
11     INSERT INTO Product(maker, model, type)
12     VALUES (NewTuple.maker, NewTuple.model, 'pc');
```

c)

```
1  CREATE TRIGGER NewPCUpdate
2  INSTEAD OF INSERT ON NewPC
3  REFERENCING
4      NEW ROW AS NewTuple
5  FOR EACH ROW
6  UPDATE PC
7  SET model=NewTuple.model
8      speed=NewTuple.speed,
9      ram=NewTuple.ram,
10     hd=NewTuple.hd,
11     price=NewTuple.price;
12
13  UPDATE Product
14  SET maker=NewTuple.maker,
15      model=NewTuple.model,
16      type='pc';
17
```

### Correct Solution:

```
1  CREATE TRIGGER NewPCUpdate
2  INSTEAD OF UPDATE ON NewPC
3  REFERENCING
4      NEW ROW AS NewTuple
5  FOR EACH ROW
6  UPDATE PC
7  SET model=NewTuple.model
8      speed=NewTuple.speed,
9      ram=NewTuple.ram,
10     hd=NewTuple.hd,
11     price=NewTuple.price;
12
13  UPDATE Product
14  SET maker=NewTuple.maker,
15      model=NewTuple.model,
16      type='pc';
17
```

d)

```
1  CREATE TRIGGER NewPCDelete
2  INSTEAD OF DELETE ON NewPC
```

```

3  REFERENCEING
4      NEW ROW AS NewTuple
5  FOR EACH ROW
6  DELETE FROM PC
7  WHERE model=NewTuple.model;
8
9  DELETE FROM Product
10 WHERE model=NewTuple.model;
11

```

7. a) 

```
CREATE INDEX studioNameIndex Studio(name)
```

### Notes:

- Indexes
  - **Syntax (Create Index):**  
CREATE INDEX < index-name > R(< attributes >)
  - **Syntax (Drop Index):**  
DROP INDEX < index-name >
  - Used to find tuples in a very large database
    - \* Is efficient
  - Can be thought as (key, value) pair in a binary search tree
  - e.g. Declaring Index

```

1  CREATE INDEX KeyIndex ON Movies(title, year);
2

```

- e.g. Dropping index

```

1  CREATE INDEX KeyIndex ON Movies(title, year);
2

```

b) 

```
CREATE INDEX movieExecAddressIndex MovieExec(address)
```

c) 

```
CREATE INDEX movieKeyIndex Movies(genre, length)
```

### 8. Exercise 8.4.1:

Action	No Index	Star Index	Movie Index	Both Indexes
$Q_1$	100	4	100	4
$Q_2$	100	100	4	4
$I$	2	4	4	6
Average	$2 + 100p_1 + 100p_2$	$4 + 96p_2$	$4 + 96p_1$	$6 - 2p_1 - 2p_2$

### Notes:

- Database Tuning
  - Index speeds up queries that can use it
  - Index should NOT be created when modifications are the frequent choice of action

9. **Exercise 8.4.2:**

Omitted for the time being

10. **Exercise 8.5.1:**

```
1  UPDATE MovieProd
2  SET name='New Name'
3  WHERE (title, year) IN
4  (
5      SELECT title, year FROM Movies
6      INNER JOIN MovieExecs
7      ON Movies.productC# = MovieExec.cert#
8      WHERE cert# = '4567'
9  );
10
```

Notes:

- Materialized Views
  - Is also known as a summary
  - Is also known as black-box abstraction
  - Stores view in physical storage
  - Useful when storing expensive operation like AVG or COUNT