### Worksheet 16 Solution

### March 29, 2020

### Question 1

a. Part 1.a - Finding minimum possible change for a loop in a single iteration

The minimum possible change in a loop occurs when i increments by 1.

Part 1.b - Finding maximum possible change for a loop in a single iteration

The maximum possible change in a loop occurs when i increments by 6.

Part 2.a - Determine formula for an exact lower bound on the value

Since the loop starts at i = 0 and ends at n - 1, the loop has

$$n - 1 + 1 = n \tag{1}$$

iterations.

Since the smallest step increases by 1 per iteration, the total cost of the loop at minimum possible change is

$$(n) \cdot 1 = n \tag{2}$$

steps.  $\,$ 

## Part 2.a - Determine formula for an exact upper bound on the value

Since the loop starts at i = 0 and ends at n - 1, the loop has

$$n - 1 + 1 = n \tag{3}$$

iterations.

## Part 2.b - Determine formula for an exact lower bound on the value

Since the largest step increases by 6 per iteration, the total cost of the loop at minimum possible change is

$$\left\lceil \frac{n}{6} \right\rceil \tag{4}$$

steps.

Part 3.a - Determine formula for an exact upper bound on the value Is it n?

Part 3.a - Determine formula for an exact upper bound on the value Is it  $\lceil \frac{n}{6} \rceil$ ?

#### Part 4 - Determine Big Oh and Big Omega

The big Oh bound of running time is  $\mathcal{O}(n)$ , and the big theta of running time is  $\Omega(n)$ .

Since n in  $\mathcal{O}(n)$  and  $\Omega(n)$  are the same,  $\Theta(n)$  is also true.

#### Correct Solution:

# Part 1.a - Finding minimum possible change for a loop in a single iteration

The minimum possible change in a loop occurs when i increments by 1.

Part 1.b - Finding maximum possible change for a loop in a

#### single iteration

The maximum possible change in a loop occurs when i increments by 6.

Part 2.a - Determine formula for an exact upper bound on the value

The upper bound of loop termination is when  $k \geq n$ 

Part 2.b - Determine formula for an exact lower bound on the value

The lower bound of loop termination is when  $6k \leq n$ 

Part 3.a - Use the formula to determine the exact number of loops that will occur for upper bound

Since the loop starts from 0 and ends at n-1, the loop has total of

$$n - 1 - 0 + 1 = n \tag{5}$$

iterations.

Since 1 step is taken for each iteration, the upper bound total cost of loop iteration is

$$n \cdot 1 = n \tag{6}$$

Since the statement on line 2 has cost of 1, the upper bound total cost of the algorithm is n + 1, or  $\mathcal{O}(n)$ .

Part 3.b - Use the formula to determine the exact number of loops that will occur for lower bound

Since the loop starts from 0 and ends at n-1, the loop has total of

$$n - 1 - 0 + 1 = n \tag{7}$$

iterations.

Since 6 steps are taken for each iteration, the lower bound total cost of loop iteration is

$$\left\lceil \frac{n}{6} \right\rceil \tag{8}$$

Since the statement on line 2 has cost of 1, the lower bound total cost of the algorithm is  $\lceil \frac{n}{6} \rceil + 1$ , or  $\Omega(n)$ 

#### Part 4 - Determine Big Oh and Big Omega

The big Oh bound of running time is  $\mathcal{O}(n)$ , and the big theta of running time is  $\Omega(n)$ .

Since n in  $\mathcal{O}(n)$  and  $\Omega(n)$  are the same,  $\Theta(n)$  is also true.

# b. Part 1.a - Finding minimum possible change for a loop in a single iteration

The minimum possible change for a look in a single iteration is when i increases by a factor of 2

# Part 1.b - Finding maximum possible change for a loop in a single iteration

The maximum possible change for a look in a single iteration is when i increases by a factor of 3

## Part 2.a - Determine formula for an exact upper bound of the loop variable after k iterations

The exact upper bound of the loop variable after k iteration is  $2^k \ge n$ 

Part 2.b - Determine formula for an exact lower bound of the loop variable after k iterations

The exact lower bound of the loop variable after k iteration is  $3^k \geq n$ 

Part 3.a - Use the formula to determine the exact number of loops that will occur for upper bound

The upper bound of loop iteration is  $\lceil \log n \rceil$ , or  $\mathcal{O}(\log n)$ 

Part 3.b - Use the formula to determine the exact number of loops that will occur for lower bound

The lower bound of loop iteration is  $\lceil \log_3 n \rceil$ , or  $\Omega(\log n)$ 

#### Part 4 - Determine Big Oh and Big Omega

For the upper bound, we have  $\mathcal{O}(\log n)$ .

For the lower bound, we have  $\Omega(\log n)$ 

Since Big Oh and Big Omega have the same value,  $\Theta(\log n)$  is also true.

### Question 2

a. Since **helper1** has cost of n steps, and **helper2** has cost of  $n^2$  steps, the algorithm has total run time of  $n^2 + n$  steps, or  $\Theta(n^2)$ 

### Question 3