
# CSC369 Week 9 Notes

Hyungmo Gu

May 29, 2020


# 1 Disk I/O

- File system implementation
  - Files and directories live on **secondary storage** 
    - \* Anything outisde of "Primary memory"
    - \* Is persistent (or non-volatile): Data survives loss of power
- Disk components



#### – Actuator:


\* is an electronic device controlled by a motor that moves the hard drive head arm. <sup>[1]</sup>



## - Read/Write Heads:


\* are the small parts of a hard drive which move above the disk platter and transform the platter's magnetic field into electric current [1]

# Hard drive read/write head



## - Platter:

- \* One or more aluminum, glass, or ceramic disk that is coated in a magnetic media  $^{[1]}$
- $\ast\,$  All modern drives use glass or glass-ceramic platters  $^{[2]}$



# - Cylinder:

\* is any set of all tracks of equal diameter in a hard disk drive (HDD) [3]



computerhope.com

### - Track:

\* is a data storage ring on a computer hard drive that is capable of storing information.




### - Sector:

- \* A division of storage medium on a hard drive that is a wedge shaped section of one of the circular tracks.
- \* Each arc is sector that usually holds 512 byte of data.



### References:

- 1) Computer Hope: Actuator, link
- 2) Etty94. (2016, August 1). Hard disk drive components. Medium. link
- 3) The Linux Information Project: Cylinder Definition, link
- OS  $\leftrightarrow$  disk interaction
  - The old way
    - \* Is called **Extended CHS** (Extended Cylinder, Head, Sector)
    - \* Specifying disk requests requires a lot of info
      - · Cylinder #, Surface #, Track #, Sector #, transfer size · · ·
    - \* Modern disks are even more complicated
      - · Not all tracks have the same number of sectors
      - · Sectors are remapped
    - \* Older disks require OS to specify all of this
      - · The OS needs to know all disk parameters
  - Now
    - \* Logical Block Addressing
- Logical Block Addressing
  - Is a common scheme used for specifying the location of blocks of data on computer storage device [1]
  - Is implemented in most hard disk drives after 1996 [1]
  - Hides disk parameters from the OS
  - Exposes storage as linear array of blocks
    - \* Maps blocks to cylinder/surface/track/sector
    - \* Each block size is 512 bytes



## Refernces:

- 1) Wikipedia: Logical Block Addressing, link
- Disk Scheduling
  - Is also known as I/O scheduling [1]
  - Is done by operating systems <sup>[1]</sup>
  - Is important because <sup>[1]</sup>
    - \* Hard drives are one of the slowest parts of the computer system and thus need to be accessed in an efficient manner

## Refernces:

- 1) Geeks for Geeks: Disk Scheduling Algorithms, link
- File System Implementation
- Original Unix File System
- FFS
- Cylinder Groups
- Log Structured File System (LSF)
- NFTS (Windows)
- MFT Record