

# CSC 209 Review 9 Solution

August 31, 2020

1. a) 0

## Notes

- a) is 0 because  $(i \gg 1 + j \gg 1 = i \gg 10 \gg 1 = 0)$
- **Bitwise Shift Operators**
  - has lower precedence than arithmetic operators

## Example:

$i \ll 2 + 1$  means  $i \ll (2+1)$  and not  $(i \ll 2) + 1$

- $\ll$  : Left Shift
- $\gg$  : Right Shift
- *Tip*: Always shift only on unsigned numbers for portability

## Example

```
unsigned short i, j;

i = 13;          /* i is now 13 (binary 0000000000001101) */
j = i << 2;       /* j is now 52 (binary 0000000000110100) */
j = i >> 2;       /* j is now 3  (binary 0000000000000011) */
```

As these examples show, neither operator modifies its operands. To modify a variable by shifting its bits, we'd use the compound assignment operators  $\ll=$  and  $\gg=$ :

```
i = 13;          /* i is now 13 (binary 0000000000001101) */
i <<= 2;         /* i is now 52 (binary 0000000000110100) */
i >>= 2;         /* i is now 3  (binary 0000000000001101) */
```

Shifts to left

Shifts to right

- $\gg=$  /  $\ll=$  : Are bitwise shift equivalent of  $+=$

b) 0

## Notes

- `i` is 1111111111111111
- `i` is 0000000000000000
- so `i & i = 0`
- `~`: Bitwise complement (NOT)

| a | $\sim a$ |
|---|----------|
| 0 | 1        |
| 1 | 0        |

**Example:**

```

1      0   1   1   1   //<- this is 7
2      -----
3      1   0   0   0   //<- this is 8
4
5      so, ~ 7 = 8

```

- `&`: Bitwise *and*

| a | b | a & b |
|---|---|-------|
| 0 | 0 | 0     |
| 0 | 1 | 0     |
| 1 | 0 | 0     |
| 1 | 1 | 1     |

**Example:**

```

1      0   1   1   1   //<- this is 7
2      0   1   0   0   //<- this is 4
3      -----
4      0   1   0   0   //<- this is 4
5
6      so, 7 & 4 = 4

```

- `^`: Bitwise *exclusive or*
- `|`: Bitwise *inclusive or*

c) 1

**Notes**

- `i` is 1111111111111110
- `j` is 0000000000000000
- `i & j` is 0000000000000000 or 1
- `i & j ^ k` is 1

- $\wedge$ : Bitwise XOR

| a | b | $a \wedge b$ |
|---|---|--------------|
| 0 | 0 | 0            |
| 0 | 1 | 1            |
| 1 | 0 | 1            |
| 1 | 1 | 0            |

### Example:

```

1      0   1   1   1   //<- this is 7
2      0   1   0   0   //<- this is 4
3      -----
4      0   0   1   1   //<- this is 3
5
6      so, 7 ^ 4 = 3
7

```

d) 0

### Example

- i is 0000000000000111
- j is 0000000000001000
- $i \wedge j$  is 0000000000000000 or 0
- k is 0000000000001001
- $i \wedge j \& k$  is 0000000000000000 or 0

### Correct Solution

15

### Notes

- There is a precedence to the order of operations

|          |          |
|----------|----------|
| Highest: | $\sim$   |
|          | $\&$     |
|          | $\wedge$ |
| Lowest:  | $ $      |

- e) • toggling from 0 to 1

```
i = 0x0000;
i |= 0x0001;
```

or

```
i |= 1 << 0; where i = 0x0000;
```

- toggling from 1 to 0

```
i = 0x0001;
i &= ~0x0001;
```

or

```
i &= ~(1 << 0); where i = 0x0001;
```

### Correct Solution

- toggling from 0 to 1 of 4th bit

```
i = 0x0010;
i ^= 0x0000;
```

or

```
i ^= 1 << 4; where i = 0x0000;
```

- toggling from 1 to 0 of 4th bit

```
i = 0x0010;
i ^= 0x0010;
```

or

```
i ^= (1 << 4); where i = 0x0010;
```

### Notes

- Toggling can be done using bitwise XOR
- **Setting a bit**
  - Is done using `|` or bitwise OR

```
i = 0x0000;          /* i is now 0000000000000000 */
i |= 0x0010;          /* i is now 0000000000010000 */
```

- The idiom of above is `i |= 1 << j`

- **Clearing a bit**

- Is done using `|` or bitwise AND

```
i = 0x00ff;          /* i is now 0000000011111111 */
i &= ~0x0010;        /* i is now 0000000011101111 */
```

- The idiom of above is `i &= ~(i << j)`

2. It swaps the elements between `x` and `y`.

### Notes

- Preprocessor performs operations of statements in order from left to right

```
#define M(x,y) ((x)^(y), (y)^(x), (x)^(y))
```

New value of x → New value of y → New value of x

3. `#define MK_COLOR(r,g,b) (long) ((b | (g << 8)) | (b | (r << 16)))`

### Rough Work

1. store `b` in bit 0

`b`

2. store `g` in bit 8

`b | g << 8`

3. store `r` in bit 16

`b | r << 16`

### Correct Solution

```
#define MK_COLOR(r,g,b) (long) ((r | (g << 8)) | (r | (b << 16)))
```

### Notes

-