

CSC343 Worksheet 8 Solution

June 24, 2020

1. a) Notes:

- Using Call-Level Interface
 - Uses host language to connect to and access a database
 - Replaces embedded SQL
- Standard SQL/CLI
 - Is database CLI for C
 - Included in file *sqlcli.h*
 - Creates deals with four kinds of records

1. Environment handle

- * Prepares one or more connections to database server
- * Is required
- * Is allocated using **SQLHENV**
- * Is established via function **SQLAllocHandle**

```
1) #include sqlcli.h
2) SQLHENV myEnv;
3) SQLHDBC myCon; ← Is declared here :)
4) SQLHSTMT execStat;
5) SQLRETURN errorCode1, errorCode2, errorCode3;

6) errorCode1 = SQLAllocHandle(SQL_HANDLE_ENV, ← Connection is prepared here :)
   SQL_NULL_HANDLE, &myEnv); (Hey DB, can I connect with you?)
7) if(!errorCode1) {
8)     errorCode2 = SQLAllocHandle(SQL_HANDLE_DBC,
   myEnv, &myCon);
9) if(!errorCode2)
10)    errorCode3 = SQLAllocHandle(SQL_HANDLE_STMT,
   myCon, &execStat); }
```

2. Connection handle

- * Conenects application program to database
- * Is required
- * Is declared after **SQLHENV**

- * Is allocated using **SQLHDBC**
- * Is established via function **SQLAllocHandle**

```

1) #include sqlcli.h
2) SQLHENV myEnv;
3) SQLHDBC myCon; ← Is declared here :)
4) SQLHSTMT execStat;
5) SQLRETURN errorCode1, errorCode2, errorCode3;

6) errorCode1 = SQLAllocHandle(SQL_HANDLE_ENV,
    SQL_NULL_HANDLE, &myEnv);
7) if(!errorCode1) {
8)     errorCode2 = SQLAllocHandle(SQL_HANDLE_DBC,
        myEnv, &myCon); ← Connection established here :)
9)     if(!errorCode2)
10)        errorCode3 = SQLAllocHandle(SQL_HANDLE_STMT,
            myCon, &execStat); }

```

Sure you can

(Yay!!! Thank you database)

3. Statements

- * Created by application program (the user)
- * Can be created as many as needed
- * Holds information about a single SQL statement, including cursor
- * Can represent different SQL statements at different times
- * Is required
- * Is declared after **SQLHDBC**
- * Is allocated using **SQLHSTMT**
- * Is sent using the function **SQLAllocHandle**

```

1) #include sqlcli.h
2) void worthRanges() {

3)     int i, digits, counts[15];
4)     SQLHENV myEnv;
5)     SQLHDBC myCon;
6)     SQLHSTMT execStat; ← Is declared here :)
7)     SQLINTEGER worth, worthInfo;

8)     SQLAllocHandle(SQL_HANDLE_ENV,
        SQL_NULL_HANDLE, &myEnv);
9)     SQLAllocHandle(SQL_HANDLE_DBC, myEnv, &myCon);
10)    SQLAllocHandle(SQL_HANDLE_STMT, myCon, &execStat); ← Statement pointer established here :)
11)    SQLPrepare(execStat,
        "SELECT netWorth FROM MovieExec", SQL_NTS);
12)    SQLExecute(execStat); ← (Hey DB, thank you so much for the connection!!
        I will send you my SQL statement via execStat)
13)    SQLBindCol(execStat, 1, SQL_INTEGER, &worth,
        sizeof(worth), &worthInfo);
14)    while(SQLFetch(execStat) != SQL_NO_DATA) {
15)        digits = 1;
16)        while((worth /= 10) > 0) digits++;
17)        if(digits <= 14) counts[digits]++;
    }
18)    for(i=0; i<15; i++)
19)        printf("digits = %d: number of execs = %d\n",
            i, counts[i]);
}

```

(Hehe. Here it comes XD. Thank you DB!!)

4. Descriptions

- * Holds information about either tuples or parameters
- * Each statement has this information implicitly
- Processing Statements
 - is done using **SQLPrepare** and **SQLExecute**

SQLPrepare(*sh*, *st*, *SQL_NTS*) (1)

SQLExecute(*sh*) (2)

- *sh* is the statement handle created using **SQLHSTMT**
- *SQL_NTS* evaluates the length of string in *st*

Example:

```

1  SQLPrepare(execStat, "SELECT netWorth FROM MovieExec",
    SQL_NTS);
2  SQLExecute(execStat);
3

```

- the function **SQLExecDirect** combines **SQLPrepare** and **SQLExecute**

Example 2:

```

1  SQLExecDirect(execStat, "SELECT netWorth FROM MovieExec",
    SQL_NTS);
2

```

- Fetching Data From
 - Fetch
 - * **Syntax:** **SQLFetch**(*sh*)
 - * Executes statement in **SQLPrepare** and **SQLExecute** and stores result to variable in **SQLBindCol**
 - * Fetches a row per call
 - * Returns a value of type **SQLRETURN**, indicating either success or error
 - **SQLBindCol**
 - * **Syntax:** **SQLBindCol**(*sh*, *colNo*, *colType*, *pVar*, *varSize*, *varInfo*)
 - **sh**: the handle of statement (e.g *execStat*)
 - **colNo**: the position of column in tuple we obtain
 - **colType**: the SQL data type of variable (e.g. **SQL_INTEGER**, **SQL_CHAR**)
 - **pVar**: the pointer to variable the value is placed
 - **varSize**: the length in bytes of the value in *pVar*
 - **varInfo**: a pointer to an integer used by **SQLBindCol** for additional value about the value produced
 - * Stores data from **SQLFetch** to host-language variable
 - * Must be setup before **SQLFetch**(*sh*) is run
- Passing Parameters to Queries
 -