

CSC 369 Worksheet 1

August 16, 2020

Source: [link](#)

1. Run `process-run.py` with the following flags: `-l 5:100,5:100`. What should the CPU utilization be (e.g., the percent of time the CPU is in use?) Why do you know this? Use the `-c` and `-p` flags to see if you were right
2. Now run with these flags: `./process-run.py -l 4:100,1:0`. These flags specify one process with 4 instructions (all to use the CPU), and one that simply issues an I/O and waits for it to be done. How long does it take to complete both processes? Use `-c` and `-p` to find out if you were right.
3. Switch the order of the processes: `-l 1:0,4:100`. What happens now? Does switching the order matter? Why? (As always, use `-c` and `-p` to see if you were right)
4. We'll now explore some of the other flags. One important flag is `-S`, which determines how the system reacts when a process issues an I/O. With the flag set to `SWITCH ON END`, the system will NOT switch to another process while one is doing I/O, instead waiting until the process is completely finished. What happens when you run the following two processes (`-l 1:0,4:100 -c -S SWITCH ON END`), one doing I/O and the other doing CPU work?
5. Now, run the same processes, but with the switching behavior set to switch to another process whenever one is `WAITING` for I/O (`-l 1:0,4:100 -c -S SWITCH ON IO`). What happens now? Use `-c` and `-p` to confirm that you are right.
6. One other important behavior is what to do when an I/O completes. With `-I IO RUN LATER`, when an I/O completes, the process that issued it is not necessarily run right away; rather, whatever was running at the time keeps running. What happens when you run this combination of processes? (Run `./process-run.py -l 3:0,5:100,5:100,5:100 -S SWITCH ON IO -I IO RUN LATER -c -p`) Are system resources being effectively utilized?
7. Now run the same processes, but with `-I IO RUN IMMEDIATE` set, which immediately runs the process that issued the I/O. How does this behavior differ? Why might running a process that just completed an I/O again be a good idea?

8. Now run with some randomly generated processes: `-s 1 -l 3:50,3:50` or `-s 2 -l 3:50,3:50` or `-s 3 -l 3:50,3:50`. See if you can predict how the trace will turn out. What happens when you use the flag `-I IO RUN IMMEDIATE` vs. `-I IO RUN LATER`? What happens when you use `-S SWITCH ON IO` vs. `-S SWITCH ON END`?