

# CSC 209 Review 9 Solution

September 1, 2020

1. a) 0

## Notes

- a) is 0 because  $(i \gg 1 + j \gg 1 = i \gg 10 \gg 1 = 0)$
- **Bitwise Shift Operators**
  - has lower precedence than arithmetic operators

## Example:

$i \ll 2 + 1$  means  $i \ll (2+1)$  and not  $(i \ll 2) + 1$

- $\ll$  : Left Shift
- $\gg$  : Right Shift
- *Tip*: Always shift only on unsigned numbers for portability

## Example

```
unsigned short i, j;

i = 13;          /* i is now 13 (binary 0000000000001101) */
j = i << 2;       /* j is now 52 (binary 0000000000110100) */
j = i >> 2;       /* j is now 3 (binary 0000000000000011) */
```

As these examples show, neither operator modifies its operands. To modify a variable by shifting its bits, we'd use the compound assignment operators  $\ll=$  and  $\gg=$ :

```
i = 13;          /* i is now 13 (binary 0000000000001101) */
i <<= 2;         /* i is now 52 (binary 0000000000110100) */
i >>= 2;         /* i is now 13 (binary 0000000000001101) */
```

Shifts to left

Shifts to right

- $\gg=$  /  $\ll=$  : Are bitwise shift equivalent of  $+=$

b) 0

## Notes

- `i` is 1111111111111111
- `i` is 0000000000000000
- so `i & i = 0`
- `~`: Bitwise complement (NOT)

a	$\sim a$
0	1
1	0

**Example:**

```

1      0   1   1   1   //<- this is 7
2      -----
3      1   0   0   0   //<- this is 8
4
5      so, ~ 7 = 8

```

- `&`: Bitwise *and*

a	b	a & b
0	0	0
0	1	0
1	0	0
1	1	1

**Example:**

```

1      0   1   1   1   //<- this is 7
2      0   1   0   0   //<- this is 4
3      -----
4      0   1   0   0   //<- this is 4
5
6      so, 7 & 4 = 4

```

- `^`: Bitwise *exclusive or*
- `|`: Bitwise *inclusive or*

c) 1

**Notes**

- `i` is 1111111111111110
- `j` is 0000000000000000
- `i & j` is 0000000000000000 or 1
- `i & j ^ k` is 1

- $\wedge$ : Bitwise XOR

a	b	$a \wedge b$
0	0	0
0	1	1
1	0	1
1	1	0

### Example:

```

1      0   1   1   1   //<- this is 7
2      0   1   0   0   //<- this is 4
3      -----
4      0   0   1   1   //<- this is 3
5
6      so, 7 ^ 4 = 3
7

```

d) 0

### Example

- i is 0000000000000111
- j is 0000000000001000
- $i \wedge j$  is 0000000000000000 or 0
- k is 0000000000001001
- $i \wedge j \& k$  is 0000000000000000 or 0

### Correct Solution

15

### Notes

- There is a precedence to the order of operations

Highest:	$\sim$
	$\&$
	$\wedge$
Lowest:	$ $

- e) • toggling from 0 to 1

```
i = 0x0000;
i |= 0x0001;
```

or

```
i |= 1 << 0; where i = 0x0000;
```

- toggling from 1 to 0

```
i = 0x0001;
i &= ~0x0001;
```

or

```
i &= ~(1 << 0); where i = 0x0001;
```

### Correct Solution

- toggling from 0 to 1 of 4th bit

```
i = 0x0010;
i ^= 0x0000;
```

or

```
i ^= 1 << 4; where i = 0x0000;
```

- toggling from 1 to 0 of 4th bit

```
i = 0x0010;
i ^= 0x0010;
```

or

```
i ^= (1 << 4); where i = 0x0010;
```

### Notes

- Toggling can be done using bitwise XOR
- **Setting a bit**
  - Is done using `|` or bitwise OR

```
i = 0x0000;          /* i is now 0000000000000000 */
i |= 0x0010;         /* i is now 0000000000010000 */
```

- The idiom of above is `i |= 1 << j`

- **Clearing a bit**

- Is done using `|` or bitwise AND

```
i = 0x00ff;          /* i is now 0000000011111111 */
i &= ~0x0010;        /* i is now 0000000011101111 */
```

- The idiom of above is `i &= ~(i << j)`

2. It swaps the elements between x and y.

### Notes

- Preprocessor performs operations of statements in order from left to right

```

1           2           3
#define M(x,y) ((x)^(y) , (y)^(x) , (x)^(y) )

```

New value of x → New value of y, using x from 1 → New value of x, using y from 2, x from 1

3. `#define MK_COLOR(r,g,b) (long) ( (b | (g << 8)) | (b | (r << 16)))`

### Rough Work

1. store b in bit 0

b

2. store g in bit 8

b | g << 8

3. store r in bit 16

b | r << 16

### Correct Solution

```
#define MK_COLOR(r,g,b) (long) ((r | (g << 8)) | (r | (b << 16)))
```

Notes

- First Byte is furthest from 0x and first byte is closest to 0x



4. • GET\_RED

```
#define GET_RED(c) (long) (c & 0x007)
```

- GET\_GREEN

```
#define GET_GREEN(c) (long) ((c >> 8) & 0x007)
```

- GET\_BLUE

```
#define GET_BLUE(c) (long) ((c >> 16) & 0x007)
```

Notes

- 0x0007 in binary is 0x00000000000001111
- `c >> 4` shifts `c` to right by 4 bits and return overlapping value between `c >> 4` and `0x00000000000001111` (0x007)
- Test code is below

```
1  #include <stdio.h>
2  #include <stdlib.h>
3
4  #define MK_COLOR(r,g,b) (long) ( (r | (g << 8)) | (r | (b << 16)) )
5  #define GET_RED(c) (long) (c & 0x007)
6  #define GET_GREEN(c) (long) ((c >> 8) & 0x007)
7  #define GET_BLUE(c) (long) ((c >> 16) & 0x007)
8
9  int main() {
10     long i, r = 4, g = 5, b = 6, r2, g2, b2;
11
12     i = MK_COLOR(r,g,b);
```

```
13
14     r2 = GET_RED(i);
15     g2 = GET_GREEN(i);
16     b2 = GET_BLUE(i);
17
18     printf("%ld\n", i);
19     printf("%ld\n", r2);
20     printf("%ld\n", g2);
21     printf("%ld\n", b2);
22
23     return 0;
24 }
```

5. a)

```
    unsigned short swap_bytes(unsigned short i) {
2      unsigned short j, k;
3
4      j = i & 0x007; // extract first byte
5
6      i = i >> 4;
7      k = i & 0x007; // extract second byte
8
9      i = i >> 4; // shift down later two bytes
10
11     i |= j << 8; // add first byte to position of fourth byte
12     i |= k << 12; // add second byte to position of third byte
13
14 }
```

b)

```
    unsigned short swap_bytes(unsigned short i) {
2
3      i = i >> 8 | i << 8;
4
5      return i;
6 }
```

## Rough Works

1. Extract first two bytes

```
j = i & 0x0007
i = i >> 4
k = i & 0x0007
```

2. Shift later two bytes down

```
i = i >> 4
```

3. Add first two bytes to last two bytes

```
i |= j << 8;  
i |= k << 12;
```

```
61 unsigned int rotate_left(unsigned int i, int n) {  
2     return i >> 28 | i << n;  
3 }  
4  
5 unsigned int rotate_right(unsigned int i, int n) {  
6     return i << 28 | i >> n;  
7 }
```