

# CSC343 Worksheet 10 Solution

June 29, 2020

1. a) /Products/Maker/PC/RAM

## Notes:

- XPATH and Selecting Nodes
  - nodename
    - \* Selects all nodes with the name "nodename"
  - /
    - \* Selects from the root node
  - //
    - \* Selects node in the document from the current node that match the selection no matter where they are
  - .
    - \* Select the current node
  - ..
    - \* Selects the parent of the current node
  - @
    - \* Selects attributes

## Example:

```
1 /StarMovieData/Star//City
2
```

- selects all City element in

```
<StarMovieData>
  <Star>
    Here :)
  </Star>
</StarMovieData>
```

- Wildcards \*

- Is used to say 'any tag'

### Example:

```
1 /StarMovieData/*/@*
2
```

- '@\*' means any attributes
- '\*' means any tag

#### • Context of Expressions

- [...] means that exists or there exists
- [*integer*] selects ith child of its parent
- [*Tag*] selects elements that have one or more sublements with 'Tag'
- [*Attribute*] selects elements that have attribute 'Attribute'

### Example:

```
1 /StarMovieData/Star[//City = "Malibu"]/Name
2
```

- \* Means select all Star Name that contains City with value 'Malibu'

### Example:

```
1 /Movies/Movie/Version[1]/@year
2
```

- \* Returns value of 'year' attribute of first 'Version' tag in 'Movie'
- \* e.g. 1933 and 1984

```

1) <? xml version="1.0" encoding="utf-8" standalone="yes" ?>
2) <Movies>
3)   <Movie title = "King Kong">
4)     <Version year = "1933">
5)       <Star>Fay Wray</Star>
6)     </Version>
7)     <Version year = "1976">
8)       <Star>Jeff Bridges</Star>
9)       <Star>Jessica Lange</Star>
10)    </Version>
11)    <Version year = "2005" />
12)  </Movie>
13)  <Movie title = "Footloose">
14)    <Version year = "1984">
15)      <Star>Kevin Bacon</Star>
16)      <Star>John Lithgow</Star>
17)      <Star>Sarah Jessica Parker</Star>
18)    </Version>
19)  </Movie>
20) </Movies>

```

Result of  
/Movies/Movie/Version[1]/@year

**Example 2:**

```

1  /Movies/Movie/Version
2

```

- \* Returns all 'Version' tag in 'Movie'
- \* e.g. lines 4 through 6, 7 through 10, line 11, lines 14 through 18

```

1)  <? xml version="1.0" encoding="utf-8" standalone="yes" ?>
2)  <Movies>
3)    <Movie title = "King Kong">
4)      <Version year = "1933">
5)        <Star>Fay Wray</Star>
6)      </Version>
7)      <Version year = "1976">
8)        <Star>Jeff Bridges</Star>
9)        <Star>Jessica Lange</Star>
10)     </Version>
11)     <Version year = "2005" />
12)  </Movie>
13)  <Movie title = "Footloose">
14)    <Version year = "1984">
15)      <Star>Kevin Bacon</Star>
16)      <Star>John Lithgow</Star>
17)      <Star>Sarah Jessica Parker</Star>
18)    </Version>
19)  </Movie>
20) </Movies>

```

Result of  
/Movies/Movie/Version

**Example 3:**

```

1  /Movies/Movie/Version[Star]
2

```

- \* Selects all 'Version' tag with one or more 'Star' tag inside
- \* e.g. lines 4 through 6, 7 through 10, 14 through 18

```

1) <? xml version="1.0" encoding="utf-8" standalone="yes" ?>
2) <Movies>
3)   <Movie title = "King Kong">
4)     <Version year = "1933">
5)       <Star>Fay Wray</Star>
6)     </Version>
7)     <Version year = "1976">
8)       <Star>Jeff Bridges</Star>
9)       <Star>Jessica Lange</Star>
10)    </Version>
11)    <Version year = "2005" />
12)  </Movie>
13)  <Movie title = "Footloose">
14)    <Version year = "1984">
15)      <Star>Kevin Bacon</Star>
16)      <Star>John Lithgow</Star>
17)      <Star>Sarah Jessica Parker</Star>
18)    </Version>
19)  </Movie>
20) </Movies>

```

Result of `/Movies/Movie/Version[Star]`

- b) `/Products/Maker/*/@price`
- c) `/Products/Maker/Printer`
- d) `/Products/Maker[/Printer/Type/text() = 'ink-jet']`

**Correct Solution:**

`/Products/Maker[Printer/Type/text() = 'ink-jet']`

- e) `/Products/Maker[/PC | /Laptops]`

**Notes:**

- XPATH and OR
  - **Syntax:**  $(xpath\ expression\ 1) \mid (xpath\ expression\ 2)$  <sup>[1]</sup>

**References:**

- 1) Stack Overflow, XPath OR operator for different nodes, link
- f) `/Products/Maker/*[HardDisk/text() > 200]/@model`
2. a) `/Ships/Class/Ship/@name`
- b) `/Ships/Class[@displacement > 35000]`
- c) `/Ships/Class/Ship[@launched < 1917]`
- d) `/Ships/Class/Ship[Battle/@outcome = 'sunk']/@name`
- e) `/Ships[Class/@name = Class/Ship/@name]/Class/Ship/@launched`
- f) `/Ships/Class/Ship[Battle]/@name`

3. a) Notes:

- XQuery
  - Means **XML Query**
  - Is a functional language
- XQuery and FLWOR
  - FLWOR means
    1. **F**or - selects a sequence of nodes
    2. **L**et - binds a sequence to a variable
    3. **W**here - filters the nodes
    4. **O**rders By - sorts the nodes
    5. **R**eturn - what to return (gets evaluated once for every node)

Example:

```
1      doc("books.xml")/bookstore/book[price>30]/title
2
3      for $x in doc("books.xml")/bookstore/book
4      where $x/price>30
5      return $x/title
6
```

- Let clause
  - \* **Syntax:** *let variable := expression*
  - \* Has a use case of storing document

e.g.

```
$stars := doc('stars.xml');
```