

CSC343 Worksheet 6 Solution

June 21, 2020

1. Exercise 6.6.1:

```
a) SET TRANSACTION READONLY;  
2 BEGIN TRANSACTION;  
3     SELECT model, price FROM PC  
4     WHERE speed = speed AND  
5         ram=ram  
6 COMMIT;  
7
```

Notes:

- Transactions
 - is a collection of one or more operations that must be executed atomically
 - COMMIT causes the transaction to end successfully
 - ROLLBACK causes the transaction to abort. Any changes are undone
 - SET TRANSACTION READ ONLY
 - * tells the database that it will not be modified
 - * Must be declared before transaction
 - * Is useful when one user is running multiple queries while other is updating the same table

Example:

```
1 BEGIN TRANSACTION;  
2  
3 UPDATE accounts  
4 SET balance = balance - 1000  
5 WHERE account_no = 100;  
6  
7 UPDATE accounts  
8 SET balance = balance + 1000  
9 WHERE account_no = 200;  
10  
11 INSERT INTO account_changes(account_no,flag,amount,  
    changed_at)
```

```

12     VALUES (100, '-', 1000, datetime('now'));
13
14     COMMIT;
15
16     // Example - SET TRANSACTION READONLY
17     SET TRANSACTION READONLY;
18     BEGIN TRANSACTION;
19         ...
20     COMMIT;
21

```

b)

```

2     BEGIN TRANSACTION;
3     DELETE FROM PC
4     WHERE model=<model number>
5
6     DELETE FROM Product
7     WHERE model=<model number>
8
9     COMMIT;

```

2. Exercise 8.1.1:

a)

```

2     CREATE VIEW RichExec AS
3     SELECT * FROM MovieExec
4     WHERE netWorth >= 100000000;

```

Notes:

- Virtual Views
 - **Syntax:** CREATE VIEW < view-name > AS < view-definition >
 - Contrasts to database that exists in physical storage
 - Exists in RAM
 - Is created using query
 - can be used like a relation

Notes:

```

2     CREATE VIEW ParamountMovies AS
3     SELECT title, year
4     FROM Movies
5     WHERE studioName = 'Paramount';

```

b)

```

2     CREATE VIEW StudioPres AS
3     SELECT * FROM Movies
4     INNER JOIN Studio ON cert# = presC#;

```

```
c) CREATE VIEW ExecutiveStar AS
2   SELECT * FROM MovieExec
3   NATURAL JOIN MovieStar;
4
```

3. Exercise 8.1.2:

```
a) SELECT name, gender FROM ExecutiveStar;
2
```

```
b) SELECT name FROM RichExec WHERE netWorth > 100000000;
2
```

```
c) SELECT name FROM StudioPres
2   NATURAL JOIN ExecutiveStar
3   WHERE netWorth > 50000000
4
```

4. Exercise 8.2.1:

RichExec is updatable.

Notes:

- Updatable View Conditions
 - The WHERE clause in CREATE VIEW must not be a subquery
 - The FROM clause has only one occurrence of R
 - The SELECT clause must include enough attributes
 - NOT NULL attributes must have default values
 - * A solution to this is by including the attribute without default value in CREATE VIEW

Example:

```
1   Movies(title, year, length, genre, studioName, producerC#)
2   Suppose studioName is NOT NULL but has no default value.
   Then, a fix is:
3
4   CREATE VIEW Paramount AS
5       SELECT studioName, title, year
6       FROM Movies
7       WHERE studioName = 'Paramount';
8
```

5. Exercise 8.2.2:

a) No. It is not updatable. Since,

1. studioName attribute in Movies is NOT NULL without default value

b)

```

1 CREATE TRIGGER DisneyComediesInsert
2 INSTEAD OF INSERT ON DisneyComedies
3 REFERENCING
4     NEW ROW AS NewTuple
5 FOR EACH ROW
6 INSERT INTO Movies(title, year, length, genre, studioName)
7 VALUES(NewTuple.title, NewTuple.year, NewTuple.length, 'comedy',
8 'Disney');
```

Notes:

- Using Trigger in VIEW
 - Uses INSTEAD OF in place of BEFORE or AFTER
 - When event causes the trigger, the trigger is done instead of the event

Example:

```

1 CREATE VIEW ParamountMovies AS
2     SELECT title, year
3     FROM Movies
4     WHERE studioName = 'paramount';
5
6 CREATE TRIGGER ParamountInsert
7 INSTEAD OF INSERT ON ParamountMovies
8 REFERENCING NEW ROW AS NewRow
9 FOR EACH ROW
10 INSERT INTO Movies(title, year, studioName)
11 VALUES(NewRow.title, NewRow.year, 'Paramount');
```

c)

```

1 CREATE TRIGGER DisneyComediesInsert
2 INSTEAD OF INSERT ON DisneyComedies
3 REFERENCING
4     NEW ROW AS NewTuple
5     OLD ROW AS OldTuple
6 FOR EACH ROW
7 UPDATE Movies
8 SET length=NewTuple.length
9 WHERE title=OldTuple.title AND year=OldTuple.year;
```

6. Exercise 8.2.3

a) No. the view is not updatable. Because for it to be updatable, only one relation must exist in FROM

b)

```
1 CREATE TRIGGER NewPCInsert
2 INSTEAD OF INSERT ON NewPC
3 REFERENCING
4     NEW ROW AS NewTuple
5     OLD ROW AS OldTuple
6 FOR EACH ROW
7 INSERT INTO PC(model speed, ram, hd ,price)
8 VALUES (NewTuple.model, NewTuple.speed, NewTuple.ram, NewTuple.hd
9 , NewTuple.price);
10
11 INSERT INTO Product(maker, model, type)
12 VALUES (NewTuple.maker, NewTuple.model, 'pc');
```

c)

```
1 CREATE TRIGGER NewPCUpdate
2 INSTEAD OF INSERT ON NewPC
3 REFERENCING
4     NEW ROW AS NewTuple
5 FOR EACH ROW
6 UPDATE PC
7 SET model=NewTuple.model
8     speed=NewTuple.speed,
9     ram=NewTuple.ram,
10    hd=NewTuple.hd,
11    price=NewTuple.price;
12
13 UPDATE Product
14 SET maker=NewTuple.maker,
15     model=NewTuple.model,
16     type='pc';
17
```

Correct Solution:

```
1 CREATE TRIGGER NewPCUpdate
2 INSTEAD OF UPDATE ON NewPC
3 REFERENCING
4     NEW ROW AS NewTuple
5 FOR EACH ROW
6 UPDATE PC
7 SET model=NewTuple.model
8     speed=NewTuple.speed,
9     ram=NewTuple.ram,
10    hd=NewTuple.hd,
11    price=NewTuple.price;
12
13 UPDATE Product
14 SET maker=NewTuple.maker,
15     model=NewTuple.model,
```

```
16      type='pc';
```

```
d) 1 CREATE TRIGGER NewPCDelete
2   INSTEAD OF DELETE ON NewPC
3   REFERENCING
4     NEW ROW AS NewTuple
5   FOR EACH ROW
6   DELETE FROM PC
7   WHERE model=NewTuple.model;
8
9   DELETE FROM Product
10  WHERE model=NewTuple.model;
11
```

```
7. a) 1 CREATE INDEX studioNameIndex Studio(name)
2
```

Notes:

- Indexes

- **Syntax (Create Index):**

CREATE INDEX < index-name > R(< attributes >)

- **Syntax (Drop Index):**

DROP INDEX < index-name >

- Used to find tuples in a very large database

- * Is efficient

- Can be thought as (key, value) pair in a binary search tree

- e.g. Declaring Index

```
1 CREATE INDEX KeyIndex ON Movies(title, year);
2
```

- e.g. Dropping index

```
1 CREATE INDEX KeyIndex ON Movies(title, year);
2
```

```
b) 1 CREATE INDEX movieExecAddressIndex MovieExec(address)
2
```

```
c) 1 CREATE INDEX movieKeyIndex Movies(genre, length)
2
```

8. Exercise 8.4.1:

Action	No Index	Star Index	Movie Index	Both Indexes
Q_1	100	4	100	4
Q_2	100	100	4	4
I	2	4	4	6
Average	$2 + 100p_1 + 100p_2$	$4 + 96p_2$	$4 + 96p_1$	$6 - 2p_1 - 2p_2$

Notes:

- Database Tuning
 - Index speeds up queries that can use it
 - Index should NOT be created when modifications are the frequent choice of action

9. Exercise 8.4.2:

Omitted for the time being

10. Exercise 8.5.1:

```

1  UPDATE MovieProd
2  SET name='New Name'
3  WHERE (title, year) IN
4  (
5      SELECT title, year FROM Movies
6      INNER JOIN MovieExecs
7      ON Movies.productC# = MovieExec.cert#
8      WHERE cert# = '4567'
9  );
10

```

Notes:

- Materialized Views
 - Is also known as a summary
 - Is also known as black-box abstraction
 - Stores view in physical storage
 - Useful when storing expensive operation like AVG or COUNT