FEATURES

● The SR304.3-T is a true one-port, Surface-acoustic-wave(SAW) resonator in a low-profile, TO-39 case. It provides reliable, fundamental-mide, quartz frequency stabilization of fixed-frequency transmitters operating at 304.30MHz.



APPLICATIONS

● Communication

SPECIFICATION ＊

Parameters			Product	Option Code
			SR	SR
Centre Frequency(fc) :		304.300MHz	▲	304.300
Frequency Tolerance(△fc):		±75KHz	△	A
		±100KHz	△	B
		±150KHz	△	C
		±200KHz	△	D
Temp. Stability	Turnover Temp(To):	55℃Max.	▲	
	Turnover Frequency(fo):	fc 304.3 MHz	▲	
	Frequency Temp. Coefficient (FTC):	0.037ppm/℃²	▲	
Insertion Loss(IL):		2.0 dB Max.	▲	
Operating Temp. Range:		-10℃~+60℃	▲	
Storage Temp. Range:		-40℃~+85℃	▲	
Quality Factor	Unloaded Q(Qu):	15,333	▲	
	50Ω Loaded Q(QL):	2,000	▲	
DC Insulation Resistance between Any Two Pins:		1.0MΩ Min.	▲	
Frequency Aging Absolute Value During the First Year(fA):		≤10ppm/year	▲	
RF Equivalent RLC Model	Motional Resistance(RM):	21Ω Max.	▲	
	Motional Inductance(LM):	120.356 μH	▲	
	Motional Capacitance(CM):	2.2752 fF	▲	
	Shunt Static Capacitance (Co):	2.0 pF	▲	
CW Therefore Power Dissipation:		+10dBm	▲	
DC Voltage Between Any Two Pins:		±30V DC	▲	
Case Temperature:		-40℃~+85℃	▲	
Holder Type:		TO-39	△	T
Package:		Tube	△	U

▲ Standard ＊ Specifications Subject to Change Without Notice
△ Optional: please specify required code when inquiring or ordering

NOTE

1: Electrostatic Sensitive Device. Observe precautions for handling
2. Freq. Aging is the change in fc with time and is specified at +65℃ or less. Aging may exceed the specification for prolonged temp. Above +65℃. Typiclly, aging is greatest the first year after manufacture, decreasing in subsequent years.
3. The centre freq. Fc , is the freq. Of minimum IL with te resonator in te specified test fixture in a 50Ω test system with VSWR≤1.2:1. Typically, $f_{oscillator}$ or $f_{transmiter}$ is less than the resonator fc.
4. Typically, equipment utilizing this device requires emissions testing and government approval. Which s the responsibility of the equipment manufacturer
5.Unless noted otherwise , case temperature Tc=+25℃±2℃.
6.The design, manufacturing process, and specifications of this device are subject to change without notice.
7.Derived mathematically from one or more of the following directly measured parameters: f_c, IL, 3 dB bandwidth, f_c versus T_c , and C_o
8.Turnover temperature, T_o, is the temperature of maximum (or turnover) freq., f_o, The nominal center freq. at any case temp. , T_c, may be calculated from :f= f_o [1-FTC (T_o-T_c)²]. Typically, oscillator T_o is appr. equal to the specified resonator To.

PART NUMBER GUIDE

TGS	SR	304.30	A	T	U
Mark	SAW Resonators One-Port	Centre Freq.	Frequency Tolerance	Holder Type	Package

e.g. TGS SR 304.3 A T U

DIMENSIONS



Pin	Connection
1	Terminal 1
2	Terminal 2
3	Case Ground

Unit: mm

EQUIVALENT LC MODE



TYPICAL APPLICATION CIRCUIT



TEMPERATURE CHARACTERISTICS



The Cure shown above accounts for resonator contribution only and doesnot include oscillator temperature characteristics

TYPICAL FREQUENCY RESPONSE



PACKAGE

● Standard package in Tube: 20pcs/Tube.