N-channel Enhanced mode SOT-23 MOSFET

Features

- High ruggedness
- Low $R_{DS(ON)}$ (Typ 0.19Ω)@V_{GS}=10V (Typ 0.2Ω)@V_{GS}=4.5V
- Low Gate Charge (Typ 13nC)
- Improved dv/dt Capability
- 100% Avalanche Tested
- Application:DC-DC, Switch



1. Gate 2. Drain 3. Source

BV_{DSS} : 100V
I_D : 2A
$R_{DS(ON)}$: 0.19Ω @V_{GS}=10V



General Description

This power MOSFET is produced with advanced technology of SAMWIN.
This technology enable the power MOSFET to have better characteristics, including fast switching time, low on resistance, low gate charge and especially excellent avalanche characteristics.

LEAD-FREE RoHS

Order Codes

Item	Sales Type	Marking	Package	Packaging
1	SW E 2N10	SW 2N10	SOT-23	REEL

Absolute maximum ratings

Symbol	Parameter		Value	Unit
V_{DSS}	Drain to source voltage		100	V
I_D	Continuous drain current (@T_C=25°C)		2*	A
	Continuous drain current (@T_C=100°C)		1.26*	A
I_{DM}	Drain current pulsed	(note 1)	8	A
V_{GS}	Gate to source voltage		±15	V
E_{AS}	Single pulsed avalanche energy	(note 2)	64	mJ
E_{AR}	Repetitive avalanche energy	(note 1)	5	mJ
dv/dt	Peak diode recovery dv/dt	(note 3)	5	V/ns
T_{STG}, T_J	Operating junction temperature & storage temperature		-55 ~ + 150	°C
T_L	Maximum lead temperature for soldering purpose, 1/8 from case for 5 seconds.		300	°C

*. Drain current is limited by junction temperature.

Copyright@ SEMIPOWER Electronic Technology Co., Ltd. All rights reserved.

Electrical characteristic (T_C = 25ºC unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
Off characteristics						
BV_{DSS}	Drain to source breakdown voltage	V_{GS}=0V, I_D=250uA	100			V
ΔBV_{DSS} / ΔT_J	Breakdown voltage temperature coefficient	I_D=250uA, referenced to 25ºC		0.1		V/ºC
I_{DSS}	Drain to source leakage current	V_{DS}=100V, V_{GS}=0V			1	uA
		V_{DS}=80V, T_C=125ºC			50	uA
I_{GSS}	Gate to source leakage current, forward	V_{GS}=15V, V_{DS}=0V			100	nA
	Gate to source leakage current, reverse	V_{GS}=-15V, V_{DS}=0V			100	nA
On characteristics						
$V_{GS(TH)}$	Gate threshold voltage	V_{DS}=V_{GS}, I_D=250uA	1		3	V
$R_{DS(ON)}$	Drain to source on state resistance	V_{GS}=10V, I_D =1A		0.19	0.24	Ω
		V_{GS}=4.5V,I_D =1A		0.2	0.24	Ω
Dynamic characteristics						
C_{iss}	Input capacitance	V_{GS}=0V, V_{DS}=25V, f=1MHz		550		pF
C_{oss}	Output capacitance			50		
C_{rss}	Reverse transfer capacitance			33		
$t_{d(on)}$	Turn on delay time	V_{DS}=50V, I_D=2A, V_{GS}=10V, R_G=25Ω (note 4,5)		3.5		ns
t_r	Rising time			22		
$t_{d(off)}$	Turn off delay time			40		
t_f	Fall time			25		
Q_g	Total gate charge	V_{DS}=80V, V_{GS}=10V, I_D=2A (note 4,5)		13		nC
Q_{gs}	Gate-source charge			1.7		
Q_{gd}	Gate-drain charge			3.2		

Source to drain diode ratings characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_S	Continuous source current	Integral reverse p-n Junction diode in the MOSFET			2	A
I_{SM}	Pulsed source current				8	A
V_{SD}	Diode forward voltage drop.	I_S=2A, V_{GS}=0V			1.4	V
t_{rr}	Reverse recovery time	I_S=2A, V_{GS}=0V, dI_F/dt=100A/us		28		ns
Q_{rr}	Reverse recovery charge			33		nC

※. Notes

1. Repeatitive rating : pulse width limited by junction temperature.
2. L = 32.1mH, I_{AS} = 2A, V_{DD} = 50V, R_G=25Ω, Starting T_J = 25ºC
3. I_{SD} ≤ 2A, di/dt = 100A/us, V_{DD} ≤ BV_{DSS}, Staring T_J =25ºC
4. Pulse Test : Pulse Width ≤ 300us, duty cycle ≤ 2%.
5. Essentially independent of operating temperature.

Copyright@ SEMIPOWER Electronic Technology Co., Ltd. All rights reserved.

Fig. 1. On-state characteristics



Fig. 2. On-resistance variation vs. drain current and gate voltage



Fig. 3. Gate charge characteristics



Fig. 4. On state current vs. diode forward voltage



Fig 5. Breakdown Voltage Variation vs. Junction Temperature



Fig. 6. On resistance variation vs. junction temperature



Copyright@ SEMIPOWER Electronic Technology Co., Ltd. All rights reserved.

Fig. 7. Capacitance Characteristics



Fig. 8. Gate charge test circuit & waveform



Fig. 9. Switching time test circuit & waveform



Copyright@ SEMIPOWER Electronic Technology Co., Ltd. All rights reserved.

Fig. 10. Unclamped Inductive switching test circuit & waveform



Fig. 11. Peak diode recovery dv/dt test circuit & waveform



DISCLAIMER

* All the data & curve in this document was tested in XI'AN SEMIPOWER TESTING & APPLICATION CENTER.
* This product has passed the PCT,TC,HTRB,HTGB,HAST,PC and Solderdunk reliability testing.
* Qualification standards can also be found on the Web site (**http://www.semipower.com.cn**)
* Suggestions for improvement are appreciated, Please send your suggestions to **samwin@samwinsemi.com**

Copyright@ SEMIPOWER Electronic Technology Co., Ltd. All rights reserved.