

High Voltage Transistors

- We declare that the material of product compliance with RoHS requirements.

DEVICE MARKING AND ORDERING INFORMATION


Device	Marking	Package	Shipping
LMBTA42LT1G	1D	SOT-23	3000/Tape&Reel
LMBTA42LT3G	1D	SOT-23	3000/Tape&Reel

LMBTA42LT1G



MAXIMUM RATINGS

Rating	Symbol	Value		Unit
		LMBTA42	LMBTA43	
Collector-Emitter Voltage	V_{CEO}	300	200	Vdc
Collector-Base Voltage	V_{CBO}	300	200	Vdc
Emitter-Base Voltage	V_{EBO}	6.0	6.0	Vdc
Collector Current — Continuous	I_C	500		mAdc



THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board, (1) $T_A = 25^\circ\text{C}$	P_D	225	mW
Derate above 25°C		1.8	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	556	$^\circ\text{C/W}$
Total Device Dissipation Alumina Substrate, (2) $T_A = 25^\circ\text{C}$	P_D	300	mW
Derate above 25°C		2.4	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	417	$^\circ\text{C/W}$
Junction and Storage Temperature	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage(3) ($I_C = 1.0 \text{ mAdc}$, $I_E = 0$)	$V_{(BR)CEO}$	300	—	Vdc
Collector-Base Breakdown Voltage ($I_C = 100 \mu\text{Adc}$, $I_E = 0$)	$V_{(BR)CBO}$	300	—	Vdc
Emitter-Base Breakdown Voltage ($I_E = 100 \mu\text{Adc}$, $I_C = 0$)	$V_{(BR)EBO}$	6.0	—	Vdc
Collector Cutoff Current ($V_{CB} = 300\text{Vdc}$, $I_E = 0$) ($V_{CB} = 230\text{Vdc}$, $I_E = 0$) ($V_{CB} = 200\text{Vdc}$, $I_E = 0$)	I_{CBO}	—	0.1 0.1 0.1	μAdc
Emitter Cutoff Current ($V_{EB} = 6.0\text{Vdc}$, $I_C = 0$) ($V_{EB} = 4.0\text{Vdc}$, $I_C = 0$)	I_{EBO}	—	0.1 0.1	μAdc

1. FR-5 = $1.0 \times 0.75 \times 0.062 \text{ in.}$

2. Alumina = $0.4 \times 0.3 \times 0.024 \text{ in.}$ 99.5% alumina.

3. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2.0\%$.





LMBTA42LT1G
ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Continued)



Characteristic	Symbol	Min	Max	Unit
ON CHARACTERISTICS (3)				
DC Current Gain (I _C = 1.0 mA, V _{CE} = 10 Vdc)	h _{FE}	25	—	—
(I _C = 10 mA, V _{CE} = 10 Vdc)		40	—	—
(I _C = 30 mA, V _{CE} = 10 Vdc)		40	—	—
Collector–Emitter Saturation Voltage (I _C = 20 mA, I _B = 2.0 mA)	V _{CE(sat)}	—	0.5	Vdc
Base–Emitter Saturation Voltage (I _C = 20 mA, I _B = 2.0 mA)	V _{BE(sat)}	—	0.9	Vdc

SMALL–SIGNAL CHARACTERISTICS

Current –Gain–Bandwidth Product (V _{CE} = 20 Vdc, I _C = 10mA, f = 100 MHz)	f _T	50	—	MHz
Collector – Base Capacitance (V _{CB} = 20 Vdc, I _E = 0, f = 1.0 MHz)	C _{cb}	—	3.0	pF

3. Pulse Test: Pulse Width ≤300 μs, Duty Cycle ≤2.0%.

LMBTA42LT1G

Figure 8. DC Current Gain

Figure 2. Capacitance

Figure 3. Current-Gain — Bandwidth Product

Figure 4. "On" Voltages

LMBTA42LT1G
SOT-23

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.1102	0.1197	2.80	3.04
B	0.0472	0.0551	1.20	1.40
C	0.0350	0.0440	0.89	1.11
D	0.0150	0.0200	0.37	0.50
G	0.0701	0.0807	1.78	2.04
H	0.0005	0.0040	0.013	0.100
J	0.0034	0.0070	0.085	0.177
K	0.0140	0.0285	0.35	0.69
L	0.0350	0.0401	0.89	1.02
S	0.0830	0.1039	2.10	2.64
V	0.0177	0.0236	0.45	0.60

