POLYTRONICS TECHNOLOGY CORP.
24-1,Industry E.4th Rd. Science Park, Hsinchu,Taiwan, R.O.C.
TEL: +886-3-5643931 FAX: +886-3-5644624

EVERFUSE™
Polymeric PTC Resistor

Device Specification (Preliminary)

RoHS 2002/95/EC

ELECTRICAL CHARACTERISTICS

Part Number	I_{hold} (A)	I_{trip} (A)	V_{max} (Vdc)	I_{max} (A)	$P_{d\ max.}$ (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec.)	R_{min} (Ω)	R_{1max} (Ω)
SMD1210P175SLR	1.75	3.50	6	50	0.8	8.00	2.50	0.006	0.040

Note: I_{hold} = Hold current: maximum current device will pass without tripping in 23℃ still air.

I_{trip} = Trip current: minimum current at which the device will trip in 23℃ still air.

V_{max} = Maximum voltage device can withstand without damage at rated current (I_{max})

I_{max} = Maximum fault current device can withstand without damage at rated voltage (V_{max})

P_d = Power dissipated from device when in the tripped state at 23℃ still air.

R_{min}= Minimum resistance of device in initial (un-soldered) state.

R_{1max}= Maximum resistance of device at 23℃ measured one hour after tripping or reflow soldering of 260℃ for 20 sec.

*****Value specified were determined using the PWB with 0.030”*1.5oz copper traces.

*Customer should verify the device performance in their specified conditions.

Caution: Operation beyond the specified rating may result in damage and possible arcing and flame.

Recognitions:

Marking:

Polytronics Logo

P□□

Part Identification (TBD)

FIGURE



SOLDER PAD LAYOUTS



Note: Polystar is Polytronics’s manufacturing site in China. The Polystar ID marking shall appear on smallest package.

PHYSICAL DIMENSIONS (mm)

Part Number	A		B		C		D		E	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
SMD1210P175SLR	3.00	3.43	2.35	2.80	0.40	0.70	0.25	0.75	0.20	0.50

◎ Specifications are subject to change without notice.

THERMAL DERATING CHART – Ihold/Itrip(Amps)

RECOMMENDED DATA

Model		Ambient Operation Temperature								
		-40℃	-20℃	0℃	23℃	40℃	50℃	60℃	70℃	85℃
SMD1210P175SLR	Ihold	2.65	2.30	2.05	1.75	1.40	1.20	1.05	0.90	0.60
	Itrip	5.30	4.70	4.15	3.50	2.90	2.60	2.30	1.95	1.40