ALPHA & OMEGA SEMICONDUCTOR

AOD403
P-Channel Enhancement Mode Field Effect Transistor

General Description

The AOD403 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and low gate resistance. With the excellent thermal resistance of the DPAK package, this device is well suited for high current load applications. *Standard Product AOD403 is Pb-free (meets ROHS & Sony 259 specifications). AOD403L is a Green Product ordering option. AOD403 and AOD403L are electrically identical.*

Features

V_{DS} (V) = -30V
I_D = -85A (V_{GS} = -20V)
$R_{DS(ON)}$ < 6mΩ (V_{GS} = -20V)
$R_{DS(ON)}$ < 7.6mΩ (V_{GS} = -10V)

TO-252
D-PAK



Top View
Drain Connected
to Tab



Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±25	V
Continuous Drain Current [B,G]	T_A=25°C [G]	I_D	-85	A
	T_A=100°C [B]		-65	
Pulsed Drain Current		I_{DM}	-200	
Avalanche Current [C]		I_{AR}	-30	A
Repetitive avalanche energy L=0.1mH [C]		E_{AR}	120	mJ
Power Dissipation [B]	T_C=25°C	P_D	100	W
	T_C=100°C		50	
Power Dissipation [A]	T_A=25°C	P_{DSM}	2.5	W
	T_A=70°C		1.6	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 175	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	13	20	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		39	50	°C/W
Maximum Junction-to-Case [C]	Steady-State	$R_{\theta JL}$	0.56	1.5	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-24V, V_{GS}=0V		-0.01	-1	µA
		T_J=55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±25V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=-250µA	-1.5	-2.6	-3.5	V
$I_{D(ON)}$	On state drain current	V_{GS}=-10V, V_{DS}=-5V	-60			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-20V, I_D=-20A		5.1	6	mΩ
		T_J=125°C		7.1	8.5	
		V_{GS}=-10V, I_D=-20A		6.3	7.6	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-20A		44		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.72	-1	V
I_S	Maximum Body-Diode Continuous Current				-104	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz		4360	5300	pF
C_{oss}	Output Capacitance			1050		pF
C_{rss}	Reverse Transfer Capacitance			762		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		2.5	3	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=-10V, V_{DS}=-15V, I_D=-20A		93.2	120	nC
Q_{gs}	Gate Source Charge			18		nC
Q_{gd}	Gate Drain Charge			29.2		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=0.75Ω, R_{GEN}=3Ω		18	25	ns
t_r	Turn-On Rise Time			30	45	ns
$t_{D(off)}$	Turn-Off DelayTime			51	75	ns
t_f	Turn-Off Fall Time			35	50	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-20A, dI/dt=100A/µs		39.5	48	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-20A, dI/dt=100A/µs		30.8	37	nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The Power dissipation P_{DSM} is based on steady-state $R_{\theta JA}$ and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design, and the maximum temperature of 175°C may be used if the PCB or heatsink allows it.

B. The power dissipation P_D is based on $T_{J(MAX)}$=175°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

C: Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=175°C.

D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300µs pulses, duty cycle 0.5% max.

F. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

G. The maximum current rating is limited by the package current capability.

Rev 4: Aug 2005

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Fig 1: On-Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Drain Current and Gate Voltage



Figure 4: On-Resistance vs. Junction Temperature



Figure 5: On-Resistance vs. Gate-Source Voltage



Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area (Note F)



Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)



Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)