


SOLDER PAD LAYOUT



TOP VIEW

Scale 2:1

Features

- Plastic moulded surface mount package
- Miniature size for high density applications
- Wide operating temperature range
- 6pF version for Dallas RTC
- Supplied on tape and reel

Specifications

Parameters	Product GSX-200	Option Codes
Frequency:	32.768kHz	
Calibration tolerance:	±20ppm ±5 ~ ±100ppm	specify
Temperature stability:	-50ppm (-10 to +60°C) -130ppm (-30 to +80°C)	
Operating temperature range:	-40 to +85°C	
Storage temperature range:	-55 to +125°C	
Turnover temperature (T ₀):	+25°C ±5°C	
Frequency / temp coefficient:	-0.038ppm/°C ² typ	
Circuit condition:	12.5pF 6pF	D
Static capacitance (C ₀):	1.35pF typ	
Motional capacitance (C ₁):	3.0fF typ	
Equivalent series resistance (max):	50kΩ	
Ageing:	±3ppm max first year	
Drive level:	1.0μW typ	
Shock resistance:	±5ppm	
Soldering conditions:	240°C, 10sec max	

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + option codes (if any)

eg: **GSX-200**

GSX-200 ±10ppm

GSX-200/D ±20ppm 6pF

Option code X (eg GSX-200/X) denotes a custom specification.

- ◆ Available on T&R - 3k pcs per reel.
- ◆ Refer to our website for T&R and soldering details.
- ◆ Also available at frequencies from 30.0 ~ 100kHz