P-Channel Enhancement Mode MOSFET

Features

- -30V/-13A ,
  $R_{DS(ON)}$=8mΩ(typ.) @ V_{GS}=-20V
  $R_{DS(ON)}$=9mΩ(typ.) @ V_{GS}=-10V
  $R_{DS(ON)}$=13mΩ(typ.) @ V_{GS}=-4.5V
- Super High Dense Cell Design
- Reliable and Rugged
- SOP-8 Package
- Lead Free Available (RoHS Compliant)

Applications

- Power Management in Notebook Computer, Portable Equipment and Battery Powered Systems

Pin Description



Top View of SOP – 8



P-Channel MOSFET

Ordering and Marking Information

APM4429 □□-□□ □ Lead Free Code Handling Code Temp. Range Package Code	Package Code K : SOP-8 Operating Junction Temp. Range C : -55 to 150°C Handling Code TR : Tape & Reel Lead Free Code L : Lead Free Device Blank : Original Device
APM4429 K : APM4429 XXXXX	XXXXX - Date Code

Note: ANPEC lead-free products contain molding compounds/die attach materials and 100% matte in plate termination finish; which are fully compliant with RoHS and compatible with both SnPb and lead-free soldiering operations. ANPEC lead-free products meet or exceed the lead-free requirements of IPC/JEDEC J STD-020C for MSL classification at lead-free peak reflow temperature.

Absolute Maximum Ratings (T_A = 25°C unless otherwise noted)

Symbol	Parameter		Rating	Unit
V_{DSS}	Drain-Source Voltage		-30	V
V_{GSS}	Gate-Source Voltage		±20	
I_D*	Continuous Drain Current	V_{GS}=-20V	-13	A
I_{DM}*	Pulsed Drain Current		-50	
I_S*	Diode Continuous Forward Current		-3	A
T_J	Maximum Junction Temperature		150	°C
T_{STG}	Storage Temperature Range		-55 to 150	
P_D*	Maximum Power Dissipation	T_A=25°C	2	W
		T_A=100°C	0.8	
$R_{\theta JA}$*	Thermal Resistance-Junction to Ambient		62.5	°C/W

Note:

*Surface Mounted on 1in^2 pad area, t ≤ 10sec.

Electrical Characteristics (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	APM4429K			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V, I_{DS}=-250µA	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-24V, V_{GS}=0V			-1	µA
		T_J=85°C			-30	
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_{DS}=-250µA	-1	-1.5	-2	V
I_{GSS}	Gate Leakage Current	V_{GS}=±20V, V_{DS}=0V			±100	nA
$R_{DS(ON)}$ [a]	Drain-Source On-state Resistance	V_{GS}=-20V, I_{DS}=-13A		8	11	mΩ
		V_{GS}=-10V, I_{DS}=-13A		9	12	
		V_{GS}=-4.5V, I_{DS}=-12A		13	17	
V_{SD} [a]	Diode Forward Voltage	I_{SD}=-3A, V_{GS}=0V		-0.8	-1.3	V
Gate Charge Characteristics [b]						
Q_g	Total Gate Charge	V_{DS}=-15V, V_{GS}=-10V, I_{DS}=-13A		105	135	nC
Q_{gs}	Gate-Source Charge			10.8		
Q_{gd}	Gate-Drain Charge			13.6		

Electrical Characteristics (Cont.) (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	APM4429K			Unit
			Min.	Typ.	Max.	
Dynamic Characteristics [b]						
R_G	Gate Resistance	V_{GS}=0V,V_{DS}=0V,F=1MHz		4		Ω
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-25V, Frequency=1.0MHz		4700		pF
C_{oss}	Output Capacitance			800		
C_{rss}	Reverse Transfer Capacitance			220		
$t_{d(ON)}$	Turn-on Delay Time	V_{DD}=-15V, R_L=15Ω, I_{DS}=-1A, V_{GEN}=-10V, R_G=6Ω		15	30	ns
T_r	Turn-on Rise Time			20	37	
$t_{d(OFF)}$	Turn-off Delay Time			55	100	
T_f	Turn-off Fall Time			40	73	

Notes:

a : Pulse test ; pulse width≤300μs, duty cycle≤2%.

b : Guaranteed by design, not subject to production testing.

Typical Characteristics

Power Dissipation



Drain Current



Safe Operation Area



Thermal Transient Impedance



Typical Characteristics (Cont.)

Output Characteristics



Drain-Source On Resistance



Transfer Characteristics



Gate Threshold Voltage



Typical Characteristics (Cont.)

Drain-Source On Resistance



Source-Drain Diode Forward



Capacitance



Gate Charge



Packaging Information

SOP-8 pin (Reference JEDEC Registration MS-012)



Dim	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	5.00	0.189	0.197
E	3.80	4.00	0.150	0.157
H	5.80	6.20	0.228	0.244
L	0.40	1.27	0.016	0.050
e1	0.33	0.51	0.013	0.020
e2	1.27BSC		0.50BSC	
ϕ 1	8°		8°	

Physical Specifications

Terminal Material	Solder-Plated Copper (Solder Material : 90/10 or 63/37 SnPb), 100%Sn
Lead Solderability	Meets EIA Specification RSI86-91, ANSI/J-STD-002 Category 3.

Reflow Condition (IR/Convection or VPR Reflow)



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	3°C/second max.	3°C/second max.
Preheat - Temperature Min (Tsmin) - Temperature Max (Tsmax) - Time (min to max) (ts)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: - Temperature (T_L) - Time (t_L)	183°C 60-150 seconds	217°C 60-150 seconds
Peak/Classificatioon Temperature (Tp)	See table 1	See table 2
Time within 5°C of actual Peak Temperature (tp)	10-30 seconds	20-40 seconds
Ramp-down Rate	6°C/second max.	6°C/second max.
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.

Notes: All temperatures refer to topside of the package .Measured on the body surface.

Classification Reflow Profiles(Cont.)

Table 1. SnPb Entectic Process – Package Peak Reflow Temperatures

Package Thickness	Volume mm^3 <350	Volume mm^3 ≥350
<2.5 mm	240 +0/-5°C	225 +0/-5°C
≥2.5 mm	225 +0/-5°C	225 +0/-5°C

Table 2. Pb-free Process – Package Classification Reflow Temperatures

Package Thickness	Volume mm^3 <350	Volume mm^3 350-2000	Volume mm^3 >2000
<1.6 mm	260 +0°C*	260 +0°C*	260 +0°C*
1.6 mm – 2.5 mm	260 +0°C*	250 +0°C*	245 +0°C*
≥2.5 mm	250 +0°C*	245 +0°C*	245 +0°C*
*Tolerance: The device manufacturer/supplier **shall** assure process compatibility up to and including the stated classification temperature (this means Peak reflow temperature +0°C. For example 260°C+0°C) at the rated MSL level.			

Reliability Test Program

Test item	Method	Description
SOLDERABILITY	MIL-STD-883D-2003	245°C,5 SEC
HOLT	MIL-STD 883D-1005.7	1000 Hrs Bias @ 125°C
PCT	JESD-22-B, A102	168 Hrs, 100% RH, 121°C
TST	MIL-STD 883D-1011.9	-65°C ~ 150°C, 200 Cycles

Carrier Tape & Reel Dimensions



Carrier Tape & Reel Dimensions(Cont.)



Application	A	B	C	J	T1	T2	W	P	E
SOP-8	330±1	62 ± 1.5	12.75 + 0.1 5	2 + 0.5	12.4 +0.2	2± 0.2	12 + 0.3 - 0.1	8± 0.1	1.75± 0.1
	F	D	D1	Po	P1	Ao	Bo	Ko	t
	5.5 ± 0.1	1.55±0.1	1.55+ 0.25	4.0 ± 0.1	2.0 ± 0.1	6.4 ± 0.1	5.2± 0.1	2.1± 0.1	0.3±0.013

(mm)

Cover Tape Dimensions

Application	Carrier Width	Cover Tape Width	Devices Per Reel
SOP- 8	12	9.3	2500

Customer Service

Anpec Electronics Corp.

Head Office :

5F, No. 2 Li-Hsin Road, SBIP,

Hsin-Chu, Taiwan, R.O.C.

Tel : 886-3-5642000

Fax : 886-3-5642050

Taipei Branch :

7F, No. 137, Lane 235, Pac Chiao Rd.,

Hsin Tien City, Taipei Hsien, Taiwan, R. O. C.

Tel : 886-2-89191368

Fax : 886-2-89191369