QM8020AP

N-Ch 80V Fast Switching MOSFETs

General Description

The QM8020AP is the highest performance trench N-ch MOSFETs with extreme high cell density , which provide excellent RDSON and gate charge for most of the synchronous buck converter applications .

The QM8020AP meet the RoHS and Green Product requirement , 100% EAS guaranteed with full function reliability approved.

Features

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- 100% EAS Guaranteed
- Green Device Available

Product Summery

Green

BVDSS	RDSON	ID
80V	5.2mΩ	163A

Applications

- High Frequency Point-of-Load Synchronous Buck Converter
- Networking DC-DC Power System
- Power Tool Application

TO220 Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	80	V
V_{GS}	Gate-Source Voltage	±20	V
I_D@T_C=25℃	Continuous Drain Current, V_{GS} @ 10V[1,7]	163	A
I_D@T_C=100℃	Continuous Drain Current, V_{GS} @ 10V[1,7]	103	A
I_D@T_A=25℃	Continuous Drain Current, V_{GS} @ 10V[1]	14.3	A
I_D@T_A=70℃	Continuous Drain Current, V_{GS} @ 10V[1]	11.5	A
I_{DM}	Pulsed Drain Current[2]	350	A
EAS	Single Pulse Avalanche Energy[3]	750	mJ
I_{AS}	Avalanche Current	108	A
P_D@T_C=25℃	Total Power Dissipation[4]	260	W
P_D@T_A=25℃	Total Power Dissipation[4]	2.02	W
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-Ambient [1]	---	62	℃/W
$R_{\theta JC}$	Thermal Resistance Junction-Case[1]	---	0.48	℃/W

Electrical Characteristics (T_J=25 ℃, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V , I_D=250uA	80	---	---	V
$\triangle BV_{DSS}/\triangle T_J$	BV_{DSS} Temperature Coefficient	Reference to 25℃ , I_D=1mA	---	0.078	---	V/℃
$R_{DS(ON)}$	Static Drain-Source On-Resistance[2]	V_{GS}=10V , I_D=30A	---	4	5.2	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{GS}=V_{DS} , I_D =250uA	2.5	---	4.5	V
$\triangle V_{GS(th)}$	$V_{GS(th)}$ Temperature Coefficient		---	-7.7	---	mV/℃
I_{DSS}	Drain-Source Leakage Current	V_{DS}=64V , V_{GS}=0V , T_J=25℃	---	---	1	uA
		V_{DS}=64V , V_{GS}=0V , T_J=55℃	---	---	5	
I_{GSS}	Gate-Source Leakage Current	V_{GS}=±20V , V_{DS}=0V	---	---	±100	nA
gfs	Forward Transconductance	V_{DS}=5V , I_D=30A	---	98	---	S
R_g	Gate Resistance	V_{DS}=0V , V_{GS}=0V , f=1MHz	---	2.8	5.6	Ω
Q_g	Total Gate Charge (10V)	V_{DS}=60V , V_{GS}=10V , I_D=15A	---	87		nC
Q_{gs}	Gate-Source Charge		---	23.7		
Q_{gd}	Gate-Drain Charge		---	22.4		
$T_{d(on)}$	Turn-On Delay Time	V_{DD}=30V , V_{GS}=10V , R_G=3.3Ω, I_D=15A	---	30		ns
T_r	Rise Time		---	56		
$T_{d(off)}$	Turn-Off Delay Time		---	60.4		
T_f	Fall Time		---	21.2		
C_{iss}	Input Capacitance	V_{DS}=15V , V_{GS}=0V , f=1MHz	---	6735		pF
C_{oss}	Output Capacitance		---	1350		
C_{rss}	Reverse Transfer Capacitance		---	312		

Guaranteed Avalanche Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
EAS	Single Pulse Avalanche Energy[5]	V_{DD}=50V , L=0.1mH , I_{AS}=30A	59.6	---	---	mJ

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current[1,6]	V_G=V_D=0V , Force Current	---	---	163	A
I_{SM}	Pulsed Source Current[2,6]		---	---	350	A
V_{SD}	Diode Forward Voltage[2]	V_{GS}=0V , I_S=A , T_J=25℃	---	---	1.2	V
t_{rr}	Reverse Recovery Time	IF=15A , dI/dt=100A/μs , T_J=25℃	---	51	---	nS
Q_{rr}	Reverse Recovery Charge		---	90	---	nC

Note :
1.The data tested by surface mounted on a 1 inch^2 FR-4 board with 2OZ copper.
2.The data tested by pulsed , pulse width ≦ 300us , duty cycle ≦ 2%
3.The EAS data shows Max. rating . The test condition is V_{DD}=50V,V_{GS}=10V,L=0.1mH,I_{AS}=108A
4.The power dissipation is limited by 150℃ junction temperature
5.The Min. value is 100% EAS tested guarantee.
6.The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.
7.Calculated continuous current based on maximum allowable junction temperature. Package limitation current is 120A.

Typical Characteristics



Fig.1 Typical Output Characteristics



Fig.2 On-Resistance v.s Gate-Source



Fig.3 Forward Characteristics of Reverse



Fig.4 Gate-Charge Characteristics



Fig.5 Normalized $V_{GS(th)}$ v.s T_J



Fig.6 Normalized R_{DSON} v.s T_J



Fig.7 Capacitance



Fig.8 Safe Operating Area



Fig.9 Normalized Maximum Transient Thermal Impedance



Fig.10 Switching Time Waveform



Fig.11 Unclamped Inductive Switching Waveform