杰力科技股份有限公司
Excelliance MOS Corporation

EMBB0N10J

N-Channel Logic Level Enhancement Mode Field Effect Transistor

Product Summary:

BV_{DSS}	100V
$R_{DSON\ (MAX.)}$	220mΩ
I_D	1.4A



UIS 100% Tested

Pb-Free Lead Plating & Halogen Free

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNIT
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_C = 25 °C	I_D	1.4	A
	T_C = 100 °C		0.85	
Pulsed Drain Current[1]		I_{DM}	5.6	
Power Dissipation	T_C = 25 °C	P_D	1.5	W
	T_C = 100 °C		1	
Operating Junction & Storage Temperature Range		T_j, T_{stg}	-55 to 175	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to- Ambient	$R_{\theta JA}$		100	°C / W

[1]Pulse width limited by maximum junction temperature.

[2]Duty cycle ≤ 1%

ELECTRICAL CHARACTERISTICS (T_C = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = 250μA	100			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250μA	1	1.5	3	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0V, V_{GS} = ±20V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 80V, V_{GS} = 0V			1	μA
		V_{DS} = 70V, V_{GS} = 0V, T_J = 125 °C			25	
On-State Drain Current[1]	$I_{D(ON)}$	V_{DS} = 5V, V_{GS} = 10V	3			A
Drain-Source On-State Resistance[1]	$R_{DS(ON)}$	V_{GS} = 10V, I_D = 1.4A		185	220	mΩ
		V_{GS} = 5V, I_D = 0.5A		205	250	
Forward Transconductance[1]	g_{fs}	V_{DS} = 5V, I_D = 1.4A		4		S
DYNAMIC						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = 50V, f = 1MHz		858		pF
Output Capacitance	C_{oss}			22		
Reverse Transfer Capacitance	C_{rss}			16		
Total Gate Charge[1,2]	Q_g	V_{DS} = 15V, V_{GS} = 10V, I_D = 1.4A		20		nC
Gate-Source Charge[1,2]	Q_{gs}			4		
Gate-Drain Charge[1,2]	Q_{gd}			5		
Turn-On Delay Time[1,2]	$t_{d(on)}$	V_{DS} = 15V, I_D = 1A, V_{GS} = 10V, R_{GS} = 6Ω		20		nS
Rise Time[1,2]	t_r			40		
Turn-Off Delay Time[1,2]	$t_{d(off)}$			36		
Fall Time[1,2]	t_f			30		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_C = 25 °C)						
Continuous Current	I_S				1.4	A
Pulsed Current[3]	I_{SM}				5.6	
Forward Voltage[1]	V_{SD}	I_F = I_S, V_{GS} = 0V			1.2	V
Reverse Recovery Time	t_{rr}			50		nS
Reverse Recovery Charge	Q_{rr}			90		nC

[1]Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

[2]Independent of operating temperature.

[3]Pulse width limited by maximum junction temperature.

On-Region Characteristics



On-Resistance Variation with Drain Current and Gate Voltage



On-Resistance Variation with Temperature



On-Resistance Variation with Gate-Source Voltage



Transfer Characteristics



Body Diode Forward Voltage Variation
with Source Current and Temperature



Gate Charge Characteristics



Capacitance Characteristics



Maximum Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve



Ordering & Marking Information:

Device Name: EMBB0N10J for SOT-23



1C: Device Code, 1C for EMBB0N10J

ABC: Date Code

Outline Drawing



Dimension in mm

Dimension	A	A1	A2	b	C	D	E	E1	e	e1	L1
Min.	0.85	0		0.30	0.08	2.75	2.6	1.35			0.35
Typ.			0.80						0.95	1.90	
Max.	1.25	0.13		0.50	0.20	3.10	3.0	1.80			0.75

Footprint