

156. Binary Tree Upside Down

Question


My Submissions (/problems/binary-tree-upside-down/submissions/)

Total Accepted: **7960** Total Submissions: **21522** Difficulty: **Medium**


Given a binary tree where all the right nodes are either leaf nodes with a sibling (a left node that shares the same parent node) or empty, flip it upside down and turn it into a tree where the original right nodes turned into left leaf nodes. Return the new root.

For example:

Given a binary tree {1,2,3,4,5} ,



return the root of the binary tree [4,5,2,##,3,1] .



confused what "{1, #, 2, 3}" means? > read more on how binary tree is serialized on OJ.

Show Tags

Show Similar Problems

Have you met this question in a real interview?

Discuss (/discuss/questions/oj/binary-tree-upside-down)

C++



```

1 /** ✉ Send Feedback (mailto:admin@leetcode.com?subject=Feedback)
2  * Definition for a binary tree node.

```

```
3  * struct TreeNode {
4  *      int val;
5  *      TreeNode *left;
6  *      TreeNode *right;
7  *      TreeNode(int x) : val(x), left(NULL), right(NULL) {}
8  * };
9  */
10 class Solution {
11 public:
12     TreeNode* upsideDownBinaryTree(TreeNode* root) {
13
14     }
15 };
```

Custom Testcase ☐

Run Code

Submit Solution

[Frequently Asked Questions \(/faq/\)](#) | [Terms of Service \(/tos/\)](#)

[Privacy](#)

Copyright © 2016 LeetCode