


class07

AUTHOR

Ziheng Huang

Test data:

```
tmp <- c(rnorm(30,-3),rnorm(30,3))  
x <- cbind(x=tmp,y=rev(tmp))  
plot(x)
```



K-means Clustering

kmeans()

```
km <- kmeans(x,centers=2,nstart=20)  
km
```

K-means clustering with 2 clusters of sizes 30, 30

Cluster means:

	x	y
1	3.138279	-2.864207
2	-2.864207	3.138279

```
2 -2.864207 3.138279
```

Clustering vector:

```
[1] 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 1 1 1 1 1 1 1 1
[39] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
```

Within cluster sum of squares by cluster:

```
[1] 56.88259 56.88259
(between_SS / total_SS = 90.5 %)
```

Available components:

```
[1] "cluster"      "centers"      "totss"        "withinss"     "tot.withinss"
[6] "betweenss"    "size"         "iter"         "ifault"       "
```

Q: points in cluster

```
km$size
```

```
[1] 30 30
```

Q: cluster assignment, center

```
km$cluster
```


```
[1] 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 1 1 1 1 1 1 1 1
[39] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
```

```
km$centers
```

```
      x      y
1  3.138279 -2.864207
2 -2.864207  3.138279
```

Q: plot clusters, centers

```
plot(x,col=km$cluster)
points(km$centers,col='blue',pch=15)
```




hclust()

```
hc <- hclust(dist(x))
```

plot() for hc

```
plot(hc)
```

Cluster Dendrogram



get cluster groupings for hc, cut the tree with height

```
cutree(hc, h=8)
```


```
[1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2
[39] 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
```

use cutree with k=2

```
grps <- cutree(hc, k=2)
```

plot

```
plot(x, col=grps)
```



1. PCA of UK food data

load data

```
url <- "https://tinyurl.com/UK-foods"  
x <- read.csv(url)
```

Q1: rows/cols

```
dim(x)
```

```
[1] 17  5
```

fixed row/col num

```
x <- read.csv(url, row.names=1)  
head(x)
```


	England	Wales	Scotland	N.Ireland
Cheese	105	103	103	66
Carcass_meat	245	227	242	267

Other_meat	685	803	750	586
Fish	147	160	122	93
Fats_and_oils	193	235	184	209
Sugars	156	175	147	139

Q2: Which approach to solving the 'row-names problem' mentioned above do you prefer and why? Is one approach more robust than another under certain circumstances?


I like the second approach. first approach is a hack.

```
barplot(as.matrix(x), beside=T, col=rainbow(nrow(x)))
```




Q3: Changing what optional argument in the above **barplot()** function results in the following plot?

```
barplot(as.matrix(x), beside=FALSE, col=rainbow(nrow(x)))
```



Q5: Generating all pairwise plots may help somewhat. Can you make sense of the following code and resulting figure? What does it mean if a given point lies on the diagonal for a given plot?

```
pairs(x, col=rainbow(10), pch=16)
```



lying on diagonal means the two values are same

Q6. What is the main differences between N. Ireland and the other countries of the UK in terms of this data-set?

little fruit, lots of potato

PCA starts here


```
pca <- prcomp( t(x) )
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4
Standard deviation	324.1502	212.7478	73.87622	5.552e-14
Proportion of Variance	0.6744	0.2905	0.03503	0.000e+00
Cumulative Proportion	0.6744	0.9650	1.00000	1.000e+00


Q7. Complete the code below to generate a plot of PC1 vs PC2. The second line adds text labels over the data points.

```
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2", xlim=c(-270,500))
text(pca$x[,1], pca$x[,2], colnames(x))
```

Q8. Customize your plot so that the colors of the country names match the colors in our UK and Ireland map and table at start of this document.


```
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2", xlim=c(-270,500))  
text(pca$x[,1], pca$x[,2], colnames(x),col=c('orange','red','blue','darkgreen'))
```



```
v <- round( pca$sdev^2/sum(pca$sdev^2) * 100 )
z <- summary(pca)
z$importance
```


	PC1	PC2	PC3	PC4
Standard deviation	324.15019	212.74780	73.87622	5.551558e-14
Proportion of Variance	0.67444	0.29052	0.03503	0.000000e+00
Cumulative Proportion	0.67444	0.96497	1.00000	1.000000e+00

```
barplot(v, xlab="Principal Component", ylab="Percent Variation")
```




Variable loading: PCA1

```
par(mar=c(10, 3, 0.35, 0))  
barplot( pca$rotation[,1], las=2 )
```




Q9: Variable loading: PCA2

```
par(mar=c(10, 3, 0.35, 0))  
barplot( pca$rotation[,2], las=2 )
```



Biplot:

```
biplot(pca)
```



2. PCA of RNA-seq data

```
url2 <- "https://tinyurl.com/expression-CSV"
rna.data <- read.csv(url2, row.names=1)
head(rna.data)
```

	wt1	wt2	wt3	wt4	wt5	ko1	ko2	ko3	ko4	ko5
gene1	439	458	408	429	420	90	88	86	90	93
gene2	219	200	204	210	187	427	423	434	433	426
gene3	1006	989	1030	1017	973	252	237	238	226	210
gene4	783	792	829	856	760	849	856	835	885	894
gene5	181	249	204	244	225	277	305	272	270	279
gene6	460	502	491	491	493	612	594	577	618	638


Q10: How many genes and samples are in this data set? 100 gene, 10 samples

```
dim(rna.data)
```

```
[1] 100 10
```

```
## Again we have to take the transpose of our data
pca <- prcomp(t(rna.data), scale=TRUE)

## Simple un polished plot of pc1 and pc2
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2")
```



```
summary(pca)
```


Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	9.6237	1.5198	1.05787	1.05203	0.88062	0.82545	0.80111
Proportion of Variance	0.9262	0.0231	0.01119	0.01107	0.00775	0.00681	0.00642
Cumulative Proportion	0.9262	0.9493	0.96045	0.97152	0.97928	0.98609	0.99251

	PC8	PC9	PC10
Standard deviation	0.62065	0.60342	3.327e-15
Proportion of Variance	0.00385	0.00364	0.000e+00
Cumulative Proportion	0.99636	1.00000	1.000e+00

```
plot(pca, main="Quick scree plot")
```

Quick scree plot




```
## Variance captured per PC
pca.var <- pca$sdev^2

## Percent variance is often more informative to look at
pca.var.per <- round(pca.var/sum(pca.var)*100, 1)
pca.var.per
```

```
[1] 92.6  2.3  1.1  1.1  0.8  0.7  0.6  0.4  0.4  0.0
```

```
barplot(pca.var.per, main="Scree Plot",
        names.arg = paste0("PC", 1:10),
        xlab="Principal Component", ylab="Percent Variation")
```



Scree Plot



```
## A vector of colors for wt and ko samples
colvec <- colnames(rna.data)
colvec[grep("wt", colvec)] <- "red"
colvec[grep("ko", colvec)] <- "blue"

plot(pca$x[,1], pca$x[,2], col=colvec, pch=16,
     xlab=paste0("PC1 (", pca.var.per[1], "%)"),
     ylab=paste0("PC2 (", pca.var.per[2], "%)"))

text(pca$x[,1], pca$x[,2], labels = colnames(rna.data), pos=c(rep(4,5), rep(2,5)))
```



Plot with GGPLOT:

```
library(ggplot2)


df <- as.data.frame(pca$x)

df$samples <- colnames(rna.data)
df$condition <- substr(colnames(rna.data),1,2)

p <- ggplot(df) +
  aes(PC1, PC2, label=samples, col=condition) +
  geom_label(show.legend = FALSE)
p + labs(title="PCA of RNASeq Data",
  subtitle = "PC1 clearly separates wild-type from knock-out samples",
  x=paste0("PC1 (", pca.var.per[1], "%)"),
  y=paste0("PC2 (", pca.var.per[2], "%)"),
  caption="Class example data") +
  theme_bw()
```

PCA of RNASeq Data

PC1 clearly separates wild-type from knock-out samples



Class example data

Gene loadings

```
loading_scores <- pca$rotation[,1]

## Find the top 10 measurements (genes) that contribute
## most to PC1 in either direction (+ or -)
gene_scores <- abs(loading_scores)
gene_score_ranked <- sort(gene_scores, decreasing=TRUE)

## show the names of the top 10 genes
top_10_genes <- names(gene_score_ranked[1:10])
top_10_genes
```

```
[1] "gene100" "gene66" "gene45" "gene68" "gene98" "gene60" "gene21"
[8] "gene56" "gene10" "gene90"
```