

Attention and BERT

Alexandre Allauzen

Fall 2023



Roadmap

Introduction to attention

Transformer architecture

Conclusion

References

Outline

Introduction to attention


Transformer architecture

Conclusion


References

From Embeddings to Contextualized Embeddings


Static word embeddings



Contextualized representation with bi-recurrent encoder:



Draw attention for classification



- $\mathbf{a} = (a_i)$, $\sum_{i=1}^L a_i = 1$ and $0 \leq a_i \leq 1$
- \mathbf{a} : attention vector for the "query" \mathbf{q} and the "keys" \mathbf{X} .
- \mathbf{q} is a vector to be learnt [8, 5]

Attention to weight inputs

- $\mathbf{a} = X\mathbf{q}$ is the attention vector

$$\mathbf{h} = \sum_{i=1}^L a_i \mathbf{x}_i = \mathbf{aX}$$

- A new vector, focused on the classification task (\mathbf{q})
- To summarize:


$$\mathbf{h} = \text{softmax}(\mathbf{X}\mathbf{q})\mathbf{X} \rightarrow \text{classification}$$

Issues:

- Scale the dot product
- \mathbf{X} is involved everywhere !

Basic attention mechanism for classification


this movie was a great experience




$$\mathbf{h} = \text{softmax} \left(\frac{\mathbf{K}\mathbf{q}}{\sqrt{d}} \right)^t \mathbf{V}$$

- \mathbf{X} can be static emb.
- Derived from bi-LSTM
- \mathbf{q} is learnt as a target for selection
- $pa = \mathbf{K}\mathbf{q}$: selection in \mathbf{V}

In a few dates



Bigger is ...



Outline

Introduction to attention

Transformer architecture

Conclusion

References

Contextualized word embeddings

Consider the word **driver**:

the audio **driver** is really outdated
the **driver** exceeded the speed limit

Contextualized word embeddings

Consider the word **driver**:


the audio **driver** is really outdated
the **driver** exceeded the speed limit

The context

The	■	The	■	$\lambda_{1,2}$
audio	■■■	driver	■■■■■	$\lambda_{2,2}$
driver	■■■■■	exceeded	■	$\lambda_{3,2}$
is	■	the	■	$\lambda_{4,2}$
really	■	speed	■■■	$\lambda_{5,2}$
outdated	■■■	limit	■	$\lambda_{6,2}$

Self attention


Consider the word **driver**:



- $(\lambda_{i,j})$ are the attention coefficients, $\sum_i \lambda_{i,j} = 1$, and
- Reflects the influence of \mathbf{x}_i on \mathbf{x}_j (transformed version)


Transformer : Queries, Keys, Values

the driver exceeded the speed limit




Tranformer : Attention matrix

The distance matrix between Q and K



Scaled Dot-Product Attention

$$\mathbf{Z} = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^t}{\sqrt{d}}\right)\mathbf{V} =$$



QKV and Metric Learning

$$\begin{aligned}\mathbf{Q}\mathbf{K}^t &= \mathbf{X}\mathbf{W}_K \times (\mathbf{X}\mathbf{W}_K)^t = \mathbf{X}\mathbf{W}_Q \times (\mathbf{W}_K^t \mathbf{X}^t) \\ &= \mathbf{X}\mathbf{M}\mathbf{X}^t\end{aligned}$$

- If \mathbf{M} would be PSD, it is a metric.
- Otherwise, it is a transformed similarity (bilinear similarity)

\mathbf{M} is learnt: a transformer block learns its own similarity.

Multi-head attention (with 2 heads)




Putting all together (with more tricks)


Transformer block

From [7]

- Inputs is \mathbf{X}
- Positional embeddings
- Multihead attention
- Residual connections [4]
- Layer Normalization [2]
- Final filtering



Positional embeddings




- Originally "absolute"
- Can be learnt [3, 1]
- Or relative [6]

(figure generated by the following code


```
https://github.com/jalammar/jalammar.github.io/blob/master/notebooks/  
transformer/transformer\_positional\_encoding\_graph.ipynb)
```

A Transformer layer




Transformer layers can be stacked !

Pre-training as a (Masked) language model




BERT Encoder for text classification



Transformers / bi-lstm encoders

Reminder of bi-recurrent encoder



The difference

- Two different ways to encode the dependence
- Richer for attention since we stack transformers
- all the deep-learning tricks \Rightarrow over-parametrization

Outline

Introduction to attention

Transformer architecture

Conclusion

References

Transformers are everywhere

State of the art encoder

- For text !
- And also for speech, DNA, vision, ...

Also a powerful generator

- For text (GPT, ...)
- Speech, ... sequences

Outline

Introduction to attention

Transformer architecture

Conclusion

References

- [1] Rami Al-Rfou et al. *Character-Level Language Modeling with Deeper Self-Attention*. 2018. arXiv: 1808.04444 [cs.CL].
- [2] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. *Layer Normalization*. 2016. arXiv: 1607.06450 [stat.ML].
- [3] Jonas Gehring et al. “Convolutional Sequence to Sequence Learning”. In: *CoRR* abs/1705.03122 (2017). arXiv: 1705.03122. URL: <http://arxiv.org/abs/1705.03122>.
- [4] Kaiming He et al. “Deep Residual Learning for Image Recognition”. In: *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. 2016, pp. 770–778. arXiv: 1512.03385 [cs.CV].
- [5] Zhouhan Lin et al. “A STRUCTURED SELF-ATTENTIVE SENTENCE EMBEDDING”. In: *International Conference on Learning Representations*. 2017. URL: https://openreview.net/forum?id=BJC_jUqxe.
- [6] Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. *Self-Attention with Relative Position Representations*. 2018. arXiv: 1803.02155 [cs.CL].
- [7] Ashish Vaswani et al. “Attention is All you Need”. In: *Advances in Neural Information Processing Systems 30*. Ed. by I. Guyon et al. Curran Associates, Inc., 2017, pp. 6000–6010. URL: <http://papers.nips.cc/paper/7181-attention-is-all-you-need.pdf>.
- [8] Zichao Yang et al. “Hierarchical Attention Networks for Document Classification”. In: *Proceedings of the North American Chapter of the Association for Computational Linguistics (NAACL)*.