

<https://www.overleaf.com/project/654921273e7a71dc9effd402>

Master IASD
Data Science Lab
Generative adversarial network

ganier:

Mehdi Maaninou, Zhe Huang, Insaf Medjaouri

November 2023

Table of content

1 Introduction

2 Vanilla GAN

3 Wasserstein GAN

Introduction

Problem Statement

- **MNIST** : Hand-written digit images ranging from 0 to 9.
- **Objective** : Training a Generative Adversarial Network (GAN) to generate 10K synthetic samples from the MNIST dataset.
- **Evaluation Metric** : The Frechet Inception Distance (FID) :

$$FID = \sqrt{\sum_i (\mu_1(i) - \mu_2(i))^2 + \text{Tr}(C_1 + C_2 - 2\sqrt{C_1 C_2})}$$

where $\mu_1(i)$ and $\mu_2(i)$ represent means and C_1 and C_2 represent covariances of features in real and generated samples, respectively.

Training and Results (Vanilla GAN)

| Hyperparameters | Training Time (s) | FID | Precision | Recall |
|------------------|-------------------|--------|-----------|--------|
| Default values | 106.2 | 379.21 | 0.0 | 0.0 |
| Optimized values | 113.74 | 42.5 | 0.57 | 0.22 |



Figure – Generated by model trained with default Hyperparameters




Figure – Generated by model trained with optimized hyperparameters

Vanilla GAN

Structure






Figure – Structure of a Vanilla Generative Adversarial Network (GAN)


Problems



(a) Figure 1
Mode collapse



(b) Figure 2
Vanishing Gradient



(c) Figure 3
Nash Equilibrium

Figure – Common problems in training GANs.

Wasserstein GAN

Structure




Figure – Structure of a Wasserstein GAN (WGAN)

- **W-Loss** : $L = \min_g \max_f \mathbb{E}(f(x)) - \mathbb{E}(f(g(z)))$

solution to problems

- **Vanishing gradient** : critic function needs to be **K-Lipschitz continuous**
 - weight clipping : forces the weight of critic to a fixed interval $[-c, c]$
 - regularization term : penalize gradient far from **K**

$$\lambda (\|\nabla f(\hat{x})\|_2 - K)^2$$

where $\hat{x} = \varepsilon x + (1 - \varepsilon)g(z)$

- **Mode collapse** : The Wasserstein loss in WGANs is more informative and continuous and encourages diverse data distribution coverage, unlike the binary cross-entropy loss in traditional GANs that may lead to single-mode focus.

Bibliography

- [1] Lilian Weng. (2017). *From GAN to WGAN* [Blog Post].
<https://lilianweng.github.io/posts/2017-08-20-gan/>
- [2] Martin Arjovsky, Soumith Chintala, Léon Bottou. (2017).
Wasserstein GAN [Research Paper].
<https://arxiv.org/abs/1701.07875>