

# Fully convolutional neural networks

E. Decencière

MINES ParisTech  
PSL Research University  
Center for Mathematical Morphology



# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion

# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion

# Image definition

## Definition

Here an image is a 2D array of size  $p \times q$ . Each array element belongs to  $\mathbb{R}^d$ . The dimension of the value space  $d$ , is often called the **number of channels** of the image.  
The set of these images is noted  $\mathcal{I}^d$ .

## Examples





Figure:  $28 \times 28$  grey level image ( $d = 1$ ) from the MNIST data set, and  $481 \times 321$  colour image ( $d = 3$ ) from the Berkeley segmentation data set.


# Learning image transformations

- An image classification task is a function from the set of considered images into a set of labels




# Learning image transformations

- An image classification task is a function from the set of considered images into a set of labels



- In many applications, we want to transform an image into another image



# Image-to-image translation


Definition: image-to-image translation

An image-to-image operator is a function that transforms an image into another image of same size:

$$F : \mathcal{I}^{d_1} \longrightarrow \mathcal{I}^{d_2}$$


$$I \longmapsto J$$

Note that the number of channels of input and output images can be different.



# Examples


## Bulge / disk decomposition



(Credits: Tuccillo, Huertas-Company, Velasco-Forero, Decencière)

# Examples

## Bulge / disk decomposition



(Credits: Tuccillo, Huertas-Company, Velasco-Forero, Decencière)

## Deblurring network [Hradiš et al., 2015]

where subscript  $j$  indicates  
ated vector, and  $L_j(z; u) =$   
and  $e_j \in \mathbb{R}^{64}$  is the vector  
all others be 0. The coordi  
marized in Algorithm I.


Note that  $g_j(z)$  is not  
we calculate the Newton di  
second-order approximation  
and solve

where subscript  $j$  indicates  
ated vector, and  $L_j(z; u) =$   
and  $e_j \in \mathbb{R}^{64}$  is the vector  
all others be 0. The coordi  
marized in Algorithm I.


Note that  $g_j(z)$  is not  
we calculate the Newton di  
second-order approximation  
and solve

# Counting cells


Best count






real density map



Inferred density map




Worst count



Credits: Tristan Lazard, master thesis.  
Images: L'Oréal.

# Microscopy cross-modality prediction [Ounkomol et al., 2018]



# Image segmentation

- Image segmentation is often an important step in an image processing work flow
- Image segmentation has been a very active deep learning research field

## Example




## Other applications

- Image filtering
- Style modification
- Motion estimation
- etc ...



# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion


## From classification nets to image-to-image nets





## From classification nets to image-to-image nets




## From classification nets to image-to-image nets




## From classification nets to image-to-image nets



## From classification nets to image-to-image nets




## From classification nets to image-to-image nets



- The neuron membrane segmentation challenge winner [Cireşan et al., 2012] used this strategy. It is inefficient.
- The idea to compute the whole output image with a single pass through the network had already been proposed [Feng Ning et al., 2005, Jain et al., 2007] (but with architectures more complex than those used today).


# The simplest image-to-image architecture

Example: plain CNN [Pang et al., 2010]



# The simplest image-to-image architecture

Example: plain CNN [Pang et al., 2010]




Note that today we would use ReLU activations on all layers except the last.

How many parameters does the first layer contain? The last? The second?

# The simplest image-to-image architecture

Example: plain CNN [Pang et al., 2010]




Note that today we would use ReLU activations on all layers except the last.


How many parameters does the first layer contain? The last? The second?

$$(9 + 1) \times d ; 9d + 1 ; (9d + 1) \times d$$


## Going back to the original image size



## Going back to the original image size




## Going back to the original image size




## Upsampling techniques

- Replication
- Transposed convolution
- Pooling index memorization



## Upsampling through replication






# Transposed convolution



# Transposed convolution



# Transposed convolution



# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
  - Receptive field
  - Translation equivariance
  - Other properties
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion

# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
  - Receptive field
  - Translation equivariance
  - Other properties
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion

# Receptive field

## Definition: links between neurons

In a NN, we say that neuron  $a$  is linked to neuron  $b$  if there is an oriented path in the corresponding graph going from  $a$  to  $b$ .


## Definition

The **receptive field** of a neuron in a NN is the set of *input neurons* that are linked to that neuron.


The size of the receptive field is an essential property when designing a fully-convolutional NN architecture.

Note that in most cases, receptive fields are square shaped (border effects ignored).


## Illustration




## Illustration



## Illustration




## Example



What is the width of the receptive field of the neurons in the last layer?

- ①  $n$
- ②  $1 + 2 \times n$
- ③  $1 + 2 \times (n + 1)$
- ④ It depends on the input image

## Example




What is the width of the receptive field of the neurons in the last layer?

- ①  $n$
- ②  $1 + 2 \times n$
- ③  $1 + 2 \times (n + 1)$
- ④ It depends on the input image

Answer:  $1 + 2 \times (n + 1)$

# Effective receptive field: intuition



## Criterion

For a given output neuron  $y$ , what criterion seems sound to estimate the impact of a pixel  $x_{i,j}$  of its receptive field on its value?

## Criterion


For a given output neuron  $y$ , what criterion seems sound to estimate the impact of a pixel  $x_{i,j}$  of its receptive field on its value?

$$\frac{\partial y}{\partial x_{i,j}}$$

# Effective receptive field

## Shape of the effective receptive field

- Under some simplification hypotheses, the authors of [Luo et al., 2017] have shown that the effective receptive field has a gaussian shape.
- They have experimentally checked that this is (approximately) the case
- Moreover, as the network gets deeper, the size of the effective receptive field gets proportionally smaller



## Conclusion on the receptive field

When choosing or designing a NN architecture:

- Establish its minimal required size with respect to the application
- Make it larger than that...

# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
  - Receptive field
  - **Translation equivariance**
  - Other properties
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion

# Equivariance

## Definition

A function  $f : E \longrightarrow F$  is **equivariant** with respect to the functions  $t_E : E \longrightarrow E$  and  $t_F : F \longrightarrow F$  iff  $\forall x \in E$ :

$$f(t_E(x)) = t_F(f(x))$$

## Translation equivariance

- When  $E = F$  and  $t_E$  and  $t_F$  are the same, any, translation, then we have *translation equivariance*.
- Translation equivariance is an often sought property for image processing operators.
- Note that we often abusively say *invariant* to translation instead of *equivariant* to translation.
- Given that in all practical cases images are defined on a bounded set, this property is only true “far enough” from the borders

# Quizz

Which operator is NOT translation equivariant?

- ① Convolution ( $\text{stride} = 1$ )
- ② Max-pooling ( $\text{stride} > 1$ )
- ③ Transposed convolution ( $\text{stride} \geq 1$ )
- ④ Upsampling ( $\text{stride} > 1$ )

# Translation equivariant operators

<b>Operator</b>	<b>Translation equivariant</b>
Convolution (stride= 1)	
Max-pooling (stride > 1)	
Transposed convolution (stride $\geq$ 1)	
Upsampling (stride> 1)	

# Translation equivariant operators

Operator	Translation equivariant
Convolution (stride= 1)	yes
Max-pooling (stride > 1)	
Transposed convolution (stride $\geq$ 1)	
Upsampling (stride> 1)	

# Translation equivariant operators

Operator	Translation equivariant
Convolution (stride= 1)	yes
Max-pooling (stride > 1)	no
Transposed convolution (stride $\geq$ 1)	
Upsampling (stride> 1)	

# Translation equivariant operators

Operator	Translation equivariant
Convolution (stride= 1)	yes
Max-pooling (stride > 1)	no
Transposed convolution (stride $\geq$ 1)	yes
Upsampling (stride> 1)	

# Translation equivariant operators

Operator	Translation equivariant
Convolution (stride= 1)	yes
Max-pooling (stride > 1)	no
Transposed convolution (stride $\geq$ 1)	yes
Upsampling (stride> 1)	yes

## Translation equivariance: comments

- If padding is used in the network, border effects can be important.

## Translation equivariance: comments

- If padding is used in the network, border effects can be important.
- Translation equivariance is not always welcome!

## Translation equivariance: comments

- If padding is used in the network, border effects can be important.
- Translation equivariance is not always welcome!
- Position information can also be used in the network:

## Translation equivariance: comments

- If padding is used in the network, border effects can be important.
- Translation equivariance is not always welcome!
- Position information can also be used in the network:
  - Through masks or segmentations

## Translation equivariance: comments

- If padding is used in the network, border effects can be important.
- Translation equivariance is not always welcome!
- Position information can also be used in the network:
  - Through masks or segmentations
  - Through pixel coordinates

## Illustration



When aiming to segment the papilla or the macula, translation equivariance is not necessarily welcome.

# Contents

1 Introduction

2 From classification to image-to-image translation

3 Properties of fully-convolutional neural networks

- Receptive field
- Translation equivariance
- Other properties

4 Image segmentation

5 Using fully-convolutional networks

6 Conclusion

## Image size flexibility

- A NN containing fully-connected layers can only process images of a given size.

## Image size flexibility

- A NN containing fully-connected layers can only process images of a given size.
- A **fully convolutional NN** can be applied to images of any size, as long as its dimensions are compatible with the subsampling steps of the network.

## Image size flexibility

- A NN containing fully-connected layers can only process images of a given size.
- A **fully convolutional NN** can be applied to images of any size, as long as its dimensions are compatible with the subsampling steps of the network.
- Practical limit: the memory of the system.

## Image size flexibility

- A NN containing fully-connected layers can only process images of a given size.
- A fully convolutional NN can be applied to images of any size, as long as its dimensions are compatible with the subsampling steps of the network.
- Practical limit: the memory of the system.
- Note that as the input image gets larger, border effects become proportionally less present.

# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
  - Binary segmentation
  - Semantic segmentation
  - Instance segmentation
  - U-Net
- 5 Using fully-convolutional networks
- 6 Conclusion

# The specific case of image segmentation

## Definition: image segmentation

Let  $I$  be an image defined on  $D$ . A segmentation of  $I$  is a partition of  $D$ . In practice the regions of the segmentation should correspond to the objects in  $I$ , which is application dependant.

- A partition is often represented as a labelled image
- In order to make the segments symmetric, each one is represented by a different channel

## Image segmentation example



Credits: Pascal VOC database

## Some vocabulary on segmentation


- **Object detection / localization:** bounding box around the object(s).
- **Binary segmentation:** segmentation in 2 classes, background and object.
- **Semantic segmentation:** a label is given to each pixel, according to the object it belongs to.
- **Instance segmentation:** identify each separate object, even if they belong to the same class.

# Contents


- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
  - Binary segmentation
  - Semantic segmentation
  - Instance segmentation
  - U-Net
- 5 Using fully-convolutional networks
- 6 Conclusion

# Neuron membrane segmentation challenge (ISBI 2012)

- Train: single stack of size  $30 \times 512 \times 512$ .
- Test: a second stack of same size.



# Neuron membrane segmentation challenge winner [Cireşan et al., 2012]




# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
  - Binary segmentation
  - **Semantic segmentation**
  - Instance segmentation
  - U-Net
- 5 Using fully-convolutional networks
- 6 Conclusion

# Pascal visual object classes segmentation challenge 2012 [Everingham et al., 2014]

- 1464 training and 1449 validation images
- automatic online test, with unknown images
- 20 image categories (cat, sofa, motorbike, person, etc.)



# Convolutional nets for semantic image segmentation

Three papers in 2015:

- Fully convolutional networks for semantic segmentation [Long et al., 2015]
- U-Net: convolutional networks for biomedical image segmentation [Ronneberger et al., 2015]
- SegNet: A Deep Convolutional Encoder-Decoder Architecture for Image Segmentation [Badrinarayanan et al., 2015]

## Remarks

- These architectures easily contain a number of parameters of the order of  $10^7$  (28 million for U-Net)
- Their optimization might be difficult
- But you can reduce the number of filters or the number of layers

# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
  - Binary segmentation
  - Semantic segmentation
  - **Instance segmentation**
  - U-Net
- 5 Using fully-convolutional networks
- 6 Conclusion


## COCO: common objects in context [Lin et al., 2014]

- 2 million objects, from 80 categories, in 300 000 images




Winner 2016: Fully Convolutional Instance-aware Semantic Segmentation (Microsoft) [Li et al., 2016]


# COCO instance segmentation challenge: examples of 2016 winner results



# State of the art on the COCO database: Mask R-CNN [He et al., 2017]




# Mask R-CNN on the COCO database




# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
  - Binary segmentation
  - Semantic segmentation
  - Instance segmentation
  - U-Net
- 5 Using fully-convolutional networks
- 6 Conclusion

# U-Net architecture [Ronneberger et al., 2015]




# U-Net architecture [Ronneberger et al., 2015]



## Quizz


- Size and number of channels of input images?
- Segmentation into how many regions?

# U-Net main ideas



- Encoding branch inspired by classification nets
- Decoding branch is symmetrical
- Skip connections

# U-Net details



- Activation of the last layer: soft-max
- Other activations: ReLU
- Loss used in the original publication: cross entropy with a weight map  $w$  to favor some pixels:

$$L(\theta) = \sum_{M \in D} w(M) \log(\hat{y}_{l(M)}(M))$$

## U-Net improvements

- Convolutions with stride 2 instead of max-pooling in the encoder
- Transposed convolutions instead of simple up-sampling in the decoder
- Batch normalization
- Using an already optimized classification network as backbone for the encoder

# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion

## Dealing with image sizes during training

- In segmentation applications, original images are often of different sizes and possibly very large.

## Dealing with image sizes during training

- In segmentation applications, original images are often of different sizes and possibly very large.
- In theory, given the translation equivariance of fully-convolutional NN, we could use them directly as input. In practice, we are limited by memory size.

## Dealing with image sizes during training

- In segmentation applications, original images are often of different sizes and possibly very large.
- In theory, given the translation equivariance of fully-convolutional NN, we could use them directly as input. In practice, we are limited by memory size.
- Solution: extract fixed-sized crops from your training set:

## Dealing with image sizes during training

- In segmentation applications, original images are often of different sizes and possibly very large.
- In theory, given the translation equivariance of fully-convolutional NN, we could use them directly as input. In practice, we are limited by memory size.
- Solution: extract fixed-sized crops from your training set:
  - make them as large as possible, to reduce border effects

## Loss functions for image segmentation

- $\hat{\mathbf{y}} = (\hat{y}_i)$ : network output
- $\mathbf{y} = (y_i)$ : binary expected output
- We suppose that all  $\hat{y}_i$  are in  $[0, 1]$
- We want the  $\hat{\mathbf{y}}$  to be *as close as possible* to  $\mathbf{y}$

# Loss functions for image segmentation

A loss function inherited from image classification

- Cross-entropy:  $-\sum_i y_i \log(\hat{y}_i)$

# Measures used in image processing


Let  $A$  and  $B$  be two sets, not simultaneously empty.

## Dice coefficient

$$D(A, B) = \frac{2|A \cap B|}{|A| + |B|}$$

## Jaccard index

$$J(A, B) = \frac{|A \cap B|}{|A \cup B|}$$



## Properties

- $\forall A, B : 0 \leq J(A, B) \leq D(A, B) \leq 1$
- If  $A = B$ , then  $D(A, B) = J(A, B) = 1$
- If  $A \cap B = \emptyset$ , then  $D(A, B) = J(A, B) = 0$

## Generalization to $[0, 1]$

Jaccard index

$$J(A, B) = \frac{|A \cap B|}{|A \cup B|}$$

But  $y$  and  $\hat{y}$  are in  $[0, 1]^n \dots$

## Generalization to [0, 1]

Jaccard index

$$J(A, B) = \frac{|A \cap B|}{|A \cup B|}$$

But  $\mathbf{y}$  and  $\hat{\mathbf{y}}$  are in  $[0, 1]^n \dots$

Jaccard similarity

$$J(\mathbf{y}, \hat{\mathbf{y}}) = \frac{\sum_i y_i \hat{y}_i}{\sum_i y_i + \sum_i \hat{y}_i - \sum_i y_i \hat{y}_i}$$

( $\mathbf{y}$  and  $\hat{\mathbf{y}}$  are not simultaneously equal to 0)

## Corresponding loss function

### Jaccard loss

$$j(\mathbf{y}, \hat{\mathbf{y}}) = 1 - \frac{\sum_i y_i \hat{y}_i}{\sum_i y_i + \sum_i \hat{y}_i - \sum_i y_i \hat{y}_i + \epsilon}$$

Constant  $\epsilon$ , which is typically “small”, keeps the denominator “far enough” from zero.

## Corresponding loss function - variant

### Jaccard loss


$$j_2(\mathbf{y}, \hat{\mathbf{y}}) = 1 - \frac{\sum_i y_i \hat{y}_i}{\sum_i y_i^2 + \sum_i \hat{y}_i^2 - \sum_i y_i \hat{y}_i + \epsilon}$$

This version works slightly better than the first [Duque-Arias et al., 2021].

## Conclusion on loss functions

- Use the Jaccard loss as base line for segmentation problems.
- Note that these losses compute their values pixel-wise: they do not take into account any structure (for example, continuity).
- Working on specific losses enforcing structure is an interesting research path.

# Applying fully-convolutional networks



## Case study

Suppose that we have satisfactorily optimized this U-Net model, using images of size  $512 \times 512$  during training. Now I want to apply this model to a new image, of size  $1000 \times 1000$ . How should I proceed?

- ① Resize the image?
- ② Cut it into  $512 \times 512$  crops, predict and stitch the results together?
- ③ Pad the image.

# Contents

- 1 Introduction
- 2 From classification to image-to-image translation
- 3 Properties of fully-convolutional neural networks
- 4 Image segmentation
- 5 Using fully-convolutional networks
- 6 Conclusion

## Segment anything

<https://ai.facebook.com/blog/segment-anything-foundation-model-image-segmentation/>

## Image segmentation: a solved problem?

- Progress in image segmentation since 2012 has been enormous
- Several complex problems have now satisfactory solutions
- Training can be a problem (large annotated databases, difficult optimization)
- There are still challenges ahead...

## Some research subjects

- Optimization - a very general, and essential, subject
- Making training databases as small as possible
- Specific losses
- Taking *a priori* structural information into account

# References |

- [Badrinarayanan et al., 2015] Badrinarayanan, V., Kendall, A., and Cipolla, R. (2015). SegNet: A Deep Convolutional Encoder-Decoder Architecture for Image Segmentation. *arXiv:1511.00561 [cs]*. arXiv: 1511.00561.
- [Cireşan et al., 2012] Cireşan, D., Giusti, A., Gambardella, L. M., and Schmidhuber, J. (2012). Deep Neural Networks Segment Neuronal Membranes in Electron Microscopy Images. In Pereira, F., Burges, C. J. C., Bottou, L., and Weinberger, K. Q., editors, *Advances in Neural Information Processing Systems 25*, pages 2843–2851. Curran Associates, Inc.
- [Duque-Arias et al., 2021] Duque-Arias, D., Velasco-Forero, S., Deschaud, J.-E., Goulette, F., Serna, A., Decencière, E., and Marcotegui, B. (2021). On power Jaccard losses for semantic segmentation. In *VISAPP 2021 : 16th International Conference on Computer Vision Theory and Applications*, Vienne (on line), Austria.
- [Everingham et al., 2014] Everingham, M., Eslami, S. M. A., Gool, L. V., Williams, C. K. I., Winn, J., and Zisserman, A. (2014). The Pascal Visual Object Classes Challenge: A Retrospective. *International Journal of Computer Vision*, 111(1):98–136.
- [Feng Ning et al., 2005] Feng Ning, Delhomme, D., LeCun, Y., Piano, F., Bottou, L., and Barbano, P. E. (2005). Toward automatic phenotyping of developing embryos from videos. *IEEE Transactions on Image Processing*, 14(9):1360–1371. Conference Name: IEEE Transactions on Image Processing.

## References II

- [He et al., 2017] He, K., Gkioxari, G., Dollár, P., and Girshick, R. (2017). Mask R-CNN. *arXiv:1703.06870 [cs]*. arXiv: 1703.06870.
- [Hradiš et al., 2015] Hradiš, M., Kotera, J., Zemcík, P., and Šroubek, F. (2015). Convolutional neural networks for direct text deblurring. In *Proceedings of BMVC*, volume 10.
- [Jain et al., 2007] Jain, V., Murray, J. F., Roth, F., Turaga, S., Zhigulin, V., Briggman, K. L., Helmstaedter, M. N., Denk, W., and Seung, H. S. (2007). Supervised Learning of Image Restoration with Convolutional Networks. In *2007 IEEE 11th International Conference on Computer Vision*, pages 1–8. ISSN: 2380-7504.
- [Li et al., 2016] Li, Y., Qi, H., Dai, J., Ji, X., and Wei, Y. (2016). Fully Convolutional Instance-aware Semantic Segmentation. *arXiv:1611.07709 [cs]*. arXiv: 1611.07709.
- [Lin et al., 2014] Lin, T.-Y., Maire, M., Belongie, S., Bourdev, L., Girshick, R., Hays, J., Perona, P., Ramanan, D., Zitnick, C. L., and Dollár, P. (2014). Microsoft COCO: Common Objects in Context. *arXiv:1405.0312 [cs]*. arXiv: 1405.0312.
- [Long et al., 2015] Long, J., Shelhamer, E., and Darrell, T. (2015). Fully Convolutional Networks for Semantic Segmentation. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3431–3440.

## References III

- [Luo et al., 2017] Luo, W., Li, Y., Urtasun, R., and Zemel, R. (2017). Understanding the Effective Receptive Field in Deep Convolutional Neural Networks. *arXiv:1701.04128 [cs]*. arXiv: 1701.04128.
- [Ounkomol et al., 2018] Ounkomol, C., Seshamani, S., Maleckar, M. M., Collman, F., and Johnson, G. R. (2018). Label-free prediction of three-dimensional fluorescence images from transmitted light microscopy. *Nature methods*, 15(11):917–920.
- [Pang et al., 2010] Pang, B., Zhang, Y., Chen, Q., Gao, Z., Peng, Q., and You, X. (2010). Cell Nucleus Segmentation in Color Histopathological Imagery Using Convolutional Networks. In *2010 Chinese Conference on Pattern Recognition (CCPR)*, pages 1–5.
- [Ronneberger et al., 2015] Ronneberger, O., Fischer, P., and Brox, T. (2015). U-Net: Convolutional Networks for Biomedical Image Segmentation. In Navab, N., Hornegger, J., Wells, W. M., and Frangi, A. F., editors, *Medical Image Computing and Computer-Assisted Intervention – MICCAI 2015*, number 9351 in Lecture Notes in Computer Science, pages 234–241. Springer International Publishing.