

# Crystal Unit

## 32.768KHZ

### YST310S




#### Applications

- RTC

#### Features

- Dimensions: 3.20 x 1.50 x 0.70mm
- Standard Frequency: 32.768KHz
- High Precision and Tight Frequency Stability
- Excellent Heat Resistance and Environmental Characteristics



### Specifications (规格参数)

| Item                                 | Symbol | Specifications                                       |
|--------------------------------------|--------|------------------------------------------------------|
| Nominal Frequency (标称频率)             | f_nom  | 32.768KHz                                            |
| Load Capacitance (负载电容)              | CL     | 7pF, 9pF, 12.5pF, or specify                         |
| Frequency Tolerance (频率偏差) (at 25°C) | f_tol  | ±10ppm, ±20ppm, or specify                           |
| Parabolic Coefficient (频率温度系数)       | B      | $(-0.03 \pm 0.01) \times 10^{-6} / ^\circ\text{C}^2$ |
| Operating Temperature (工作温度)         | T_use  | -20~+70°C, -40~+85°C, or specify                     |
| Storage Temperature (储存温度)           | T_stg  | -55~+125°C                                           |
| Shunt Capacitance (静态电容)             | C0     | 1.2pF Typ                                            |
| Motional Capacitance (动态电容)          | C1     | 4.4fF                                                |
| Level of Drive (激励电平)                | DL     | 1.0μW Max                                            |
| Aging (老化) (at 25°C)                 | f_age  | ±3ppm/year Max                                       |

### Equivalent Series Resistance (等效串联电阻(ESR))

| YST310S  |
|----------|
| 70KΩ Max |

### Dimensions and Recommended Land Pattern (外观尺寸及推荐焊盘)

| Dimensions (Unit: mm)                               | Recommended Land Pattern (Unit: mm) |
|-----------------------------------------------------|-------------------------------------|
| <p>Top View</p> <p>Side View</p> <p>Bottom View</p> |                                     |