

### EEC / COC / L6e-BP



#### Standard Configuration

Model	A8P
Dimensions(mm)	2545*1227*1610
Body type	unitary body
Body structure	2doors and 2seats
Motor	60V3000W AC
Controller	60V 24tubes
Battery(kwh)	60V80AH
Charging time(H)	6-8
Range per charge/km	≥90
Front suspension	McPherson suspension
Rear suspension	Drag-arm suspension
Front/rear tire	135/70R12
Rim	Aluminum Alloy Hub
Brake system	front/rear:disc
Climbing degree (%)	≥20
Top speed(km/h)	45km/h
Steering Mode	Steering
Certificate	EEC / COC / L6e-BP
Container Capacity	9 PCS SKD/40'HQ
Function Device	One Button Start LED lights Reverse Camera/ Heater/ Electric window



#### Standard Configuration

Model	X5
Dimensions(mm)	2560*1330*1550
Body type	unitary body
Body structure	4doors and 3seats
Motor	60V3000W AC
Controller	60V 24tubes
Battery(kwh)	60V80AH
Charging time(H)	6-8
Range per charge/km	≥90
Front suspension	hydraulic shocker
Rear suspension	Drag-arm suspension
Front/rear tire	"Front:4.00-12 Rear:135/70R12"
Rim	Aluminum Alloy Hub
Brake system	front/rear:disc
Climbing degree (%)	≥20
Top speed(km/h)	45km/h
Steering Mode	Steering/Middle Handlebar
Container Capacity	5 PCS SKD/40'HQ
Function Device	One Button Start LED lights Reverse Camera/ Heater/ Electric window

### EEC / COC / L7e-CP



#### Standard Configuration

Model	A900
Dimensions(mm)	2810*1316*1509
Body type	unitary body
Body structure	4doors and 4seats
Motor	72V3000W AC
Controller	72V 24tubes
Battery(kwh)	72V100AH
Charging time(H)	6-8
Range per charge/km	≥100
Front suspension	McPherson suspension
Rear suspension	Drag-arm suspension
Front/rear tire	135/70R12
Rim	Aluminum Alloy Hub
Brake system	front/rear:disc
Climbing degree (%)	≥20
Top speed(km/h)	45km/h
Steering Mode	Steering
Container Capacity	5 PCS SKD/40'HQ
Certificate	EEC / COC / L7e-CP
Function Device	One Button Start LED lights Reverse Camera/ Heater/ Electric window