

✓ **Congratulations! You passed!**
TO PASS 80% or higher

Keep Learning
Retake the assignment in 7h 59m

GRADE
100%

Graded Quiz: Test your Project Understanding

LATEST SUBMISSION GRADE

100%

1. In the *Build a Machine Learning Web App with Streamlit and Python* hands-on project, we used HTML to build parts of a webpage. True or False?

1 / 1 point

- ☐ True
☒ False

✓ **Correct**

Correct! The entire webpage for the application was build in pure Python with Streamlit. Ex: Rather than explicitly writing HTML tags to title the page, we used **st.title** instead.

2. Which of the following Python libraries, besides Streamlit, did we use in our data science web app? (Select all that apply)

1 / 1 point

☒ pandas

✓ **Correct**

Correct! We used pandas extensively to load and manipulate data.

☒ scikit-learn / sklearn

✓ **Correct**

Correct! We used the scikit-learn library in Python to train and evaluate three binary classification algorithms

☐ statsmodels

3. Does Streamlit support Markdown?

1 / 1 point

- ☒ Yes
☐ No

✓ **Correct**

Correct! Streamlit does support displaying strings formatted as Markdown, using a call to **st.markdown**. We used Markdown in Tasks 2 and 4 of this hands-on project.

4. In the following code-snippet, a dataset is loaded into a pandas dataframe and the NA values are dropped when the **load_data()** is called. The **load_data()** function is called **twice**: first after the function definition and the second time after missing values are counted. How many times do you think the entire dataset is loaded into a pandas dataframe using the **read_csv()** function?

1 / 1 point

```
1 @st.cache(persist=True)
2 def load_data():
3     data = pd.read_csv('dataset.csv')
4     data.dropna(inplace=True)
5     return data
6
7 df = load_data()
8 count_missing_vals = df.isnull().sum()
9 df = load_data()
```

- ☒ Once
☐ Twice
☐ None of the above

✓ **Correct**

Good job! It is loaded only once, even though the **load_data()** function was called twice. This is because we marked the function with Streamlit's cache annotation. As neither the name of the function, the code that makes up the function, nor its input parameters changed, Streamlit knows to skip executing the function altogether. Instead, it just reads the output from the local cache and passes it on to the caller.

5. You have just written Python code for your new data science web app with Streamlit and saved the code to a file called **app.py**. How do you run the app from a terminal?

1 / 1 point

- ☐ streamlit app.py
- ☐ streamlit.py run app.py
- ☒ streamlit run app.py

✓ **Correct**

Correct!