10/10

CSCI-21 Quiz #5 Name Ismael Cortez

Please use pencil and erase mistakes. No books, notes or electronic devices. 10 points

Some useful instructions: `and andi or ori sll srl sra`

Write a complete MIPS program that sets a 1 bit into the low-order position of $t0, then, using only bits directly derived from that single bit, sets the pattern `0x96969696` into $t1. You may explain your thinking in comments to the right of each assembly mnemonic; but otherwise add no comments.

0x96 = 1001 0110 —

ok -

```
.text
.globl main
main:
    ori  $t0, $0, 0x01      # $t0 = 0001
    sll  $t1, $t0, 3        # $t1 = 1000
    or   $t1, $t0, $t1      # $t1 = 1001
    sll  $t2, $t0, 1        # $t2 = 0010
    or   $t0, $t0, $t2      # $t0 = 0011
    sll  $t0, $t0, 1.       # $t0 = 0110
    sll  $t1, $t1, 4        # $t1 = 1001 0000
    or   $t1, $t0, $t1.     # $t1 = 1001 0110
    sll  $t0, $t1, 8.       # $t0 = 0x9600
    or   $t1, $t0, $t1.     # $t1 = 0x9696
    sll  $t0, $t1, 16.      # $t0 = 0x9696 0000
    or   $t1, $t0, $t1.     # $t1 = 0x96969696
```