

Selenium WebDriver (JAVA) CheatSheet - Naveen Automation Labs

Feature	Command / Method	Example with Return	Use Case
Open Browser	<code>new ChromeDriver()</code>	<code>WebDriver driver = new ChromeDriver();</code>	Launch a Chrome browser instance.
Navigate to URL	<code>get(String url)</code>	<code>driver.get("https://example.com");</code>	Opens a URL.
Get Page Title	<code>getTitle()</code>	<code>String title = driver.getTitle();</code>	Returns page title.
Get Current URL	<code>getCurrentUrl()</code>	<code>String url = driver.getCurrentUrl();</code>	Returns current page URL.
Find Element	<code>findElement(By)</code>	<code>WebElement el = driver.findElement(By.id("user"));</code>	Locates a single element.
Find Elements	<code>findElements(By)</code>	<code>List<WebElement> list = driver.findElements(By.className("item"));</code>	Locates multiple elements.
Send Text	<code>sendKeys(String)</code>	<code>el.sendKeys("admin");</code>	Sends input to a field.
Click Element	<code>click()</code>	<code>el.click();</code>	Clicks buttons, links, etc.
Clear Input Field	<code>clear()</code>	<code>el.clear();</code>	Clears input field content.
Get Text	<code>getText()</code>	<code>String text = el.getText();</code>	Gets element's visible text.
Get DOM Attribute	<code>getDomAttribute(String)</code>	<code>String value = el.getDomAttribute("value");</code>	Gets the HTML attribute value from DOM.
Get DOM Property	<code>getDomProperty(String)</code>	<code>String value = el.getDomProperty("value");</code>	Gets the JavaScript property value.
Check Displayed	<code>isDisplayed()</code>	<code>boolean b = el.isDisplayed();</code>	Checks if element is visible.
Check Enabled	<code>isEnabled()</code>	<code>boolean b = el.isEnabled();</code>	Checks if element is interactable.
Check Selected	<code>isSelected()</code>	<code>boolean b = el.isSelected();</code>	Checks if checkbox/radio is selected.
Implicit Wait	<code>implicitlyWait()</code>	<code>driver.manage().timeouts().implicitlyWait(Duration.ofSeconds(20));</code>	Waits globally for elements.
Explicit Wait	<code>WebDriverWait + ExpectedConditions</code>	<code>wait.until(ExpectedConditions.elementToBeClickable(el));</code>	Waits conditionally.
Explicit Wait - Element Clickable	<code>WebDriverWait + ExpectedConditions</code>	<code>WebDriverWait wait = new WebDriverWait(driver, Duration.ofSeconds(10)); wait.until(ExpectedConditions.elementToBeClickable(By.id("submit")));</code>	Waits until the element is clickable before proceeding.
Explicit Wait - Element Visible	<code>WebDriverWait + ExpectedConditions</code>	<code>WebDriverWait wait = new WebDriverWait(driver, Duration.ofSeconds(10)); wait.until(ExpectedConditions.visibilityOfElementLocated(By.id("username")));</code>	Waits until the element is visible on the page.
Explicit Wait - URL Contains	<code>WebDriverWait + ExpectedConditions</code>	<code>WebDriverWait wait = new WebDriverWait(driver, Duration.ofSeconds(10)); wait.until(ExpectedConditions.urlContains("dashboard"));</code>	Waits until the URL contains the specified text.
Fluent Wait	<code>FluentWait</code>	<code>Wait<WebDriver> wait = new FluentWait<>(driver) .withTimeout(Duration.ofSeconds(30)) .pollingEvery(Duration.ofSeconds(5)) .ignoring(NoSuchElementException.class); WebElement el = wait.until(driver -> driver.findElement(By.id("elementId")));</code>	Custom wait with polling interval and exception handling.
Maximize Window	<code>window().maximize()</code>	<code>driver.manage().window().maximize();</code>	Maximizes browser window.
Navigate Back	<code>navigate().back()</code>	<code>driver.navigate().back();</code>	Goes back one page.
Navigate Forward	<code>navigate().forward()</code>	<code>driver.navigate().forward();</code>	Goes forward in browser history.
Refresh Page	<code>navigate().refresh()</code>	<code>driver.navigate().refresh();</code>	Reloads current page.
Switch to Alert	<code>switchTo().alert()</code>	<code>driver.switchTo().alert().accept();</code>	Handles browser alerts.
Switch to Frame	<code>switchTo().frame()</code>	<code>driver.switchTo().frame("frame1");</code>	Switches to iframe.
Switch to Default Content	<code>switchTo().defaultContent()</code>	<code>driver.switchTo().defaultContent();</code>	Exits frame and returns to main page.
Switch to Window	<code>switchTo().window(handle)</code>	<code>driver.switchTo().window(id);</code>	Switches to a different tab/window.
Get Window Handles	<code>getWindowHandles()</code>	<code>Set<String> ids = driver.getWindowHandles();</code>	Gets all open window handles.
Take Screenshot	<code>getScreenshotAs()</code>	<code>File src = ((TakesScreenshot) driver).getScreenshotAs(OutputType.FILE);</code>	Captures browser screenshot.
Close Current Window	<code>close()</code>	<code>driver.close();</code>	Closes current browser window.
Quit All Windows	<code>quit()</code>	<code>driver.quit();</code>	Closes all browser windows.
Scroll (JavaScript)	<code>JavaScriptExecutor.executeScript()</code>	<code>js.executeScript("window.scrollBy(0, 400)");</code>	Scrolls down/up the page.
Wait for Page Load	<code>document.readyState</code>	<code>js.executeScript("return document.readyState").equals("complete");</code>	Ensures page is fully loaded.
Select by Visible Text	<code>selectByVisibleText(String)</code>	<code>select.selectByVisibleText("India");</code>	Selects option with visible text.
Select by Index	<code>selectByIndex(int)</code>	<code>select.selectByIndex(2);</code>	Selects option by index.
Select by Value	<code>selectByValue(String)</code>	<code>select.selectByValue("IN");</code>	Selects option by value attribute.
Deselect All	<code>deselectAll()</code>	<code>select.deselectAll();</code>	Deselects all options (multi-select).
Deselect by Index	<code>deselectByIndex(int)</code>	<code>select.deselectByIndex(2);</code>	Deselects by index.
Deselect by Value	<code>deselectByValue(String)</code>	<code>select.deselectByValue("IN");</code>	Deselects by value.
Deselect by Visible Text	<code>deselectByVisibleText(String)</code>	<code>select.deselectByVisibleText("India");</code>	Deselects by visible text.
Get Selected Option	<code>getFirstSelectedOption()</code>	<code>WebElement selected = select.getFirstSelectedOption();</code>	Returns selected option.
Get All Selected Options	<code>getAllSelectedOptions()</code>	<code>List<WebElement> all = select.getAllSelectedOptions();</code>	Returns list of selected options.
Get All Options	<code>getOptions()</code>	<code>List<WebElement> options = select.getOptions();</code>	Returns all dropdown options.
Is Multiple Select?	<code>isMultiple()</code>	<code>boolean isMulti = select.isMultiple();</code>	Checks if multi-select dropdown.
Click Dropdown Trigger	<code>click()</code>	<code>dropdownBtn.click();</code>	Opens custom dropdown.
Find Dropdown Options	<code>findElements(By)</code>	<code>List<WebElement> items = driver.findElements(By.xpath("//ul/li"));</code>	Gets custom dropdown options.
Select from Non-Select Dropdown	<code>Loop + getText() + click()</code>	<code>for(WebElement e : items){ if(e.getText().equals("Option")) { e.click(); break; } }</code>	Selects item from non-select dropdown.