

JS Fundamentals

Arrays, Strings, Objects and Associative
Arrays



SoftUni Team

Technical Trainers



SoftUni



Software University

<https://softuni.bg>

You Have Questions?

sli.do

#QA-Auto-BackEnd

Table of Contents

1. Working with Arrays
2. Array's Methods
3. Manipulating Strings
4. Objects
5. Associative Arrays
6. Functions Overview





Working with Arrays of Elements

Arrays in JavaScript

Arrays in JavaScript

- Neither the **length** of a JavaScript array **nor** the **types** of its elements are **fixed**
- An array's **length can be changed** at any time
- Data can be stored at non-contiguous locations in the array
- JavaScript arrays are not guaranteed to be dense



Creating Arrays in JavaScript

- Array **literal**

```
let myArray = ["John Doe", 24, true];
```

```
let myArray = [];  
myArray[0] = "John Doe";  
myArray[1] = 24;  
myArray[2] = true;
```

- Array **constructor**

```
let myArray = new Array("John Doe", 24, true);
```

- Array elements are accessed using their **index**

```
let cars = ['BMW', 'Audi', 'Opel'];  
let firstCar = cars[0];    // BMW  
let lastCar = cars[cars.length - 1]; // Opel
```

- Accessing indexes that do not exist in the array returns **undefined**

```
console.log(cars[3]);    // undefined  
console.log(cars[-1]);   // undefined
```


- Expression that **unpacks values** from **arrays** or **objects**, into distinct **variables**

```
let numbers = [10, 20, 30, 40, 50];  
let [a, b, ...elems] = numbers;
```

Rest operator

```
console.log(a) // 10  
console.log(b) // 20  
console.log(elems) // [30, 40, 50]
```

- The **rest operator** can also be used to collect function parameters into an array



Array's Methods

Modify the Array

- Removes the **last element** from an array and returns that element
- This method **changes** the **length** of the array

```
let nums = [10, 20, 30, 40, 50, 60, 70];  
console.log(nums.length); // 7  
console.log(nums.pop()); // 70  
console.log(nums.length); // 6  
console.log(nums);        // [ 10, 20, 30, 40, 50, 60 ]
```

- The **push()** method **adds one or more** elements to the **end** of an array and **returns** the new **length** of the array

```
let nums = [10, 20, 30, 40, 50, 60, 70];  
console.log(nums.length); // 7  
console.log(nums.push(80)); // 8 (nums.Length)  
console.log(nums); // [ 10, 20, 30, 40, 50, 60, 70, 80 ]
```

- The **shift()** method **removes** the **first element** from an array and **returns** that **removed element**
- This method **changes** the **length** of the array

```
let nums = [10, 20, 30, 40, 50, 60, 70];  
console.log(nums.length); // 7  
console.log(nums.shift()); // 10 (removed element)  
console.log(nums); // [ 20, 30, 40, 50, 60, 70 ]
```

- The **unshift()** method **adds one or more** elements to the **beginning** of an array and **returns** the new **length** of the array

```
let nums = [40, 50, 60];  
console.log(nums.length);           // 3  
console.log(nums.unshift(30));      // 4 (nums.Length)  
console.log(nums.unshift(10,20));  // 6 (nums.Length)  
console.log(nums);                 // [ 10, 20, 30, 40, 50, 60 ]
```

- Changes the contents of an array by **removing** or **replacing** existing **elements** and / or **adding new** elements

```
let nums = [1, 3, 4, 5, 6];  
nums.splice(1, 0, 2);           // inserts at index 1  
console.log(nums);              // [ 1, 2, 3, 4, 5, 6 ]  
nums.splice(4, 1, 19);          // replaces 1 element at index 4  
console.log(nums);              // [ 1, 2, 3, 4, 19, 6 ]  
let e1 = nums.splice(2, 1);      // removes 1 element at index 2  
console.log(nums);              // [ 1, 2, 4, 19, 6 ]  
console.log(e1);                // [ 3 ]
```

- Reverses the array
- The **first** array element becomes the **last**, and the **last** array element becomes the **first**

```
let arr = [1, 2, 3, 4];  
arr.reverse();  
console.log(arr); // [ 4, 3, 2, 1 ]
```

- Creates and returns a **new string** by **concatenating** all of the elements in an array (or an array-like object), **separated** by commas or a **specified separator** string

```
let elements = ['Fire', 'Air', 'Water'];  
console.log(elements.join());    // "Fire,Air,Water"  
console.log(elements.join('')); // "FireAirWater"  
console.log(elements.join('-')); // "Fire-Air-Water"  
console.log(['Fire'].join(".")); // Fire
```


- The **slice()** method **returns** a shallow **copy** of a **portion** of an array into a **new array** object selected from begin to end (end not included)
- The **original array** will **not** be **modified**

```
let fruits = ['Banana', 'Orange', 'Lemon', 'Apple'];  
let citrus = fruits.slice(1, 3);  
let fruitsCopy = fruits.slice();  
// fruits contains ['Banana', 'Orange', 'Lemon', 'Apple']  
// citrus contains ['Orange', 'Lemon']
```

- Determines whether an array contains a certain element, returning **true** or **false** as appropriate

```
// array length is 3
// fromIndex is -100
// computed index is 3 + (-100) = -97
let arr = ['a', 'b', 'c'];
arr.includes('a', -100); // true
arr.includes('b', -100); // true
arr.includes('c', -100); // true
arr.includes('a', -2); // false
```

- The **indexOf()** method **returns** the **first index** at which a given **element** can be **found** in the array
 - Output is **-1** if element is **not present**

```
const beasts = ['ant', 'bison', 'camel', 'duck', 'bison'];  
  
console.log(beasts.indexOf('bison')); // 1  
// start from index 2  
console.log(beasts.indexOf('bison', 2)); // 4  
console.log(beasts.indexOf('giraffe')); // -1
```

- The **forEach()** method **executes a provided function** once for each array element

```
const items = ['item1', 'item2', 'item3'];  
const copy = [];  
  
// For Loop  
for (let i = 0; i < items.length; i++) {  
  copy.push(items[i]);  
}  
  
// ForEach  
items.forEach(item => { copy.push(item); });
```

- **Creates a new array** with the results of calling a **provided function** on every element in the calling array

```
let numbers = [1, 4, 9];  
let roots = numbers.map(function(num, i, arr) {  
  return Math.sqrt(num)  
});  
// roots is now [1, 2, 3]  
// numbers is still [1, 4, 9]
```

- Returns the **first found value** in the array, if an **element** in the array **satisfies** the **provided** testing **function** or **undefined** if not found

```
let array1 = [5, 12, 8, 130, 44];  
let found = array1.find(function(element) {  
  return element > 10;  
});  
console.log(found); // 12
```

- Creates a **new array** with **filtered elements only**
- Calls a **provided** callback **function** once for each element in an array
- **Does not mutate** the **array** on which it is called

```
let fruits = ['apple', 'banana', 'grapes', 'mango', 'orange'];  
// Filter array items based on search criteria (query)  
function filterItems(arr, query) {  
  return arr.filter(function(e1) {  
    return e1.toLowerCase().indexOf(query.toLowerCase()) !== -1;  
  });  
};  
console.log(filterItems(fruits, 'ap')); // ['apple', 'grapes']
```



abc

Manipulating Strings

- Use the "+" or the "+=" operators

```
let text = "Hello" + ", ";  
// Expected output: "Hello, "  
text += "JS!"; // "Hello, JS!"
```

- Use the `concat()` method

```
let greet = "Hello, ";  
let name = "John";  
let result = greet.concat(name);  
console.log(result); // Expected output: "Hello, John"
```

- **indexOf(substr)**

```
let str = "I am JavaScript developer";  
console.log(str.indexOf("Java")); // Expected output: 5  
console.log(str.indexOf("java")); // Expected output: -1
```

- **lastIndexOf(substr)**

```
let str = "Intro to programming";  
let last = str.lastIndexOf("o");  
console.log(last); // Expected output: 11
```

- **substring(startIndex, endIndex)**

```
let str = "I am JavaScript developer";  
let sub = str.substring(5, 10);  
console.log(sub); // Expected output: JavaS
```

- `replace(search, replacement)`

```
let text = "Hello, john@softuni.bg, you have been  
using john@softuni.bg in your registration.";  
let replacedText = text.replace(".bg", ".com");  
console.log(replacedText);  
// Hello, john@softuni.com, you have been using  
john@softuni.bg in your registration.
```

- **split(separator)**

```
let text = "I love fruits";  
let words = text.split(' ');  
console.log(words); // Expected output: ['I', 'Love', 'fruits']
```

- **includes(substr)**

```
let text = "I love fruits."  
console.log(text.includes("fruits")); // Expected output: True  
console.log(text.includes("banana")); // Expected output: False
```

- **repeat(count)** - Creates a new string repeated count times

```
let n = 3;  
for(let i = 1; i <= n; i++) {  
  console.log('*'.repeat(i));  
}
```



```
// *  
// **  
// ***
```

- Use **trim()** method to remove **whitespaces** (spaces, tabs, no-break space, etc.) from **both ends** of a string

```
let text = "   Annoying spaces   ";  
console.log(text.trim()); // Expected output: "Annoying spaces"
```

- Use **trimStart()** or **trimEnd()** to remove whitespaces **only** at the beginning or at the end

```
let text = "   Annoying spaces   ";  
text = text.trimStart();  
text = text.trimEnd();  
console.log(text); // Expected output: "Annoying spaces"
```

Starts With/Ends with

- Use **startsWith()** to determine whether a string **begins** with the characters of a specified substring

```
let text = "My name is John";  
console.log(text.startsWith('My')); // Expected output: true
```

- Use **endsWith()** to determine whether a string **ends** with the characters of a specified substring

```
let text = "My name is John";  
console.log(text.endsWith('John')); // Expected output: true
```


Padding at the Start and End

- Use **padStart()** to add to the current string **another substring** at the **start** until a **length** is reached

```
let text = "010";
```

Receives **length** and **substring**


```
console.log(text.padStart(8, '0')); // Expected output: 00000010
```

- Use **padEnd()** to add to the current string **another substring** at the **end** until a **length** is reached

```
let sentence = "He passed away";
```

```
console.log(sentence.padEnd(20, '.'));
```

```
// Expected output: He passed away.....
```




Objects

Definition, Properties and Methods

What Are Objects ?

- **Structure** of related data or functionality
- Contains **values** accessed by **string keys**
 - Data values are called **properties**
 - Function values are called **methods**



Object	
'name'	'Peter'
'age'	20

Property name (key)

Property value

- You can **add** and **remove** properties **during runtime**

- We can create an object with an **object literal**

```
let person = { name: 'Peter', age: 20, height: 183 };
```

- We can define an **empty object** and **add properties** later

```
let person = {};  
person.name = 'Peter';  
person.age = 20;  
person.hairColor = 'black';
```

```
person['lastName'] = 'Parker';
```

- Functions within a JavaScript object are called **methods**
- We can **define** methods using several syntaxes:

```
let person = {  
  sayHello: function() {  
    console.log('Hi, guys');  
  }  
}
```

```
let person = {  
  sayHello() {  
    console.log('Hi, guys');  
  }  
}
```

- We can **add** a method to an already defined object

```
let person = { name: 'Peter', age: 20 };  
person.sayHello = () => console.log('Hi, guys');
```

- Get array of all property **names** (keys)

```
Object.keys(cat);  
// ['name', 'age']
```

cat	
'name'	'Tom'
'age'	5

- Get array with of all property **values**

```
Object.values(cat);  
// ['Tom', 5]
```

- Get and array of all properties as **key-value tuples**

```
Object.entries(cat);  
// [['name', 'Tom'], ['age', 5]]
```




`{a:1}`

Associative Arrays

Storing Key-Value Pairs

What is an Associative Array ?

- Arrays indexed by **string keys**
- Hold a set of pairs **[key → value]**
 - The key is a **string**
 - The **value** can be of **any** type



Key	Value
John Smith	+1-555-8976
Lisa Smith	+1-555-1234
Sam Doe	+1-555-5030

- An associative array in JavaScript is just an **object**
- We can declare it **dynamically**

```
let assocArr = {  
  'one': 1,  
  'two': 2,  
  'three': 3,  
  [key]: 6  
};
```

Quotes are used if the key contains **special characters**

```
assocArr['four'] = 4;
```

```
assocArr.five = 5;
```

```
let key = 'six';  
assocArr[key] = 6;
```

Valid ways to access **values** through **keys**

- We can use **for-in** loop to iterate through the keys

```
let assocArr = {};  
assocArr['one'] = 1;  
assocArr['two'] = 2;  
assocArr['three'] = 3;  
  
for(let key in assocArr) {  
    console.log(key + " = " + assocArr[key]);  
}
```

```
// one = 1  
// two = 2  
// three = 3
```



- Check if a key is **present**

```
let assocArr = { /* entries */ };  
if (assocArr.hasOwnProperty('John Smith')) { /* Key found */ }
```

- **Remove** entries

```
delete assocArr['John Smith'];
```

Sorting Associative Arrays

- Objects **cannot be sorted**, they must be converted first
 - Convert to **array** for **sorting**, **filtering** and **mapping**

```
let phonebook = { 'Tim': '0876566344',  
                  'Bill': '0896543112' };  
  
let entries = Object.entries(phonebook);  
console.log(entries); // Array of arrays with two elements each  
// [ ['Tim', '0876566344'],  
//   ['Bill', '0896543112'] ]  
  
let firstEntry = entries[0];  
console.log(firstEntry[0]); // Entry key -> 'Tim'  
console.log(firstEntry[1]); // Entry value -> '0876566344'
```

The entry is turned into an array of **[key, value]**

- The **entries** array can be **sorted**, using a **Compare function**
 - To **sort by key**, use the **first element** of each entry

```
entries.sort((a, b) => {  
  keyA = a[0];  
  keyB = b[0];  
  // Perform comparison and return negative, 0 or positive  
});
```



- You can also **destructure** the entries

```
entries.sort(([keyA, valueA], [keyB, valueB]) => {  
  // Perform comparison and return negative, 0 or positive  
});
```

Array and Object Destructuring

- The **destructuring assignment** syntax makes it possible to unpack values from arrays, or properties from objects, into distinct variables
- On the left-hand side of the assignment to define what values to unpack from the sourced variable

```
const x = [1, 2, 3, 4, 5];  
const [y, z] = x;  
console.log(y); // 1  
console.log(z); // 2
```

```
obj = { a: 1, b: 2 };  
const { a, b } = obj;  
// is equivalent to:  
// const a = obj.a;  
// const b = obj.b;
```

- To **sort by value**, use the **second element** of each entry

```
entries.sort((a, b) => {  
  valueA = a[1];  
  valueB = b[1];  
  // Perform comparison and return negative, 0 or positive  
});
```

- You can also **destructure** the entries

```
entries.sort(([keyA, valueA],[keyB, valueB]) => {  
  // Perform comparison and return negative, 0 or positive  
});
```

A background network diagram consisting of a grid of light gray lines intersecting at various points. Some of these intersections are marked with small, empty light gray circles. A larger, solid dark blue circle is centered in the upper half of the image, containing the mathematical expression $f(x)$ in white.
$$f(x)$$

Functions Overview

Definition and Objectives

Functions in JS

- A **function** is a **named subprogram** designed to perform a particular task
 - Functions are executed when they are called. This is known as **invoking** a function
 - Values can be **passed** into functions and used within the function

Use **camelCase**

Parameter

```
function printStars(count) {  
    console.log("*".repeat(count));  
}
```



- Functions can be declared in two ways:
 - **Function declaration** (recommended way)

```
function printText(text) {  
    console.log(text);  
}
```

- Functions can have **parameters**
- Functions **always** return a value (custom or default)

Invoking a Function

- Functions are first **declared**, then **invoked** (many times)

```
function hLine() {  
    console.log("-----");  
}
```

- Functions can be **invoked (called)** by their name

```
hLine();
```

- Invocation from another function

```
function printDocument() {  
    printLabel();  
}
```

Functions Without Parameters

- Does **not** receive arguments when invoked
- The result is **always the same** (unless it reads data from outside)

```
function printHeader() {  
    console.log('~~~-    {@}    -~~~');  
    console.log('~- Certificate -~');  
    console.log('~~~- ~---~ -~~~');  
}  
printHeader();    // Output is always the same
```

Functions With Parameters

- Can receive **any number** and **type** of arguments when invoked

```
function multiply(a, b) {  
  console.log(a*b);  
}  
multiply(5, 7); // 35
```

Pass two numbers

```
function printName(nameArr) {  
  console.log(nameArr[0] + ' ' + nameArr[1]);  
}  
printName(['John', 'Smith']); // John Smith
```

Pass array of strings

The Return Statement

- The **return** keyword immediately **stops the function's execution**
- **Returns** the specified value to the caller

```
function readFullName(firstName, lastName) {  
    return firstName + " " + lastName;  
}  
  
const fullName = readFullName("John", "Smith");  
console.log(fullName) //John Smith
```

- Return value can be
 - Assigned** to a variable

```
let max = getMax(5, 10);
```

- Used** in expression

```
let total = getPrice() * quantity * 1.20;
```

- Passed** to another function

```
multiply(getMax(5,10), 20)
```

- Special **shorthand syntax** for declaration
- They operate in the **context** of their **enclosing scope**
- Useful in **functional programming**

```
let increment = x => x + 1;  
console.log(increment(5)); // 6
```

```
let increment = function(x) {  
  return x + 1;  
}
```

```
let sum = (a, b) => a + b;  
console.log(sum(5, 6)); // 11
```


- **First-class functions** are treated like any other variable
 - Passed as an **argument**
 - **Returned** by another function
 - We can do that, because we treated functions in JavaScript as a **value**
 - Assigned as a **value** to a **variable**

```
const write = function () {  
    return "Hello, world!";  
}
```

- Can take **other functions as arguments**
- Can **return a function**


```
const numbers = [1, 2, 3, 4, 5];  
const squared = numbers.map(num => num * num);  
console.log(squared); // Output: [1, 4, 9, 16, 25]
```

```
function greaterThan(n)  
{  
    return m => m > n;  
}  
let greaterThan10 = greaterThan(10);  
console.log(greaterThan10(11)); // Output: true
```

- **Arrays** in JS can hold mixed data
- Various methods for working with them
- **Strings** can be manipulated
- **Objects** == structure of related data
- **Associative arrays** == arrays indexed by key-value
- **Functions** in JS == named subprograms
 - Designed to perform particular tasks



Questions?



SoftUni Diamond Partners



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://about.softuni.bg/>
- © Software University – <https://softuni.bg>



- Software University – High-Quality Education, Profession and Job for Software Developers

- softuni.bg, about.softuni.bg

- Software University Foundation

- softuni.foundation

- Software University @ Facebook

- facebook.com/SoftwareUniversity

