

# Associative Networks

Carlos García Martínez



# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

# Introducción

- **Associative Nets:** Knowledge representation paradigm where ideas are expressed by means of nodes and arcs (graphs)
- Initially, they were oriented for natural language processing (***Semantic networks***)
- Nowadays, they are employed in many different applications

# Characteristics

- Common characteristics:
  - Nodes often stand for concepts, entities, attributes, events or states
  - Several Nodes may stand for the same concept
  - Arcs create connections between nodes (relations)
- Differing characteristics:
  - Node and Arc semantics
  - Inference capacities
  - Notation

# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

# Conceptual Dependency

- Schank, 1972, 1975. Proposed to tackle the natural language processing problem.
- Characteristics:
  - It does not depend on the language, in contrast to other models
  - ***It represents concepts instead of terms***

# Model


- It constructs sentences by means of:
  - Six ***Conceptual Categories***:
    - Physical object
    - Action
    - Attributes of objects (adjectives)
    - Attributes of actions (adverbs)
    - Time of a conceptualization
    - Location of a conceptualization
  - 16 ***realization rules*** that links the elements of a sentence
  - A set of ***primitives*** (12 primitives are enough to represent most of natural language)

# Basic primitives


- PTRANS: Transfer of the physical location of an object (go, move an object...)
- ATRANS: Transfer of an abstract relationship (give, lend...)
- MTRANS: Transfer of mental information (tell, teach...)
- PROPEL: Application of a physical force to an object (push)
- MOVE: Movement of a body part by owner (kick)
- GRASP: Actor grasping an object (clutch)
- INGEST: Actor ingesting an object (eat)
- Etc.



# Example: Juan drinks water



# Ejemplo: Juan compró un libro



# Advantages

- Sentences are divided in elements that do not depend on the language
- A limited set of primitives allow us to:
  - associate knowledge and representation in just one way
  - design an interpreter that performs inferences
- Inferences capacities:
  - *It affirms conditions*: Juan exists and filete exists
  - *It may guess causes / intentions*: “Juan pidió el libro a Marta”  $\Rightarrow$  “Marta tenía un libro” y “Juan quería ese libro”.
  - *It deducts results*: “Juan comió un filete”  $\Rightarrow$  “Filete dejó de existir”.

# Drawbacks

- More primitives lead to an efficiency reduction
- Critiques to using primitives:
  - The meaning of a phrase depends on the language it is formulated
  - The graphs represent a too detailed situation.  
Simple sentences  $\Rightarrow$  Complex graphs
  - How to determine the number and meaning of the primitives needed?
  - It focus the attention on verbs

# Drawbacks of Relational Graphs


- There are sentences that can be represented by logic, but not by relational graphs
  - You can not represent the universal quantifier
- It is difficult to represent the interaction of propositions:
  - Night comes and temperature falls (two actions at the same time)
  - If it is night and foggy, it is dangerous to drive (It can not be represented)

# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

# Sowa's Conceptual Structures

- They can draw contextual situations gathering up nodes in rectangles



# Linear Notation

- Shapiro's nets and conceptual structures can be expressed in a linear notation:

[PENSAR] -

→ (AGT) → [PERS: Antonio]

→ (OBJ) → [PROPOSICION: [LEER] -

→ (AGT) → [PERS: Luisa]

→ (OBJ) → [LIBRO]]



# Linear Notation Examples

- Un río:  $[RÍO: *] \equiv [RÍO]$
- Un río caudaloso:  $[RÍO] \rightarrow (ATR) \rightarrow [CAUDALOSO]$
- Algunos ríos:  $[RÍO: \{*\}]$
- Tres ríos:  $[RÍO: \{*\}@3]$
- El río (uno específico):  $[RÍO: \#]$
- ¿Qué río?:  $[RÍO: ?]$
- El río Ebro:  $[RÍO: Ebro]$
- Los ríos Duero y Tajo:  $[RÍO: \{Duero, Tajo\}]$
- Todo río, todos los ríos:  $[RÍO: \forall]$
- Cinco litros de agua:  
 $[AGUA] \rightarrow (MEDIDA) \rightarrow [CANTIDAD: 5L.]$

# Linear Notation Examples


- Las 10 de la mañana: [HORA: 10 a.m.]
- Todos los seres humanos son mortales:  
[PERS:  $\forall$ ]  $\rightarrow$  (ATR)  $\rightarrow$  [MORTAL]
- Algún ser humano es mortal:  
[PERS]  $\rightarrow$  (ATR)  $\rightarrow$  [MORTAL]
- Él no ha venido:  
(NEG)  $\leftarrow$  [PROPOSICIÓN: [VENIR]  
 $\rightarrow$  (AGT)  $\rightarrow$  [HOMBRE: #]  
 $\rightarrow$  (PASADO)]

# Linear Notation Examples

- Probablemente iré mañana:  
[PROBABLE] ← (MOD) ← [PROPOSICIÓN: [IR]  
→ (AGT) → [PERS: #yo]  
→ (TIEMPO) → [DÍA: #mañana]
- ¿Quién es el profesor de Luis?:  
[PERS: ?] → (PROFESOR-DE) → [PERS: Luis]
- ¿Dónde está tu libro?:  
[LUGAR: ?] ← (LOC) ← [LIBRO: #] → (POS) → [PERS: #tú]

# Variables

CONDICIONAL



[CONDICIONAL:

(SI) → [PROPOSICION: [POSEER]

→ (AGT) → [PERS: \*x]

→ (OBJ) → [CONCHE: \*y]]

(ENT) → [PROPOSICIÓN: [UTILIZAR]

→ (AGT) → [T: \*x]

→ (OBJ) → [T: \*y]]]

# Variables

## [DECIR]

- (AGT) → [PERS: Ana]
- (RCP) → [PERS: #él]
- (OBJ) → [PROPOSICIÓN: [SUSPENDER]
  - (OBJ) → [CLASE: #] \*y]
- (PASADO)

## [COMENTAR]

- (AGT) → [#él]
- (RCP) → [PERS: Luis]
- (OBJ) → [\*y]
- (PASADO)

# Summary

Conceptual Structures consist of three types of elements:

- ***Generic concepts:*** BOOK, PERSON, THINK
- ***Individual concepts:*** [PERSON: #me]
- ***Conceptual relations:***
  - Unit: PAST, NEG, etc
  - Binary: AGT, OBJ, RCV, ATTR, LOC, MEASURE, MOD, TEMP, THEACHER-OF etc
  - Ternary: BETWEEN

# Inference Engine

- **Specialization:** To obtain a particular proposition from a general one by specializing some elements.
- **Generalization:** Opposite to specialization.
- **Union and simplification:** It is similar to the resolution principle in logic

# Inference Examples

G1: [PERS:∀] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

*specialization*

G2: [PERS: Marta] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

G3: [NIÑA] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

*specialization*

G4: [NIÑA: Marta] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

G5: [NIÑA:Marta] ← (AGT) ← [BEBER] → (INSTR) → [VASO]

*union and simplification*

G6: [BEBER]

→ (AGT) → [NIÑA: Marta]

→ (OBJ) → [AGUA]

→ (INSTR) → [VASO]



# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

# Causal Networks

- They consist of:
  - Nodes = variables
  - Links = ***influence relations*** between variables
- Often used in diagnostic problems



# CASNET


- Casual Associational NETwork, 1970.
- Objective: to help when diagnosing and treating glaucoma and ***eye diseases***
- Advantages over other expert systems:
  - ***Temporal reasoning:*** it takes into account the evolution of the disease
  - ***Multiple diagnostic***
  - ***It explains its conclusions***

# Diagnostic Network


- Nodes are placed in three levels:
  - **Observations:**
    - Symptoms (whatever patient feels)
    - Signs (whatever doctor perceives)
    - Results of laboratory tests
  - **Pathological states:** disfunction of organs
  - **Illness states:** structured by means of a taxonomic tree
- Inter-level and Intra-level links with associated ***causal factors***

# CASNET


## PLANO DE LOS ESTADOS DE ENFERMEDAD



## PLANO DE LOS ESTADOS PATO-FISIOLÓGICOS



## PLANO DE LAS OBSERVACIONES



# Diagnosis and Therapy

- There are two types of diagnosis:
  - Pathological states (simple).
  - Illness
- It also offer ***therapeutic recommendations*** in another plane where nodes are therapies and links can relate:
  - therapies with pathological or illness estates
  - therapies among them (interactions, toxicity and temporal dependencies)


# Bayesian Networks: Model

- It is a connex acyclic directed graph with an associated probability distribution on its variables, which fulfils graphical property of ***directed-separation***.
- For each node, designer has to provide the probabilities of its values conditioned to the values of its parent nodes

$$P(x_i) \quad P(x_i | \{ \text{parents}(x) \})$$

# Example

- Let it be the following network with the following probabilities  $P(O)$ ,  $P(S)$ ,  $P(A \mid O, S)$ ,  $P(F \mid A)$ ,  $P(G \mid A)$



- Conditional independence  $\Rightarrow P(F \mid A, O, S, G) = P(F \mid A)$
- $P(O, S, A, F, G) = P(O) P(S) P(A \mid O, S) P(F \mid A) P(G \mid A)$



# Directed Separation Property

- If two sets of nodes  $X$  and  $Y$  are d-separated in the graph by a third set  $Z$ , then, they are independent given the values of nodes in  $Z$
- A path (undirected) is d-separated by set  $Z$  if:
  - it contains a chain  $i \rightarrow m \rightarrow j$  and  $m$  is in  $Z$ , or
  - a chain  $i \leftarrow m \leftarrow j$  and  $m$  is in  $Z$
  - a chain  $i \leftarrow m \rightarrow j$  and  $m$  is in  $Z$
  - a chain  $i \rightarrow m \leftarrow j$  and no descendant of  $m$  is in  $Z$ , neither  $m$
- It allows to work with probabilities without the necessity of exponential amounts of information<sup>33</sup>

# Bayes' Theorem (1)

- Given the *a priori* probability of one hypothesis  $P(B_i)$  and the conditional hypothesis  $P(A|B_i)$ , we can obtain the probability of the following hypothesis:

$$P(B_i|A) = \frac{P(A|B_i) \cdot P(B_i)}{P(A)} = \frac{P(A|B_i) \cdot P(B_i)}{\sum_{j=1}^n P(A|B_j) \cdot P(B_j)}$$

- If we have  $P(\text{Flu})$  y  $P(\text{Fever} | \text{Flu})$ ,  $P(\text{Fever} | \text{Constipation})$  ..., we can infer  $P(\text{Flu} | \text{Fever})$ .
- $\{B_j \mid j = 1, \dots, n\}$  forms a partition of the event space


# Bayesian Networks: Advantages

- They hold the advantages derived from the classic probabilistic model
- ***They efficiently computes probabilities***
- ***They did not include rare suppositions***
- They present a high modularity level, which allow them to locally compute probabilities

# DIAVAL Expert System

- First Spanish Expert System
- It diagnoses heart diseases
- It takes into account:
  - Patient data
  - Antecedents
  - Symptoms and signs
  - Clinic tests' results (echocardiogram).
- It consist of 300 nodes

# The Bayesian Network



# Inference

- It consists in fixing the value of some nodes (observations) and computing the probability of the interesting variables (diagnostics)
- Example

# Advantages of DIAVAL

- It stores a deep knowledge of the internal processes
- It can ***explain the causal chain of anomalies*** from the diagnosed illness to the observations
- It can perform ***three types of reasoning***:
  - *Adductive*: To diagnose from observations (upward).
  - *Deductive*: It takes into account inheritable diseases (downward).
  - *Intercausal*: It looks for some causes from another ones (horizontal).
- It is based on a solid probability theory

# Drawbacks of Bayesian Networks

- ***Limited range of applications:***
  - They are good diagnosing
  - They do not fit well planning, control or design problems
- They still a huge amount of information (probabilities)
- Loops complicate computing. Researchers propose stochastic simulation methods



# Associative Networks

Carlos García Martínez



# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

## Introducción

- **Associative Nets:** Knowledge representation paradigm where ideas are expressed by means of nodes and arcs (graphs)
- Initially, they were oriented for natural language processing (***Semantic networks***)
- Nowadays, they are employed in many different applications

# Characteristics

- Common characteristics:
  - Nodes often stand for concepts, entities, attributes, events or states
  - Several Nodes may stand for the same concept
  - Arcs create connections between nodes (relations)
- Differing characteristics:
  - Node and Arc semantics
  - Inference capacities
  - Notation

# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

# Conceptual Dependency

- Schank, 1972, 1975. Proposed to tackle the natural language processing problem.
- Characteristics:
  - It does not depend on the language, in contrast to other models
  - ***It represents concepts instead of terms***

# Model


- It constructs sentences by means of:
  - Six ***Conceptual Categories***:
    - Physical object
    - Action
    - Attributes of objects (adjectives)
    - Attributes of actions (adverbs)
    - Time of a conceptualization
    - Location of a conceptualization
  - 16 ***realization rules*** that links the elements of a sentence
  - A set of ***primitives*** (12 primitives are enough to represent most of natural language)

## Basic primitives


- PTRANS: Transfer of the physical location of an object (go, move an object...)
- ATRANS: Transfer of an abstract relationship (give, lend...)
- MTRANS: Transfer of mental information (tell, teach...)
- PROPEL: Application of a physical force to an object (push)
- MOVE: Movement of a body part by owner (kick)
- GRASP: Actor grasping an object (clutch)
- INGEST: Actor ingesting an object (eat)
- Etc.



## Example: Juan drinks water



## Ejemplo: Juan compró un libro



## Advantages

- Sentences are divided in elements that do not depend on the language
- A limited set of primitives allow us to:
  - associate knowledge and representation in just one way
  - design an interpreter that performs inferences
- Inferences capacities:
  - *It affirms conditions*: Juan exists and filete exists
  - *It may guess causes / intentions*: “Juan pidió el libro a Marta”  $\Rightarrow$  “Marta tenía un libro” y “Juan quería ese libro”.
  - *It deducts results*: “Juan comió un filete”  $\Rightarrow$  “Filete dejó de existir”.

## Drawbacks

- More primitives lead to an efficiency reduction
- Critiques to using primitives:
  - The meaning of a phrase depends on the language it is formulated
  - The graphs represent a too detailed situation. Simple sentences  $\Rightarrow$  Complex graphs
  - How to determine the number and meaning of the primitives needed?
  - It focus the attention on verbs

## Drawbacks of Relational Graphs


- There are sentences that can be represented by logic, but not by relational graphs
  - You can not represent the universal quantifier
- It is difficult to represent the interaction of propositions:
  - Night comes and temperature falls (two actions at the same time)
  - If it is night and foggy, it is dangerous to drive (It can not be represented)

# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

## Sowa's Conceptual Structures

- They can draw contextual situations gathering up nodes in rectangles



## Linear Notation

- Shapiro's nets and conceptual structures can be expressed in a linear notation:

[PENSAR] -

→ (AGT) → [PERS: Antonio]

→ (OBJ) → [PROPOSICION: [LEER] -

→ (AGT) → [PERS: Luisa]

→ (OBJ) → [LIBRO]]



## Linear Notation Examples

- Un río:  $[RÍO: *] \equiv [RÍO]$
- Un río caudaloso:  $[RÍO] \rightarrow (ATR) \rightarrow [CAUDALOSO]$
- Algunos ríos:  $[RÍO: \{*\}]$
- Tres ríos:  $[RÍO: \{*\}@3]$
- El río (uno específico):  $[RÍO: \#]$
- ¿Qué río?:  $[RÍO: ?]$
- El río Ebro:  $[RÍO: Ebro]$
- Los ríos Duero y Tajo:  $[RÍO: \{Duero, Tajo\}]$
- Todo río, todos los ríos:  $[RÍO: \forall]$
- Cinco litros de agua:  
 $[AGUA] \rightarrow (MEDIDA) \rightarrow [CANTIDAD: 5L.]$

## Linear Notation Examples


- Las 10 de la mañana: [HORA: 10 a.m.]
- Todos los seres humanos son mortales:  
[PERS:  $\forall$ ]  $\rightarrow$  (ATR)  $\rightarrow$  [MORTAL]
- Algún ser humano es mortal:  
[PERS]  $\rightarrow$  (ATR)  $\rightarrow$  [MORTAL]
- Él no ha venido:  
(NEG)  $\leftarrow$  [PROPOSICIÓN: [VENIR]  
 $\rightarrow$  (AGT)  $\rightarrow$  [HOMBRE: #]  
 $\rightarrow$  (PASADO)]

## Linear Notation Examples

- Probablemente iré mañana:  
[PROBABLE] ← (MOD) ← [PROPOSICIÓN: [IR]  
→ (AGT) → [PERS: #yo]  
→ (TIEMPO) → [DÍA: #mañana]
- ¿Quién es el profesor de Luis?:  
[PERS: ?] → (PROFESOR-DE) → [PERS: Luis]
- ¿Dónde está tu libro?:  
[LUGAR: ?] ← (LOC) ← [LIBRO: #] → (POS) → [PERS: #tú]

# Variables

CONDICIONAL



[CONDICIONAL:

(SI) → [PROPOSICION: [POSEER]

→ (AGT) → [PERS: \*x]

→ (OBJ) → [CONCHE: \*y]]

(ENT) → [PROPOSICIÓN: [UTILIZAR]

→ (AGT) → [T: \*x]

→ (OBJ) → [T: \*y]]]

# Variables

[DECIR]

- (AGT) → [PERS: Ana]
- (RCP) → [PERS: #él]
- (OBJ) → [PROPOSICIÓN: [SUSPENDER]
  - (OBJ) → [CLASE: #] \*y]
- (PASADO)

[COMENTAR]

- (AGT) → [#él]
- (RCP) → [PERS: Luis]
- (OBJ) → [\*y]
- (PASADO)

## Summary

Conceptual Structures consist of three types of elements:

- ***Generic concepts:*** BOOK, PERSON, THINK
- ***Individual concepts:*** [PERSON: #me]
- ***Conceptual relations:***
  - Unit: PAST, NEG, etc
  - Binary: AGT, OBJ, RCV, ATTR, LOC, MEASURE, MOD, TEMP, THEACHER-OF etc
  - Ternary: BETWEEN

## Inference Engine

- **Specialization:** To obtain a particular proposition from a general one by specializing some elements.
- **Generalization:** Opposite to specialization.
- **Union and simplification:** It is similar to the resolution principle in logic

# Inference Examples

G1: [PERS:∅] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

*specialization*

G2: [PERS: Marta] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

G3: [NIÑA] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

*specialization*

G4: [NIÑA: Marta] ← (AGT) ← [BEBER] → (OBJ) → [AGUA]

G5: [NIÑA:Marta] ← (AGT) ← [BEBER] → (INSTR) → [VASO]

*union and simplification*

G6: [BEBER]

→ (AGT) → [NIÑA: Marta]

→ (OBJ) → [AGUA]

→ (INSTR) → [VASO]



# Outline

- Introduction
- Conceptual dependency
- Propositional Networks
- Causal Networks

# Causal Networks

- They consist of:
  - Nodes = variables
  - Links = ***influence relations*** between variables
- Often used in diagnostic problems




# CASNET

- Casual Associational NETwork, 1970.
- Objective: to help when diagnosing and treating glaucoma and **eye diseases**
- Advantages over other expert systems:
  - **Temporal reasoning:** it takes into account the evolution of the disease
  - **Multiple diagnostic**
  - **It explains its conclusions**

# Diagnostic Network

- Nodes are placed in three levels:
  - **Observations:**
    - Symptoms (whatever patient feels)
    - Signs (whatever doctor perceives)
    - Results of laboratory tests
  - **Pathological states:** disfunction of organs
  - **Illness states:** structured by means of a taxonomic tree
- Inter-level and Intra-level links with associated ***causal factors***

# CASNET



## Diagnosis and Therapy

- There are two types of diagnosis:
  - Pathological states (simple).
  - Illness
- It also offer ***therapeutic recommendations*** in another plane where nodes are therapies and links can relate:
  - therapies with pathological or illness estates
  - therapies among them (interactions, toxicity and temporal dependencies)


## Bayesian Networks: Model

- It is a connex acyclic directed graph with an associated probability distribution on its variables, which fulfils graphical property of ***directed-separation***.
- For each node, designer has to provide the probabilities of its values conditioned to the values of its parent nodes

$$P(x_i) \quad P(x_i | \{parents(x)\})$$

## Example

- Let it be the following network with the following probabilities  $P(O)$ ,  $P(S)$ ,  $P(A \mid O, S)$ ,  $P(F \mid A)$ ,  $P(G \mid A)$



- Conditional independence  $\Rightarrow P(F \mid A, O, S, G) = P(F \mid A)$
- $P(O, S, A, F, G) = P(O) P(S) P(A \mid O, S) P(F \mid A) P(G \mid A)$



## Directed Separation Property

- If two sets of nodes  $X$  and  $Y$  are d-separated in the graph by a third set  $Z$ , then, they are independent given the values of nodes in  $Z$
- A path (undirected) is d-separated by set  $Z$  if:
  - it contains a chain  $i \rightarrow m \rightarrow j$  and  $m$  is in  $Z$ , or
  - a chain  $i \leftarrow m \leftarrow j$  and  $m$  is in  $Z$
  - a chain  $i \leftarrow m \rightarrow j$  and  $m$  is in  $Z$
  - a chain  $i \rightarrow m \leftarrow j$  and no descendant of  $m$  is in  $Z$ , neither  $m$
- It allows to work with probabilities without the necessity of exponential amounts of information<sup>33</sup>

# Bayes' Theorem (1)

- Given the *a priori* probability of one hypothesis  $P(B_i)$  and the conditional hypothesis  $P(A|B_i)$ , we can obtain the probability of the following hypothesis:

$$P(B_i|A) = \frac{P(A|B_i) \cdot P(B_i)}{P(A)} = \frac{P(A|B_i) \cdot P(B_i)}{\sum_{j=1}^n P(A|B_j) \cdot P(B_j)}$$

- If we have  $P(\text{Flu})$  y  $P(\text{Fever} | \text{Flu})$ ,  $P(\text{Fever} | \text{Constipation})$  ..., we can infer  $P(\text{Flu} | \text{Fever})$ .
- $\{B_j | j = 1, \dots, n\}$  forms a partition of the event space


## Bayesian Networks: Advantages

- They hold the advantages derived from the classic probabilistic model
- ***They efficiently computes probabilities***
- ***They did not include rare suppositions***
- They present a high modularity level, which allow them to locally compute probabilities

## DIAVAL Expert System

- First Spanish Expert System
- It diagnoses heart diseases
- It takes into account:
  - Patient data
  - Antecedents
  - Symptoms and signs
  - Clinic tests' results (echocardiogram).
- It consist of 300 nodes

# The Bayesian Network



# Inference

- It consists in fixing the value of some nodes (observations) and computing the probability of the interesting variables (diagnostics)
- Example

## Advantages of DIAVAL

- It stores a deep knowledge of the internal processes
- It can ***explain the causal chain of anomalies*** from the diagnosed illness to the observations
- It can perform ***three types of reasoning***:
  - *Adductive*: To diagnose from observations (upward).
  - *Deductive*: It takes into account inheritable diseases (downward).
  - *Intercausal*: It looks for some causes from another ones (horizontal).
- It is based on a solid probability theory

## Drawbacks of Bayesian Networks

- ***Limited range of applications:***
  - They are good diagnosing
  - They do not fit well planning, control or design problems
- They still a huge amount of information (probabilities)
- Loops complicate computing. Researchers propose stochastic simulation methods