


Level 4

Watsonx Orchestrate

Hands-on lab guide: Agent knowledge



Version 3.1

July 2026

LEGAL NOTICES

This information was developed for products and services offered in the USA. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing IBM Corporation
North Castle Drive, MD-NC119 Armonk, NY 10504-1785
United States of America

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions; therefore, this statement may not apply to you. This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice. Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk. IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you. Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All names and references for organizations and other business institutions used in this deliverable's scenarios are fictional. Any match with real organizations or institutions is coincidental. All names and associated information for people in this deliverable's scenarios are fictional. Any match with a real person is coincidental.

TRADEMARKS

IBM, the IBM logo, and [ibm.com](https://www.ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at “Copyright and trademark information” at <https://www.ibm.com/legal/copyright-trademark>.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates. INFOBLOX is a trademark of Infoblox Inc. or its affiliated companies, registered in the United States and other countries.

Microsoft®, Azure, Windows, Windows NT, Windows Server, Microsoft® Excel®, Microsoft® Word®, Microsoft® Outlook®, Microsoft® Excel® logo, Microsoft® Word® logo, Microsoft® Outlook® logo, Microsoft® Windows App, Microsoft® Windows App logo and the Windows logo are trademarks of Microsoft® Corporation in the United States, other countries, or both.

Salesforce and Salesforce logo are registered trademarks of SALESFORCE, INC. (CORPORATION; CALIFORNIA, USA).

Slack is a registered trademark of Salesforce, Inc (CORPORATION; DELAWARE, USA).

Red Hat®, JBoss®, OpenShift®, Fedora®, Hibernate®, Ansible®, CloudForms®, RHCA®, RHCE®, RHCSA®, Ceph®, and Gluster® are trademarks or registered trademarks of Red Hat, Inc. or its subsidiaries in the United States and other countries.

Google, Google logo, Google Tasks, Google Cloud Platform, GMAIL, GMAIL logo are registered trademarks of GOOGLE LLC and this material is not endorsed by or affiliated with Google in any way.

Elasticsearch, Elastic search logo, Elastic, Elastic logo are registered trademarks of Elasticsearch BV (LIMITED LIABILITY COMPANY; NETHERLANDS) in United States, other countries or both.

Milvus, Milvus logo are registered trademarks of LF Projects, LLC (LIMITED LIABILITY COMPANY; DELAWARE, USA) in United States, other countries or both.

Meta, Meta logos, Llama, Llama logos are registered trademarks of META PLATFORMS, INC. (CORPORATION; California, USA) in United States, other countries or both.

Mistral, Mistral logo, Mistral AI, Mistral AI logo are registered trademarks of Mistral AI (SOCIÉTÉ PAR ACTIONS SIMPLIFIÉE (SAS); FRANCE) in United States, other countries or both.

PyCharm, PyCharm logo are registered trademarks of JetBrains s.r.o. (CORPORATION; CZECH REPUBLIC) in United States, other countries or both.

Bruno is a trademark held by Anoop M D. Bruno logo is sourced from OpenMoji. License: CC BY-SA 4.0

Apple, Apple logo, Apple store, App store, App store logo are registered trademarks of Apple Inc. (CORPORATION; CALIFORNIA, USA) in United States, other countries or both.

VMWARE, VMWARE logos are registered trademarks of VMware LLC (LIMITED LIABILITY COMPANY; Delaware, USA) in United States, other countries or both.

RANCHER, RANCHER logo, Rancher Desktop, Rancher Desktop logo are registered trademarks of SUSE LLC (LIMITED LIABILITY COMPANY; MASSACHUSETTS, USA) in United States, other countries or both.

Langfuse, Langfuse logo are registered trademarks of Langfuse GmbH (GESELLSCHAFT MIT BESCHRÄNKTER HAFTUNG (GMBH); Germany, Germany) in United States, other countries or both.

OpenMeteo is a registered trademark owned by Patrick Zippenfenig (Individual, Germany) in United States, other countries or both.

© Copyright International Business Machines Corporation 2025. This document may not be reproduced in whole or in part without the prior written permission of IBM.

Table of Contents

Introduction 1

 Lab overview.....1

 What you will learn2

 Environment2

 How to get support.....2

 Prerequisites2

IBM knowledge base agent 3

 Knowledge base creation3

 Agent creation.....8

 Agent testing10

Summary..... 16

Appendix: Troubleshooting..... 17

 System unresponsive17

 LLM Error17

Appendix: Reset your environment 18

Introduction

Lab overview

In watsonx Orchestrate, agents can use knowledge bases to search for relevant, grounded content or answers.

With the watsonx Orchestrate Agent Development Kit (ADK 2.4), you can define knowledge bases using YAML or JSON, and import them to your active environment using the ADK 2.4 CLI.

You can create two types of knowledge bases: built-in and external. Built-in knowledge bases are created using a built-in Milvus instance and are populated with documents you import. External knowledge bases refer to your own Milvus or Elasticsearch instances, which you can connect to watsonx Orchestrate for use by agents.

This lab will guide you through the steps to use the built-in Milvus instance to create your knowledge base. When complete, the agent will be able to respond any questions related to the content of the pdf documents. In this lab, we will use two pdf documents:

- The history of IBM
- The exported IBM Wikipedia page (Source: <https://en.wikipedia.org/wiki/IBM>)

The agent will provide citations describing the source of information the response is based on and the precise location in the source document as shown below:

The screenshot displays the IBM watsonx Orchestrate web interface. On the left, a sidebar contains navigation options: 'Agents' (with a dropdown for 'ibm_agent'), 'Chats', and a 'Today' section. The 'Chats' section is active, showing a chat history with the question 'What was the origin...'. The main area shows a chat window with the question 'What was the original creation name of IBM?'. The agent's response is: 'The original creation name of IBM was the Computing-Tabulating-Recording Company (CTR)'. Below the response, a citation box is shown for 'IBM_wikipedia.pdf', containing a snippet of text: '[21] On June 16, 1911, their four companies were amalgamated in New York State by Charles Ranlett Flint forming a fifth company, the Computing-Tabulating-Recording Company (CTR) based in Endicott, New York.' A 'View source' link is provided. At the bottom, there is a text input field with the placeholder 'Type something...' and a send button.

What you will learn

Once you have completed this lab you will have developed skills enabling you to complete the following tasks:

1. Create a knowledge base in watsonx Orchestrate.
2. Create an agent that uses this knowledge base.
3. Use the agent description and agent instructions to define the agent's behavior.

Environment

This lab has been tested with the Agent Development Kit (ADK) version 2.12 or higher

How to get support

If you encounter an issue with this lab,

- IBM employees can open an IBM Support ticket at <http://ibm.biz/support>.
- Business Partners can request help at the [Partner Plus Support](#) website.

Prerequisites


Make sure the following prerequisites are satisfied before proceeding with this lab:

- You have performed the Preparation Lab guide including the environment validation step
- You have your local ADK 2.12 (or higher) environment up and running (Orchestrate server started after validating the environment in the preparation guide OR after having performed another ADK related lab)

Note: If for some reason your server is not started correctly, reset your server following the [Reset your environment](#) appendix.

IBM knowledge base agent


In this section you will create and test an IBM agent. You will create the agent and provide this agent with a knowledge base populated with two documents. The diagram below provides an overview of the configuration used in this section. Review the agent and knowledge base configuration shown below before proceeding.




Knowledge base creation

In this section you will learn how to use the watsonx Orchestrate ADK to create a knowledge base in your watsonx Orchestrate instance. This knowledge base will then be used by an agent to answer topic specific questions.


1. Open the ADK environment and start the watsonx Orchestrate server if not yet done. Refer to the [Reset your environment appendix](#) if your orchestrate server is not started.
2. Navigate in your `wxo-ADK/ibm_knowledge/Knowledge_base` folder (A).



3. Edit the `ibm_knowledge_base.yaml` file using your preferred text editor (A).



4. Review the implementation of the Knowledge base (this is explained below).



prompt_instruction	If specified, this instruction will be included in the prompt sent to the language model to guide response generation.
Idk_message	I don't know message. Set this under generation. Defines the fallback message sent to the user when the knowledge base cannot provide an answer.
generated_response_length	Set this to one of Concise, Moderate or Verbose. This setting adjusts the prompt to request responses of the specified length. If not set, the default is Moderate.
Max_docs_passed_to_llm	Set this under generation. If specified, define the maximum number of documents passed to the LLM. This field accepts values from 1 to 20.
retrieval_confidence_threshold	Set this to one of Lowest , Low , High or Highest . This threshold determines the minimum confidence required that the retrieved documents answer the user's query. If the confidence is below the threshold, the agent will return a default "I don't know" response instead of generating a response. The default is "Low".
response_confidence_threshold	Set this to one of Lowest , Low , High or Highest . This threshold evaluates the confidence that both the generated response and the retrieved documents answer the user's query. If the confidence is below the threshold, the agent will return a default "I don't know"

	response. The default is Low .
query_rewrite	If enabled, the user's query is rewritten using the context of the conversation to support multi-turn interactions. This setting is enabled by default.
citations_shown	This controls the maximum number of citations shown to the user in a knowledge-based response. If not set, the default is -1, which means all available citations will be displayed

Note: You can change the **prompt_instruction** parameter to add your own instructions for the content generation engine. We will use the default in this lab.

- Enter the following command into the terminal (A) to create the knowledge base.

```
orchestrate knowledge-bases import -f
ibm_knowledge/knowledge_base/ibm_knowledge_base.yaml
```

```
wxo-ADK --zsh -- 119x31
Skipping already applied migration: 20251111.sql
Skipping already applied migration: 20251112.sql
Existing wxo_observability DB found
Skipping already applied observability migration: 00_init_db.sql
Skipping already applied observability migration: 01_create_tables.sql
Skipping already applied observability migration: 02_triggers_and_functions.sql
Skipping already applied observability migration: 03_security.sql
Skipping already applied observability migration: 04_rls_policies.sql
Skipping already applied observability migration: 20250116.sql
[INFO] - Migration ran successfully.
[INFO] - Waiting for orchestrate server to be fully initialized and ready...
[INFO] - Orchestrate services initialized successfully
[INFO] - local tenant found
[INFO] - You can run 'orchestrate env activate local' to set your environment or 'orchestrate chat start' to start the
UI service and begin chatting.
[INFO] - You can access the observability platform Langfuse at http://localhost:3010, username: orchestrate@ibm.com, pa
ssword: orchestrate
ADK >orchestrate agents import -f city-agent/city_agent.yaml
[INFO] - Agent 'city_agent' imported successfully
ADK >orchestrate chat start
[INFO] - local tenant found
[INFO] - Auto-detecting local IP address for async tool callbacks...
[INFO] - Auto-configured CALLBACK_HOST_URL to: http://9.83.134.220:4321
[INFO] - Waiting for orchestrate server to be fully started and ready...
[INFO] - Starting docker-compose UI service inside LimaLifecycleManager...
[INFO] - Chat UI Service started successfully.
[INFO] - Waiting for UI component to be initialized...
[INFO] - Opening chat interface at http://localhost:3000/chat-lite
[WARNING] - When using local chat, requests that the user 'Connect Apps' must be resolved by running 'orchestrate conne
ctions set conditionals'
ADK >orchestrate knowledge-bases import -f ibm_knowledge/knowledge_base/ibm_knowledge_base.yaml
```

Note: On Windows, if you use folder name completion using the TAB key, the slashes are changed into back-slashes. The orchestrate command still finds the correct yaml file but then fails to find the PDF documents. Ensure you use forward slash “/”.

You should see the following message when the knowledge base is created:

```

[INFO] - orchestrate services initialized successfully
[INFO] - local tenant found
[INFO] - You can run 'orchestrate env activate local' to set your environment or 'orchestrate chat start' to start the
UI service and begin chatting.
[INFO] - You can access the observability platform Langfuse at http://localhost:3010, username: orchestrate@ibm.com, pa
ssword: orchestrate
ADK >orchestrate agents import -f city-agent/city_agent.yaml
[INFO] - Agent 'city_agent' imported successfully
ADK >orchestrate chat start
[INFO] - local tenant found
[INFO] - Auto-detecting local IP address for async tool callbacks...
[INFO] - Auto-configured CALLBACK_HOST_URL to: http://9.83.134.220:4321
[INFO] - Waiting for orchestrate server to be fully started and ready...
[INFO] - Starting docker-compose UI service inside LimalifecycleManager...
[INFO] - Chat UI Service started successfully.
[INFO] - Waiting for UI component to be initialized...
[INFO] - Opening chat interface at http://localhost:3000/chat-lite
[WARNING] - When using local chat, requests that the user 'Connect Apps' must be resolved by running 'orchestrate conne
ctions set-credentials'
ADK >orchestrate knowledge-bases import -f ibm_knowledge/knowledge_base/ibm_knowledge_base.yaml
[INFO] - Successfully imported knowledge base 'ibm_knowledge_base'
ADK >

```

6. Type 'orchestrate knowledge-bases status -n ibm_knowledge_base' and check the status and the documents contained in your knowledge base (A).

wxo-ADK -- zsh -- 170x34


A >orchestrate knowledge-bases status -n ibm_knowledge_base

Name	Description	Prioritize Built In Index	Ready	Built In Index Status	Built In Index Status Msg	Documents (2)	Id
ibm_knowledge_base	General information about IBM and its history	true	true	ready		history_of_ibm.pdf, IBM_wikipedia.pdf	9262d76c-a813-4ea6-...


ADK >

Agent creation


1. Navigate to your `wxo-ADK/ibm_knowledge/agents` (A) folder.



2. Edit the `ibm_agent.yaml` file(A).



- Review the definition of the agent (A).




```
! ibm_agent.yaml X
Users > laurenttarin > wxo-ADK > ibm_knowledge > agents > ! ibm_agent.yaml
1 spec_version: v1
2 kind: native
3 name: ibm_agent
4 description: >
5   | You are a helpful agent that has knowledge about IBM and its history
6 llm: groq/openai/gpt-oss-120b
7 style: react
8 instructions: use the ibm_agent for any IBM related question
9 knowledge_base:
10   - ibm_knowledge_base
11 tools: []
```

This yaml file defines the agent, its description behavior/instructions, and the LLM it will use for planning and reasoning. This agent has no collaborators and no tools, but a single knowledge base is declared.

- Enter the following command into the terminal (A) to create the agent.

```
orchestrate agents import -f ibm_knowledge/agents/ibm_agent.yaml
```



```
wxo-ADK -- -zsh -- 119x31
Existing wxo_observability DB found
Skipping already applied observability migration: 00_init_db.sql
Skipping already applied observability migration: 01_create_tables.sql
Skipping already applied observability migration: 02_triggers_and_functions.sql
Skipping already applied observability migration: 03_security.sql
Skipping already applied observability migration: 04_rls_policies.sql
Skipping already applied observability migration: 20250116.sql
[INFO] - Migration ran successfully.
[INFO] - Waiting for orchestrate server to be fully initialized and ready...
[INFO] - Orchestrate services initialized successfully
[INFO] - local tenant found
[INFO] - You can run 'orchestrate env activate local' to set your environment or 'orchestrate chat start' to start the
UI service and begin chatting.
[INFO] - You can access the observability platform Langfuse at http://localhost:3010, username: orchestrate@ibm.com, pa
ssword: orchestrate
ADK > orchestrate agents import -f city-agent/city_agent.yaml
[INFO] - Agent 'city_agent' imported successfully
ADK > orchestrate chat start
[INFO] - local tenant found
[INFO] - Auto-detecting local IP address for async tool callbacks...
[INFO] - Auto-configured CALLBACK_HOST_URL to: http://9.83.134.220:4321
[INFO] - Waiting for orchestrate server to be fully started and ready...
[INFO] - Starting docker-compose UI service inside LimalifecycleManager...
[INFO] - Chat UI Service started successfully.
[INFO] - Waiting for UI component to be initialized...
[INFO] - Opening chat interface at http://localhost:3000/chat-lite
[WARNING] - When using local chat, requests that the user 'Connect Apps' must be resolved by running 'orchestrate conne
ctions set-credentials'
ADK > orchestrate knowledge-bases import -f ibm_knowledge/knowledge_base/ibm_knowledge_base.yaml
[INFO] - Successfully imported knowledge base - ibm_knowledge_base
ADK > orchestrate agents import -f ibm_knowledge/agents/ibm_agent.yaml
```

- Wait for the message (A) indicating successful agent creation:

```
wxo-ADK --zsh -- 119x31

Skipping already applied observability migration: 01_create_tables.sql
Skipping already applied observability migration: 02_triggers_and_functions.sql
Skipping already applied observability migration: 03_security.sql
Skipping already applied observability migration: 04_rls_policies.sql
Skipping already applied observability migration: 20250116.sql
[INFO] - Migration ran successfully.
[INFO] - Waiting for orchestrate server to be fully initialized and ready...
[INFO] - Orchestrate services initialized successfully
[INFO] - local tenant found
[INFO] - You can run `orchestrate env activate local` to set your environment or `orchestrate chat start` to start the
UI service and begin chatting.
[INFO] - You can access the observability platform Langfuse at http://localhost:3010, username: orchestrate@ibm.com, pa
ssword: orchestrate
ADK >orchestrate agents import -f city-agent/city_agent.yaml
[INFO] - Agent 'city_agent' imported successfully
ADK >orchestrate chat start
[INFO] - local tenant found
[INFO] - Auto-detecting local IP address for async tool callbacks...
[INFO] - Auto-configured CALLBACK_HOST_URL to: http://9.83.134.220:4321
[INFO] - Waiting for orchestrate server to be fully started and ready...
[INFO] - Starting docker-compose UI service inside LimaLifecycleManager...
[INFO] - Chat UI Service started successfully.
[INFO] - Waiting for UI component to be initialized...
[INFO] - Opening chat interface at http://localhost:3000/chat-lite
[WARNING] - When using local chat, requests that the user 'Connect Apps' must be resolved by running `orchestrate conne
ctions set-credentials`
ADK >orchestrate knowledge-bases import -f ibm_knowledge/knowledge_base/ibm_knowledge_base.yaml
[INFO] - Successfully imported knowledge base 'ibm_knowledge_base'
ADK >orchestrate agents import -f ibm_knowledge/agents/ibm_agent.yaml
[INFO] - Agent 'ibm_agent' imported successfully
ADK >
```

Agent testing


In this section you will start the chat interface, test the agent and review its reasoning in the chat UI.

- Enter the following command into the terminal (A) to start the chat server.

```
orchestrate chat start
```


```
[INFO] - Agent 'city_agent' imported successfully
ADK >orchestrate chat start
[INFO] - local tenant found
[INFO] - Auto-detecting local IP address for async tool callbacks...
[INFO] - Auto-configured CALLBACK_HOST_URL to: http://9.83.134.220:4321
[INFO] - Waiting for orchestrate server to be fully started and ready...
[INFO] - Starting docker-compose UI service inside LimaLifecycleManager...
[INFO] - Chat UI Service started successfully.
[INFO] - Waiting for UI component to be initialized...
[INFO] - Opening chat interface at http://localhost:3000/chat-lite
[WARNING] - When using local chat, requests that the user 'Connect Apps' must be resolved by running `orchestrate conne
ctions set-credentials`
ADK >orchestrate knowledge-bases import -f ibm_knowledge/knowledge_base/ibm_knowledge_base.yaml
[INFO] - Successfully imported knowledge base 'ibm_knowledge_base'
ADK >orchestrate agents import -f ibm_knowledge/agents/ibm_agent.yaml
[INFO] - Agent 'ibm_agent' imported successfully
ADK >orchestrate chat start
```

- When the browser opens, ensure **ibm_agent** is selected (A) and enter "What was the original name of IBM?" into the chat window (B), then press Enter.




The user input is interpreted as a question about the IBM history. The agent will use the knowledge base that you created as the basis for the response. If the agent isn't visible, refresh your browser.

- After a few seconds the agent should reply (A):




Please note that it can take 10-15 minutes for the citations to become available after uploading the documents.


- Expand the citations panel (A).




- Click View source (A).




- Review the source of the answer from the document (A).




- Click the X icon to close the information panel (A).



8. Click Show Reasoning (A).



9. Expand the Step 1 panel (A).



10. The reasoning panel shows the input and output parameters (A) passed between the agent and the tool:

The screenshot displays the IBM watsonx Orchestrate interface. On the left sidebar, the 'Agents' section shows 'ibm_agent' selected. The main chat area shows a conversation with 'ibm_agent' at 4:43 PM. The query 'What was the original name of IBM?' is entered. The reasoning panel, labeled 'Step 1', is expanded and highlighted with a red box. It shows the input and output parameters passed between the agent and the tool. A red circle with the letter 'A' is placed next to the reasoning panel.

IBM watsonx Orchestrate

What was the original name of IBM?

You 4:43 PM

What was the original name of IBM?

ibm_agent 4:43 PM | Hide Reasoning

Step 1

Input - 3 Lines

```
{
  "query": "original name of IBM"
}
```

Output - 22 Lines

```
[
  {
    "title": "IBM_wikipedia.pdf",
    "body": "IBM\n\nInternational Business Machines Corporation\n\nLogo since 1972, designed by Paul Rand\n\n# IBM CHQ in Armonk, New York, in 2014\n\nTrade name\n\nIBM\n\nFormerly Computing-Tabulating-Recording Company (1911-1924)\n\nCompany type Public\n\nTraded as\n\nNYSE: IBM\n\nDJIA component\n\nS&P 100 component\n\nS&P 500 component\n\nISIN ISIN: US4592001014\n\nIndustry\n\nInformation technology\n\nPredecessors\n\nBundy Manufacturing Company\n\nComputing Scale Company of America\n\nInternational Time Recording Company\n\nTabulating Machine Company\n\nComputing-
```

Type something...

Summary

In this lab you created a knowledge base with topic specific documents and created an agent that was able to answer IBM history questions. The agent was able to adapt to the users request and interpret the information provided using the reasoning power of an LLM.

Appendix: Troubleshooting

System unresponsive

If your ADK environment becomes unresponsive use the command below to stop all running containers.

```
docker stop $(docker ps -q)
```

Enter the following command into the terminal to reset your server, then press Enter.

```
orchestrate server reset
```

Enter the following command into the terminal to restart your server, then press Enter.

```
orchestrate server start -l -e env
```

Enter the following command into the terminal (A) to start the chat server.

```
orchestrate chat start
```

You will need to repeat any commands to create tools and agents.


LLM Error

If you receive an error when using your agent (that worked previously), your API key may have been deleted. You will need to recreate the API key from your watsonx Orchestrate instance, update your env file, and restart the server.

Appendix: Reset your environment


These steps will remove any existing tools and agents from your environment and restart the local watsonx Orchestrate server in readiness to start the lab.

1. Open a Terminal window on your **wxO-ADK** folder (A).



2. Enter the following command into the terminal to start your virtual environment:

```
source .venv/bin/activate
```




3. Check that the prompt starts with (.venv) (A) indicating that you are in your virtual environment.



A terminal window titled "wxo-ADK - zsh - 119x31". The output shows the last login time and the execution of the command `source .venv/bin/activate`. The prompt has changed from `laurenttarin@mac wxo-ADK %` to `(.venv) laurenttarin@mac wxo-ADK %`, indicating the virtual environment is active.

4. Enter the following command into the terminal to improve the command visibility, then press Enter:

```
MS Windows users: function prompt{"ADK>"}  
Mac users: prompt="ADK >"
```



A terminal window titled "wxo-ADK - zsh - 119x31". The prompt is `(.venv) laurenttarin@mac wxo-ADK %`. The command `prompt="ADK >"` is being entered. A red box highlights the command, and a red circle with the letter 'A' is next to it, indicating the step number.

5. Enter the following command into the terminal to stop your chat service, then press Enter.


```
orchestrate chat stop
```

6. Enter the following command into the terminal to reset your server, then press Enter.

```
orchestrate server reset
```

7. Enter the following command into the terminal to start the server with your env configuration, then press Enter.

```
orchestrate server start -l -e env --with-ai-builder
```



Note: Some services may fail to start on the first attempt, and you may encounter issues connecting to the docker repository. Retry the start command in this situation, depending on the volume of requests, it can take several attempts to connect.

When startup is complete the terminal output will resemble the example below, restart can take 2-3 minutes to complete. The local server will be ready when you will see this **INFO** in the terminal screen (A):

```
wxo-ADK -- -zsh -- 119x31

Skipping already applied migration: 20251001.sql
Skipping already applied migration: 20251006.sql
Skipping already applied migration: 20251007.sql
Skipping already applied migration: 20251008.sql
Skipping already applied migration: 20251009.sql
Skipping already applied migration: 20251022.sql
Skipping already applied migration: 20251023.sql
Skipping already applied migration: 20251029.sql
Skipping already applied migration: 20251101.sql
Skipping already applied migration: 20251103.sql
Skipping already applied migration: 20251104.sql
Skipping already applied migration: 20251107.sql
Skipping already applied migration: 20251110.sql
Skipping already applied migration: 20251111.sql
Skipping already applied migration: 20251112.sql
Existing wxo_observability DB found
Skipping already applied observability migration: 00_init_db.sql
Skipping already applied observability migration: 01_create_tables.sql
Skipping already applied observability migration: 02_triggers_and_functions.sql
Skipping already applied observability migration: 03_security.sql
Skipping already applied observability migration: 04_rls_policies.sql
Skipping already applied observability migration: 20250116.sql
[INFO] - Migration ran successfully.
[INFO] - Waiting for orchestrate server to be fully initialized and ready...
[INFO] - Orchestrate services initialized successfully
[INFO] - local tenant found
[INFO] - You can run 'orchestrate env activate local' to set your environment or 'orchestrate chat start' to start the
UI service and begin chatting.
[INFO] - You can access the observability platform Langfuse at http://localhost:3010, username: orchestrate@ibm.com, pa
ssword: orchestrate
ADK
```



You are now ready to work with watsonx Orchestrate ADK.

