

Aryan Jamshidian

Personal Portfolio

Semiconductor Laser Characterization


UBC Blusson Quantum Matter Institute

Goal:

Design an automated testing procedure to characterize an unknown semiconductor laser.

Setup:

1. Customize a photonic chip mount in Onshape, assemble optical stage.
2. Interface with:
 1. Laser Diode Controller
 2. Thermoelectric Cooler
 3. Photodetector
 4. Optical Spectrum Analyzerover GPIB connection.
3. Solder thermistors, set up microscope, land electrical probes.



On-Chip Distributed Feedback Laser



Semiconductor Laser Characterization



UBC Blusson Quantum Matter Institute

Characterizing External Components:

The laser must be connected to an isolator to remain stable during the experiment. So, I first characterize the losses in the isolator and the fiber optic wire.

I used a known reference laser and did a sweep across the usable power range.

Comparison of Insertion Loss and Reverse Leakage for Two Isolators



Semiconductor Laser Characterization

UBC Blusson Quantum Matter Institute


Characterizing Laser:

I wrote an automated script to perform a current sweep across the usable range of the laser at 25°C, 35°C, and 45°C.

I used the data from the reference laser experiment to calibrate out the isolator losses, alongside known values of photonic wire-bond losses.

I used the second derivative test to find the threshold current of the laser, and linearly fit the data to find the slope efficiency.

The datasheet of this laser reports a slope efficiency of 0.28 mW/mA @ 25°C, which is very similar to my experimental result of 0.281.



Semiconductor Laser Characterization

UBC Blusson Quantum Matter Institute


Characterizing Laser:

Next, I use an optical spectrum analyzer to observe the stability of the laser. A stable DFB laser has one large peak, a suppressed sister mode, and multiple smaller side modes.

I also ran an analysis program to extract some parameters for simulation. These include:

1. Central Mode Parameters (largest spike)
 1. Peak Wavelength
 2. Peak Power
 3. -20dB WD (Width of spike at -20dB below peak)
2. Side Mode Parameters (bumps)
 1. Side-Mode Suppression Ratio: how much smaller the second largest spike is compared to the first
 2. Mode Offset: wavelength difference between the two largest peaks

Optical Spectrum of a DFB Laser



Mars Habitat Robot Competition



ENPH 253 – Instrument Design

Goal:

To design a fully autonomous robot that can complete various tasks themed around Mars exploration during a timed competition.

System Overview:

- Kiwi drive (holonomic motion w/ 3 omniwheels)
- Phototransistor-based PID line following
- Sensor fusion of sonar, encoders, and cameras
- 4-DOF Arm + claw with metal detector
- ESP32 + Raspberry Pi architecture
- Computer vision using YOLO




Mars Habitat Robot Competition

ENPH 253 – Instrument Design

Metal Detector:

- Designed a custom metal detector circuit to identify aluminum foil hidden in plastic rocks.
- An inductor (made of coiled wire) will experience a decrease in inductance when exposed to ferro/paramagnetic materials due to eddy currents and polarization.
- Two matched 555 timer oscillators convert inductance into frequency. Subtracting their frequencies improves resolution, allowing for detection of paramagnets such as aluminum.
- Experimental results show that we can detect up to a 0.5% change in inductance!



All the computation and thresholding is done in hardware on the claw, insulating the system from noise as it passes back down the arm.

Mars Habitat Robot Competition



ENPH 253 – Instrument Design

PCB Design:


Schematics and layouts done in Altium.

All PCBs shown are custom-built for this project and soldered in-lab!

H-Bridge + Bang-Bang Controller PCB




Signal Debouncer for
Rotary Encoders PCB



Phototransistor Array
Controller PCB

Metal Detector PCB



Mars Habitat Robot Competition


ENPH 253 – Instrument Design

Arm:

- 4-bar linkages keep the claw parallel to the ground while maintaining mobility and reach.
- Two DOFs on the arm driven by servos, rotation of the chassis about COM acts as third DOF.

Claw:

- Has yaw + open/close DOFs, can reach around corners and deposit rock onto chassis.
- Pincer geometry is optimized for picking up rocks and aligning with the habitat door.
- Also supports the metal detector coils + PCB.



Electrical Architecture Redesign

UBC Rover Design Team


Problem:

- The rover arm has eight degrees of freedom, and extends over a metre in length.
- Running power cables directly from the chassis to every motor driver is messy, difficult to assemble, and almost impossible to test.

Solution:

- Design a new wiring architecture that creates modular disconnection points between every link, groups nearby I/O ports together, and allows for fuses, limit switches, and debugging LEDs.

Wiring Architecture Diagram





Electrical Architecture Redesign

UBC Rover Design Team

Results:

- I designed six custom breakout PCBs in Altium, as well as PCB mounts in SolidWorks for secure and easy access.
- I used impedance matching techniques to minimize signal reflection along the CAN line.
- With the help of my team, we verified PCBs and rewired the arm.
- The project was successful, and has advanced the testing schedule by two months while improving quality of life for the arm subteam.



Silent Tokens in Transformer Models

Self-Guided Research Project

Problem:

- The current generation of Large Language Models is very good at predicting text, but is still incapable of holding a real conversation.
- The architecture of prompt -> response -> prompt -> response places a hard restriction on the capabilities of conversational models, especially speech models.

Theory:

- LLMs process inputs in the form of tokens. Most of these tokens are words or word stubs, but some of them represent more abstract concepts such as “the start of the user prompt” or “the end of a message”.

Hypothesis:

- Transformer models could be trained to have fluid, uninterrupted conversations by adding a new token, for the concept of “silence”, into the model’s architecture.

Silent Tokens in Transformer Models


Self-Guided Research Project

Procedure:

- I self-taught the fundamentals of machine learning and neural networks, starting from binary classifiers and progressing up to GPT-style self-attention transformers.
- I implemented and modified the GPT architecture, then retrained it on a curated dataset.
- A simplified example of my constructed training set is shown below.

Assistant: Hello! [pauses to wait for response]
Assistant: Are you there? [no reply, so speaks again]

This is a normal interaction with a person that didn't hear/understand you.



This is what gpt-5 would be trained on.

*Since it never sees the [pause], it will learn to say
“Hello! Are you there?” without waiting for a response.



This is what my model would be trained on.

Silent Tokens in Transformer Models

Self-Guided Research Project

- In theory, the model would learn that after completing a thought, it should output silence tokens (which are relayed to the user as pauses).
- If the user responds, it continues as normal. But if the user doesn't respond, then after a few silence tokens have built up it will learn to start messaging again.
- The number of silence tokens allow it to differentiate between a user responding quickly or slowly.

Results:

- Unfortunately, this experiment did not yield significant results.
- Although the model did sometimes output silence tokens, they did not match the patterns from the training data and mapped to pseudo-random pauses in speech.
- I believe that this idea could be promising with a more suitable model architecture and better training set. I intend to revisit this project in the future.

Contact

Thank you for your interest!

If my experience aligns with your company goals, feel free to contact me with:

Email: ajamshidian22@gmail.com

LinkedIn: <https://www.linkedin.com/in/aryan-jamshidian-444007337/>

Phone: 604-716-4807

Or learn more about the Engineering Physics program at <https://www.engphys.ubc.ca/>