

Conservative Constrained Interpolating Polynomials

Oleg Kravchenko* & Manuel Diaz¹

* Department of Nuclear Physics, University of Examples, Moscow, Russia.

¹ Institute of Applied Mechanics, National Taiwan University, Taiwan R.O.C.

July 28, 2015

Abstract

This a sample L^AT_EX document that explains some of the L^AT_EX commands

1 Introduction

L^AT_EX is a markup language designed and implemented by **Leslie Lamport**, based on **Donald E. Knuth**'s typesetting language T_EX. The markup in the source file of a L^AT_EX document may appear somewhat challenging, but the compiled result of the document is certainly a pleasing rendering of the mark-up material. Yabe and Aoki (1991), Yabe et al. (2001), Ii and Xiao (2007), Nakamura et al. (2001), Ii and Xiao (2009), Xiao and Yabe (2001), Xiao (2004).

L^AT_EX was built on T_EX's foundation. An article is divided into *logical units*, including an abstract, various sections and subsections, theorems, and a bibliography. The logical units are typed independently of one another. Once all the units have been typed, L^AT_EX controls the *placement* and *formatting* of these elements. L^AT_EX automatically numbers the sections, theorems, and equations in your article, and builds the cross-references. If any changes are made to the article, it automatically rennumbers its various parts and rebuilds the cross-references.

Packages are extensions of L^AT_EX. L^AT_EX commands, as a rule, start with a backslash (\) and tell L^AT_EX to do something special. For example, in the instruction `\emph{instructions to \LaTeX}`, `\emph` is a L^AT_EX command. Another kind of instruction is called an *environment*. For example, the commands `\begin{flushright}` and `\end{flushright}` enclose a `flushright` environment—texts that are typed inside this environment are right justified (lined up against the right margin) when typeset.

2 Typing Text

The following keys are used to type text in a L^AT_EX source file:

a-z A-Z 0-9

+ = * / () []

You may also use the following punctuation marks:

, ; . ? ! : ' ' -

and the spacebar, and the Return (or Enter) key.

There are thirteen special keys that are mostly used in L^AT_EX instructions:

\$ % & ~ _ ^ \ { } @ " |

If you need to use them in your document, there are commands available for typesetting these special characters. For example, \$ is typed as `\$`, the underscore (`_`) is typed as `_`, and % is typed as `\%`, whereas ä is typed as `\{"a}`, and @ is simply typed `@`.

In a L^AT_EX source file, each *comment* line begins with `%`. L^AT_EX will ignore everything on the line after the `%` character.

The *document class*, declared by the command `\documentclass{.}`, in a L^AT_EX source file controls how the document will be formatted. L^AT_EX, by default, fully justifies the text by placing a certain size space between words—the *interword space*—and a somewhat larger space between sentences—the *intersentence space*. To force an interword space, you can use the `_` command (the `_` symbol indicates a blank space). The `~` (tilde) command also forces an interword space, but with a difference: it keeps words together on the same line. It is called a “tie” or “non-breakable space.”

When L^AT_EX encounters a period, it must decide whether or not it indicates the end of a sentence. It uses the following rule: A period following a capital letter (e.g., A.) is interpreted as being part of an abbreviation or an initial and will be followed by an interword space; otherwise, it signifies the end of a sentence and will be followed by an intersentence space. If this rule causes problems in your document, you can follow the period with `_` to force an interword space, or precede the period with `\@` to force an intersentence space.

In a L^AT_EX document source file, left double quotes are typed as `' '` (two left single quotes) and right double quotes are type as `' '` (two right single quotes). The left single quote key is usually in the upper-left or upper-right corner of the keyboard, and shares a key with the tilde (`~`) key.

In a L^AT_EX command that requires an argument, the argument follows the name of the command and is placed between `{` and `}`. Command names are *case sensitive*. The command `\\` (`\newline` is another form) breaks a line. You can use the `\\` command and specify an appropriate amount of vertical space, for example `\\[1in]`. Note that this command uses *square brackets* rather than braces because the

argument is *optional*. The distance/spacing may be given in points(pt), centimeters(cm), or inches(in). To force a page break, use `\newpage`.

3 Typing Math

In addition to the keys listed above, you need the keys `|`, `<`, and `>` to type mathematical formulas. (`|` is the shifted `\` key on many keyboards).

There are two kinds of math formulas and environments:

1. *Inline math environments* open and close with `$` or open with `\(` and close with `\)`.
2. *Displayed math environments* open with `\[` and close with `\]`. Other forms of the displayed environment are `\begin{equation*} ... \end{equation*}` and `\begin{equation} ... \end{equation}`.

Within the math environment, L^AT_EX uses its own spacing rules and completely ignores the number of white spaces typed with two exceptions:

1. Spaces that delimit commands (e.g., in `∞a`, the space is not ignored; in fact, `\infty a$` is an error)
2. Spaces in the arguments of commands that temporarily revert to text mode (`\mbox` and `\text` are such commands).

In text mode, many spaces equal one space; whereas, in math mode, spaces are ignored (unless they terminate a command). To adjust the spacing in a typeset document, use a spacing command. The same formula may be typeset differently depending on whether it is inline or display. For example, $\sum_{i=1}^n i^2$ is inline math. The following is the same expression as displayed math

$$\sum_{i=1}^n i^2.$$

Math symbols are invoked by commands inside a math formula or environment. The math symbols are organized into tables in Appendix A of textbook. Some commands (e.g. `\sqrt`) need arguments enclosed in braces (`{` and `}`). For example, to typeset $\sqrt{x^2y^2}$, type `$\sqrt{x^2 y^2}$`. To typeset $\sqrt[n]{x^2y^2}$, type `$\sqrt[n]{x^2 y^2}$`. Some commands need more than one arguments. For example to typeset

$$\frac{\sin x}{\cos^2 x + \tan x}$$

type

```
\[
  \frac{\sin x}{\cos^2 x + \tan x}
\]
```

`\frac` is the command; $\sin x$ and $\cos^2 x + \tan x$ are the arguments.

Theorem 1. *This is the Pythagorean Theorem. It says*

$$x^2 + y^2 = z^2. \tag{1}$$

Definition 1. *Earth is where life is possible.*

4 Concluding Remarks

References

Ii, S. and F. Xiao

2007. Cip/multi-moment finite volume method for euler equations: a semi-lagrangian characteristic formulation. *Journal of Computational Physics*, 222(2):849–871.

Ii, S. and F. Xiao

2009. High order multi-moment constrained finite volume method. part i: Basic formulation. *Journal of Computational Physics*, 228(10):3669–3707.

Nakamura, T., R. Tanaka, T. Yabe, and K. Takizawa

2001. Exactly conservative semi-lagrangian scheme for multi-dimensional hyperbolic equations with directional splitting technique. *Journal of Computational Physics*, 174(1):171–207.

Xiao, F.

2004. Unified formulation for compressible and incompressible flows by using multi-integrated moments i: one-dimensional inviscid compressible flow. *Journal of Computational Physics*, 195(2):629–654.

Xiao, F. and T. Yabe

2001. Completely conservative and oscillationless semi-lagrangian schemes for advection transportation. *Journal of computational physics*, 170(2):498–522.

Yabe, T. and T. Aoki

1991. A universal solver for hyperbolic equations by cubic-polynomial interpolation i. one-dimensional solver. *Computer Physics Communications*, 66(2):219–232.

Yabe, T., R. Tanaka, T. Nakamura, and F. Xiao

2001. An exactly conservative semi-lagrangian scheme (cip-csl) in one dimension. *Monthly Weather Review*, 129(2):332–344.