

# New Directions in Cryptography

*Invited Paper*

WHITFIELD DIFFIE AND MARTIN E. HELLMAN, MEMBER, IEEE

**Abstract**—Two kinds of contemporary developments in cryptography are examined. Widening applications of teleprocessing have given rise to a need for new types of cryptographic systems, which minimize the need for secure key distribution channels and supply the equivalent of a written signature. This paper suggests ways to solve these currently open problems. It also discusses how the theories of communication and computation are beginning to provide the tools to solve cryptographic problems of long standing.

## I. INTRODUCTION

WE STAND TODAY on the brink of a revolution in cryptography. The development of cheap digital hardware has freed it from the design limitations of mechanical computing and brought the cost of high grade cryptographic devices down to where they can be used in such commercial applications as remote cash dispensers and computer terminals. In turn, such applications create a need for new types of cryptographic systems which minimize the necessity of secure key distribution channels and supply the equivalent of a written signature. At the same time, theoretical developments in information theory and computer science show promise of providing provably secure cryptosystems, changing this ancient art into a science.

The development of computer controlled communication networks promises effortless and inexpensive contact between people or computers on opposite sides of the world, replacing most mail and many excursions with telecommunications. For many applications these contacts must be made secure against both eavesdropping and the injection of illegitimate messages. At present, however, the solution of security problems lags well behind other areas of communications technology. Contemporary cryptography is unable to meet the requirements, in that its use would impose such severe inconveniences on the system users, as to eliminate many of the benefits of teleprocessing.

Manuscript received June 3, 1976. This work was partially supported by the National Science Foundation under NSF Grant ENG 10173. Portions of this work were presented at the IEEE Information Theory Workshop, Lenox, MA, June 23–25, 1975 and the IEEE International Symposium on Information Theory in Ronneby, Sweden, June 21–24, 1976.

W. Diffie is with the Department of Electrical Engineering, Stanford University, Stanford, CA, and the Stanford Artificial Intelligence Laboratory, Stanford, CA 94305.

M. E. Hellman is with the Department of Electrical Engineering, Stanford University, Stanford, CA 94305.

The best known cryptographic problem is that of privacy: preventing the unauthorized extraction of information from communications over an insecure channel. In order to use cryptography to insure privacy, however, it is currently necessary for the communicating parties to share a key which is known to no one else. This is done by sending the key in advance over some secure channel such as private courier or registered mail. A private conversation between two people with no prior acquaintance is a common occurrence in business, however, and it is unrealistic to expect initial business contacts to be postponed long enough for keys to be transmitted by some physical means. The cost and delay imposed by this key distribution problem is a major barrier to the transfer of business communications to large teleprocessing networks.

Section III proposes two approaches to transmitting keying information over public (i.e., insecure) channels without compromising the security of the system. In a *public key cryptosystem* enciphering and deciphering are governed by distinct keys,  $E$  and  $D$ , such that computing  $D$  from  $E$  is computationally infeasible (e.g., requiring  $10^{100}$  instructions). The enciphering key  $E$  can thus be publicly disclosed without compromising the deciphering key  $D$ . Each user of the network can, therefore, place his enciphering key in a public directory. This enables any user of the system to send a message to any other user enciphered in such a way that only the intended receiver is able to decipher it. As such, a public key cryptosystem is a multiple access cipher. A private conversation can therefore be held between any two individuals regardless of whether they have ever communicated before. Each one sends messages to the other enciphered in the receiver's public enciphering key and deciphers the messages he receives using his own secret deciphering key.

We propose some techniques for developing public key cryptosystems, but the problem is still largely open.

*Public key distribution systems* offer a different approach to eliminating the need for a secure key distribution channel. In such a system, two users who wish to exchange a key communicate back and forth until they arrive at a key in common. A third party eavesdropping on this exchange must find it computationally infeasible to compute the key from the information overheard. A possible solution to the public key distribution problem is given in Section III, and Merkle [1] has a partial solution of a different form.

A second problem, amenable to cryptographic solution, which stands in the way of replacing contemporary busi-