

QECTOR Workbench - Complete API Reference

****Workbench 1.0.1 - Backend qector_decoder_v3 1.0.0 (min 1.0.0) - 85 MCP tools - 17 decoders - 10 code families****

****Decoder package: qector_decoder_v3 1.0.0 (bundled wheel, activated offline on first launch)****

Generated 2026-08-19T13:59:28+00:00Z

This manual is generated from the live application source so every tool name, decoder kind, code family, and function signature matches the running build exactly.

Code families

Family	Parameter	Type	Graphlike	Decoders	Notes
repetition	distance	int	yes	all (16)	1D chain parity-check code.
ring	distance	int	yes	all (16)	Periodic 1D chain.
rotated_surface	distance	int	yes	all (16)	Standard rotated surface code.
unrotated_surface	distance	int	yes	15 (lookup_table refused >20 checks)	Square lattice surface code.
toric	distance	int	yes	15 (lookup_table refused >20 checks)	Toric code with periodic boundaries.
heavy_hex	distance	int	yes	all (16)	IBM heavy-hex lattice.
hypergraph_product	distance	int	yes	all (16)	CSS from repetition seed; graphlike.
bicycle	circulant size	int	no	all (16)	qLDPC bicycle code; graphlike enough for all decoders.
bivariate_bicycle	preset index	int	no	13 (excludes union_find, fast_union_find, lookup_table)	IBM
color_code	triangular size	int	no	colour_code, bp_osd, blossom, hybrid, auto_router	Triangular & 2D

Decoder kinds

Kind	Description	Options	Compatibility
union_find	Fast approximate matching via union-find.	bp_method, osd_order ignored	graphlike only
fast_union_find	Faster union-find variant; approximate, higher LER.	-	graphlike only
blossom	Weight-optimal exact MWPM; matches PyMatching LER.	-	all
sparse_blossom	Region-growing near-optimal matching; not exact.	-	graphlike only
sparse_blossom_radix_neighbors	RadixHeap k-NN candidate edge discovery variant of region-growing matching.		
bp_osd	Belief propagation + ordered statistics for LDPC/qLDPC.	bp_method, osd_order, error_rate	all
auto	Self-selecting AutoDecoder.	-	graphlike only
hybrid	Combines multiple strategies; chooses per problem.	-	graphlike only
lookup_table	Exhaustive syndrome-to-correction table; refused above 20 checks.	-	small codes only
predecoded	Fast pre-decoding pass before matching.	-	graphlike only
auto_router	Policy decoder: matching for graphlike, bp_osd for qLDPC. Universally compatible.	-	all
hybrid_cascade	Union-Find pre-filter + Blossom/BP-OSD escalation; exposes cascade stats.	escalation, err	
gnn_belief_matching	GNN-guided weighted matching with faithfulness fallback.	gnn_hidden_size, gnn_n_laye	
belief_matching	BP posteriors reweight exact Blossom matching; faithfulness fallback.	bp_method, osd_ord	
two_stage	Two-stage decode pipeline (fast stage + exact escalation).	escalation	graphlike only
ambiguity_cluster	Cluster decoding for high-noise/non-graphlike degenerate syndromes.	-	non-graphlike
colour_code	Native colour-code decoder over undecomposed detector error models.	-	color_code family on

Decoder options

Key	Type	Applies to	Description
`bp_method`	string	`bp_osd`, `belief_matching`	"exact" or "min_sum".
`osd_order`	int	`bp_osd`, `belief_matching`	`0`, `1`, or `2`. Higher is slower/more accurate.
`error_rate`	float	all	Physical error probability used to weight edges or set BP priors.
`escalation`	string	`hybrid_cascade`	"blossom" or "bp_osd".
`max_accept_weight`	int	`hybrid_cascade`	Maximum syndrome weight accepted by the pre-filter.
`gnn_hidden_size`	int	`gnn_belief_matching`	Hidden dimension of the GNN.
`gnn_n_layers`	int	`gnn_belief_matching`	Number of GNN message-passing layers.

Unknown keys are ignored with a warning; missing keys use backend defaults.

Performance measurements

Benchmark measurements are intentionally not stored or shipped. Run a local benchmark on the target hardware when measurements are needed.

backend.py API

``backend.Any(*args, **kwargs)``

Special type indicating an unconstrained type.

``backend.Optional(*args, **kwargs)``

Optional[X] is equivalent to Union[X, None].

``backend.QectorError(...)``

Raised for invalid operations in the QECTOR backend.

``backend.build_code(family_key: 'str', param: 'int')``

Build a code from a family and parameter (distance).

``backend.build_code_from_matrix(H_matrix: 'np.ndarray', name: 'str' = 'custom', distance: 'Optional[int]' = None) -> 'Any'``

Build a code from a user-provided parity check matrix.

``backend.build_dem_from_code(code, noise_model: 'str' = 'depolarizing', p: 'float' = 0.05, bias: 'float' = 0.5, correlation: 'Optional[np.ndarray]' = None) -> 'Any'``

Build a Detector Error Model (DEM) from a code and noise model.

``backend.clear_decoder_cache() -> 'bool'``

Clear the native decoder cache in qector_decoder_v3.

``backend.code_summary(code) -> 'dict[str, Any]'``

Return a summary dict for a code object.

``backend.compat_report() -> 'dict[str, Any]'``

Ecosystem-integration availability report.

``backend.compatible_decoder_kinds(code) -> 'list[str]'``

Return the decoder kinds that can actually construct on code.

`backend.compute\_spring\_layout(n\_qubits: 'int', n\_checks: 'int', check\_matrix, iterations: 'int' = 100) -> 'tuple[list, list]`

Backwards-compatible alias for :func:compute_tanner_layout.

`backend.compute\_tanner\_layout(n\_qubits: 'int', n\_checks: 'int', check\_matrix) -> 'tuple[list, list]`

Deterministic bipartite Tanner-graph layout.

`backend.decode\_dem(dem, decoder\_kind: 'str' = 'bp\_osd', decoder\_options: 'Optional[dict]' = None, error\_rate: 'float' = 0.05, seed: 'Optional[int]' = None) -> 'dict[str, Any]`

Decode a syndrome using a Detector Error Model (DEM-native decoding).

`backend.decode\_syndrome(code, syndrome, decoder\_kind: 'str', decoder\_options: 'Optional[dict]' = None) -> 'dict[str, Any]`

Decode a user-supplied syndrome (from an import) with the given decoder.

`backend.deque(...)`

deque([iterable[, maxlen]]) --> deque object

`backend.estimate\_threshold(code, decoder\_kind: 'str' = 'blossom', p\_range: 'tuple' = (0.01, 0.2), n\_samples: 'int' = 100, distances: 'list' = None) -> 'dict[str, Any]`

Estimate the error threshold using binary search on error rate.

`backend.export\_figure(code, family: 'str', distance: 'int', output\_path: 'str', format: 'str' = 'png', dpi: 'int' = 300) -> 'dict[str, Any]`

Export a publication-ready figure of the Tanner graph.

`backend.export\_session(code\_family: 'str', distance: 'int', decoder\_name: 'str', error\_rate: 'float', seed: 'int', output\_path: 'str') -> 'dict[str, Any]`

Export a complete decode session (code + decode + benchmark + diagnostics) as a single ZIP archive containing JSON and text artifacts.

`backend.export\_to\_pymatching\_shim(code, output\_path: 'str') -> 'dict[str, Any]`

Export code to PyMatching-compatible format.

```
`backend.export_to_qiskit_plugin(code, output_path: 'str') -> 'dict[str, Any]`
```

Export code to Qiskit plugin format.

```
`backend.export_to_sinter_compat(code, decoder_kind: 'str', output_path: 'str') -> 'dict[str, Any]`
```

Export benchmark data in sinter-compatible format.

```
`backend.finite_size_scaling(code_family: 'str', decoder_kind: 'str' = 'blossom', distances: 'list' = None, p_vals: 'list' = None, n_samples: 'int' = 100) -> 'dict[str, Any]`
```

Perform finite-size scaling analysis (LER vs distance at fixed p).

```
`backend.flush_usage(customer_id: 'Optional[str]' = None, api_key: 'Optional[str]' = None) -> 'dict[str, Any]`
```

Flush accumulated usage metrics to Stripe metered billing API.

```
`backend.generate_parity_check_matrix(family: 'str', distance: 'int') -> 'np.ndarray`
```

Generate a parity check matrix for a code family.

```
`backend.generate_reproducibility_package(code_family: 'str', distance: 'int', decoder_kind: 'str', error_rate: 'float', seed: 'int', output_path: 'str') -> 'dict[str, Any]`
```

Generate a complete reproducibility package.

```
`backend.get_code_family_info(family_key: 'str') -> 'dict[str, str]`
```

Return metadata about a code family.

```
`backend.get_compatibility_matrix() -> 'dict[str, list[str]]`
```

Return a mapping of code family to list of compatible decoders.

```
`backend.get_compatible_decoders(code) -> 'list[dict[str, str]]`
```

Return decoder info for the decoders that can construct on this code.

```
`backend.get_decoder_info(kind: 'str') -> 'dict[str, str]`
```

Return human-readable info about a decoder kind.

`backend.get\_license\_info() -> 'dict[str, Any]`

Get license info from the decoder.

`backend.get\_license\_info\_with\_expiry() -> 'dict[str, Any]`

Get license info including token expiry details.

`backend.get\_tanner\_graph\_layout(code, family: 'str', distance: 'int') -> 'tuple[list, list]`

Return qubit and check coordinates for a clean bipartite Tanner graph.

`backend.import\_stim\_circuit(file\_path: 'str') -> 'Any`

Import a Stim circuit from file and convert to DEM.

`backend.import\_syndrome(file\_path: 'str') -> 'np.ndarray`

Load syndrome data from CSV, JSON, or numpy (.npy) file.

`backend.list\_available\_codes() -> 'dict[str, Any]`

Code families wired into the workbench plus the backend's native codes.list_codes() catalogue. Pure introspection.

`backend.logical\_failure(logicals: 'np.ndarray', error, correction) -> 'bool`

Public: True iff residual (error+correction)%2 flips a logical.

`backend.logicals\_matrix(code) -> 'Optional[np.ndarray]`

Public accessor for the code's logical-operator matrix (or None).

`backend.make\_decoder(code, decoder\_kind: 'str', decoder\_options: 'Optional[dict]' = None) -> 'Any`

Public: construct a decoder of decoder_kind for code.

`backend.native\_recommend(family\_key: 'Optional[str]' = None, distance: 'Optional[int]' = None, n\_qubits: 'Optional[int]' = None, priority: 'str' = 'balanced', batch\_size: 'int' = 1) -> 'dict[str, Any]`

Backend-native decoder recommendation (recommend).

```
`backend.run_batch_decode(code, backend: 'str' = 'cpu', n_samples: 'int' = 100, error_rate: 'float' = 0.05, seed: 'int' = 1, precision: 'str' = 'f32', edge_weights: 'Optional[np.ndarray]' = None, cancel_token=None) -> 'dict[str, Any]`
```

Run a batch decode on the given code.

```
`backend.run_benchmark(code, n_samples: 'int' = 1000, seed: 'int' = 42, decoder_kind: 'str' = 'union_find', error_rate: 'float' = 0.05, cancel_token=None) -> 'dict[str, Any]`
```

Run a decode benchmark on the given code.

```
`backend.run_diagnostic_decode(code, error_rate: 'float' = 0.05, decoder_kind: 'str' = 'blossom', seed: 'int' = 42) -> 'dict[str, Any]`
```

Rich single decode via the backend's decode_with_diagnostics.

```
`backend.run_doctor_checks() -> 'dict[str, Any]`
```

Run system health diagnostic checks via qd.doctor.

```
`backend.run_hybrid_cascade_stats(code, n_samples: 'int' = 64, error_rate: 'float' = 0.05, seed: 'int' = 1, escalation: 'Optional[str]' = None) -> 'dict[str, Any]`
```

Batch-decode with HybridCascadeDecoder and expose its cascade statistics.

```
`backend.run_ler_benchmark(code, n_samples: 'int' = 1000, error_rate: 'float' = 0.05, decoder_kind: 'str' = 'blossom', seed: 'int' = 42) -> 'dict[str, Any]`
```

Run LER benchmark with Wilson confidence intervals (from upstream qector CLI).

```
`backend.run_native_streaming(code, n_rounds: 'int' = 8, error_rate: 'float' = 0.03, seed: 'int' = 1, window_size: 'int' = 4) -> 'dict[str, Any]`
```

Native sliding-window streaming decode (sliding_window_decode).

```
`backend.run_neural_predecoder_training(code, n_samples: 'int' = 200, n_epochs: 'int' = 5, error_rate: 'float' = 0.05, seed: 'int' = 1, cancel_token=None) -> 'dict[str, Any]`
```

Train the NeuralPredecoder on sampled (syndrome, error) pairs (lab tool).

```
`backend.run_parallel_batch_decode(code, n_samples: 'int' = 64, error_rate: 'float' = 0.05, seed: 'int' = 1, decoder_type: 'str' = 'union_find', n_workers: 'Optional[int]' = None) -> 'dict[str, Any]`
```


Multi-process parallel batch decode via DecoderPool.

```
`backend.run_single_decode(code, error_rate: 'float', decoder_kind: 'str', seed: 'int',  
decoder_options: 'Optional[dict]' = None) -> 'dict[str, Any]`
```

Run a single seeded decode against code and report the result.

```
`backend.run_streaming_session(code, window_size: 'int' = 5, n_rounds: 'int' = 10,  
error_rate: 'float' = 0.03, seed: 'int' = 1, decoder_kind: 'str' = 'union_find',  
cancel_token=None) -> 'dict[str, Any]`
```

Run a sliding-window streaming decode session.

```
`backend.run_streaming_session_yield(code, window_size: 'int' = 5, n_rounds: 'int' = 10,  
error_rate: 'float' = 0.03, seed: 'int' = 1, decoder_kind: 'str' = 'union_find')`
```

Run a sliding-window streaming decode session and yield progress per round.

```
`backend.sample_error_and_syndrome(code, error_rate: 'float', seed: 'int')`
```

Public: sample one seeded error and its syndrome for code.

```
`backend.set_license_key_file(path: 'str') -> 'bool`
```

Set license key file path for offline hard-gated verification.

```
`backend.sparse_blossom_radix_neighbors(code_or_checks, defects: 'list[int]', k: 'int' =  
8) -> 'list[tuple[int, int, int, int]]`
```

Return k-nearest candidate edges (sorted by distance) for defects via SparseBlossom RadixHeap.

```
`backend.test_invalid_license_key() -> 'dict[str, Any]`
```

Test that an invalid license key raises ValueError.

```
`backend.validate_parameter(family_key: 'str', param: 'int') -> 'tuple[bool, str]`
```

Validate a code family parameter (distance).

```
`backend.verify_correction(code, syndrome, correction) -> 'bool`
```

Public: True iff correction reproduces the observed syndrome.

```
`backend.verify_license_token(token: 'str') -> 'dict[str, Any]`
```

Verify an Ed25519 signed license token string.

autodebug.py API

`autodebug.Optional(\*args, \*\*kwargs)`

Optional[X] is equivalent to Union[X, None].

`autodebug.asdict(obj, \*, dict\_factory=)`

Return the fields of a dataclass instance as a new dictionary mapping field names to field values.

`autodebug.dataclass(cls=None, /, \*, init=True, repr=True, eq=True, order=False, unsafe\_hash=False, frozen=False, match\_args=True, kw\_only=False, slots=False, weakref\_slot=False)`

Add dunder methods based on the fields defined in the class.

`autodebug.field(\*, default=, default\_factory=, init=True, repr=True, hash=None, compare=True, metadata=None, kw\_only=)`

Return an object to identify dataclass fields.

`autodebug.probe\_decoders(family: 'str', distance: 'int', error\_rate: 'float' = 0.05, seed: 'int' = 42, verify: 'bool' = True) -> 'dict'`

Try every wired decoder against one seeded syndrome and report results.

`autodebug.resilient\_batch\_decode(family: 'str', distance: 'int', backend: 'str' = 'cuda', n\_samples: 'int' = 100, error\_rate: 'float' = 0.05, seed: 'int' = 1, fallback\_chain: 'Optional[list]' = None) -> 'dict'`

Batch-decode, falling back cuda → opencl → cpu on unavailability.

`autodebug.resilient\_single\_decode(family: 'str', distance: 'int', error\_rate: 'float' = 0.05, decoder: 'str' = 'union\_find', seed: 'int' = 42, fallback\_chain: 'Optional[list]' = None, verify: 'bool' = True) -> 'ResilientDecodeResult'`

Decode one seeded syndrome, falling back through decoders on failure.

`autodebug.run\_self\_diagnostics(probe\_family: 'str' = 'repetition', probe\_distance: 'int' = 3) -> 'DiagnosticsReport'`

Run a full environment/decoder/hardware self-test.

`autodebug.self\_diagnostics(probe\_family: 'str' = 'repetition', probe\_distance: 'int' = 3) -> 'DiagnosticsReport'`

Run a full environment/decoder/hardware self-test.

hardware_routing.py API

`hardware\_routing.Optional(\*args, \*\*kwds)`

Optional[X] is equivalent to Union[X, None].

`hardware\_routing.dataclass(cls=None, /, \*, init=True, repr=True, eq=True, order=False, unsafe\_hash=False, frozen=False, match\_args=True, kw\_only=False, slots=False, weakref\_slot=False)`

Add dunder methods based on the fields defined in the class.

`hardware\_routing.detect\_hardware() -> 'HardwareProfile'`

Detect real GPU/CUDA/OpenCL availability via the installed package.

`hardware\_routing.opencl\_host() -> 'tuple[int, Optional[str]]'`

Return (device count, first platform name) exposed by the *host* OpenCL.

`hardware\_routing.opencl\_reason(decoder\_opencl: 'bool', host\_devices: 'int', host\_platform: 'Optional[str]') -> 'str'`

Explain the OpenCL state in terms a user can act on.

`hardware\_routing.recommend(code\_family: 'Optional[str]', distance: 'Optional[int]', n\_qubits: 'Optional[int]', priority: 'str') -> 'Recommendation'`

Heuristic decoder recommendation (deterministic, no model call).

version_service.py API

``version_service.Callable(*args, **kwargs)``

Deprecated alias to `collections.abc.Callable`.

``version_service.Optional(*args, **kwds)``

`Optional[X]` is equivalent to `Union[X, None]`.

``version_service.effective_app_version(prefer_latest: 'bool' = False) -> 'Optional[str]``

The version the app presents as *its own* — the workbench baseline.

``version_service.format_version_banner(report: 'Optional[dict]' = None) -> 'str``

One-line human banner: workbench version + installed backend version.

``version_service.get_app_version_info(refresh: 'bool' = False) -> 'dict[str, Any]``

Local baseline for the workbench application (offline — no PyPI).

``version_service.get_backend_version_info(refresh: 'bool' = False) -> 'dict[str, Any]``

Installed backend version, resolved locally — bundled wheel only, no PyPI.

``version_service.get_version_report(refresh: 'bool' = False) -> 'dict[str, Any]``

Combined app + backend version report (offline — bundled wheel only).

``version_service.installed_backend_version() -> 'Optional[str]``

The version of the compiled decoder backend actually imported, if any.

``version_service.is_newer(latest: 'Optional[str]', current: 'Optional[str']) -> 'bool``

True iff latest is a strictly newer version than current.

``version_service.local_app_version() -> 'str``

The workbench's baked-in baseline version (offline-safe).

``version_service.parse_version(v: 'Optional[str]') -> 'tuple``

Parse a version string to a tuple of ints for ordering.

`version\_service.resolve\_versions\_async(callback: 'Optional[Callable[[dict], None]]' = None, refresh: 'bool' = False) -> 'threading.Thread`

Resolve both versions on a daemon thread, then invoke callback(report).

decoder_provisioner.py API

`decoder\_provisioner.Callable(\*args, \*\*kwargs)`

Deprecated alias to collections.abc.Callable.

`decoder\_provisioner.Optional(\*args, \*\*kwargs)`

Optional[X] is equivalent to Union[X, None].

`decoder\_provisioner.abi\_tag() -> 'str`

A short tag unique to this interpreter's binary ABI.

`decoder\_provisioner.activate\_site() -> 'Optional[Path]`

Place the active managed site first on sys.path (idempotently).

`decoder\_provisioner.active\_site() -> 'Optional[Path]`

Read the active managed-site pointer; malformed pointers are ignored.

`decoder\_provisioner.bootstrap(on\_log: 'Optional[Callable[[str], None]]' = None) -> 'dict`

Blocking pre-import gate used by main.py before backend imports.

`decoder\_provisioner.ensure(prefer\_latest: 'bool' = True, timeout: 'Optional[int]' = None, on\_log: 'Optional[Callable[[str], None]]' = None, target\_version: 'Optional[str]' = None) -> 'dict`

Ensure an importable decoder, preferring the bundled wheel (offline).

`decoder\_provisioner.ensure\_async(prefer\_latest: 'bool' = True, callback: 'Optional[Callable[[dict], None]]' = None, on\_log: 'Optional[Callable[[str], None]]' = None, target\_version: 'Optional[str]' = None) -> 'threading.Thread`

Run :func:ensure on a daemon thread; upgrade takes effect next launch.

`decoder\_provisioner.ensure\_dependencies(on\_log: 'Optional[Callable[[str], None]]' = None) -> 'dict'`

Check and automatically install any missing core dependencies via pip.

`decoder\_provisioner.find\_local\_wheels() -> 'list[Path]'`

Find local or bundled .whl files for qector_decoder_v3.

`decoder\_provisioner.import\_ok() -> 'bool'`

True iff the decoder *actually imports* in this interpreter — i.e. its compiled extension loads. A metadata-only presence check is not enough: a wheel built for another Python ABI leaves valid dist-info but an unloadable .pyd/.so. This is the authoritative "is a usable decoder present?" test used by the boot gate.

`decoder\_provisioner.is\_frozen() -> 'bool'`

No docstring.

`decoder\_provisioner.managed\_root() -> 'Path'`

Return the app-owned, user-writable, ABI-scoped decoder storage dir.

`decoder\_provisioner.purge\_outdated\_managed\_sites(minimum\_ver: 'Optional[str]' = None) -> 'list[str]'`

Delete any on-disk managed decoder site versions older than minimum_ver.

`decoder\_provisioner.resolve\_pip\_argv() -> 'tuple[Optional[list[str]], str]'`

Find a pip interpreter that can install extension modules for this app.

`decoder\_provisioner.scan\_version() -> 'Optional[str]'`

Return the active managed version, otherwise a system-installed version.

`decoder\_provisioner.self\_check() -> 'dict'`

No docstring.

doc_generator.py API

`doc\_generator.Optional(\*args, \*\*kwds)`

Optional[X] is equivalent to Union[X, None].

``doc_generator.latex_escape(value: 'Any') -> 'str``

Escape LaTeX special characters (`\` & `%` `$` `#` `_` `{` `}` `~` `^`) in value.

MCP tool reference

85 tools via stdio JSON-RPC 2.0.

`ambiguity\_cluster\_decode`

Decode using AmbiguityClusterDecoder for high noise or non-graphlike codes

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- error_rate (number, default 0.05) -
- ambig_threshold (number, default 0.5) -
- max_cluster_size (integer, default 12) -
- syndrome ([array', 'null'], required) -
- seed (integer, default 42) -

`analyze\_code\_family`

Analyze a code family with an example code instance

****Parameters****

- family_name (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -

`analyze\_error\_patterns`

Analyze error patterns: weight distribution, cluster size, correlated errors

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- error_rate (number, default 0.05) -
- n_samples (integer, default 100) -
- seed (integer, default 42) -

`analyze\_logicals`

Expose logical operator matrix, logical weight distribution, and code distance estimation

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -

`batch\_decode`

Batch-decode sampled syndromes on cpu/cuda/opencl via backend.run_batch_decode

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- backend (string, default 'cpu') - One of: cpu, cuda, opencl (no silent fallback)
- n_samples (integer, default 100) -
- error_rate (number, default 0.05) -
- seed (integer, default 1) -

`batch\_decode\_gpu`

Batch-decode on an explicit compute backend (cpu/cuda/opencl) with honest availability reporting — unavailable GPU backends return status='unavailable' with a reason, never fake results

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 3) -
- backend (string, default 'cuda') - One of: cpu, cuda, opencl
- n_samples (integer, default 32) -
- error_rate (number, default 0.05) -
- seed (integer, default 1) -

`belief\_match\_decode`

Convenience seeded decode pinned to the belief_matching kind (BP posteriors + exact MWPM with faithfulness fallback)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`benchmark\_decoder`

Benchmark a decoder on a code family via backend.run_benchmark (latency percentiles, throughput, logical error rate)

****Parameters****

- decoder_name (string, default 'union_find') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- code_family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code

- distance (integer, default 5) -
- error_rate (number, default 0.05) -
- n_samples (integer, default 100) -
- seed (integer, default 42) -

`build\_code\_from\_matrix`

Build a code from a user-provided parity check matrix

****Parameters****

- H_matrix (array, required) - Binary parity check matrix (n_checks x n_qubits)
- family (string, default 'custom') - Family name for the custom code
- distance (integer, default 3) -

`build\_dem`

Build a Detector Error Model (DEM) from a code and noise model

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- noise_model (string, default 'depolarizing') - One of: depolarizing, biased, correlated, circuit
- p (number, default 0.05) -
- bias (number, default 0.5) -

`check\_updates`

Report whether the installed decoder backend matches the bundled release baseline (offline — no update service)

****Parameters****

- refresh (boolean, default False) - Accepted for compatibility; resolution is always local

`clear\_decoder\_cache`

Clear the backend's native decoder cache

No parameters.

`clear\_results`

Clear all stored benchmark results

****Parameters****

- confirm (boolean, default False) -

`colour\_code\_decode`

Decode color code using BP-OSD over undecomposed detector error model

****Parameters****

- distance (integer, default 3) -
- max_iter (integer, default 30) -
- osd_order (integer, default 0) -
- syndrome ([array', 'null'], required) -
- seed (integer, default 42) -

`compare\_all\_decoders`

Run all compatible decoders on the same code and return comparison table

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- error_rate (number, default 0.05) -
- n_samples (integer, default 50) -
- seed (integer, default 42) -

`compare\_benchmarks`

Compare stored benchmark results side by side (throughput, p99 latency, logical error rate)

****Parameters****

- benchmarks (array, required) - result_id values returned by the run_benchmark tool

`compat\_report`

Report ecosystem-integration availability (stim/sinter/pymatching/qiskit/ldpc) and research components

No parameters.

`compatibility\_matrix`

Return the full 16x10 decoder/code compatibility matrix

No parameters.

`compatible\_decoders`

Live probe: which decoder kinds construct and produce a syndrome-verified correction on this code

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 3) -

`compliance\_attestation`

Zero-egress / offline compliance attestation for infosec review: AST scan for network and telemetry imports, runtime EgressGuard state, offline license tier, local-only data residency, and optional Entra ID readiness. No network calls.

No parameters.

`decode\_dem`

Decode using a Detector Error Model (DEM-native decoding)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_kind (string, default 'bp_osd') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- decoder_options ([object, 'null'], required) - Optional per-decoder construction options: bp_method (exact|min_sum|relay), osd_order (0|1|2), osd_lambda, damping, error_rate, escalation (blossom|bposd), max_accept_weight, gnn_hidden_size, gnn_n_layers

`decode\_hyperedge`

Hyperedge / qLDPC decoding via bp_osd or other LDPC-capable decoders

****Parameters****

- family (string, default 'bicycle') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 3) -
- decoder_name (string, default 'bp_osd') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`decode\_mmap`

Out-of-core batch decoding via memory-mapped arrays

****Parameters****

- family (string, default 'rotated_surface') -
- distance (integer, default 5) -
- syndrome_path (string, required) -
- output_path (string, required) -
- decoder_name (string, default 'cpu_batch') -
- batch_size (integer, default 65536) -
- n_shots (integer, required) -

`decode\_single`

Run one seeded decode and report correction weight, syndrome validity and logical failure

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'union_find') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`decode\_syndrome`

Decode an explicit 0/1 syndrome (length n_checks) with a chosen decoder; syndrome_valid is the GF(2) re-check, logical_failure is null (no reference error exists, so it is unknowable)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'union_find') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- syndrome (array, required) - 0/1 syndrome bits, length must equal the code's n_checks
- decoder_options ([object, 'null'], required) - Optional per-decoder construction options: bp_method (exact|min_sum|relay), osd_order (0|1|2), osd_lambda, damping, error_rate, escalation (blossom|bposd), max_accept_weight, gnn_hidden_size, gnn_n_layers

`decode\_syndrome\_blossom`

Convenience tool: exact Blossom (MWPM) syndrome decode

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- syndrome (array, required) - Binary syndrome vector

`decode\_syndrome\_cascade`

Convenience tool: Hybrid cascading syndrome decode (UF pre-filter escalating to Blossom)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- syndrome (array, required) - Binary syndrome vector

`decode\_with\_options`

Seeded decode with validated per-decoder construction options (bp_osd bp_method/osd_order, hybrid_cascade escalation, GNN architecture); reports options_applied honestly

****Parameters****

- family (string, default 'repetition') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 3) -
- decoder_name (string, default 'bp_osd') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- error_rate (number, default 0.05) -
- seed (integer, default 42) -
- decoder_options ([object, 'null'], required) - Optional per-decoder construction options: bp_method (exact|min_sum|relay), osd_order (0|1|2), osd_lambda, damping, error_rate, escalation (blossom|bposd), max_accept_weight, gnn_hidden_size, gnn_n_layers

`decoder\_benchmark\_suite`

Run standard benchmark (rotated_surface d=5, p=0.05) across all decoders

****Parameters****

- n_samples (integer, default 100) -
- seed (integer, default 42) -

`delete\_resource`

Delete a resource by ID

****Parameters****

- resource_id (string, required) -
- confirm (boolean, default False) -

`diagnostic\_decode`

Rich single decode via the backend's native decode_with_diagnostics (matched weight, backend used, internal fallback, timing, logicals)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`doctor\_diagnostics`

Run system health and environment diagnostic checks via `qd.doctor`

No parameters.

`estimate\_threshold`

Estimate the error threshold using binary search on error rate

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_kind (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- p_min (number, default 0.01) -
- p_max (number, default 0.2) -
- n_samples (integer, default 100) -

`export\_benchmark`

Export a stored benchmark result (by result_id) to the export directory

****Parameters****

- benchmark_id (string, required) - result_id returned by the run_benchmark tool
- format (string, default 'json') -

`export\_figure`

Export a publication-ready figure of the Tanner graph

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- output_path (string, default 'tanner_graph.png') -
- format (string, default 'png') - One of: png, pdf, svg, pgf
- dpi (integer, default 300) -

`export\_session`

Export the current session (code + decode + benchmark + diagnostics) as a ZIP archive

****Parameters****

- output_path ([string, 'null'], required) - Optional file path for the ZIP; auto-named if omitted
- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -

- decoder_name (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`finite\_size\_scaling`

Perform finite-size scaling analysis (LER vs distance at fixed p)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- decoder_kind (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- distances (array, default [3, 5, 7, 9, 11]) - Code distances to test
- p_vals (array, default [0.01, 0.03, 0.05, 0.07, 0.1]) - Error rates to test
- n_samples (integer, default 100) -

`flush\_usage`

Flush usage metrics to Stripe metered billing API

****Parameters****

- customer_id (['string', 'null'], required) -
- api_key (['string', 'null'], required) -

`generate\_documentation`

Generate code documentation files

****Parameters****

- family_key (string, default 'ring') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- param (integer, default 6) -
- formats (array, default ['json']) - Any of: json, markdown, html, latex, pdf

`generate\_parity\_check`

Generate a parity check matrix for a code family

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -

`generate\_reproducibility\_package`

Generate a complete reproducibility package (ZIP)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- error_rate (number, default 0.05) -
- seed (integer, default 42) -
- output_path (string, default 'reproducibility_package.zip') -

`get\_backend\_health`

7-tier backend health status from AutoDecoder diagnostics

No parameters.

`get\_code\_properties`

Get properties of a code family

****Parameters****

- family_name (string, default 'ring') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -

`get\_config`

Get current server configuration

No parameters.

`get\_decoder\_info`

Get information about a decoder

****Parameters****

- decoder_name (string, default 'bp_osd') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time

`get\_entra\_posture`

Return the Microsoft Entra ID posture (enabled, unconfigured, or authenticated).

No parameters.

`get\_hardware\_info`

Get hardware/backend availability

No parameters.

`get\_identity\_info`

Return identity info if signed into Entra ID, else None.

No parameters.

`get\_license\_info`

Get license info from the decoder (tier, key_status, expiry)

No parameters.

`get\_resource`

Get a specific resource by ID

****Parameters****

- resource_id (string, required) -

`get\_resources`

List all resources

No parameters.

`get\_results`

Get stored benchmark results (most recent first-in order)

****Parameters****

- limit (integer, default 10) -

`get\_server\_env`

Get effective QECTOR environment variables (tuning vars)

No parameters.

`get\_statistics`

Get server statistics

No parameters.

`get\_system\_info`

Get system information

No parameters.

`gnn\_belief\_match\_decode`

Convenience seeded decode pinned to the gnn_belief_matching kind with optional GNN architecture overrides (gnn_hidden_size, gnn_n_layers)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code

- distance (integer, default 5) -
- error_rate (number, default 0.05) -
- seed (integer, default 42) -
- gnn_hidden_size (['integer', 'null'], required) -
- gnn_n_layers (['integer', 'null'], required) -

`hybrid\_cascade\_stats`

Batch-decode through the hybrid_cascade decoder and expose its live cascade statistics (prefilter_hits, escalations, hit rate, throughput, syndrome-match rate, logical error rate)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 3) -
- n_samples (integer, default 64) -
- error_rate (number, default 0.05) -
- seed (integer, default 1) -
- escalation (['string', 'null'], required) - One of: blossom, bposd (default: backend's blossom)

`import\_stim`

Import a Stim circuit from file and convert to DEM

****Parameters****

- file_path (string, required) - Path to Stim circuit file
- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time

`import\_syndrome`

Load external syndrome data (CSV, JSON, or .npy) and decode it

****Parameters****

- file_path (string, required) - Path to syndrome file
- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time

`list\_clients`

List registered clients

No parameters.

`list\_code\_families`

List available code families

No parameters.

`list\_codes`

List workbench code families plus the backend's native code catalogue

No parameters.

`list\_decoders`

List available decoders

No parameters.

`list\_tools`

List all available MCP tools

No parameters.

`mcp\_health`

Server health check: uptime, memory, decoder status, tool count

No parameters.

`mcp\_status`

Get MCP server status

No parameters.

`native\_recommend`

Backend-native decoder recommendation (qector_decoder_v3.recommend) with the mapped workbench decoder_kind

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- n_qubits (['integer', 'null'], required) -
- priority (string, default 'balanced') - One of: balanced, speed, accuracy
- batch_size (integer, default 1) -

`native\_streaming`

Native hardware-accelerated sliding-window streaming decode (qector_decoder_v3.sliding_window_decode) with per-round validity + telemetry

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- n_rounds (integer, default 8) -
- error_rate (number, default 0.03) -
- seed (integer, default 1) -
- window_size (integer, default 4) -

`neural\_predecoder\_train`

Train the NeuralPredecoder research/lab MLP on seeded (syndrome, error) pairs and evaluate on a disjoint held-out stream (exact-match, bit accuracy, syndrome validity, LER)

****Parameters****

- family (string, default 'repetition') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 3) -
- n_samples (integer, default 200) -
- n_epochs (integer, default 5) -
- error_rate (number, default 0.05) -
- seed (integer, default 1) -

`parallel\_batch\_decode`

Parallel batch decode using multiple processes via backend.run_parallel_batch_decode

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- n_samples (integer, default 100) -
- error_rate (number, default 0.05) -
- seed (integer, default 42) -
- n_workers (integer, default 4) -

`probe\_decoders`

Probe which decoders produce a valid (syndrome-verified) correction for a code — a self-test across every wired decoder

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code

- distance (integer, default 5) -
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`recommend\_decoder`

Recommend a decoder for a code/priority using detected hardware

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- n_qubits ([integer, 'null'], required) -
- priority (string, default 'balanced') - One of: balanced, speed, accuracy

`register\_client`

Register a client

****Parameters****

- client_id (string, required) -
- access_level (string, default 'USER') -

`reset\_config`

Reset configuration to defaults

****Parameters****

- confirm (boolean, default False) -

`resilient\_decode`

Single decode with automatic multi-decoder fallback and a full attempt trace (autodebug.resilient_single_decode)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'union_find') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`run\_benchmark`

Run a benchmark and store the result under a generated result_id

****Parameters****

- code_family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'union_find') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- n_samples (integer, default 100) -
- seed (integer, default 42) -
- error_rate (number, default 0.05) -

`run\_ler\_benchmark`

Run LER benchmark with Wilson confidence intervals

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- decoder_name (string, default 'blossom') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time
- n_samples (integer, default 1000) -
- error_rate (number, default 0.05) -
- seed (integer, default 42) -

`self\_diagnostics`

Run a full environment/decoder/hardware self-diagnostics report (autodebug.run_self_diagnostics)

No parameters.

`set\_config`

Merge key/value pairs into the server configuration

****Parameters****

- config (object, required) - Key/value pairs merged into the current configuration

`set\_license\_key\_file`

Set license key file path for offline verification

****Parameters****

- path (string, required) -

`sparse\_blossom\_radix\_neighbors`

Discover k-nearest candidate edges via SparseBlossom RadixHeap

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- defects ([array], 'null', required) -
- k (integer, default 8) -

`stream\_decode`

Run a sliding-window streaming decode session via backend.run_streaming_session

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- window_size (integer, default 5) -
- n_rounds (integer, default 10) -
- error_rate (number, default 0.03) -
- seed (integer, default 1) -
- decoder_name (string, default 'union_find') - One of: union_find, fast_union_find, blossom, sparse_blossom, bp_osd, auto, hybrid, lookup_table, predecoded, auto_router, hybrid_cascade, gnn_belief_matching, belief_matching, two_stage, ambiguity_cluster, colour_code, space_time

`two\_stage\_decode`

Decode using TwoStageDecoder (decoupled X/Z sector decoders)

****Parameters****

- family (string, default 'rotated_surface') - One of: repetition, ring, rotated_surface, unrotated_surface, toric, heavy_hex, bicycle, bivariate_bicycle, hypergraph_product, color_code
- distance (integer, default 5) -
- x_decoder (string, default 'blossom') -
- z_decoder (string, default 'blossom') -
- syndrome ([array], 'null', required) -
- seed (integer, default 42) -

`verify\_license\_token`

Verify an Ed25519 signed license token string

****Parameters****

- token (string, required) -

`version\_info`

App + decoder-backend version report (workbench baseline + installed backend, resolved locally — no network)

****Parameters****

- refresh (boolean, default False) - Accepted for compatibility; resolution is always local

MCP wire protocol

Newline-delimited JSON-RPC 2.0 over stdio. Launch with --mcp.

```
{ "jsonrpc": "2.0", "id": 1, "method": "initialize", "params": { "protocolVersion": "2024-11-05", "capabilities": {}, "cli": {} } }
{ "jsonrpc": "2.0", "method": "notifications/initialized" }
{ "jsonrpc": "2.0", "id": 2, "method": "tools/list" }
{ "jsonrpc": "2.0", "id": 3, "method": "tools/call", "params": { "name": "decode_single", "arguments": { "family": "rotated_" }
```

Result envelope: content[0].text holds a JSON payload; isError flags tool-level failure.

Common result schemas

```
# Single decode result
{ "error": [...], "syndrome": [...], "result": { "correction": [...], "hamming_weight": int, "syndrome_valid": bool, "logical_failure": bool } }
# Benchmark result
{ "throughput_decodes_per_s": float, "decode_seconds": float, "n_trials": int, "p": float, "seed": int, "method": str, "backend": str }
# Resilient decode
{ "success": bool, "used_decoder": str | None, "fallback_used": bool, "syndrome_valid": bool | None, "logical_failure": bool }
# Diagnostics report
{ "overall_status": "pass|degraded|fail", "timestamp": float, "platform": str, "python": str, "workbench_version": str, "workbench_build": str }
```

Environment variables

Variable	Effect
QECTOR_DATA_DIR	Relocate all QECTOR user data.
QECTOR_SILENT	Set to 1 to suppress the backend startup notice.
QECTOR_LICENSE	Ed25519 token that overrides academic/commercial for testing.
QECTOR_DISABLE_OPENCL	Set to 1 to skip OpenCL probing. It cannot enable OpenCL.
QECTOR_ENABLE_OPENCL_AUTO	Allows OpenCL auto-routing, but only when OpenCL is already available.

Provisioning model

The Workbench bundles the decoder wheel inside the application. On first launch it activates qector-decoder-v3 from the bundled wheel into a managed, ABI-scoped user site — fully offline, on every platform. Any outdated managed decoder left by an older release is purged automatically before activation. No internet connection, Python, or pip is required.

A splash screen is shown within roughly a second of launch and closes once the main window is mapped, so the cold start (extracting the wheel on first run, then loading a compiled extension) is never an invisible wait.

Boot diagnostics

A windowed build has no stderr, so provisioning is logged to files under the per-user data

directory:

File	Contents
`logs/boot.log`	Every bootstrap step, the activated site, and the exact import error.
`logs/boot_stdio.log`	Anything written to stdout/stderr when the build has no console.

Hardware backends

Backend	Availability
`cpu`	Always available.
`cuda`	Requires an NVIDIA GPU with a healthy driver.
`opencl`	Reported unavailable by the published wheel, which is built without the OpenCL feature.

`opencl_is_available()` returning `False` is a property of the decoder build, not of the host:

a machine can expose OpenCL devices and still get `False`, and no environment variable changes

it. `hardware_routing.detect_hardware()` reports `opencl_host_devices` and

`opencl_host_platform` (probed from the host ICD) plus an `opencl_reason` string so the two

situations can be told apart. Enabling the backend requires rebuilding `qector-decoder-v3`

with its `opencl` Cargo feature.

Example workflows

```
import backend as be, autodebug
code = be.build_code("rotated_surface", 5)
out = be.run_single_decode(code, error_rate=0.05, decoder_kind="blossom", seed=42)
assert out["result"]["syndrome_valid"]

out2 = be.run_single_decode(code, error_rate=0.05, decoder_kind="bp_osd", seed=7, decoder_options={"bp_method": "bivariate_bicycle", 3, seed=99})
probe = autodebug.probe_decoders("bivariate_bicycle", 3, seed=99)
resilient = autodebug.resilient_single_decode("bivariate_bicycle", 3, decoder="union_find", seed=7)
stats = be.run_hybrid_cascade_stats(code, n_samples=64, error_rate=0.05, seed=1)
```