

# A mathematical understanding of deep learning

Jiang J.

Data Engineer, Data Scientist

ENSEEIH Computer Science Engineering Degree, INP Toulouse Dual MSc Research Degree in  
AI / Big Data / Ops  
France

## 1 – Introduction

Frameworks such as TensorFlow or PyTorch make deep learning developments easy. They have made this field wide spread for every enthusiast. Implementations only needs an instinctive understanding of deep learning. Thus, the proper math aspect is little by little forgotten.

The objective is to do a summary of the important propositions. These propositions will be mathematically proven. The subject tackled is a multi-class classification problem with – dense layers, ReLU and Softmax activation layers, Categorical cross-entropy loss, Stochastic gradient descent optimizer. However, most the elements below can be re-used or easily modified to cover a regression problem.

## 2 – Notation and Nomenclature

**Definition 1** – Let  $a_{i,j} \in \mathbb{R}$  ,  $i \in \{1,2,\dots,n\}$  ,  $j \in \{1,2,\dots,m\}$  . Then the ordered rectangular array

$$A = \begin{bmatrix} a_{1,1} & a_{1,2} & \cdots & a_{1,m} \\ a_{2,1} & a_{2,2} & \cdots & a_{2,m} \\ \vdots & \vdots & \ddots & \vdots \\ a_{n,1} & a_{n,2} & \cdots & a_{n,m} \end{bmatrix}$$

is a real matrix of dimension  $n \times m$  .

The notation following notations are considered

$$[A]_{i,j} = a_{i,j} , \quad i \in \{1,2,\dots,n\} , \quad j \in \{1,2,\dots,m\}$$

$$[A]_{:,j} = \begin{bmatrix} a_{1,j} \\ a_{2,j} \\ \vdots \\ a_{n,j} \end{bmatrix} , \quad j \in \{1,2,\dots,m\}$$

$$[A]_{i,:} = [a_{i,1} \quad a_{i,2} \quad \cdots \quad a_{i,n}] , \quad i \in \{1,2,\dots,n\} , \quad j \in \{1,2,\dots,m\}$$

The notation  $M_{n,m}$  means the real matrix set of dimension  $n \times m$  .

**Convention 1** – A vector is a matrix with only one row. Thus, the real vector set  $\mathbb{R}^n$  is equivalent to  $M_{1,n}$ .

**Notation 1** – The matrix transpose operation will be noted as  $A^T$ .

**Definition 2** – Let  $A \in M_{n,m}$ , and  $B \in M_{m,p}$ , and let the product noted  $A \times B$  or  $AB$  be

$$C = A \times B = AB$$

where  $C$  is a  $m \times p$  matrix with

$$[C]_{i,j} = \sum_{k=1}^m [A]_{i,k} * [B]_{k,j}, \quad i \in \{1, 2, \dots, n\}, \quad j \in \{1, 2, \dots, p\}$$

**Definition 3** – Let  $z \in M_{n,m}$ , then the vector wise application

### 3 – Simple perceptron

**Definition 4** – Let  $y \in M_{1,m}$  the input vector, and  $W \in M_{1,m}$  the weight matrix and fThen the simple perceptron is defined as the operation

### 4 – Neural Network

**Definition 2** – Suppose a data set with  $n$  samples. Each sample have  $m$  features and a corresponding one-hot encoded label among  $l$  possible labels.

Let  $X \in M_{n,m}$ , and  $Y \in M_{n,l}$  the matrices defining the features and the labels respectively for each sample.

Suppose a neural network with  $k$  layers.

### 2 – References